IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES PROVISIONAL PATENT APPLICATION

for

IMPROVED WIRELESS COMMUNICATIONS SYSTEMS AND METHODS

Inventors:

John H. Oates
598 Seaverns Bridge Road
Amherst, New Hampshire 03031

Alden J. Fuchs
160 Pine Hill Road
Nashua, New Hampshire 03063

Jonathan E. Greene
83n Hollenbeck Avenue
Great Barrington, Massachusetts 01230

Frank P. Lauginiger
772 Russell Station Road
Francestown, New Hampshire 03043

Paul E. Cantrell
15 Prescott Drive
Chelmsford, Massachusetts 01863

Jan N. Dunn
48 North Court Street, #1
Providence, Rhode Island 02903

Steven R. Imperiali
43 Haynes Road
Townsend, Massachusetts 01469

Kathleen J. Jacques
10 Juniper Street
Jay, Maine 04239

William J. Jenkins
61 Heritage Lane #C4
Leominster, Massachusetts 01453

David E. Majchrzak
11 Regine Street
Hudson, New Hampshire 03051

Mirza Cifric
705 Mass Avenue
Boston, Massachusetts 02118

Michael J. Vinskus
5 Cranberry Lane
Litchfield, New Hampshire 03052

Background of the Invention

The invention pertains to wireless communications and, more particularly, to methods and apparatus for interference cancellation in code-division multiple access communications. The invention has application, by way of non-limiting example, in improving the capacity of cellular phone base stations.

Code-division multiple access (CDMA) is used increasingly in wireless communications. It is a form of multiplexing communications, e.g., between cellular phones and base stations, based on distinct digital codes in the communication signals. This can be contrasted with other wireless protocols, such as frequency-division multiple access and time-division multiple access, in which multiplexing is based on the use of orthogonal frequency bands and orthogonal time-slots, respectively.

A limiting factor in CDMA communication and, particularly, in so-called direct sequence CDMA (DS-CDMA), is the interference between multiple simultaneous communications, e.g., multiple cellular phone users in the same geographic area using their phones at the same time. This is referred to as multiple access interference (MAI). It has effect of limiting the capacity of cellular phone base stations, since interference may exceed acceptable levels -- driving service quality below acceptable levels -- when there are too many users.

A technique known as multi-user detection (MUD) reduces multiple access interference and, as a consequence, increases base station capacity. MUD can reduce interference not only between multiple signals of like strength, but also that caused by users so close to the base station as to otherwise overpower signals from other users (the so-called near/far problem). MUD generally functions on the principle that signals from multiple simultaneous users can be jointly used to improve detection of the signal from any single user. Many forms of MUD are known; surveys are provided in Moshavi, "Multi-User Detection for DS-CDMA Systems," IEEE Communications Magazine (October, 1996) and Duel-Hallen et al, "Multiuser Detection for CDMA Systems," IEEE Personal Communications (April 1995). Though a promising solution to increasing the capacity of cellular phone base stations, MUD techniques are typically so computationally intensive as to limit practical application.

1

An object of this invention is to provide improved methods and apparatus for wireless communications. A related object is to provide such methods and apparatus for multi-user detection or interference cancellation in code-division multiple access communications.

A further object of the invention is to provide such methods and apparatus as can be cost-effectively implemented and as require minimal changes in existing wireless communications infrastructure.

A still further object of the invention is to provide methods and apparatus for executing multi-user detection and related algorithms in real-time.

A still further object of the invention is to provide such methods and apparatus as manage faults for high-availability.

2

Summary of the Invention

These and other objects are met by the invention which provides, in one aspect, a wireless communications system, referred to as the "MCW-1" (among other terms) in the materials that follow, and methods of operation thereof. An overview of that system is provided in the document entitled "Software Architecture of the MCW-1 MUD Board," immediately following this Summary. A more complete understanding of its implementation may be attained by reference to the other attached materials.

In view of those materials, aspects of the invention include, but are not limited to, the following:

- hardware and/or software architectures (and methods of operation thereof) for multi-user detection in wireless communications systems and particularly, for example, in a wireless communications base station;

- a hardware architecture (and methods of operation thereof) for multi-user detection in wireless communications systems pairing each processing node with NVRAM and watchdog PLD for fault management;

- methods and apparatus for connecting watchdog PLDs with an out-of-band fault-management bus;

- methods and apparatus for use of an embedded host with the RACEway™ architecture of Mercury Computer Systems, Inc.

- methods and apparatus for interfacing a digital signal processor to the RACEway™ architecture;

3

- methods and apparatus for interfacing the RACEway™ architecture to a programming port in a device for multi-user detection in wireless communications systems;

- methods and apparatus for implementing a DMA Engine FPGA for use in multi-user detection in a wireless communications systems;

- methods and apparatus for implementing a hardware-based reset voter and stop voter;

- methods and apparatus for scalable mapping of handset and BTS functions to multiple processors;

- methods and apparatus for facilitating allocation and management of buffers for interconnecting processors that implement the aforementioned mapping;

- methods and apparatus for implementing a hybrid operating system, e.g., with the VxWorks operating system (of WindRiver Systems, Inc.) on a host computer and the MC/OS operating system on RACE®-based nodes. (Race and MC/OS are trademarks of Mercury Computer Systems, Inc.);

- methods and apparatus for high-availability multi-user detection in wireless communications systems, including (by way of non-limiting example) round-robin fault testing and use of NVRAM to store fault symptoms and use of master to diagnose faults from NVRAM contents;

- class library-based methods and apparatus for facilitating interprocessor communications, by way of non-limiting example, in buffering for multi-user detection in wireless communications systems;

4

- methods and apparatus for implementation of R-matrix, gamma-matrix and MPIC computations on separate processors in a device for multi-user detection in wireless communications systems;

- methods and apparatus for computing complementary R-matrix elements in parallel using multiple processors in a device for multi-user detection in wireless communications systems;

- methods and apparatus for depositing results of R-matrix calculations contiguously in memory in a device for multi-user detection in wireless communications systems;

- methods and apparatus for increasing the number of MPIC and R-matrix calculations performed in cache in a device for multi-user detection in wireless communications systems;

- methods and apparatus for performing a gamma-matrix calculation in FPGA in a device for multi-user detection in wireless communications systems;

- methods and apparatus for equalizing load of R-matrix-element calculation among multiple processors in a device for multi-user detection in wireless communications systems; and

- methods and apparatus for use of Altivec registers and instruction set in performing MUD calculations in a wireless communications system.

These and other aspects of the invention (including utilization of the aforementioned methods and aspects for other than wireless communications and/or interference cancellation) are evident in the materials that follow.

5

Detailed Description of the Invention

(see attached materials)

6

Software Architecture of the MCW-1 MUD Board

11

12 ## Table of Contents

13

35

36 ## Table of Figures

37

40

41

Software Architecture of the MCW-1 MUD Board

42

1 Purpose

The purpose of this document is to describe the software architecture of the MCW-1 board. The MCW-1 application is a digital signal processing application that performs interference cancellation for a cellular base station modem board.

.The software project consists of 3 major parts:

- Support for the custom MCW-1 board being designed by the Wireless Communications Group hardware department. This consists of porting the existing host (VxWorks) and multicomputer (MC/OS) software to the board, and adding code to support specialized features of the board such as LED control, voltage monitoring, hardware watchdogs, etc.
- Increasing the MTBF of the system by addition of high availability software. This software includes monitoring features such as watchdogs, fault detection/repair algorithms, and remote software download.
- Implementation of the application software. This includes optimal implementation of the MUD algorithms, as well as implementing degraded versions of the algorithm that can be executed when some of the computational hardware is unavailable due to failures.

Detailed information on the design of new software for the MCW-1 board can be found in the appropriate functional design documents, which are listed in the References section of this document.

2 Glossary

1. MTBF – Mean Time Between Failures
2. MUD – Multi User Detection. A class of algorithms to detect multiple interference sources and remove those effects from the signal.
3. Multicomputer – a parallel computer which achieves it's increase in performance by having more than one CPU working on the application simultaneously.
4. VxWorks – a proprietary real time operating system sold by Wind River, Inc.

3 Application Execution Environment

3.1 Overview

The purpose of the MUD application is to input raw antenna data from the base station modem card, detect sources of interference, produce a new stream of data which has had interference removed, and then output the data to the modem card for further processing.

Characteristics of this processing are are that it must have low latency (< 300 microseconds), and must deal with large amounts of data (> 110 million bytes of data per second), and must be very reliable.

The Mercury computer system is well suited to this kind of signal processing, exhibiting both very low latencies and high bandwidths.

Software Architecture of the MCW-1 MUD Board

83	The system hardware and software were not designed with high availability as
84	a goal, so reliability is in line with other standard computer systems designed for
85	commercial applications
86	Input data flows from the Modem Motherboard, over the PCI bus, through the
87	PXB++ bridge, onto the fabric, through the crossbar, and into the memory of the
88	computing elements. Output data flows in the opposite direction. Some data will
89	also flow between the 8240 Host CPU and the compute elements, via a similar
90	pathway, i.e. from the PCI bus through the PXB++ and thus onto the fabric.
91	Although the software tries to treat the system as if the hardware were
92	symmetric, as can be seen in the following figure, the host 8240 CPU is attached
93	via the PCI bus, not directly to the fabric.
94	
95	Error! Not a valid link.
96	**Figure 1**

97 **3.2 Operating System**

98	MC/OS was selected as the operating system for the MCW-1 board because it
99	provides the low latencies and high I/O and IPC bandwidths required for these
100	sorts of algorithms, and also because it already provides support for most of the
101	hardware being incorporated on the MCW-1 board.
102	The MUD application can be kept as portable as possible by minimizing the
103	use of non-POSIX MC/OS system calls, and encapsulating calls into proprietary
104	MC/OS interfaces such as DX.
105	MC/OS requires the presence of a host computer system, which in this case
106	will be a Motorola 8240 PowerPC processor running the VxWorks operating
107	system.

Application		Application
Watchdogs		Watchdogs
Fault Reporting		Fault Reporting
TCP/IP	DX/ICS	DX/ICS
VxWorks		MC/OS
H.A. Bootstrap		H.A. Bootstrap

Host
8240

Compute
Elements

108

109   **Figure 2**

110   *3.3 IPC*

111   The MC/OS DX subsystem will be used for IPC within the application. This
112   API provides low overhead, low latency access to the Mercury DMA engines,
113   which in turn provide high bandwidth transfers of data. DX will be used to move
114   data between the G4 compute elements during parallel processing, and also will
115   be used to move data between the MC/OS compute elements, the VxWorks host
116   computer, and the motherboard modem card.

117   *3.4 I/O*

118   Input / Output between the MUD card and the motherboard modem card takes
119   place by moving data between the Race++ Fabric and the PCI bus via the PXB++
120   bridge. The application will use DX to initialize the PXB++ bridge, and to cause
121   input/output data to move as if it were regular DX IPC traffic.
122   Discussions with the customer need to take place in order to determine exactly
123   how data flows over the PCI bus. For instance, it is currently unclear who will
124   initiate data transfers, and how the initiator will know which PCI addresses should
125   be involved in the transfer. A number of meetings with the customer are required
126   to resolve these issues.

Software Architecture of the MCW-1 MUD Board

127 **3.5 High Availability**

128   The approach to high availability on the MCW-1 card is to do most of the high
129 availability processing at a time when the application is not running. Specifically,
130 faults are handled by rebooting the system (fairly quickly). When the system
131 comes up, the application can determine which processing resources are available,
132 and it is up to the application to determine how to map its processing needs onto
133 the available resources.

134   This approach to high availability means that there are short interruptions in
135 service, but that the application does not need to know how to continue execution
136 across faults. For instance, the application can make the assumption that the
137 hardware configuration will not change without the system first rebooting.

138   If the application has state which needs to be preserved across reboots, the
139 application is responsible for checkpointing the data on a regular basis. The
140 system software will provide an API to a portion of the non-volatile RAM for this
141 purpose. It should be noted that the non-volatile RAM is quite small, and that
142 storage of more than a few hundred bytes of data will require another mechanism
143 to be put in place.

144 # 4 Operating System Environment

145 **4.1 Overview**

146   Mercury Computer Systems, Inc. has historically had the concept of a host
147 computer system. This dates back to the days when Mercury produced array
148 processors that were attached to customers' mainframe computers. The evolution
149 of Mercury multicomputers has left a vestigial host that often performs little more
150 service than as a bootstrap device for the multicomputer.

151   The host computer system survives in the MCW-1 design primarily as a way to
152 reduce schedule risk. The existence of a host computer system is assumed in so
153 many ways by the existing Mercury software, that it would add significant
154 schedule risk to attempt to remove this assumption in the MCW-1 timeframe.

155   In the MCW-1 board, the host system performs the following functions:
156 • It configures the Compute Elements, Fabric, and Bridges
157 • It loads executable code into the Compute Elements
158 • It serves as a bridge to the TCP/IP internetwork
159 • It serves as a file system daemon
160 • It runs some of the application software
161 • It manages some of the specialized high availability hardware

162 **4.2 Bootstrap**

163   The host computer system is based on a Motorola 8240 PowerPC processor on
164 the MCW-1 board. The 8240 is attached to an amount of linear flash memory.
165 This flash memory serves several purposes.

166   The first purpose the flash memory serves is as a source of instructions to
167 execute when the 8240 comes out of reset. **Linear** flash is flash which can be
168 addressed as if it was normal RAM. Flash memories can also be organized to look
169 like disk controllers; however in that configuration they require a disk driver to

Software Architecture of the MCW-1 MUD Board

170   provide access to the flash memory. Although such an organization has several
171   benefits such as automatic reallocation of bad flash cells, and write wear leveling,
172   it is not appropriate for initial bootstrap.
173   The flash memory also serves as a file system for the host (see Section 4.6),
174   and as a place to store board permanent information (such as a serial number).
175   Refer to the function design specification (TBS) for more details on how flash
176   memory is used.
177   When the 8240 first comes out of reset, memory is not turned on. Since high
178   level languages such as C assume some memory is present (for a stack, for
179   instance), the initial bootstrap code must be coded in assembler. This assembler
180   bootstrap should only be a few hundred lines of code, sufficient to configure the
181   memory controller, initialize memory, and initialize the configuration of the 8240
182   internal registers.
183   After the assembler bootstrap has finished execution, control is passed to the
184   MCW-1 H.A. code (which is also contained in boot flash memory). The purpose
185   of the H.A. code is to attempt to configure the fabric, and load the compute
186   element CPUs with H.A. code. Once this is complete, all the processors
187   participate in the H.A. algorithm. The output of the algorithm is a configuration
188   table which details which hardware is operational and which hardware is not. This
189   is an input to the next stage of bootstrap, the **Multicomputer Configuration**.

190   *4.3   Multicomputer Configuration*

191   MC/OS expects the host computer system to configure the multicomputer. The
192   configmc program reads a textual description of the computer system
193   configuration, and produces a series of binary data structures that describe the
194   computer system configuration. These data structures are used in MC/OS to
195   describe the routing and configuration of the multicomputer.
196   The MCW-1 board will use almost exactly the same sequence to configure the
197   multicomputer. The major difference is that MC/OS expects configurations to be
198   totally static, whereas the MCW-1 configuration will need to change dynamically
199   as faulty hardware cause various resources to be unavailable for use.
200   There are currently two proposals being considered for how this dynamic
201   reconfiguration takes place.
202   The first proposal is that the binary data structures produced by configmc are
203   modified to include flags that indicate whether a piece of hardware is usable or
204   not. A modification to MC/OS would prevent it from using hardware marked as
205   broken. The risk here is that the modifications to MC/OS may be non-trivial. The
206   benefit may be faster reboot times.
207   The second proposal is that the output of the H.A. algorithm is used to produce
208   a new configuration file input to configmc, the configmc execution is repeated
209   with the new file, and MC/OS is configured and loaded with no knowledge of the
210   broken hardware whatsoever. This proposal has the added benefit that configmc
211   may be able to calculate the most optimal routing tables in the face of failed
212   hardware, minimizing the performance impact of the failure on the remaining
213   components. This proposal provides risk reduction given that MC/OS changes
214   would not be required.

Software Architecture of the MCW-1 MUD Board

215 ## 4.4 Multicomputer Loading

216 After the host computer has configured the multicomputer, the **runmc** program
217 loads the functional compute elements with a copy of MC/OS. The only changes
218 required for the MCW-1 board is for the loading process to examine which
219 hardware may be offline because it is faulty, and take this into account when
220 determining which compute elements need to be loaded.

221 ## 4.5 TCP/IP Bridge

222 We believe that the customer is likely to require access to the MCW-1 board
223 from a TCP/IP network. MC/OS nodes do not contain a TCP/IP stack; therefore
224 the host computer system acts as a connection to the TCP/IP network. The
225 VxWorks operating system contains a fully functional TCP/IP stack. All currently
226 envisioned daemons that need access to the TCP/IP network will run on the host
227 processor. Should the need arise for compute elements to access network
228 resources, the host computer would have to act as a proxy, exchanging
229 information with the compute element utilizing DX transfers, and then making the
230 appropriate TCP/IP calls on behalf of the compute element.

231 ## 4.6 File System

232 The host computer system needs a file system to store configuration files,
233 executable programs, and MC/OS images. Rotating disks have insufficient MTBF
234 times; therefore flash memory will be utilized. Rather than have a separate flash
235 memory from the host computer boot flash, the same flash is utilized for both
236 bootstrap purposes and for holding file system data. A commercial flash file
237 system will be purchased and ported which provides DOS file system semantics
238 as well as write wear leveling. Wear leveling attempts to spread the number of
239 writes evenly across the sectors of flash memory, as flash memory can only be
240 written a finite number of times before it is worn out. Modern flash devices can be
241 written around 100,000 times before they are worn out.

242 ## 4.7 Remote Software Upgrade

243 The current design of the MCW-1 board assumes that the customer will want
244 to update system and application code in the field, via network. There are two
245 portions of code which need to be updated – the bootstrap code which is executed
246 by the 8240 processor when it comes out of reset, and the rest of the code which
247 resides on the flash file system as files.
248 When code is initially downloaded to the MCW-1, it is written as a group of
249 files within a directory in the flash file system. A single top level file keeps track
250 of which directory tree is used to boot the system. This file continues to point at
251 the existing directory tree until a download of new software is successfully
252 completed. When a download has been completed and verified, the top-level file
253 is updated to point to the new directory tree, the boot flash is rewritten, and the
254 system can be rebooted.
255 A possible problem in multi-board systems is how to deal with different
256 versions of released software on different boards. For instance, if board 1 has
257 revision 1.0 of the software distribution, and board 2 has revision 1.1 of the
258 software distribution, will the two versions work together, or will there be a way

259   to ensure that the same version of software is installed on all boards. This issue
260   does not occur on the MCW-1 because it is a single board solution; therefore this
261   issue can be addressed at a later time.
262   A commercial solution to remote software upgrade is available, and has been
263   ported to VxWorks. It is our intent to port this code at a future date.

264   # 5   High Availability

265   ## 5.1   Goals

266   The goal of the high availability features of the MCW-1 is to increase the
267   MTBF of the system as much as possible with little or no increase in cost to the
268   board. The requirement for minimal cost increase rules out such common
269   approaches as hot or cold standby, replicated hardware, etc.
270   It is not a goal to provide uninterrupted computing during hardware or software
271   failures, nor is it a goal to provide fault tolerance.

272   ## ~~1.2~~5.2   Fault Detection & Isolation

273   Fault detection is performed by having each CPU in the system gather as much
274   information about what it observed during a fault, and then comparing the
275   information in order to detect which components could be the common cause of
276   the symptoms. In some cases, it may take multiple faults before the algorithm can
277   detect which component is at fault. The requirement not to add expensive
278   hardware for fault detection means that in many cases the algorithm will not be
279   able to determine which component is at fault.
280   The MCW-1 board has many single points of failure. Specifically, everything
281   on the board is a single point of failure except for the compute elements. This
282   means that the only hard failures that can be configured out are failures in the
283   compute elements. However, many failures are transient or soft, and these can be
284   recovered from with a reboot cycle. Therefore, we expect the high availability
285   features to have a positive effect on the MTBF of the card.
286   More detailed information is available in the functional design specification
287   (1).

288   ## 5.3   Degraded Application

289   In the case of hard failures of a compute element, the application will have to
290   execute with reduced demand for computing resources. There are several
291   strategies possible for the MUD algorithm to decrease computing demands, such
292   as working with a smaller number of interference sources, or performing a less
293   complete job of interference cancellation.
294   We expect the computing requirements of the algorithm to be high enough that
295   failure of more than a single compute element will cause the board to be
296   inoperative. Therefore, the MCW-1 application only needs to handle two
297   configurations: all compute elements functional and 1 compute element
298   unavailable. We believe that a small amount of startup code can map the
299   application onto the two possible configurations. Note that the single crossbar
300   means that there are no issues as to which processes need to go on which
301   processors – the bandwidth and latencies for any node to any other node are

Software Architecture of the MCW-1 MUD Board

302   identical on the MCW-1. This will not be true of larger systems in the future, and
303   we will eventually need a way to map computing and I/O requirements onto
304   arbitrary hardware configurations.

305   **5.4   *Remote Software Upgrade***

306   Downtime due to the updating of software is counted against the availability of
307   a computer system, and therefore a remote reload of software is a necessity. The
308   MCW-1 is capable of downloading new software during normal operation. The
309   reboot strategy means that the downtime due to starting up new software is only a
310   few seconds.
311

312   **<u>Referenced Documents</u>**

313
314   1.   "MC/OS High Availability Functional Design Specification", Yevgeniy
315   Tarashchanskiy, 17 April, 2000.
316

Mercury Computer Systems

Wireless Communications

Hardware Engineering

MCW-1a Functional Specification
Memorandum #SRI-1
31 January 2001

Revision 3.00

This document was created using MS Word 97 and is located at
TBD

Notice: *If you are not viewing this document in electronic form at the above full path-name, it is not guaranteed to be the latest revision.*

MCW-1a Functional Specification   Created on 2/2/01

MCW-1a Functional Specification   Created on 2/2/01

- 3 –

Mercury Computer Systems, Inc.   COMPANY CONFIDENTIAL

1   REVISION HISTORY

Revision 0.0 - 3/17/00 Steven Imperiali
    Initial Entry

Revision 0.01 - 4/25/00 Steven Imperiali
    Minor corrections, filled in missing sections.

Revision 0.1 - 5/5/00 Steven Imperiali
    Incorporated review comments.

Revision 0.2 - 5/8/00 Steven Imperiali
    Incorporated review comments.
    Removed reference to RapidIO/Race++ bridge

Revision 0.21 - 5/16/00 Steven Imperiali
    Incorporated review comments.
    Modified MPC8240 memory map

Revision 0.22 - 5/26/00 Steven Imperiali
    Modified MPC8240 Memory Map

Revision 1.00 - 7/24/00 Steven Imperiali
    Modified MPC8240 Memory Map
    Updated memo with current design status

Revision 2.01 - 11/01/00 Steven Imperiali
    Modified power supply ramp requirements

Revision 2.02 - 11/15/00 Steven Imperiali
    Modified interrupt controller

Revision 2.03 - 1/26/01 Steven Imperiali
    Minor documentation corrections

Revision 3.00 - 1/31/01 Steven Imperiali
    Modified memo to reflect MCW-1a modules

2   REFERENCE DOCUMENTS

1.   American National Standard for RACEway Interlink (ANSI/VITA 5-1994)
2.   PCI Rev 2.2 Local Bus Specification
3.   PCE133 ASIC Hardware Specification
4.   XBAR++ Function Specification
5.   PXB++ PCI Bridge Functional Specification
6.   PowerPC 7400 PPC Microprocessor Hardware Specification
7.   Flash Memory Specification p/n TBD
8.   MCW-1 Product Definition Document (PDD) vTBD
9.   Technical brief of Mercury Computer Systems RACE++ series topologies
10. MPC8240 Users Manual (MPC8240UM/D 07/1999 Rev. 0)

MCW-1a Functional Specification   Created on 2/2/01
                                              - 5 -

Mercury Computer Systems, Inc.   COMPANY CONFIDENTIAL

3   MERCURY PART NUMBER

The board identifier name is MCW-1a and the Mercury part number is 560549.

Mercury Computer Systems, Inc.   COMPANY CONFIDENTIAL

4   FUNCTIONAL DESCRIPTION

4.1   OVERVIEW

The MCW-1a is designed to be an algorithm processing daughter card utilizing the MPC7400 PPC, MPC8240, PCE133 ASIC, XBAR++ ASIC, and PXB++ FPGA. The MCW-1mates with a Motorola base station modem board. MCW-1a can provide additional connectivity between processing elements in different sector slots utilizing over-the-top RACEway++ cables. It is a Motorola form factor card with four computational nodes and one host node. The computational nodes (CNs) are based on the latest MPC7400 PPC microprocessor and the host is an MPC8240. The MCW-1can provide one Ethernet 10/100 BT port on the front panel. A 32-bit, 66 MHz PCI interface provide the interface to the Motorola board.

The MCW-1a block diagram is shown in Figure 1.

MCW-1a Functional Specification   Created on 2/2/01

Mercury Computer Systems, Inc.   COMPANY CONFIDENTIAL

Figure 1.   MCW-1a BLOCK DIAGRAM

Mercury Computer Systems, Inc.   COMPANY CONFIDENTIAL

Figure 2 shows the MCW-1a system topology. Table 1 gives the proposed route codes for the board.

Figure 2.   MCW-1A BOARD-LEVEL TOPOLOGY

Table 1.   Route Codes for MCW-1a Board XBAR

Route Code	Destination for Virtual Ports	Physical XBAR 1 Ports
0		
1		
2		
3		
4		
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
15		

MCW-1a Functional Specification   Created on 2/2/01

Mercury Computer Systems, Inc.   **COMPANY CONFIDENTIAL**

4.2 FEATURES

- Custom size daughter card

- Master PCI 32-bit @ 66MHz compliant with REV2.2 PCI local bus spec.
  PCI write peak performance is 240 MB/sec.
  PCI read peak performance is 220 MB/sec.

- Single IEEE802.3 compliant Ethernet 10BASE-T//100BASE-T

- Four computation nodes (CNs) based on MPC7400 PPC running @ 400 MHz.
  1 MB L2 cache per CN @ 200 MHz to 266 MHz.
  128 MB SDRAM with ECC per CN @ 133 MHz.
  Hardware based watchdog monitor.
  One PCE133 ASIC per CN.

- Two, over-the-top, 66 MHz RACEway++ interlink ports
  configured in cable mode.

- PCI interface 32-bit @ 66 MHz.

- RACEway++ crossbar to connect nodes.

- PXB++ 64-bit @ 33 MHz PCI bus.

- Non-transparent 64-bit/33 MHz to 32-bit/66 MHz PCI bridge.

- 200MHz PPC8240 PowerPC processor.
  32-bit 33MHz PCI bus.
  100MHz, 64Mbytes SDRAM.

- Bulk FLASH interface.
  Linear address mode.
  32 banks of 1Mbytes.

- LEDs.

- 8Kbytes non-volatile SRAM.

- Real time clock.

- Compute node fault isolation control.

- JTAG test port.

Mercury Computer Systems, Inc.   **COMPANY CONFIDENTIAL**

4.3   CONFIGURATION OPTIONS

4.3.1   CPU Options
- MPC7400 @ 400 MHz.
- MPC7410 @ 400 MHz.

4.3.2   SDRAM Options
- 128 MB SDRAM @ 133 MHz with ECC.

4.3.3   FLASH Memory Options
- 16 MB FLASH memory.
- 32MB FLASH memory

4.3.4   Ethernet Options
- No Ethernet.
- Single Ethernet

MCW-1a Functional Specification   ,Created on 2/2/01

Mercury Computer Systems, Inc.   **COMPANY CONFIDENTIAL**

4.4 REQUIREMENTS

4.4.1 Mechanical Form Factor

The MCW-1a form factor conforms to TBD Motorola mechanical requirements.

4.4.2 Power Requirements

The MCW-1a requires +5.0 volts from the modem board. The +1.5V to +2.1V MPC7400 core voltage required by the core of MPC7400 is converted from +5.0V on the board. There are two core supplies used to power the four cpu cores. The 2.5V voltage required is converted from +5.0V by an onboard power supply. The 3.3V voltage required is also converted from +5.0V by an onboard power supply. The MCW-1a estimated typical power dissipation is 50 watts @ 5.0V.

4.4.3 Electrical Interface

The MCW-1a provides a PCI 32-bit, 66 MHz interface to the Motorola modem board via an 80-pin connector.

The MCW-1a provides two over-the-top RACEway++ ports via two connectors located on the front panel.

The MCW-1a provides the single Ethernet 10/100 BT interface available from one RJ-45 connector. The Ethernet interface is provided by a third party Ethernet-to-PCI interface controller chip that is bridged to the crossbar RACEway++ port by means of a PXB++ FPGA (See Figure 2).

4.4.4 Functional

1. Shall have the Main SDRAM memory at 133MHz or greater.
2. Shall have a 1Mbyte L2 Cache at 200MHz or greater.
3. All CE nodes shall have 128Mbyte of SDRAM.
4. Host node shall have at least 32Mbytes of nonvolatile memory.

Form factor requirements:

5. Shall be a daughter card that is ¾ of a Motorola proprietary form factor modem payload card sized 11" by 14". On 20mm centers board to board.{actual shape, dimensions etc TBD via drawings from Motorola.}
6. Shall be electrically a PMC module, TBD from further discussions with customer.
7. Shall use P1, P2 for 32/66MHz PCI bus.
8. Shall have a maximum heat dissipation of 50W

System requirements

9. A minimum of 105Mbyte/sec from the modem payload module to the MCW-1a card shall be provided through the PCI interface.
10. From the MCW-1a card to Motorola Modem Payload module output bandwidth shall be at least 200kbyte/sec, concurrent with the 105Mbyte/sec input.
11. The system shall have a bandwidth of at least 250Mbyte/sec between CE's, e.g. RACE++ at 66Mhz, as a minimum.
12. Shall have non-volatile memory, for at least 32Mbytes of data.
13. Shall support software upgrade from remote locations.

4.5 COMPATIBILITY

The MCW-1a board is a custom daughter card designed for the Motorola base station modem board.

4.6 PERFORMANCE

The PCI bus standard and the PXB++ FPGA limits the RACEway++ to the PCI performance. Peak transfers of 240 MB/sec are achievable between the PXB++, PPC8240 and the non-transparent PCI Bridge. (See Figure 1)

MCW-1a Functional Specification   Created on 2/2/01

Data transfers of up to 266 MB/sec peak are supported for access from RACEway++ to/from the MPC7400 CE's local SDRAM memory.

PCE133 ASIC-initiated DMA transfers run at optimum RACEway++ speeds approaching 266 MB/sec peak. Data can be transferred with the DMA from a single DMA command transfer to/from the CN's local SDRAM memory to/from RACEway++. The DMA engine formats transfers across RACEway++ optimally using packets up to 2048 Bytes.

The operating clock frequency of the PCE133 ASIC, SDRAM, and MPC7400 processor bus is 133 MHz. Likewise, the operating frequency for the RACEway++ is 66 MHz. The local PCI clock is used by the corresponding PXB++ FPGA and does not exceed 33 MHz.

A separate 25 MHz oscillator is included on the MCW-1a for driving the Ethernet interface.

4.7   DETAILED DESCRIPTION
The MCW-1a block diagram is shown in Figure 1.

4.7.1   Modem Board Interface
TBD (PCI 32-bit 66MHz).
TBD PCI to PCI bridge stuff.
TBD Motorola requirements.

4.7.2   Board Resets

There are several sources of reset to the daughter card. A MAX823 voltage supervisor will generate a 200ms reset after VCC rises above 4.38 volts. When the MAX823 reset is deasserted, state machine logic will monitor PCI_RESET_0. The state machine will continue driving RESET_0 until both the MAX823 and PCI_RESET_0 are deasserted. Either reset will generate the signal RESET_0 which will reset the card into its power-on state. RESET_0 will also generate the HRESET_0 and TRST signals to the five CPUs. HRESET_0 and TRST for each of the cpus can also be generated by their JTAG ports; JTAG_HRESET_0 and JTAG_TRST respectively. The MCP8240 is capable of generating a reset request, a soft reset (C_SRESET_0) to each CPU, a checkstop request, and a CE ASIC reset (CE_RESET_0) to each of the four CE ASICs. A discrete from the 5v powered reset PLD will generate the signal NPORESET_1 (not a power on reset). This signal is fed into the MPC8240's discrete input word. The MPC8240 will read this signal as a logic low only if it is coming out of reset due to either a power condition or an external reset from offboard. Each node, as well as the MPC8240 may request a board level reset. These requests are majority voted, and the result RESETVOTE_0 will generate a board level reset

Figure 3 shows the MCW-1a hard reset generation function

Figure 3.   HARD RESET FUNCTIONAL BLOCK DIAGRAM

MCW-1a Functional Specification   Created on 2/2/01
                                                    - 14 -

Mercury Computer Systems, Inc.   **COMPANY CONFIDENTIAL**

4.7.3 Watchdog Monitor

There are five independent watchdog monitors on the MCW-1a card. Each processor node is responsible for strobing its watchdog once every 20 msec (initial window after board level reset is 2 sec) but no sooner than 500 usec. Strobing the watchdog for the processing nodes is accomplished by writing a zero/one sequence to the DIAG3 discrete coming from the PC133PCE ASIC. The MPC8240's watchdog is serviced by writing to the memory mapped discrete location FFFF_D027. A single write of any value will strobe the watchdog. Upon power-on, the watchdogs come up in a failed state; once a valid strobe is issued; the watchdog will be satisfied. If the CPU fails to service the watchdog within the valid window, the watchdog will fail. A watchdog of a failing processing node will trigger an interrupt to the MPC8240. An MPC8240 watchdog fault will trigger a reset to the board. The watchdog will then remain in a latched failed state until a CPU reset occurs followed by a valid service sequence. Figure 4 shows a valid service sequences of the watchdog.

Figure 4. EXAMPLE WATCHDOG SERVICE SEQUENCES

4.7.4 Operating Frequency

The MPC7400 bus runs at 133 MHz. The L2 cache bus of the MPC7400 runs at 200 MHz to 266 MHz. The SDRAMs run at 133 MHz. The RACEway++ interface runs at 66 MHz. The local PCI bus runs at 33 MHz and the off board PCI runs at 66MHz. The MPC8240's internal frequency is 200 MHz while its SDRAM interface is 100 MHz.

4.7.4.1 Clock Margining

This card has two crystal oscillators for the three clock domains present on the card, a 66 MHz oscillator for the RACEway++ interface and MPC7400 CNs. The 66MHz frequency is divided in half to generate a 33 MHz signal for the PCI interface. A second oscillator, 25 MHz, clocks the Ethernet and watchdog circuitry. Both the PCI and MPC clocks are marginable. In order to provide clock margining, a 4-pin connector allows the test engineer to functionally disable the onboard oscillator and replace it with a test frequency. The pinout of this connector is detailed in Table 2.

MCW-1a Functional Specification   Created on 2/2/01

Mercury Computer Systems, Inc.   COMPANY CONFIDENTIAL

Table 2. Test Clock Connector

Pin	Signal
1	GND
2	/Test Clock
3	Test Clock
4	Test Clock Enable L

4.7.5 Serial Configuration EEPROM

There are several serial EEPROMs used to loadconfiguration to the CE ASICs, PXB++ and XBAR++ after reset. The serial PROM functionality can be found in the ASIC's functional specification.

4.7.5.1 CE ASIC Serial EEPROM

The serial EEPROM can be read and programmed by means of the RACEway++ bus. It is programmed during manufacture of the MCW-1a to contain configuration information for CE ASIC. The serial EEPROM AT24C128 is controlled from the CE ASIC. After reset, the CE ASIC automatically reads the first location from the serial EPROM. Refer to the CE ASIC functional specification, reference 3, for information on reading and writing this device.

4.7.5.2 PXB++ FPGA Serial EEPROM

The serial EEPROM can be read and programmed by means of the PCI bus or the RACEway++ bus. It is programmed during manufacture of the MCW-1a to contain configuration information for PXB. The serial EEPROM AT24C128 device is 128K bits and is controlled from the PXB++. After reset, the PXB++ automatically reads 8 KB from the serial EEPROM and initializes the PXB++ internal registers. Refer to the PXB++ FPGA functional specification, reference 5, for information on reading and writing this device.

4.7.5.3 XBAR++ ASIC Serial EEPROM

The serial EEPROM can be read and programmed by means of the RACEway++ bus. It is programmed during manufacture of the MCW-1a to contain configuration information for XBAR++. The serial EEPROM AT24C128 is controlled from the XBAR++ ASIC. After reset, the XBAR++ ASIC automatically reads from the serial EPROM and initializes the XBAR++ internal registers. Refer to the XBAR++ ASIC functional specification, reference 4, for information on reading and writing this device.

4.7.5.3.1 Register Description

Reference 4 f describes the registers of the XBAR++ ASIC.

4.7.6 RACEway++ Interconnect

Communication between all processing and I/O elements on the system card is provided by a Mercury eight-port crossbar XBAR++ ASIC. The XBAR++ provide up to three simultaneous 266 MB/sec peak throughput data paths between elements for a total peak throughput of 798 MB/sec. Three crossbar ports connect to the RapidIO Bridge FPGA. Each MPC7400 CN uses one crossbar port. The Ethernet and MPC8240 interface to a crossbar port through the PXB++. (See 0) Reference 4 describes the operation and registers of the XBAR++ ASIC.

4.7.7 Local PCI I/O Bus

The PXB++ FPGA provides the local PCI I/O bus. This bus is accessible by means of the RACEway++ from the processing nodes. All resources on this bus are initialized and controlled by the MPC8240. This bus provides access to an Ethernet controller, PCI to PCI transparent bridge and the PPC8240 host controller. Transfers from devices on this local PCI bus to and from devices on the RACEway++ can achieve 240 MB/sec for writes and 220 MB/sec for reads. These rates assume block transfers of reasonable size.

MCW-1a Functional Specification   Created on 2/2/01

Mercury Computer Systems, Inc. _____

4.7.7.1   PXB++ Program EEPROM

The PXB++ FPGA is programmed by an XC18V04 configuration EEPROM running in parallel mode. Configuration initiates when a power-on or board level reset occurs. Dividing the onboard 33MHz generates the configuration clock of 16.6MHz. The configuration EEPROM itself is onboard programmable through the JTAG scan chain.

4.7.7.1.1   Register Description

Reference 5 describes the registers of the PXB++ ASIC.

4.7.8   Ethernet Interface

The PCI-to-Ethernet interface uses the AM79C973 Pcnet-FAST III single chip 10/100 Mbps Ethernet controller. This device is equipped with a built in physical layer interface to achieve a minimal parts count Ethernet interface. A 25 MHz oscillator provides the proper clock frequency to the Ethernet chip. The PCI interrupt from the Ethernet chip is wired to the MPC8240's external interrupt controller.

4.7.9   MPC7400 or Nitro Computer Nodes (CNs)

The board contains four MPC7400 CNs. Each MPC CN uses a PCE133 ASIC to interface the cpu to RACEway++. The PCE133 ASIC provides all the standard features of a CN, such as a DMA engine, mail box interrupts, timers, RACEway++ page mapping registers, SDRAM interface, and so on. Local memory for each CN consists of 32, 64, or 128 MB SDRAM, and L2 cache SRAM. Each CN also has a nonvolatile SRAM and watchdog monitor. The cpu bus is 64-bit data, 32-bit address, and operates synchronously at 133 MHz.

4.7.9.1   Processor

The MCW-1a card is designed to use either the 400 MHz MPC7400 or the 400 MHz Nitro processors. The processor is packaged in a 25mm, 360-ball CBGA package. Each processor requires the attachment of a heat sink to keep it within its thermal limits.

4.7.9.2   MPC7400 L2 Cache

The MPC7400 L2 cache for each CN is composed of pipelined, single-cycle deselect, sync burst SRAM. This is implemented using two 64K, 128K, or 256K by 36-bit sync burst SRAM parts to make a 0.5 MB, 1 MB, or 2 MB L2 cache. MPC7400 L2 cache can be depopulated to 0 MB.

4.7.9.3   PCE133 ASIC

The MPC processor compute element ASIC (PCE133 ASIC) is a Mercury-designed component. It provides the interface between the MPC7400, the synchronous DRAM, and the RACEway++. All the PCE133 features such as DMA, mailbox interrupts, timers, address snooping, prefetch buffers, and so on, are available in this configuration. This chip is provided in a 35mm, 388-ball BGA package. Reference 3 describes the operation and registers of the PCE133 ASIC.

4.7.9.3.1   Register Description

Reference 3 describes the registers of the PCE133 ASIC.

4.7.9.4   Address Map

4.7.9.4.1   Master Address Map

Mercury Computer Systems, Inc.   **COMPANY CONFIDENTIAL**

Transfers from the MPC7400 to the PCE133 ASIC and RACEway++ are address mapped as shown in Table 3. The SDRAM is 8-, 16-, 32-, or 64-bit addressable. RACEway++ locked read/write and locked read transactions are supported for all data sizes. The 16 Mbyte boot FLASH area is further divided in Table 4

Table 3. Master Address Map

From Address	To Address	Function
0x0000 0000	0x0FFF FFFF	Local SDRAM 256 MB
0x1000 0000	0x1FFF FFFF	XBAR 256 MB map window 1
0x2000 0000	0x2FFF FFFF	XBAR 256 MB map window 2
0x3000 0000	0x3FFF FFFF	XBAR 256 MB map window 3
0x4000 0000	0x4FFF FFFF	XBAR 256 MB map window 4
0x5000 0000	0x5FFF FFFF	XBAR 256 MB map window 5
0x6000 0000	0x6FFF FFFF	XBAR 256 MB map window 6
0x7000 0000	0x7FFF FFFF	XBAR 256 MB map window 7
0x8000 0000	0x8FFF FFFF	XBAR 256 MB map window 8
0x9000 0000	0x9FFF FFFF	XBAR 256 MB map window 9
0xA000 0000	0xAFFF FFFF	XBAR 256 MB map window A
0xB000 0000	0xBFFF FFFF	XBAR 256 MB map window B
0xC000 0000	0xCFFF FFFF	XBAR 256 MB map window C
0xD000 0000	0xDFFF FFFF	XBAR 256 MB map window D
0xE000 0000	0xEFFF FFFF	XBAR 256 MB map window E
0xF000 0000	0xFBFF FBFF	Not used (CE reg replicated mapping)
0xFBFF FC00	0xFBFF FDFF	Internal CN ASIC registers
0xFBFF FE00	0xFEFF FFFF	Prefetch control
0xFF00 0000	0xFFFF FFFF	16 MB boot FLASH memory area

Table 4. Boot FLASH Address Map

From Address	To Address	Function
0xFF00 2006	0xFF00 2006	Software Fail Register
0xFF00 2005	0xFF00 2005	MPC8240 HA Register
0xFF00 2004	0xFF00 2004	Node 3 HA Register
0xFF00 2003	0xFF00 2003	Node 2 HA Register
0xFF00 2002	0xFF00 2002	Node 1 HA Register
0xFF00 2001	0xFF00 2001	Node 0 HA Register
0xFF00 2000	0xFF00 2000	Local HA Register (status/control)
0xFF00 0000	0xFF00 1FFF	NovRAM

4.7.9.4.2   Slave Address Map

Slave accesses are defined as accesses initiated by an external RACEway++ device directed toward the MPC7400 CN. The MPC is not accessible as a slave device. The SDRAM is 8-, 16-, 32-, or 64-bit addressable. RACEway++ locked read/write and locked read are supported for all data sizes. The PCE RACEway port supports a 256 MB address space partitioned as follows in Table 5:

Table 5.   Slave Address Map

From Address	To Address	Function
0x0000 0000	0x0FFF FBFF	256 MB less 1 KB hole SDRAM
0Xfff_FC00	0xFFF_FFFF	PCE133 internal registers

4.7.9.5   Interrupt

Reference 3 describes the internal interrupt sources for the PCE133 ASIC. The external interrupt pin on the PCE133 ASIC is driven by the HA PLD and is currently not used. The interrupt output from the PCE133 ASIC is wired to the CPU's external interrupt input pin.

MCW-1a Functional Specification   Created on 2/2/01
- 19 -

4.7.9.6   PCE133 DIAG Bits

The DIAG3 signal is wired to the HA PLD and is used to strobe the nodes hardware watchdog monitor. The DIAG2 signal is wired to the MPC8240's interrupt controller and is used, by the node, to generate a general purpose interrupt to the MPC8240. The DIAGBIT signal is wired to the HA PLD and is currently not used.

4.7.9.7   MPC7400 Reset

The MPC7400 hard reset signal is driven by three sources gated together: the HRESET_0 pin on the PCE133 ASIC, HRESET_0 from the JTAG connector, and HRESET_0 from the majority voter. The HRESET_0 pin from the CE ASIC is set by the "node run" bit field (bit 0) of the PCE133 ASIC's Miscon_A register. Setting HRESET_0 low causes the MPC7400 to be held in reset. HRESET_0 is low immediately after system reset or power-up, the MPC7400 is held in reset until the HRESET_0 line is pulled high by setting the node run bit to 1. The JTAG HRESET_0 is controlled by debugger software when a JTAG debugger module is connected to the card. The HRESET_0 from the majority voter is generated by a majority vote from all healthy nodes to reset.

4.7.9.8   Boot Procedures

When a cpu reset is asserted, the MPC7400 is put into reset state. The MPC7400 will remain in a reset state until the RUN bit 0 of the Miscon_A register is set to 1 and the MPC8240 has released the reset signals in the discrete output word. The RUN bit should be set to 1 after the boot code has been loaded into the SDRAM starting at location 0x0000_0100. The ASIC maps the reset vector 0xFFF0_0100 generated by the MPC7400 to address 0x0000_0100.

4.7.9.9   MPC7400 CN SDRAM

The main memory for each CN is composed of one bank of synchronous DRAM. This is implemented using five K4S280832A-TC/L75 @133 MHz synchronous DRAM parts. As shown in the memory map (See Table 3), the main memory begins at address 0x0 and grows upward in the address space as memory is increased. The PCE133 ASIC supports error correction (ECC) on the SDRAM.

The SDRAM operates as zero wait state memory and can provide up to 1 GB/sec peak bandwidth on writes from MPC7400 and 800 MB/sec peak bandwidth on read from the MPC7400. ECC error correction is supported.

4.7.9.10   MPC7400 Non-Volatile RAM

Each node will be equipped 8Kx8 of non-volatile RAM for the storage of fault record data and configuration information. This function is implemented using a SIMTEK STK12C68S45 NOVRAM attached to the PCE133 ASIC's boot FLASH interface. The data bus of the device is isolated from the PCE ASIC through an IDT IDTQS32244SO buffer. This buffer provides loading isolation and 3.3v to 5v translation.

4.7.10   MPC8240 Host Controller

The MPC8240 integrated processor is comprised of a peripheral logic block and a 32-bit embedded MPC603e PowerPC processor core. The peripheral logic integrates a PCI bridge, memory controller, DMA controller, EPIC interrupt controller, a message unit, and an I2C controller. The processor core is a full featured, high-performance processor with floating-point support, memory management, 16Kbytes instruction cache, 16Kbytes data cache, and power management features.

Major features of the MPC8240 are as follows:

Peripheral logic

- Memory interface
> High-bandwidth bus, 64-bit data bus, to SDRAM.
> ECC Protected SDRAM
> 16 Mbytes of ROM space (32Mbytes paged).
> 8-bit ROM.
> Write buffering for PCI and processor accesses.

- PCI Interface
> 32-bit PCI interface operating at 33 MHz (66 MHz capable).
> PCI 2.1-compatible.
> Support for accesses to all PCI address spaces.
> Selectable big- or little-endian operation.
> Store gathering of processor-to-PCI write and PCI-to-memory write accesses.
> PCI bus arbitration unit (five request/grant pairs).

- Two-channel integrated DMA controller
> Supports direct mode or chaining mode (automatic linking of DMA transfers).
> Supports scatter gathering read or write discontinuous memory.
> Interrupt on completed segment, chain, and error.
> Local-to-local memory.
> PCI-to-PCI memory.
> PCI-to-local memory.
> Local-to-PCI memory.

- Message unit
> Two doorbell registers.
> Inbound and outbound messaging registers.
> I 2 O message controller.

- I 2 C controller with full master/slave support

- Embedded programmable interrupt controller (EPIC)
> Five hardware interrupts (IRQs) or 16 serial interrupts.
> Four programmable timers.

- Integrated PCI bus and SDRAM clock generation

- Programmable memory and PCI bus output drivers

- Debug features
> Memory attribute and PCI attribute signals.
> Debug address signals.
> MIV signal: Marks valid address and data bus cycles on the memory bus.
> Error injection/capture on data path.
> IEEE 1149.1 (JTAG)/test interface.

Processor core

- High-performance, superscalar processor core
> Integer unit (IU).
> Foating-point unit (FPU) (user enabled or disabled).
> Load/store unit (LSU).
> System register unit (SRU).
> Branch processing unit (BPU).

MCW-1a Functional Specification   Created on 2/2/01

Mercury Computer Systems, Inc.   **COMPANY CONFIDENTIAL**

- 16-Kbyte instruction cache
- 16-Kbyte data cache
- Lockable L1 cache - entire cache or on a per-way basis
- Dynamic power management

4.7.10.1 Address Map

The MPC8240 in PCI host mode supports two address mapping configurations designated as address map A, and address map B. Address map A conforms to the PowerPC reference platform (PReP) specification. Address map B conforms to the PowerPC microprocessor common hardware reference platform (CHRP). Note that the support of map A is provided for backward compatibility only. It is strongly recommended that new designs use map B because map A may not be supported in future devices.

Address map B complies with the PowerPC microprocessor common hardware reference platform (CHRP). The address space of map B is divided into four areas: system memory, PCI memory, PCI I/O, and system ROM space. When configured for map B, the MPC8240 translates addresses across the internal peripheral logic bus and the external PCI bus as shown in Table 6.

Table 6.   **MPC8240 Address Map B**

Processor Core Address Range				PCI Address Range	Definition
Hex		Decimal			
0000_0000	0009_FFFF	0	640K - 1	NO PCI CYCLE	System memory
000A_0000	000F_FFFF	640K	1M-1	000A_0000 – 000F_FFFF	Compatibility hole
0010_0000	3FFF_FFFF	1M	1G-1	NO PCI CYCLE	System memory
4000_0000	7FFF_FFFF	1G	2G-1	NO PCI CYCLE	Reserved
8000_0000	FCFF_FFFF	2G	4G-48M-1	8000_0000 – FCFF_FFFF	PCI memory
FD00_0000	FDFF_FFFF	4G-48M	4G-32M-1	0000_0000 – 00FF_FFFF	PCI/ISA memory
FE00_0000	FE7F_FFFF	4G-32M	4G-24M-1	0000_0000 – 007F_FFFF	PCI/ISA I/O
FE80_0000	FEBF_FFFF	4G-24M	4G-20M-1	0080_0000 – 00BF_FFFF	PCI I/O
FEC0_0000	FEDF_FFFF	4G-20M	4G-18M-1	CONFIG_ADDR	PCI configuration address
FEE0_0000	FEEF_FFFF	4G-18M	4G-17M-1	CONFIG_DATA	PCI configuration data
FEF0_0000	FEFF_FFFF	4G-17M	4G-16M-1	FEF0_0000 – FEFF_FFFF	PCI interrupt acknowledge
FF00_0000	FF7F_FFFF	4G-16M	4G-8M-1	FF00_0000 – FF7F_FFFF	32/64-bit FLASH/ROM (1)
FF80_0000	FFFF_FFFF	4G-8M	4G-1	FF80_0000 – FFFF_FFFF	8/32/64-bit FLASH/ROM (2)

Notes:
(1) This bank of FLASH is not used.
(2) This bank of FLASH is configured in 8-bit mode and is further broken down in Table 7.

Table 7.   **Port X Address Map**

MCW-1a Functional Specification   Created on 2/2/01

Bank Select	Processor Core Address Range		Definition
11111	FFE0_0000	FFEF_FFFF	Accesses Bank 0
11110 - 00001	FFE0_0000	FFEF_FFFF	Application code (1) (30 pages)
00000	FFE0_0000	FFEF_FFFF	Application/boot code (1), (2)
	FFF0_0000	FFFF_CFFF	Application/boot code (2)
	FFFF_D000	FFFF_D000	Discrete input word 0
	FFFF_D001	FFFF_D001	Discrete input word 1
	FFFF_D002	FFFF_D002	Discrete output word 0
	FFFF_D003	FFFF_D003	Discrete output word 1
	FFFF_D004	FFFF_D004	Discrete output word 2
	FFFF_D010	FFFF_D010	IC (Pending interrupt)
	FFFF_D011	FFFF_D011	IC (Interrupt mask low)
	FFFF_D012	FFFF_D012	IC (Interrupt clear low)
	FFFF_D013	FFFF_D013	IC (Unmasked, pending low)
	FFFF_D014	FFFF_D014	IC (Interrupt input low)
XXXX (3)	FFFF_D015	FFFF_D015	Unused (read FF)
	FFFF_D016	FFFF_D016	Unused (read FF)
	FFFF_D017	FFFF_D017	Unused (read FF)
	FFFF_D018	FFFF_D018	Unused (read FF)
	FFFF_D019	FFFF_D019	Unused (read FF)
	FFFF_D020	FFFF_D020	HA (Local HA register)
	FFFF_D021	FFFF_D021	HA (Node 0 HA register)
	FFFF_D022	FFFF_D022	HA (Node 1 HA register)
	FFFF_D023	FFFF_D023	HA (Node 2 HA register)
	FFFF_D024	FFFF_D024	HA (Node 3 HA register)
	FFFF_D025	FFFF_D025	HA (8240 HA register)
	FFFF_D026	FFFF_D026	HA (Software Fail)
	FFFF_D027	FFFF_D027	HA (Watchdog Strobe)
	FFFF_D028	FFFF_DFFF	4068 Bytes FLASH
	FFFF_E000	FFFF_FFFF	8K NOVRAM

Notes:
(1) Thirtyone 1Mbyte blocks of application memory residing at address FFE0_0000 – FFEF_FFFF selected by the FLASH page bits.
(2) 2Mbyte block available after reset.
(3) Always available

4.7.10.2   Register Description
Reference 10 describes the registers of the MPC8240.

4.7.10.3   Interrupt

The MPC8240 contains an embedded programmable interrupt controller (EPIC) device. The EPIC implements the necessary functions to provide a flexible and general-purpose interrupt controller solution. The EPIC pools hardware-

generated interrupts from many sources, both within the MPC8240 and externally, and delivers them to the processor core in a prioritized manner. The solution adopts the OpenPIC architecture (architecture developed jointly by AMD and Cyrix for SMP interrupt solutions) and implements the logic and programming structures according to that specification. The MPC8240's EPIC unit supports up to five external interrupts, four internal logic-driven interrupts and four timers with interrupts. See Reference 10 for a detailed description of the EPIC unit.

The five external interrupt inputs to the EPIC are wired to the external interrupt controller PLD.

4.7.10.4   MPC8240 Reset
The MPC8240 can be reset from three sources: a board level reset (RESET_0), JTAG controlled reset, or a failure in it's watchdog monitor. Any reset to the MPC8240 shall cause the discrete output registers to reset (low) state, this in turn, will cause all G4 nodes to enter the reset state.

4.7.10.5   Boot Procedure
After the release of reset to the MPC8240, it will begin executing code out of the FLASH memory. A reset will automatically set the FLASHSEL(4:0) bits to all zero's, therefore, the MPC8240's boot code must reside in bank 0. Once it's application code is copied to SDRAM, the MPC8240 can then sequence through the FLASH banks by setting the appropriate bits in the discrete output word. Application code for the G4 nodes resides in the remaining thirtyone banks of FLASH.

4.7.11   Bulk FLASH Memory
There are 32Mbytes of bulk FLASH memory, comprised of two Intel 28F128J3 StrataFLASH memory devices. The MPC8240's memory map limits the size of the 8-bit wide FLASH to 2Mbytes, this requires hardware to divide the FLASH into thirty-two 1Mbyte banks. Five software-controlled discretes allow switching between banks. Accesses to the 1Mbyte address range of FFE0_0000 through FFEF_FFFF will always access the first first block of FLASH, NOVRAM,Discrete I/O, HA registers, watchdog monitor, and the interrupt controller. Accesses to the 1Mbyte address range of FFF0_0000 through FFFF_FFFF will access a page of memory in the FLASH. The actual page is selected is based on the five FLASH select bits, driven by the Discrete Output word.

4.7.12   Real Time Clock
The PCF8563 is a CMOS real-time clock/calendar optimized for low power consumption. A programmable clock output, interrupt output and voltage-low detector are also provided. All addresses and data are transferred serially via a two-line bidirectional I 2 C-bus. Maximum bus speed is 400 kbits/s.

Real Time Clock Features:
   - Provides year, month, day, weekday, hours, minutes and seconds
         (Based on an external 32.768 kHz quartz crystal)
   - Century flag
   - Wide operating supply voltage range: 1.0 to 5.5 V
   - Low back-up current; typical 0.25 mA at VDD = 3.0 V and Tamb =2 °C
   - 400 kHz two-wire I 2 C-bus interface (at VDD = 1.8 to 5.5 V)
   - Programmable clock output for peripheral devices: 32.768 kHz, 1024 Hz, 32 Hz and 1 Hz
   - Alarm and timer functions
   - Voltage-low detector
   - Integrated oscillator capacitor
   - Internal power-on reset
   - I 2 C-bus slave address: read A3H; write A2H
   - Open drain interrupt pin

4.7.13   NonVolatile Memory
The MPC8240 will be equipped with 8Kx8 of non-volatile RAM for the storage of fault record data and configuration information. This function is implemented using a SIMTEK STK12C68S45 NOVRAM attached to the local bus

MCW-1a Functional Specification   Created on 2/2/01

interface. The device's data bus is isolated from the local bus through an IDT IDTQS32244SO buffer. This buffer provides 3.3v to 5v translation.

4.7.14 Fault Status and Control Registers

The MPC8240 has access to five 8-bit status registers. One register represents its own status while the others represent that fault status of the other four G4 CPUs. Each register has the identical format as shown in Table 8:
These five registers grant the MPC8240 status information from each node on the board, without going through the Raceway fabric.

The MPC8240 will have one 8-bit Fault control register. The control register for each CPU will have the following format as shown in Table 9:

Bit	Name	Description
0	CHECKSTOP_OUT	Checkstop state of CPU (0 = CPU in checkstop)
1	WDM_FAULT	WDM failed (0 = WDM failed, set high after reset and valid service)
2	SOFTWARE_FAULT	Software fault detected (Set to 0 when a software exception was detected) **(R/W local)**
3	RESETREQ_IN	Wrap status of the local CPU's reset request
4	WDM_INIT	WDM failed in initial 2 second window (0 = WDM failed)
5	Software definable 0	Software definable 0
6	Software definable 1	Software definable 1
7	unused	unused

Table 8. Fault Status Register Format

Bit	Name	Description
0	RESETREQ_OUT_0	Request a reset event (0 => forces reset)
1	CHKSTOPOUT_0	Request that node 0 enter checkstop state (0 => request checkstop)
2	CHKSTOPOUT_1	Request that node 1 enter checkstop state (0 => request checkstop)
3	CHKSTOPOUT_2	Request that node 2 enter checkstop state (0 => request checkstop)
4	CHKSTOPOUT_3	Request that node 3 enter checkstop state (0 => request checkstop)
5	CHKSTOPOUT_8240	Request that the MPC8240 enter checkstop state (0 => request checkstop)
6	Software definable 0	Software definable 0
7	Software definable 1	Software definable 1

Table 9. Fault Control Register Definition

4.7.15 Majority Voter

There are two different functions controlled by majority voters. The first is local to each CPU, this voter controls the assertion of CHECKSTOP_IN to the CPU. The second voter is centralized to the board, it will control the master reset to the board. Both voters shall follow the same set of rules: The output will follow the majority of non-checkstopped CPUs. A 1-on-1 or 2-on-2 condition in either voter will result in a board level reset.

Mercury Computer Systems, Inc. COMPANY CONFIDENTIAL

4.7.16 Discrete I/O
There are 16 discrete output signals directly controllable and readable by the MPC8240. The 16 discretes are divided up into two addressable 8-bit words. Writing to a discrete output register will cause the upper 8-bits of the data bus to be written to the discrete output latch. Reading a discrete output register will drive the 8-bit discrete output onto the upper 8-bits of the MPC8240's data bus. Table 10 defines the bits in the discrete output word.

There are 16 discrete input signals accessible by the MPC8240. Reads from the discrete input address space will latch the state of the signals, and return the latched state of the discretes to the MPC8240. Table 11 defines the bits in the discrete input word.

Mercury Computer Systems, Inc.   COMPANY CONFIDENTIAL

Table 10.   Discrete Output Words

Word 2		
DH(0:7)	**Signal**	**Description**
0	ND0_FLASH_EN_1	Enable the CE ASIC's FLASH port when 1
1	ND1_FLASH_EN_1	Enable the CE ASIC's FLASH port when 1
2	ND2_FLASH_EN_1	Enable the CE ASIC's FLASH port when 1
3	ND3_FLASH_EN_1	Enable the CE ASIC's FLASH port when 1
4	Wrap 1	Wrap to discrete input
5		
6		
7		

Word 1		
DH(0:7)	**Signal**	**Description**
0	WRAP0	Wrap to Discrete Input
1	I2C_RESET_0	Reset the I2C serial bus when 0
2	SWLED	Software controlled LED
3	FLASHSEL4	Flash bank select address bit 4
4	FLASHSEL3	Flash bank select address bit 3
5	FLASHSEL2	Flash bank select address bit 2
6	FLASHSEL1	Flash bank select address bit 1
7	FLASHSEL0	Flash bank select address bit 0

Word 0		
DH(0:7)	**Signal**	**Description**
0	C_SRESET3_0	Issue a Soft Reset to cpu on Node 3 when 0
1	C_PRESET3_0	Reset PCE133 ASIC Node 3 when 0
2	C_SRESET2_0	Issue a Soft Reset to cpu on Node 2 when 0
3	C_PRESET2_0	Reset PCE133 ASIC Node 2 when 0
4	C_SRESET1_0	Issue a Soft Reset to cpu on Node 1 when 0
5	C_PRESET1_0	Reset PCE133 ASIC Node 1 when 0
6	C_SRESET0_0	Issue a Soft Reset to cpu on Node 0 when 0
7	C_PRESET0_0	Reset PCE133 ASIC Node 0 when 0

Table 11.   Discrete Input Words

Word 1		
DH(0:7)	**Signal**	**Description**
0	WRAP1	Wrap from discrete output word
1	TBD	
2	V3.3_FAIL_0	Latched status of power supply since last reset
3	V2.5_FAIL_0	Latched status of power supply since last reset
4	VCORE1_FAIL_0	Latched status of power supply since last reset
5	VCORE0_FAIL_0	Latched status of power supply since last reset
6	RIOR_CNF_DONE_1	RIO/RACE++ FPGA configuration complete
7	PXB0_CNF_DONE_1	PXB++ FPGA configuration complete

DH(0:7)	Signal	Word 0 Description
0 1 2 3 4 5 6 7	WRAP0 WDMSTATUS NPORESET_1	Wrap from discrete output word MPC8240's watchdog monitor status (0 = failed) Not a power on reset when high

4.7.17 Interrupt Controller

The MPC8240 interfaces with an 8-input interrupt controller external from MPC8240 itself. The interrupt inputs are wired, through the controller to interrupt zero of the MPC8240 external interrupt inputs. The remaining four MPC8240 interrupt inputs are unused.

The Interrupt Controller comprises the following five 8-bit registers;

Pending Register - A low bit indicates a falling edge was detected on that interrupt (read only)
Clear Register - Setting a bit low will clear the corresponding latched interrupt (write only)
Mask Register – Setting a bit low will mask the pending interrupt from generating an MPC8240 interrupt
Unmasked Pending Register – A low bit indicates a pending interrupt that is not masked out
Interrupt State Register – indicates the actual logic level of each interrupt input pin

4.7.17.1 Interrupt Controller Operation

Table 12 lists the interrupt input sources and their bit positions within each of the six registers. A falling edge on an interrupt input will set the appropriate bit in the pending register low. The pending register is gated with the mask register and any unmasked pending interrupts will activate the interrupt output signal to the MPC8240's external interrupt input pin. Software will then read the unmasked pending register to determine which interrupt(s) caused the exception. Software can then clear the interrupt(s) by writing a zero to the corresponding bit in the clear register. If multiple interrupts are pending, the software has the option of either servicing all pending interrupts at once and then clearing the pending register or servicing the highest priority interrupt (software priority scheme) and the clearing that single interrupt. If more interrupts are still latched, the interrupt controller will generate a second interrupt to the MPC8240 for software to service. This will continue until all interrupts have been serviced. An interrupt that is masked will show up in the pending register but not in the unmasked pending register and will not generate an MPC8240 interrupt. If the mask is then cleared, that pending interrupt will flow through the unmasked pending register and generate an MPC8240 interrupt.

Table 12.   Interrupt Controller Inputs

Bit	Signal	Description
0	SWFAIL_0	8240 Software Controlled Fail Discrete
1	RTC_INT_0	Real time clock event
2	NODE0_FAIL_0	WDFAIL_0 or IWDFAIL_0 or SWFAIL_0 active
3	NODE1_FAIL_0	WDFAIL_0 or IWDFAIL_0 or SWFAIL_0 active
4	NODE2_FAIL_0	WDFAIL_0 or IWDFAIL_0 or SWFAIL_0 active
5	NODE3_FAIL_0	WDFAIL_0 or IWDFAIL_0 or SWFAIL_0 active
6	PCI_INT_0	PCI interrupt
7	XB_SYS_ERR_0	XBAR internal error

4.7.18   Configuration Jumpers

J18-1 – J18-2, the watchdog monitor mask, when installed, will mask all watchdog failures.

J18-3 – J18-4, the serial EEPROM's write enable jumper, when installed, enables modification of the serial EEPROMs.

J18-5 – J18-6, the flash write-protect jumper, when installed, prevents modification of any flash memory location.

J18-7 – J18-8, the PXB0 use PROM jumper, when installed will enable the PXB0's serial configuration PROM.

4.7.19   LEDs
There are nine LEDs, visible at the top of the board.

LD1 is a software controlled LED
LD2 is a software controlled LED
LD3 is the Node 0 watchdog fail LED
LD4 is the Node 1 watchdog fail LED
LD5 is the Node 2 watchdog fail LED
LD6 is the Node 3 watchdog fail LED
LD7 is the MPC8240 watchdog fail LED
LD8 indicates the state of the board level reset
LD9 indicates a XBAR system error.

There are an additional two LEDs on the Ethernet connector for Ethernet status (located on the Ethernet connector).

4.7.20   Power Supply
The MCW-1a board requires 3.3V, 2.5V, and 1.8V. There are two 1.8V supplies, each drives the core voltage for two cpus. To provide power to the MCW-1a, the three voltages must have separate switching supplies, and proper power sequencing to the device must be provided. All three voltages are converted from 5.0V. The power to the daughter card is provided directly from the modem board.

4.7.20.1   MPC7400 Core Power Supply
There are two core voltage power supplies, each one is dedicated to two MPC7400 PPC cores. The core voltage can be in the 2.2V to 1.5V range. This power supply is rated at 12A in the range from 2.2V to 1.5V.

4.7.20.2   Main 3.3V Power Supply
A 3.3V power supply is used to provide power to the SBSRAM core, SDRAM, SCSI, PXB++, and XBAR++ PCE133 I/O. This power supply is rated at TBD Amp.

4.7.20.3   Core and I/O 2.5V Power Supply
A 2.5V power supply is used to provide power to the PCE133 and can also power the PXB++ FPGA core. The MPC7400 processor bus can run at 2.5V signaling. The MPC7400 L2 bus can operate at 2.5V signaling. This 2.5V power supply is rated at TBD Amp.

4.7.20.4   ASICs Power Supplies Tolerance Requirements
SBSRAM VDD = 3.3V+0.165V/-0.165V power supply
SBSRAM VDDQ = 3.3V+0.165V/-0.165V for 3.3V I/O or 2.5V+0.4V/-0.125V for 2.5V I/O
SDRAM VDD= 3.3V+0.3V/-0.3V power supply
XBAR++ VDD= 3.3V+0.3V/-0.3V power supply
PCE133 VDD= 2.5V+?V/-?V power supply
PCE133 VDD33= 3.3V+?V/-?V power supply

MCW-1a Functional Specification   Created on 2/2/01
                                                  - 29 –

4.7.20.5   Power Supply Voltage Sequencing

The power sequencing is very important in multivoltage digital boards. It is necessary for long-term reliability. The right power supply sequencing can be accomplished by using *power_good* and *inhibit* signals. To provide fail-safe operation of the device, power should be supplied so that if the core supply fails during operation, the I/O supply is shut down as well.

The general rule is to ramp all power supplies up and down at the same time. This is shown in Figure 5. In reality, ramp up and down depend on multiple factors: power supply, total board capacities that need to be charged, power supply load, and so on. Figure 6 shows ideal worst-case sequencing for ramp up and down that is performed by the protection sequencing circuits shown in Figure 7. This circuit keeps the voltage difference within the required range.
The MPC7400 requires the core supply to not exceed the I/O supply by more than 0.4 volts at all times. Also, the I/O supply must not exceed the core supply by more than 2 volts.

Figure 5.   IDEAL POWER SUPPLY SEQUENCING

Figure 6.   REAL POWER SUPPLY SEQUENCING

3.3V   2.5V   1.8V_1

MCW-1a Functional Specification   Created on 2/2/01
                                            - 30 -

Mercury Computer Systems, Inc.

Figure 7. VOLTAGE SEQUENCING CIRCUITS

0.7V voltage drops across one diode.

During power up sequencing:
D1 and D2 provide the ramp up voltage for the 2.5V power supply as soon as the 3.3V power supply reaches 1.4V.
D3 and D4 provide the ramp up voltage for the 1.8V_1 power supply as soon as the 2.5V power supply reaches 1.4V.
D7 and D8 provide the ramp up voltage for the 1.8V_2 power supply as soon as the 2.5V power supply reaches 1.4V.

During power down sequencing:
D5 provides the ramp down for the 2.5V power supply as soon as the 3.3V power supply reaches 1.8V.
D6 provides the ramp down for the 1.8V_1 power supply as soon as the 2.5V power supply reaches 1.1V.
D9 provides the ramp down for the 1.8V_2 power supply as soon as the 2.5V power supply reaches 1.1V.

The 3.3V power supply is connected to the VCC3P3 power plane.
The 2.5V power supply is connected to the VCC2P5 power plane.
The 1.8V_1 power supply is connected to the VCC1P8_1 power plane.
The 1.8V_2 power supply is connected to the VCC1P8_2 power plane.

4.7.20.6 Power Supply Monitoring

A PLD is used to monitor the voltage status signals from the onboard supplies. It is powered up from +5V and monitors +3.3V, +2.5V, 1.8V_1 and +1.8V_2. This circuit monitors the *power_good* signals from each supply. In the case of a power failure in one or more supplies, the PLD will issue a restart to all supplies and a board level reset to the daughter card. A latched power status signal will be available from each supply as part of the discrete input word. The latched discrete shall indicate any power fault condition since the last off-board reset condition.

5   ELECTRICAL INTERFACE

5.1.1   Power Consumption

Table 13.   MCW-1a CN Power Consumption

Description	Qty	Total Typ. Power	Total Max. Pwr.
CE ASIC	1	1W	1.5W
SDRAM	5	3W	3.5W
SBSRAM	2	1.2W	2.5W
G4	1	8W	12W
Oscillator	1	0.1W	0.1W
PLD	1	0.15W	0.2W

TBD

Table 14.   MCW-1a Power Consumption

TBD

5.1.2   I/O

5.1.2.1   Over-the-Top RACEway++ Interlink
See Appendix A for the over-the-top RACEway++ interlink connector pinout.

5.1.2.2   PCI 32-Bit Modem Connector
See Appendix B for the PCI 32-bit modem connector pinout.

5.1.2.3   Ethernet 10/100BT
See Appendix C for the Ethernet 10/100 BT connector pinout.

5.1.2.4   PPC Debugger
See Appendix D for the PPC Debugger connector pinout.

6   MECHANICAL

6.1.1   Packaging
The MCW-1is a dual-side PCB assembly. The board is designed to be used in a custom system. The MCW-1PCB is TBD thick and TBD layers.

6.1.2   Physical Constraint
The PCB board must comply with the Motorola daughter card form factor.

7   ENVIRONMENTAL

7.1.1   Temperature & Air Flow
Operating temperature: TBD
Storage temperature: TBD

7.1.2   Humidity
TBD

7.1.3   Operating Altitude
TBD

7.1.4   Shock & Vibration
TBD

7.1.5   Compliance
TBD

7.1.6   Reliability
TBD

8   SWITCHES & JUMPERS

8.1   J22 Jumper
Provisional Hotswap switch interface for the PXB0.

J22 Ref. Des.	Jumper Function
1 – 2	PXB0_HS_HNDL_SW high
2 – 3	PXB0_HS_HNDL_SW low

8.2   J11 Jumper
Raceway clock master selection

J11 Ref. Des.	Jumper Function
1 – 2 (open)	MCW-1A Master
1 – 2 (shorted)	MCW-1A Slave

Mercury Computer Systems, Inc.   **COMPANY CONFIDENTIAL**

8.3 J10 Jumper
F1 Raceway XBREQI – XBREQO crossover.

J10 Ref. Des.	Jumper Function
3 – 4, 5 – 6	Straight through
1 – 2, 7 - 8	Crossover

8.4 J4 Jumper
F2 Raceway XBREQI – XBREQO crossover.

J4 Ref. Des.	Jumper Function
3 – 4, 5 – 6	Straight through
1 – 2, 7 - 8	Crossover

8.5 J3 Jumper
F2 Raceway CBL_CLK_O – CBL_CLK_I crossover.

J3 Ref. Des.	Jumper Function
3 – 4, 5 – 6	Straight through
1 – 2, 7 - 8	Crossover

8.6 J9 Jumper
F1 Raceway CBL_CLK_O – CBL_CLK_I crossover.

J9 Ref. Des.	Jumper Function
3 – 4, 5 – 6	Straight through
1 – 2, 7 - 8	Crossover

8.7 J18 Jumper
Miscellaneous control

J18 Ref. Des.	Jumper Function
1 – 2	WDM fail disable
3 – 4	Serial PROM write enable
5 – 6	FLASH write enable
7 – 8	PXB0 use configuration PROM
9 – 10	Unused

8.8 J21 Jumper
Master clock source selector

J21 Ref. Des.	Jumper Function
1 – 2	F1 cable port master
3 – 4	F2 cable port master
Both closed	MCW-1A master
Both open	MCW-1A master

9 TESTABILITY

MCW-1a Functional Specification   Created on 2/2/01

Mercury Computer Systems, Inc.   COMPANY CONFIDENTIAL

9.1   JTAG Test Scan

The MPC7400, MPC8240, PCI-PCI bridge, PCE133 ASIC, PXB++ ASIC, XBAR++ ASIC, and the Ethernet controller provide support for the IEEE Standard 1149.1 test port (JTAG). Refer to the individual component specifications to obtain their JTAG test access port (TAP) descriptions.

The MCW-1a board contains several JTAG scan chains. They provide access to the JTAG test port on the MPC7400s, MPC8240, L2 caches, XBAR++, PCE133s, Ethernet, PCI-PCI bridge, and the PXB devices. The scan chain is defined as;
Chain 1 -> MPC7400_1
Chain 2 -> MPC7400_2
Chain 3 -> MPC7400_3
Chain 4 -> MPC7400_3
Chain 5 -> MPC8240
Chain 6 -> RESET_PLD, PCEFIX1_PLD, NODE0_HA_PLD, NODE1_HA_PLD, PCEFIX2_PLD, NODE2_HA_PLD, NODE3_HA_PLD, 8240_DECODE_PLD, VOTER_SYNC_PLD, 8240_HA_PLD, PXB_PROM, L2 Cache_1, PCE133_1, L2 Cache_2, PCE133_2, XBAR, L2_Cache_3, PCE133_3, L2 Cache_4, PCE133_4, PXB++, PCI-PCI Bridge, Ethernet

The scan path is accessible via connector J16. The enable for the scan chain buffer is controlled by jumper J20.

The RACEway++ interlink external connectors will be tested with external loop-back connectors.

Note: Both the RACEway++ clock (66 MHz) and the PCI clock (33 MHz) must be running to allow the scan path in the PXB to function properly.

10   RACEway++ Over-the-Top Connector Pinout

Table 15.   RACEway++ F1 Cable Mode Connector Pinout J-1

Pin	Signal	Pin	Signal
A1	GND	B1	CLK_X_JX1_IO
A2	GND	B2	JX1_CBL_CLK_IO
A3	GND	B3	JX1_XBREQ_I
A4	GND	B4	JX1_XBREQ_O
A5	GND	B5	JX1_XBSTROBIO
A6	GND	B6	JX1_XBRPLYIO
A7	GND	B7	JX1_XBRDCONIO
A8	GND	B8	JX1_XBIO00
A9	GND	B9	JX1_XBIO01
A10	GND	B10	JX1_XBIO02
A11	GND	B11	JX1_XBIO03
A12	GND	B12	JX1_XBIO04
A13	GND	B13	JX1_XBIO05
A14	GND	B14	JX1_XBIO06
A15	GND	B15	JX1_XBIO07
A16	GND	B16	JX1_XBIO08
A17	GND	B17	JX1_XBIO09
A18	GND	B18	JX1_XBIO10

Mercury Computer Systems, Inc. COMPANY CONFIDENTIAL

A19	GND	B19	JX1_XBIO11
A20	GND	B20	JX1_XBIO12
A21	GND	B21	JX1_XBIO13
A22	GND	B22	JX1_XBIO14
A23	GND	B23	JX1_XBIO15
A24	GND	B24	JX1_XBIO16
A25	GND	B25	JX1_XBIO17
A26	GND	B26	JX1_XBIO18
A27	GND	B27	JX1_XBIO19
A28	GND	B28	JX1_XBIO20
A29	GND	B29	JX1_XBIO21
A30	GND	B30	JX1_XBIO22
A31	GND	B31	JX1_XBIO23
A32	GND	B32	JX1_XBIO24
A33	GND	B33	JX1_XBIO25
A34	GND	B34	JX1_XBIO26
A35	GND	B35	JX1_XBIO27
A36	GND	B36	JX1_XBIO28
A37	GND	B37	JX1_XBIO29
A38	GND	B38	JX1_XBIO30
A39	JX1_XBPAR	B39	JX1_XBIO31
A40	+3.3V	B40	R_RST_JX

Table 16. RACEway++ F2 Cable Mode Connector Pinout J-2

Pin	Signal	Pin	Signal
A1	GND	B1	CLK_X_JX2_IO
A2	GND	B2	JX2_CBL_CLK_IO
A3	GND	B3	JX2_XBREQ_I
A4	GND	B4	JX2_XBREQ_O
A5	GND	B5	JX2_XBSTROBIO
A6	GND	B6	JX2_XBRPLYIO
A7	GND	B7	JX2_XBRDCONIO
A8	GND	B8	JX2_XBIO00
A9	GND	B9	JX2_XBIO01
A10	GND	B10	JX2_XBIO02
A11	GND	B11	JX2_XBIO03
A12	GND	B12	JX2_XBIO04
A13	GND	B13	JX2_XBIO05
A14	GND	B14	JX2_XBIO06
A15	GND	B15	JX2_XBIO07
A16	GND	B16	JX2_XBIO08
A17	GND	B17	JX2_XBIO09
A18	GND	B18	JX2_XBIO10
A19	GND	B19	JX2_XBIO11

Mercury Computer Systems, Inc.   **COMPANY CONFIDENTIAL**

A20	GND	B20	JX2_XBIO12
A21	GND	B21	JX2_XBIO13
A22	GND	B22	JX2_XBIO14
A23	GND	B23	JX2_XBIO15
A24	GND	B24	JX2_XBIO16
A25	GND	B25	JX2_XBIO17
A26	GND	B26	JX2_XBIO18
A27	GND	B27	JX2_XBIO19
A28	GND	B28	JX2_XBIO20
A29	GND	B29	JX2_XBIO21
A30	GND	B30	JX2_XBIO22
A31	GND	B31	JX2_XBIO23
A32	GND	B32	JX2_XBIO24
A33	GND	B33	JX2_XBIO25
A34	GND	B34	JX2_XBIO26
A35	GND	B35	JX2_XBIO27
A36	GND	B36	JX2_XBIO28
A37	GND	B37	JX2_XBIO29
A38	GND	B38	JX2_XBIO30
A39	JX2_XBPAR	B39	JX2_XBIO31
A40	+3.3V	B40	R_RST_JX

MCW-1a Functional Specification   Created on 2/2/01
- 37 –

Mercury Computer Systems, Inc.   COMPANY CONFIDENTIAL

11 Modem Board Connector Pinout

Table 17.   Modem Board Connector Pin Assignments

J29			
Pin	Signal	Signal	Pin
1	5V	PMC_AD0	2
3	5V	PMC_AD1	4
5	5V	PMC_AD2	6
7	5V	PMC_AD3	8
9	PCI_RST_0	PMC_AD4	10
11	GND	PMC_AD5	12
13	GND	PMC_AD6	14
15	PMC_IDSEL_1	PMC_AD7	16
17	5V	PMC_AD8	18
19	5V	PMC_AD9	20
21	PMC_TRDY_0	PMC_AD10	22
23	GND	PMC_AD11	24
25	GND	PMC_AD12	26
27	PMC_STOP_0	PMC_AD13	28
29	5V	PMC_AD14	30
31	5V	PMC_AD15	32
33	PMC_PERR_0	PMC_AD16	34
35	GND	PMC_AD17	36
37	GND	PMC_AD18	38
39	PMC_SERR_0	PMC_AD19	40
41	5V	PMC_AD20	42
43	5V	PMC_AD21	44
45	CLK_PMC	PMC_AD22	46
47	GND	PMC_AD23	48
49	GND	PMC_AD24	50
51	PMC_C_BE0	PMC_AD25	52
53	PMC_C_BE1	PMC_AD26	54
55	5V	PMC_AD27	56
57	5V	PMC_AD28	58
59	PMC_C_BE2	PMC_AD29	60
61	PMC_C_BE3	PMC_AD30	62
63	GND	PMC_AD31	64
65	GND	5V	66

MCW-1a Functional Specification   Created on 2/2/01

Mercury Computer Systems, Inc.   COMPANY CONFIDENTIAL

67	GND	PMC_FRAME_0	68
69	PMC_INTA_0	GND	70
71	GND	PMC_IRDY_0	72
73	GND	5V	74
75	PMC_GNT_0	PMC_DEVSEL_0	76
77	5V	PMC_LOCK_0	78
79	PMC_REQ_0	PMC_PAR	80

MCW-1a Functional Specification   Created on 2/2/01
- 39 –

Mercury Computer Systems, Inc.   COMPANY CONFIDENTIAL

12 Processor JTAG Connector Pinout

The JTAG connectors are unique to each processor. Table 18 shows the generic signal names on each connector pin, the actual names will have each processor's extension appended to the generic signal name.

Table 18.   JTAG Jx Connectors Pin Assignments

Jx-	SIGNAL	Jx-	SIGNAL
1	TDO	2	QACKN
3	TDI	4	TRSTN
5	HALTEDN	6	3.3V
7	TCK	8	CKSTOP_INN
9	TMS	10	N.C.
11	SRESETN	12	N.C.
13	HRESETN	14	<<key>>
15	CKSTOP_OUTN	16	GND

MCW-1a Functional Specification   Created on 2/2/01

13 Non-Processor JTAG Connector Pinout

The non-processor JTAG connector ties together all the remaining JTAG capable devices together. Table 18 shows the signal names on each connector pin. The connector is designed to only include the programmable PLDs and PROM when the program cable is installed, or the entire chain when the Boundary scan test connector is installed.

Table 19.   JTAG J16 Connectors Pin Assignments

J16-	Signal	Description
1	TMS_JTAG	JTAG Test Mode Select
2	TDI_JTAG	JTAG Test Data In
3	TDO_JTAG	Boundary Scan Test Data Out
4	TESTN	Driven low when connector inserted
5	TCK_JTAG	JTAG Test Clock
6	GND	Ground on module
7	PXB_CNF_TDO	TDO from end of PLD chain
8	TDI_NDO	TDI into non-PLD Chain
9	+5V	+5V Power on Module
10	TEST	Driven high when connector inserted

Figure 8.   JTAG CONNECTOR CONFIGURATION OPTIONS

14 Design Notes

14.1 MPC7400 and Nitro Bus Signaling Voltage Support

	1.8V	2.5V	3.3V
MPC7400 V 60x	Yes	Yes	Yes
MPC7400 V L2	Yes	Yes	Yes
Nitro V 60x	Yes	Yes	No
Nitro V L2	Yes	Yes	No
PCE133 V 60x	No	Yes	No
SBSRAM Vi/o	No	Yes	Yes

14.2 Bypass Capacitors Selection
(Based on App. Note from Micron TN-00-06)

Vcore = 3.3V +/- 0.165V, which is 5%
Vi/o = 2.5V +/- 0.125V, which is 5%

When the SBSRAMs are driving 21pf load from 0V to 2.5V with 1ns edges, the transient current is:

$I = (C * dV)/dt = (30pf*2.5V)/1ns = 75ma$ per one I/O pin.

For 36 I/O, 36*75ma = 2.7A in 1ns time interval.

The SyncBurst SRAM has a VDD tolerance of 3.3V +/-0.165V. Considering some droop from the power bus and a switching time of 1 ns, and allowing a maximum voltage dip (DV) on the SRAM of -0.05V, the choice of bypass capacitor becomes:

$C = (1 * dt)/dV = (2.7A * 1)/0.05 = 54nF$ per one SBSRAM.

Choosing 6 x 10nf allows some margin.
It is better to use reverse ratio capacitors 0508, 0406, or 0204.
The low ESR is also very important.
Temperature stable dielectric as X7R.
From Vishay VJ0402 style X7R.

14.3 Tantalum Capacitors Selection
Ultra-low ESR tantalum capacitors T510 are used in the switching power supply, besides several bulk storage capacitors distributed around the PCB that feed Vcore and Vi/o plains, to enable quick recharging of the bypass chip capacitors. The number of the bulk-storage tantalum capacitors depends on the power supply response time characteristic.

The MPC7400 can go from nap mode to full-on mode power within two cycles.

$I core = (10W - 2W)/1.8V = 4.5A$
$dt = 10\mu s$

$C = (1 * dt)/dV = (4.5A * 10\mu s) / 0.05V = 900\mu F$

MCW-1a Functional Specification   Created on 2/2/01

Computer Systems, Inc.

MERCURY

MEMORANDUM

TO	
FROM	Alden Fuchs
ABOUT	**Preliminary Framework interface**
	Memorandum # AF-4
VERSION	V0.2
DATE	8 December, 2000
COPIES TO	

DISTRIBUTION

1. Introduction

This is a very brief description of the prototype framework and how to use it. The purpose of this memo is to describe the software interfaces from within a transform object.

The above figure depicts the software architecture, and the transform object is a part of the Application that is managed by the Application framework.

MEMO AF-4
Prototype Framework V0.1

1.1. Transform Object
The transform object is the basic building block and can be like a Turbo-coder, QAM modulator etc.

1.2. Red-Box
The red-box collects transform objects into a logical grouping that describes all of the processing that will be carried out on a single CPU.. (Note for reasons of non real-time operation eg simulation collections of red-boxes can be on a single CPU).

MEMO AF-4
Prototype Framework V0.1

2. Transform Object Sample

2.1. Include the following files to define the interface, and variables required..

#include "mc_error.h"
#include "mcw1.h"
#include "dx_dma.h"
#include "dx_dma_var.h"

2.1.1. The contents of dx_dma_var.h:

```
int my_logical_ce;
CONFIG_data *ptr_config_base;
CONFIG_data *ptr_cur_config;
CONFIG_data *ptr_tmp_config;

int active_in_ce[(MAX_CE+1) * MAX_CHAN];
int active_in_ch[(MAX_CE+1) * MAX_CHAN];
int active_in_buf_size[(MAX_CE+1) * MAX_CHAN];
char *active_in_buf[(MAX_CE+1) * MAX_CHAN];
int active_in_index;

int active_out_ce[(MAX_CE+1) * MAX_CHAN];
int active_out_ch[(MAX_CE+1) * MAX_CHAN];
int active_out_buf_size[(MAX_CE+1) * MAX_CHAN];
char *active_out_buf[(MAX_CE+1) * MAX_CHAN];
int active_out_index;

#define  dma_send_pin(pin) \
    dma_send(                      \
            my_logical_ce,       \
            active_out_ce[pin],  \
            active_out_ch[pin],  \
            (char **)&active_out_buf[pin] \
            )

#define dma_rec_pin(pin) \
    dma_rec(                       \
            active_in_ce[pin],   \
            my_logical_ce,       \
            active_in_ch[pin],   \
            (char **)&active_in_buf[pin] \
            )
```

2.2. Initialize the interface

// get config SMB

```
  dma_all_init(
    my_logical_ce,
    active_in_ce,
    active_in_ch,
    active_in_buf_size,
```

```
        active_in_buf,
        (int *)&active_in_index,
        active_out_ce,
        active_out_ch,
        active_out_buf_size,
        active_out_buf,
        (int *)&active_out_index,
        (CONFIG_data **)&ptr_config_base
                );
  ptr_cur_config = &ptr_config_base[my_logical_ce];
#ifdef debug_print
        printf("Vir CE %i, module name is %s\n",
my_logical_ce,ptr_cur_config->module_name);
#endif
  ptr_cur_config->state = STATE_RDY; /* all init done now ready */
//wait for rx to be ready
ptr_tmp_config = &ptr_config_base[active_out_ce[0]];
while (ptr_tmp_config->state != STATE_RDY) //need reciver to be ready
                                        sched_yield();

//wait for tx to be ready
ptr_tmp_config = &ptr_config_base[active_in_ce[0]];
while (ptr_tmp_config->state != STATE_RDY) //need reciver to be ready
                                        sched_yield();

#ifdef debug_print
  printf("\nCE %i, Virtual CE %i, Starting\n",(int)ce_getid(),my_logical_ce);
#endif
```

2.3. Receive input

Receive input data if required, input pins can be left unused.

2.3.1. An Example of the receiving of data from input pin 0

```
    /* get data from other CE */
    rc = dma_rec_pin(0);
    ERROR_MCW1(rc);
```

OR

```
rc = dma_rec(
    active_in_ce[0],
    my_logical_ce,
    active_in_ch[0],
    (char **)&active_in_buf[0]
    );
ERROR_MCW1(rc);
```

MEMO AF-4
Prototype Framework V0.1

The data is available in the active_in_buf pointer,, note this always points to the next available input buffer in the case of multi-buffering,, at a later date the size of input chunk and offset will be provided so that a FIFO like structure can be used.

2.4. Send Output

Send output data if required, output pins can be left unused.

2.4.1. An Example of the sending data on output pin 0

```
/* send data to other CE */
rc = dma_send_pin(0);
ERROR_MCW1(rc);
```

OR

```
rc = (long)dma_send(
  my_logical_ce,
  active_out_ce[0],
  active_out_ch[0],
  (char **)&active_out_buf[0]
  );
ERROR_MCW1(rc);
```

The data in the active_out_buf pointer will be sent, on return this always points to the next available output buffer in the case of multi-buffering. At a later date the size of output chunk and offset will be provided so that a FIFO like structure can be used.

3. Transforms for WCDM Simulation:

3.1. handset (one of n):

This object has two input pins and one output pin. It performs the:

1. Generate transport channel
2. MUX and channel coding
3. Generate TX waveform
4. Simulate RX system for Power control etc.
5. Outputs to the chan model

3.1.1. input pins:

3.1.1.1. power_control pin 0 :

Input to this pin is from output pin 0 of the rake block and is the slot power control.

3.1.1.2. next_chunk pin 1:

Input to this pin is from output pin 1 of the BER block and is the send next n symbols for processing e.g. 2 symbols, or a slot etc.

3.1.1.3. next_chunk pin 1:

Optional input pin, used to provide external ie outside of the Generate traffic channel bits, access to the raw data input ie if we did a codec the output of the codec would go into this block.

3.1.2. Output pins:

3.1.2.1. signal_out pin 0 :

This pin goes to one input pin of the chan object group.

3.1.2.2. raw_bits pin 1:

This pin has the raw data bits as encoded into the Data channel so that the BER, BLER calculations can be done.

3.2. Chan (set of one to m objects):

In this group of objects, each has; two to n input pins; and one output pin each. They collectively perform the:

1. Channel model for each of the inputs except the carry pin
2. Sums the local signals, and adds the carry input pin
3. Outputs to the front_end object to send same data to all rake inputs

3.2.1. Input pins:

3.2.1.1. sum_in pin 0 :

Input to this pin is from output pin 0 of other channel object, currently a dummy input is required on this pin for the process to fire (needs more thought ie a special first chan??).

3.2.1.2. signal_in pin 1 to n:

Input to this pin is from output pin 0 of the handset block.

8 of 11

3.2.2. Output pins:

3.2.2.1. signal_out pin 0 :
This pin goes to input pin 0 of the broadcast object.

3.3. front_end (one object):

In this object, each has; one input pin; and one output pin. It performs the:

1. ~~Adds the multiple antenna, and other~~Receiver distortions and noise
2. Simulate RX system (AGC, A/D, multiple antennas) etc.
3. Outputs to the broadcast object to send same data to all rake inputs

Multiple antennas should be treated as separate data streams. The rake receiver will process them independently, until the MRC stage.

3.3.1. Input pins:

3.3.1.1. signal_in pin 0 :
Input to this pin is from output pin 0 of the last channel object.

3.3.2. Output pins:

3.3.2.1. signal_out pin 0 to n:
This pin goes to input pin 0 of the broadcast objects.

3.4. broadcast (set of one to k objects):

This object is required to simulate broadcast, until the simple framework supports this feature, we need this object.

Each object in the group has one input pin and one to n output pins. They collectively perform the:

1. Takes one input and copies it to all of the output pins un-modified
2. Outputs same data to all rake input 0 pins.

3.4.1. Input pins:

3.4.1.1. signal_in pin 0 :
Input to this pin is from output pin 0 of the front_end object.

3.4.2. Output pins:

3.4.2.1. signal_out pin 0 to n:
This pin goes to input pin 0 of the rake objects.

3.5. Rake (one of n):

This object has one input pin and two output pins. It performs the:

1. ~~AGC,~~ AFC
2. Initial signal acquisition and ~~s~~Searcher ~~receiver~~~~RX~~
3. Multiple finger receivers~~Rx~~

MEMO AF-4
Prototype Framework V0.1

4. Channel estimation, MRC etc.
5. Final data channel despreading.
5.6.   Outputs to:
   - MUD group of processes
   - Soft-decision symbol processing (FEC decoding and demultiplexing (25.212)

3.5.1. Input pins:

3.5.1.1. signal_in pin 0 :
This is the data from the broadcast set, and carries the signals of all the handsets, and noise etc.

3.5.2. Output pins:

3.5.2.1. power_control pin 0 :
This is the slot power control to be sent back to the handset.

3.5.2.2. signal_out pin 0 :
This pin goes to one input pin of the MUX object group.

3.6. MUX (set of one to L objects):
This object is required to gather and package information from the 1 to n rake objects. The inputs are placed into packets(???) or into arrays (???) To Be Determined (TBD). This object should be morphed into the best approximation of the packaging to be provided by a targeted modem.

Each object in the group has one to n input pins and one output pin. They collectively perform the:

1. Package rake information into simulated modem sourced data.
2. Outputs to MUD input 0 pin (for now until MUD integration there will be a dummy placeholder block).

3.6.1. Input pins:

3.6.1.1. signal_in pin 0 to L:
Input to this pin is from output pin 1 of the a rake object, or another MUX objects output pin 0 .

3.6.2. Output pins:

3.6.2.1. signal_out pin 0 :
This pin goes to input pin 0 of the rake objects.

3.7. MUD (one object for now):
This object is required to place hold until a real mud is implemented.

MUD has one input pin and one output pin.

1. Passes through data and formats it for the BER block
2. Outputs to BER input 0 pin.

3.7.1. Input pins:

3.7.1.1. signal_in pin 0 :
Input to this pin is from output pin 0 of the MUX object.

3.7.2. Output pins:

3.7.2.1. signal_out pin 0 :
This pin goes to input pin 0 of the BER object.

3.8. BER (set of one to m objects):
This object is required to gather and package information from the 1 to n handset objects and the MUD. The inputs are placed into packets(???) or into arrays (???) To Be Determined (TBD).
This object should be morphed into the best approximation of the packaging to be required by a targeted modem. It also compares the raw input data and raw received data. It also does the FEC detection and correction and Block error rate.

Each object in the group has one to n input pins and one to n+1 output pins. They collectively perform the:

1. Package rake/MUD information into simulated modem destination data.
2. Perform all of the bit level processing, interleaving, FEC, -- This should be in a separate block.
3. BER, BLER etc. BLER should be done via the CRC check, after all symbol decoding is performed.
3.4. Outputs to GUI input 0 pin to display the stats.
4.5. Outputs the generate the next slot command to the one to n handsets.

3.8.1. Input pins:

3.8.1.1. signal_in pin 0 to m:
Input to this pin is from output pin 0 {for now until MUD integrated} of the MUD object, or another output pin 0 of a BER object.

3.8.2. Output pins:

3.8.2.1. stats_out pin 0 :
This pin goes to input pin 0 of the host object for display of data on the GUI.

3.8.2.2. next_slot pin 1 (one of n):
This pin goes to input pin 1 of the handset object to indicate the system is ready for the next slot of data.

From: Jon Greene <greene@mc.com>
To: "Lauginiger, Frank" <fpl@mc.com>, <joates@mc.com>, <afuchs@mc.com>, <mvinskus@mc.com>
Date: 6/23/00 3:05PM
Subject: Some MUD analysis

All:

Obviously, I've been thinking about MUD a lot. Below is some analysis.

First, some news. We apparently have 400 Mhz, 2 meg / 266 Mhz L2 Nitros in house (samples). Vitaly is presently working to bring them up. This is excellent news. Besides the above speed/size properties, Nitros use significantly lower power than Max's and allow for varying L2 configuration options. Nitro L2's can be configured the normal way (as a cache) or all or half (1 meg) as SRAM memory and can be addressed as such directly. For example, one can write a buffer into this memory with vmov or, better yet, as the output of some computation. I'm not sure if it could be the source or target of a RACEway xfer but we should try to find this out. Even if configured as a coherent cache, it can be easily locked and unlocked in user mode. I think configuring as 2 meg of SRAM may work the best for MUD but we should determine this empirically.

Now, a critical analysis of ops, buffer sizes, bandwidth, access patterns, algorithm structure and phases of the moon, are all essential to arriving at a strategy that stands a chance of working. This of course is not easy because various techniques impact all of the above in unequal ways. Let's just consider the R1/R1m R-matrix processing on the above Nitro with a maximum of 100 users. *Without* taking advantage of the diagonal symmetry in the Corr matrix, which I now believe will be very difficult to do in the R-matrix ucoded processing loop(s) (we should discuss this), but still assuming Corr *can* effectively exist as a byte matrix without degrading accuracy beyond acceptability, a single plane (i.e., a processor's worth) of the Corr matrix requires 200 * 200 * 32 = 1,280,000 bytes which fits, albeit uncomfortably, into the L2. At 2 gigabytes/sec (~ 266 * 8), this matrix (if L2 resident) can theoretically be consumed in 0.64 ms (remember, 1.33 ms. is our budget). Now, *if* we go with a completely separate X matrix calculation without stripmining *and* we also store it as byte values, it would require at most 100 * 100 * 32 = 320,000 bytes. This must be entirely produced and consumed in the 1.33 ms. time slice. In *theory*, this can be done in 0.32 ms. Finally, the R1_temp output is of size 200 * 200 = 40,000 bytes and can be produced in .02 ms. So, with the fully separate X matrix approach and no symmetry in the Corr, we theoretically require ~1,750,000 bytes of buffer size (I added a little more for stray stuff such as the C vectors and the phys <=> virt Luts, etc.) and ~1.0 ms. to produce and consume these buffers. If we stripmined X, which seems a better way to go, we could hopefully keep it resident in L1, thereby reducing L2 buffers to ~1,350,000 bytes and 0.7 ms of L2 I/O. The stripmining also allows us the option of keeping the X strip as shorts rather than bytes.

Now lets consider the ops count. For the R1/R1m processing (including the generation of the X matrix and 2 antennas), I come up with (2 * 6 * 100 * 100 * 16 + 4 * 200 * 200 * 16) * 750 = (1920,000 + 2,560,000) * 750 = 3.36 GOPS. (BTW, if you were wondering, 750 = 1000/1.33.) The R0 processing has less GOPS due to the symmetry. I get (1920,000 + 2,560,000/2) * 750 = 2.40 GOPS. Since the R0 and R1/R1m processing use the same X matrix, we may be

tempted to consider having only the R0 processor compute the X matrix and ship it to the R1/R1m processor. This looks nice from a GOPS perspective (R0 = 2.40, R1/R1m = 1.92) but I'm not sure it will work very well given the lockstep nature of the processing pipe. For example, will the R1/R1m processor simply be idle waiting for the X matrix or will it be completing the "prior" R1_temp processing while the R0 processor is computing the current X?

But the real killer about having R0 ship X to R1/R1m is that the X matrix (320,000 bytes) will take at least 1.23 ms. over RACE++ (320,000/260,000,000). And let's not forget the 40,000 byte R_temp output matrix that has to also be shipped out in the same time frame. So I don't think this OPs balancing approach will work.

We therefore appear to require 3.36 GOPS out of R1/R1m and we might just not even bother with the R0 symmetry since it doesn't buy you very much given that mpic needs both R0 and R1/R1m as inputs. In other words, have both R-matrix processors run essentially the same code. (Will this work?)

Now 3.36 GOPS out of one processor is a tall order. We may have to resort to a more asymmetric division of labor (The R0 processor takes advantage of the R0 symmetry and also does a portion of R1/R1m). But, I'd like to pursue the more balanced division until we are absolutely sure it won't work.

It this approach, both the R0 and R1/R1m processors independently produce and consume X in strips. A variant could instead produce and consume a single "value" (actually 32 shorts) of X in a single ucode primitive that does both the complex multiplies and the dot products (the MUDder of all primitives). The former is certainly the easier approach and might get us all the way there but the latter, if it can be cleverly coded, may perform better. In all cases, the ops don't change but at least the L2 gets some breathing room.

In any event, the so-called dot-product loop, whether it's separate or includes the complex multiply, still remains a difficult piece of code to fully optimize if we allow the number of virtual to physical users to vary as MUD (and Dr. Oates) demands. Using a LUT to acquire the index list and count of virtual users for a given physical user will tend to throttle the dot product code due to short vector lengths, funny address calculations, and "random" load and store patterns. The load isn't so bad since it's two cache lines no matter where it comes from. We may want to reorder Corr anyway just to ease the address arithmetic and DST logic. We could also simply store in the order we produce and leave it to the mpic processor to reorder (poor guy). As for the short vector count, I think this can be overcome with a clever primitive that "pauses" as little as possible between index lists but this will take some careful design.

I think we should try for the "balanced" stripmine approach with essentially the same two primitives running in each processor. In the absence of dissenting views, I will continue modifying the C code to realize this structure. I'm still not sure where the Amp/fac_xx multiply(s)/shift(s) belong but for now I'll rid them entirely from the R-matrix functions that I'm preparing for ucoding.

    - Jon

CC: "Kenny , Jamie" <jfk@mc.com>

Computer Systems, Inc.

MERCURY

199 Riverneck Road
Chelmsford, MA 01824-2820
(978) 256-1300 • Fax (978) 256-3599
http://www.mc.com

Report

To: Wireless Communications Group

From: J. H. Oates

Subject: Channel Estimation   Date: October 20, 2000

1. Introduction

In the conventional RAKE receiver, channel amplitude[1] estimation is required for maximal ratio combining the RAKE fingers. The BER performance is not strongly dependent on the accuracy of the channel amplitude estimates. For Multi-User Detection (MUD) the channel amplitude estimates are used for signal subtraction, and accuracy of the channel amplitude estimates is more critical. In addition, the channel estimation error is larger when MUD is used since channel estimation is performed in a higher interference environment. This report investigates the accuracy of the conventional channel amplitude estimation techniques under elevated multiple access interference. The effect of channel amplitude estimation error on MUD efficiency is then assessed. The analysis presented here is intended to be a first-look. There are a number of ways to increase the channel amplitude estimation accuracy. A few of these are discussed below.

Section 2 presents a model for the received signal and match-filter outputs. The effect of channel estimation error on MUD efficiency is addressed in section 3. In section 4 the accuracy of the conventional channel amplitude estimates is assessed. In section 5 improved single-user methods are presented for channel amplitude estimation. Section 6 presents a multi-user channel amplitude estimation method. Section 7 addresses the effect of uncancelled multipath on the MUD efficiency, which is used in section 8 to assess the effect of dropping small amplitudes. It is shown that the overall MUD efficiency is improved by dropping small amplitudes. Conclusions are drawn in section 9.

2. Signal Model and Matched-Filter Outputs

The baseband received signal can be written

---

[1] Amplitudes are complex and hence include magnitude and phase.

$$r[t] = \sum_{k=1}^{K_v} \sum_{m} \tilde{s}_k[t - mT]b_k[m] + w[t] \tag{1}$$

where t is the integer time sample index, $T = NN_c$ is the data bit duration, $N = 256$ is the short-code length, N_c is the number of samples per chip, $w[t]$ is receiver noise, and where $\tilde{s}_k[t]$ is the channel-corrupted signature waveform for virtual user k. For L multipath components the channel-corrupted signature waveform for virtual user k is modeled as

$$\tilde{s}_k[t] = \sum_{p=1}^{L} a_{kp} s_k[t - \tau_{kp}] \tag{2}$$

where a_{kp} are the complex multipath amplitudes. Notice that $a_{kp} = a_{lp}$ if k and l are two virtual users corresponding to the same physical user. This is due to the fact that the signal waveforms of all virtual users corresponding to the same physical user pass through the same channel. For multiple antennas a_{kp} is a vector. For dual antennas, for example, primary and diversity,

$$a_{kp} = \begin{bmatrix} a_{p,kp} \\ a_{d,kq} \end{bmatrix} \tag{3}$$

The waveform $s_k[t]$ is referred to as the signature waveform for the kth virtual user. This waveform is generated by passing the spreading code sequence $c_k[n]$ through a pulse-shaping filter $g[t]$

$$s_k[t] = \sum_{r=0}^{N-1} g[t - rN_c]c_k[r] \tag{4}$$

where $N = 256$ and $g[t]$ is the raised-cosine pulse shape. Since $g[t]$ is a raised-cosine pulse as opposed to a root-raised-cosine pulse, the received signal $r[t]$ represents the baseband signal after filtering by the matched chip filter. Note that for spreading factors less than 256 some of the chips $c_k[r]$ are zero.

Combining Equations (1) through (4) gives

$$r[t] = \sum_{k=1}^{K_v} \sum_{\overline{m}} \sum_{p=1}^{L} a_{kp} s_k[t - \overline{m}T - \tau_{kp}]b_k[\overline{m}] + w[t] \tag{5}$$

The output of the despreading operation for a single multipath component is the complex statistic

$$y_{lq}[m] \equiv \frac{1}{2N_l} \sum_n r[nN_c + \hat{\tau}_{lq} + mT] \cdot c_l^*[n]$$

$$= \sum_{k=1}^{K_v} \sum_{\overline{m}} \sum_{p=1}^{L} a_{kp} \left\{ \frac{1}{2N_l} \sum_n s_k[nN_c + (m-\overline{m})T + \hat{\tau}_{lq} - \tau_{kp}] \cdot c_l^*[n] \right\} \cdot b_k[\overline{m}] + w_{lq}[m]$$

$$= \sum_{k=1}^{K_v} \sum_{m'} \sum_{p=1}^{L} a_{kp} \cdot C_{lkqp}[m'] \cdot b_k[m-m'] + w_{lq}[m] \tag{6}$$

$$C_{lkqp}[m'] \equiv \frac{1}{2N_l} \sum_n s_k[nN_c + m'T + \hat{\tau}_{lq} - \tau_{kp}] \cdot c_l^*[n]$$

$$w_{lq}[m] \equiv \frac{1}{2N_l} \sum_n w[nN_c + \hat{\tau}_{lq} + mT] \cdot c_l^*[n]$$

where $\hat{\tau}_{lq}$ is the estimate of τ_{lq}, and N_l is the (non-zero) length of code $c_l[n]$. The values $y_{lq}[m]$ are complex and are referred to as the pre-MRC matched-filter outputs. For multiple antennas, $r[t]$, $w[t]$, $y_{lq}[m]$ and $w_{lq}[m]$ are column vectors.

The matched-filter output is then

$$y_l[m] \equiv \text{Re}\left\{ \sum_{q=1}^{L} \hat{a}_{lq}^H \cdot y_{lq}[m] \right\}$$

$$= \text{Re}\left\{ \sum_{q=1}^{L} \hat{a}_{lq}^H \cdot \sum_{k=1}^{K_v} \sum_{m'} \sum_{p=1}^{L} a_{kp} \cdot C_{lkqp}[m'] \cdot b_k[m-m'] + \sum_{q=1}^{L} \hat{a}_{lq}^H \cdot w_{lq}[m] \right\}$$

$$= \sum_{k=1}^{K_v} \sum_{m'} \text{Re}\left\{ \sum_{q=1}^{L} \sum_{p=1}^{L} \hat{a}_{lq}^H a_{kp} \cdot C_{lkqp}[m'] \right\} \cdot b_k[m-m'] + w_l[m]$$

$$= \sum_{k=1}^{K_v} \sum_{m'} r_{lk}[m'] \cdot b_k[m-m'] + w_l[m] \tag{7}$$

$$r_{lk}[m'] \equiv \text{Re}\left\{ \sum_{q=1}^{L} \sum_{p=1}^{L} \hat{a}_{lq}^H a_{kp} \cdot C_{lkqp}[m'] \right\}$$

$$w_l[m] \equiv \text{Re}\left\{ \sum_{q=1}^{L} \hat{a}_{lq}^H \cdot w_{lq}[m] \right\}$$

where $\hat{a}_{lq}^H$ is the estimate of a_{lq}^H and $w_l[m]$ is the match-filtered receiver noise. The terms for $m' \neq 0$ result from asynchronous users.

3. Effect of Amplitude Estimation Error on MUD Efficiency

MUD efficiency is defined in terms of the ratio of the intra-cell interference with MUD (I_{MUD}) to the intra-cell interference with the Matched Filter (MF), that is, the intra-cell interference without MUD (I_{MF}):

$$\beta_{MUD} \equiv 1 - \frac{I_{MUD}}{I_{MF}} \tag{8}$$

The total interference without MUD is $I_{MF} + J$, where J is the inter-cell interference. Similarly, the total interference with MUD is $I_{MUD} + J$. The ratio of inter-cell interference to intra-cell interference without MUD is denoted $f = J/I_{MF}$. The increase in system capacity is equal to the ratio of the total interference without MUD to the total interference with MUD, which is $(I_{MF} + J)/(I_{MUD} + J) = (I_{MF} + fI_{MF})/(I_{MUD} + fI_{MF}) = (1 + f)/(1 - \beta_{MUD} + f)$. For $f = 0.3$ and $\beta_{MUD} = 0.7$, MUD increases the system capacity by a factor of $1.3/(1 - 0.7 + 0.3) = 2.2$. Hence, if our goal is to double system capacity the MUD efficiency must be approximately 70% or greater.

In the following we estimate the loss in MUD efficiency, $1 - \beta_{MUD}$, due to imperfect channel estimation. For simplicity of presentation we consider approximately synchronous users.

Recall that in a synchronous system the matched-filter outputs can be expressed as

$$y_l = r_{ll} b_l + \sum_{k=1, k \neq l}^{K_v} r_{lk} b_k + \eta_l \tag{9}$$

and that the intra-cell interference is then

$$I_{MF} = \sum_{k=1, k \neq l}^{K_v} E\left\{r_{lk}^2\right\} \tag{10}$$

The effect of channel amplitude errors is that the estimates of the R-matrix elements (r_{lk}) are imperfect, which reduces the interference that is cancelled. When MUD is employed with imperfect R-matrix estimates the detection statistic is

$$y_l - \sum_{k=1, k \neq l}^{K_v} \hat{r}_{lk} \hat{b}_k =$$

$$= A_l^2 b_l + \sum_{k=1, k \neq l}^{K_v} r_{lk} b_k - \sum_{k=1, k \neq l}^{K_v} \hat{r}_{lk} \hat{b}_k + \eta_l \tag{11}$$

$$= A_l^2 b_l + \sum_{k=1, k \neq l}^{K_v} (r_{lk} - \hat{r}_{lk}) b_k + \eta_l$$

where for the present case we have assumed that the bit estimates are perfect. With MUD the intra-cell interference is

$$I_{MUD} \equiv \sum_{k=1,k\neq l}^{K_v} \sum_{k'=1,k'\neq l}^{K_v} E\{(r_{lk} - \hat{r}_{lk})(r_{lk'} - \hat{r}_{lk'})\} E\{b_k b_{k'}\}$$

$$= \sum_{k=1,k\neq l}^{K_v} E\{(r_{lk} - \hat{r}_{lk})^2\}$$

(12)

Now from Equation (7), specialized for synchronous users

$$r_{lk} = \mathrm{Re}\left\{\sum_{q=1}^{L}\sum_{p=1}^{L} \hat{a}_{lq}^H a_{kp} \cdot C_{lkqp}\right\}$$

$$= \frac{1}{2}\sum_{q=1}^{L}\sum_{p=1}^{L}\left\{\hat{a}_{lq}^H a_{kp} \cdot C_{lkqp} + a_{kp}^H \hat{a}_{lq} \cdot C_{lkqp}^*\right\}$$

$$\hat{r}_{lk} = \frac{1}{2}\sum_{q=1}^{L}\sum_{p=1}^{L}\left\{\hat{a}_{lq}^H \hat{a}_{kp} \cdot C_{lkqp} + \hat{a}_{kp}^H \hat{a}_{lq} \cdot C_{lkqp}^*\right\}$$

$$r_{lk} - \hat{r}_{lk} = \frac{1}{2}\sum_{q=1}^{L}\sum_{p=1}^{L}\left\{\hat{a}_{lq}^H \left[a_{kp} - \hat{a}_{kp}\right] \cdot C_{lkqp} + \left[a_{kp}^H - \hat{a}_{kp}^H\right]\hat{a}_{lq} \cdot C_{lkqp}^*\right\}$$

(13)

$$= \frac{1}{2}\sum_{q=1}^{L}\sum_{p=1}^{L}\left\{\hat{a}_{lq}^H \varepsilon_{kp} \cdot C_{lkqp} + \varepsilon_{kp}^H \hat{a}_{lq} \cdot C_{lkqp}^*\right\}$$

$$\varepsilon_{kp} \equiv a_{kp} - \hat{a}_{kp}$$

Hence the second-order statistics are

$$E\{(r_{lk} - \hat{r}_{lk})^2\} = \frac{1}{4}\sum_{q,p=1}^{L}\sum_{q',p'=1}^{L} E\left\{\left[\hat{a}_{lq}^H \varepsilon_{kp} C_{lkqp} + \varepsilon_{kp}^H \hat{a}_{lq} C_{lkqp}^*\right]\cdot\left[\hat{a}_{lq'}^H \varepsilon_{kp'} C_{lkq'p'} + \varepsilon_{kp'}^H \hat{a}_{lq'} C_{lkq'p'}^*\right]\right\}$$

$$= \frac{1}{4}\sum_{q,p=1}^{L}\sum_{q',p'=1}^{L} E\left\{\hat{a}_{lq}^H \varepsilon_{kp} C_{lkqp} \cdot \varepsilon_{kp'}^H \hat{a}_{lq'} C_{lkq'p'}^* + \varepsilon_{kp}^H \hat{a}_{lq} C_{lkqp}^* \cdot \hat{a}_{lq'}^H \varepsilon_{kp'} C_{lkq'p'}\right\}$$

$$= \frac{1}{4N_l}\sum_{q,p=1}^{L} E\left\{\hat{a}_{lq}^H \varepsilon_{kp} \cdot \varepsilon_{kp}^H \hat{a}_{lq} + \varepsilon_{kp}^H \hat{a}_{lq} \cdot \hat{a}_{lq}^H \varepsilon_{kp}\right\}$$

$$\cong \frac{1}{2N_l}\sum_{q,p=1}^{L} E\{a_{lq}^H \varepsilon_{kp} \cdot \varepsilon_{kp}^H a_{lq}\} = \frac{1}{2N_l}\sum_{q,p=1}^{L} Tr\left[E\{a_{lq}a_{lq}^H\}\cdot E\{\varepsilon_{kp}\varepsilon_{kp}^H\}\right]$$

$$= \frac{1}{2N_l}\sum_{q=1}^{L} A_{lq}^2 \cdot \sum_{p=1}^{L} \mathrm{E}_{kp}^2 \cdot \left[2 + 2\,\mathrm{Re}(\rho_{lq}\rho_\varepsilon^*)\right]$$

$$\cong \frac{1}{2N_l} A_l^2 \cdot \mathrm{E}_k^2 \cdot 2 \cdot \left[1 + |\rho|^2\right]$$

$$A_{lq}^2 \equiv E\{|a_{p,lq}|^2\} \equiv E\{|a_{d,lq}|^2\} \quad \mathrm{E}_{kp}^2 \equiv E\{|\varepsilon_{p,kp}|^2\} \equiv E\{|\varepsilon_{d,kp}|^2\}$$

$$A_l^2 \equiv \sum_{q=1}^{L} A_{lq}^2, \quad \mathrm{E}_k^2 \equiv \sum_{p=1}^{L} \mathrm{E}_{kp}^2$$

(14)

$$\rho \approx \rho_{lq} \approx \rho_\varepsilon^*$$

where we have assumed that the amplitude error is independent of the amplitude and we have used

$$E\{a_{lq} \cdot a_{lq}^H\} = E\left\{\begin{bmatrix} a_{p,lq} \\ a_{d,lq} \end{bmatrix} \cdot \begin{bmatrix} a_{p,lq}^* & a_{d,lq}^* \end{bmatrix}\right\} = A_{lq}^2 \cdot \begin{bmatrix} 1 & \rho_{lq} \\ \rho_{lq}^* & 1 \end{bmatrix}$$

$$E\{\varepsilon_{kp} \cdot \varepsilon_{kp}^H\} = E\left\{\begin{bmatrix} \varepsilon_{p,kp} \\ \varepsilon_{d,kp} \end{bmatrix} \cdot \begin{bmatrix} \varepsilon_{p,kp}^* & \varepsilon_{d,kp}^* \end{bmatrix}\right\} = E_{kp}^2 \cdot \begin{bmatrix} 1 & \rho_\varepsilon \\ \rho_\varepsilon^* & 1 \end{bmatrix}$$

(15)

The second expression is discussed below. We refer to E_k as the error amplitude for the kth virtual user. The residual interference after MUD IC is

$$I_{MUD} = \sum_{k=1,k\neq l}^{K_v} E\{(r_{lk} - \hat{r}_{lk})^2\}$$

$$= \frac{A^2}{2N_l}\left[(K-1)\alpha E_d^2 + K E_c^2\right] \cdot 2 \cdot \left[1 + |\rho|^2\right]$$

(16)

$$\cong \frac{A^2 K}{2N_l}\left[\alpha + \beta_c^2\right] E_d^2 \cdot 2 \cdot \left[1 + |\rho|^2\right]$$

where all data channels have amplitude A. The error amplitude for the control channels is denoted E_c and the error amplitude for the data channels is denoted E_d. All data channel amplitudes are determined by scaling the corresponding control channel amplitudes by $1/\beta_c$. Hence $E_d = E_c/\beta_c$.

Similarly we can show that

$$E\{r_{lk}^2\} = \frac{1}{2N_l} A_l^2 \cdot A_k^2 \cdot 2 \cdot \left[1 + |\rho|^2\right]$$

(17)

so that the matched-filter interference is

$$I_{MF} = \sum_{k=1,k\neq l}^{K_v} E\{r_{lk}^2\}$$

$$= \frac{A^2}{2N_l}\left[(K-1)\alpha A^2 + K\beta_c^2 A^2\right] \cdot 2 \cdot \left[1 + |\rho|^2\right]$$

(18)

$$\cong \frac{A^2 K}{2N_l}\left[\alpha + \beta_c^2\right] A^2 \cdot 2 \cdot \left[1 + |\rho|^2\right]$$

Finally, the MUD efficiency is

$$\beta_{MUD} \equiv 1 - \frac{I_{MUD}}{I_{MF}} = 1 - \left(\frac{E_d}{A}\right)^2$$

(19)

4. Conventional Channel Estimation

The conventional channel amplitude estimate is given by

$$\hat{a}_{lq} = \frac{1}{M} \sum_{m=1}^{M} y_{lq}[m] \cdot b_l[m]$$

$$= \sum_{k=1}^{K_v} \sum_{p=1}^{L} a_{kp} \cdot \sum_{m'} C_{lkqp}[m'] \frac{1}{M} \sum_{m=1}^{M} b_l[m] \cdot b_k[m-m'] + \frac{1}{M} \sum_{m=1}^{M} w_{lq}[m] \cdot b_l[m] \qquad (20)$$

$$= \sum_{k=1}^{K_v} \sum_{p=1}^{L} H_{lqkp} \cdot a_{kp} + w_{lq}$$

where

$$H_{lqkp} \equiv \sum_{m'} C_{lkqp}[m'] \cdot I_{lk}[m']$$

$$I_{lk}[m'] \equiv \frac{1}{M} \sum_{m=1}^{M} b_l[m] \cdot b_k[m-m'] \qquad (21)$$

$$w_{lq} \equiv \frac{1}{M} \sum_{m=1}^{M} w_{lq}[m] \cdot b_l[m]$$

In the above $b_l[m]$ represent the known pilot bits. (The lth virtual user is implicitly a control channel.) The number M represents the number of pilot bits used to derive the channel amplitude estimates. The channel amplitude estimate can be rewritten

$$\hat{a}_{lq} = \sum_{k=1}^{K_v} \sum_{p=1}^{L} H_{lqkp} \cdot a_{kp} + w_{lq}$$

$$= \sum_{p=1}^{L} H_{lqlp} \cdot a_{lp} + \sum_{\substack{k=1 \\ k \neq l}}^{K_v} \sum_{p=1}^{L} H_{lqkp} \cdot a_{kp} + w_{lq} \qquad (22)$$

$$= a_{lq} + \sum_{\substack{p=1 \\ p \neq q}}^{L} H_{lqlp} \cdot a_{lp} + \sum_{\substack{k=1 \\ k \neq l}}^{K_v} \sum_{p=1}^{L} H_{lqkp} \cdot a_{kp} + w_{lq}$$

It is shown in the appendix that

$$E\left\{ H_{lqkp} \cdot H_{l'q'k'p'}^{*} \right\}_{lq \neq kp} = \delta_{ll'} \delta_{kk'} \delta_{qq'} \delta_{pp'} \cdot E\left\{ |H_{lqkp}|^2 \right\}_{lq \neq kp} \qquad (23)$$

Hence the variance of the estimate is

$$E\{\varepsilon_{xJq} \cdot \varepsilon^*_{y,Jq}\} = \sum_{\substack{p=1 \\ p \neq q}}^{L} E\{|H_{lqlp}|^2\} \cdot E\{a_{x,lp} \cdot a^*_{y,lp}\}$$

$$+ \sum_{\substack{k=1 \\ k \neq l}}^{K_v} \sum_{p=1}^{L} E\{|H_{lqkp}|^2\} \cdot E\{a_{x,kp} \cdot a^*_{y,kp}\} + E\{w_{xJq} \cdot w^*_{yJq}\}$$

$$E\{|\varepsilon_{pJq}|^2\} = E\{|\varepsilon_{dJq}|^2\} = \sum_{\substack{p=1 \\ p \neq q}}^{L} E\{|H_{lqlp}|^2\} \cdot A_{lp}^2 + \sum_{\substack{k=1 \\ k \neq l}}^{K_v} \sum_{p=1}^{L} E\{|H_{lqkp}|^2\} \cdot A_{kp}^2 + W_{lq}^2 \equiv E_{lq}^2 \quad (24)$$

$$E\{\varepsilon_{pJq} \cdot \varepsilon^*_{dJq}\} = \sum_{\substack{p=1 \\ p \neq q}}^{L} E\{|H_{lqlp}|^2\} \cdot \rho_{lp} A_{lp}^2 + \sum_{\substack{k=1 \\ k \neq l}}^{K_v} \sum_{p=1}^{L} E\{|H_{lqkp}|^2\} \cdot \rho_{kp} A_{kp}^2 \approx \rho_\varepsilon E_{lq}^2$$

$$W_{lq}^2 \equiv E\{|w_{p,lq}|^2\} = E\{|w_{dJq}|^2\}$$

The factor ρ_ε simply reflects the fact that the off-diagonal elements are smaller than the diagonal elements due to partial correlations ρ_{kp} between the antenna elements. In the Appendix it is also shown that

$$E\{|H_{lqlp}|^2\}_{q \neq p} \cong \frac{1}{N_l}$$

$$E\{|H_{lqkp}|^2\}_{l \neq k} = \frac{1}{MN_l} \quad (25)$$

Now combining Equations (24) and (25) gives for the variance of the channel amplitude estimate

$$E_{lq}^2 = \sum_{\substack{p=1 \\ p \neq q}}^{L} E\{|H_{lqlp}|^2\} \cdot A_{lp}^2 + \sum_{\substack{k=1 \\ k \neq l}}^{K_v} \sum_{p=1}^{L} E\{|H_{lqkp}|^2\} \cdot A_{kp}^2 + W_{lq}^2$$

$$= \frac{1}{N_l} \sum_{\substack{p=1 \\ p \neq q}}^{L} A_{lp}^2 + \frac{1}{MN_l} \sum_{\substack{k=1 \\ k \neq l}}^{K_v} \sum_{p=1}^{L} A_{kp}^2 + W_{lq}^2 \quad (26)$$

$$= \frac{1}{N_l} \cdot \frac{L-1}{L} A_l^2 + \frac{1}{MN_l} \sum_{\substack{k=1 \\ k \neq l}}^{K_v} A_k^2 + W_{lq}^2$$

where we have used $A_{lp}^2 = A_l^2/L$. The first term represents the variance due to a user's own multipath interference. This term is small compared to the variance arising from the total multiple-access interference. For simplicity we incorporate part of this term into the second term and drop the remainder. The final term represents thermal noise and other-cell interference. For now we assume that thermal noise in small. The interference arising from other cells is assumed to be proportional to the same-cell interference, with a constant of proportionality $f = 0.35$. With these assumptions we have

$$E_l^2 = \sum_{q=1}^{L} E_{lq}^2 = (1+f)\frac{L}{MN_l}\sum_{k=1}^{K_v} A_k^2 \tag{27}$$

Notice that the magnitude of the error E_l is approximately the same for all users. Also, the lth users is implicitly a control channel, and hence $N_l = PG = 256$. If the K_v virtual users are all at the highest spreading factor, then in terms of the $K = K_v/2$ physical users we have

$$E_c^2 = (1+f)\frac{L}{M \cdot PG}\left[K\beta_c^2 A^2 + K\alpha A^2\right] \tag{28}$$

where E_c is the magnitude of the channel amplitude error for a control channel, β_c is the relative control channel amplitude, A is the amplitude for the data channels, and where α is the activity factor for the data channels. Since the channel amplitudes for the data channels are determined by scaling the amplitude of the corresponding control channel it is evident that $E_d = E_c/\beta_c$. Hence,

$$\left(\frac{E_d}{A}\right)^2 = (1+f)\frac{KL}{M \cdot PG}\left[1+\frac{\alpha}{\beta_c^2}\right] \tag{29}$$

Given the parameters

f	$= 0.35$
K	$= 128$
L	$= 4$
M	$= 18$
PG	$= 256$
α	$= 0.4$
β_c	$= 0.7333$

we get

$$\begin{aligned}
\frac{E_d}{A} &= \sqrt{(1+f)\frac{KL}{M \cdot PG}\left[1+\frac{\alpha}{\beta_c^2}\right]} \\
&= \sqrt{(1+0.35)\frac{(128)(4)}{(18)(256)}\left[1+\frac{0.40}{(0.7333)^2}\right]} \\
&= 0.51
\end{aligned} \tag{30}$$

The number of pilot bits, M, is taken to be 18, which represents 6 bits per slot, the amplitudes averaged over 3 slots. The corresponding MUD efficiency is

$$\beta_{MUD} = 1-\left(\frac{E_d}{A}\right)^2 = 1-(0.51)^2 = 0.74 \tag{31}$$

5. Improved Channel Amplitude Estimates

One method for significantly improving the channel amplitude estimates is to perform a second estimate directly on the data channels after the initial data channel demodulation. Performance is improved for two reasons. First, the entire slot can be used for integration. Hence we have $M = 3(10) = 30$ bits. Secondly, the error is not scaled by $1/\beta_c$ since the estimate is performed directly on the data channel. For this method we have

$$
\frac{E_d}{A} = \sqrt{(1+f)\frac{KL}{M \cdot PG}\left[\beta_c^2 + \alpha\right]}
$$

$$
= \sqrt{(1+0.35)\frac{(128)(4)}{(30)(256)}\left[(0.7333)^2 + 0.40\right]} \tag{32}
$$

$$
= 0.29
$$

and the corresponding MUD efficiency is

$$
\beta_{MUD} = 1 - \left(\frac{E_d}{A}\right)^2 = 1 - (0.29)^2 = 0.92 \tag{33}
$$

Slightly better performance can be achieved by using both data and control channels. This method can be performed either on the daughter card or on the modem card since it is a single user method. The assumption is that the matched-filter BER is sufficiently good.

6. Multiuser Channel Amplitude Estimation

Given the conventional channel estimates and the detected user bits it is possible to subtract the MAI which corrupts channel estimation. This method of channel estimation is referred to as multiuser channel estimation, as opposed to the conventional single-user estimation techniques. A simple multiuser channel estimation technique is presented below without analysis. Performance should be determined via simulation.

From Equation (22) the conventional estimate is

$$
\hat{a}_{lq} = \sum_{kp} H_{lqkp} \cdot a_{kp} + w_{lq} \tag{34}
$$

A multiuser estimate is obtained by subtracting the known interference among the channel estimates

$$\hat{a}_{lq} = a_{lq} + \sum_{kp \neq lq} H_{lqkp} \cdot a_{kp} + w_{lq}$$

$$\bar{a}_{lq} \equiv \hat{a}_{lq} - \sum_{k'p' \neq lq} H_{lqk'p'} \cdot \hat{a}_{k'p'}$$

$$= \left[a_{lq} + \sum_{kp \neq lq} H_{lqkp} \cdot a_{kp} + w_{lq} \right] - \sum_{k'p' \neq lq} H_{lqk'p'} \left[a_{k'p'} + \sum_{kp \neq k'p'} H_{k'p'kp} \cdot a_{kp} + w_{k'p'} \right] \qquad (35)$$

$$= a_{lq} - \left[\sum_{k'p' \neq lq} \sum_{kp \neq k'p'} H_{lqk'p'} \cdot H_{k'p'kp} \cdot a_{kp} \right] + \left[w_{lq} - \sum_{k'p' \neq lq} H_{lqk'p'} w_{k'p'} \right]$$

where the (hopefully) improved multiuser channel estimate is denoted $\bar{a}_{lq}$. The first term above is the actual channel amplitude. The second term is the residual interference, and the last term represents thermal noise and other-cell interference, which is amplified by the multiuser interference subtraction. The extent of the amplification needs to be determined.

7. Effect of Uncancelled Multipath Interference

It is expected that a typical RAKE receiver will be capable of tracking up to approximately 16 multipath components. Since the computational complexity of symbol-rate MUD is quadratic in the number of multipaths L it is unlikely that MUD implementations will be able to cancel all multipath interference. The effect of uncancelled multipath is assessed below.

Suppose that the RAKE receiver processes L' multipath components, but that the MUD implementation cancels interference for $L < L'$ components. From Equation (13) we have

$$r_{lk} = \frac{1}{2} \sum_{q=1}^{L'} \sum_{p=1}^{L'} \left\{ \hat{a}_{lq}^H a_{kp} \cdot C_{lkqp} + a_{kp}^H \hat{a}_{lq} \cdot C_{lkqp}^* \right\}$$

$$= \frac{1}{2} \sum_{q=1}^{L} \sum_{p=1}^{L} \left\{ \hat{a}_{lq}^H a_{kp} \cdot C_{lkqp} + a_{kp}^H \hat{a}_{lq} \cdot C_{lkqp}^* \right\} + \frac{1}{2} \sum_{q=1}^{L} \sum_{p=L+1}^{L'} \left\{ \hat{a}_{lq}^H a_{kp} \cdot C_{lkqp} + a_{kp}^H \hat{a}_{lq} \cdot C_{lkqp}^* \right\}$$

$$+ \frac{1}{2} \sum_{q=L+1}^{L'} \sum_{p=1}^{L} \left\{ \hat{a}_{lq}^H a_{kp} \cdot C_{lkqp} + a_{kp}^H \hat{a}_{lq} \cdot C_{lkqp}^* \right\} + \frac{1}{2} \sum_{q=L+1}^{L'} \sum_{p=L+1}^{L'} \left\{ \hat{a}_{lq}^H a_{kp} \cdot C_{lkqp} + a_{kp}^H \hat{a}_{lq} \cdot C_{lkqp}^* \right\}$$

$$(36)$$

$$\hat{r}_{lk} = \frac{1}{2} \sum_{q=1}^{L} \sum_{p=1}^{L} \left\{ \hat{a}_{lq}^H \hat{a}_{kp} \cdot C_{lkqp} + \hat{a}_{kp}^H \hat{a}_{lq} \cdot C_{lkqp}^* \right\}$$

$$r_{lk} - \hat{r}_{lk} = \frac{1}{2} \sum_{q=1}^{L} \sum_{p=1}^{L} \left\{ \hat{a}_{lq}^H \varepsilon_{kp} \cdot C_{lkqp} + \varepsilon_{kp}^H \hat{a}_{lq} \cdot C_{lkqp}^* \right\} + \frac{1}{2} \sum_{q=1}^{L} \sum_{p=L+1}^{L'} \left\{ \hat{a}_{lq}^H a_{kp} \cdot C_{lkqp} + a_{kp}^H \hat{a}_{lq} \cdot C_{lkqp}^* \right\}$$

$$+ \frac{1}{2} \sum_{q=L+1}^{L'} \sum_{p=1}^{L} \left\{ \hat{a}_{lq}^H a_{kp} \cdot C_{lkqp} + a_{kp}^H \hat{a}_{lq} \cdot C_{lkqp}^* \right\} + \frac{1}{2} \sum_{q=L+1}^{L'} \sum_{p=L+1}^{L'} \left\{ \hat{a}_{lq}^H a_{kp} \cdot C_{lkqp} + a_{kp}^H \hat{a}_{lq} \cdot C_{lkqp}^* \right\}$$

and the variance is then

$$E\left\{(r_{lk} - \hat{r}_{lk})^2\right\} = \frac{1}{2N_I}\sum_{q=1}^{L}\sum_{p=1}^{L}\left\{\hat{a}_{lq}^H\varepsilon_{kp}\varepsilon_{kp}^H\hat{a}_{lq}\right\} + \frac{1}{2N_I}\sum_{q=1}^{L}\sum_{p=L+1}^{L'}\left\{\hat{a}_{lq}^H a_{kp} a_{kp}^H\hat{a}_{lq}\right\}$$

$$+ \frac{1}{2N_I}\sum_{q=L+1}^{L'}\sum_{p=1}^{L}\left\{\hat{a}_{lq}^H a_{kp} a_{kp}^H\hat{a}_{lq}\right\} + \frac{1}{2N_I}\sum_{q=L+1}^{L'}\sum_{p=L+1}^{L'}\left\{\hat{a}_{lq}^H a_{kp} a_{kp}^H\hat{a}_{lq}\right\}$$

$$\cong \frac{1}{2N_I}\sum_{q=1}^{L}\sum_{p=1}^{L}\left\{a_{lq}^H\varepsilon_{kp}\varepsilon_{kp}^H a_{lq}\right\} + \frac{1}{2N_I}\sum_{q=1}^{L}\sum_{p=L+1}^{L'}\left\{a_{lq}^H a_{kp} a_{kp}^H a_{lq}\right\}$$

$$+ \frac{1}{2N_I}\sum_{q=L+1}^{L'}\sum_{p=1}^{L}\left\{a_{lq}^H a_{kp} a_{kp}^H a_{lq}\right\} + \frac{1}{2N_I}\sum_{q=L+1}^{L'}\sum_{p=L+1}^{L'}\left\{a_{lq}^H a_{kp} a_{kp}^H a_{lq}\right\}$$

$$\cong \frac{2\cdot\left[1+|\rho|^2\right]}{2N_I}\left\{\sum_{q=1}^{L}\sum_{p=1}^{L}A_{lq}^2 E_{kp}^2 + \sum_{q=1}^{L}\sum_{p=L+1}^{L'}A_{lq}^2 A_{kp}^2 + \sum_{q=L+1}^{L'}\sum_{p=1}^{L}A_{lq}^2 A_{kp}^2 + \sum_{q=L+1}^{L'}\sum_{p=L+1}^{L'}A_{lq}^2 A_{kp}^2\right\}$$

$$= \frac{2\cdot\left[1+|\rho|^2\right]}{2N_I}\left\{\sum_{q=1}^{L}A_{lq}^2\sum_{p=1}^{L}E_{kp}^2 + \left[\beta_{x,k} + \beta_{x,l} + \beta_{x,l}\beta_{x,k}\right]\sum_{q=1}^{L}A_{lq}^2\sum_{p=L}^{L}A_{kp}^2\right\}$$

$$= \frac{2\cdot\left[1+|\rho|^2\right]}{2N_I}\left\{A_l^2 E_k^2 + \left[\beta_{x,k} + \beta_{x,l} + \beta_{x,l}\beta_{x,k}\right]A_l^2 A_k^2\right\}$$

(37)

$$\beta_{x,k} \equiv \sum_{p=L+1}^{L'}A_{kp}^2 \bigg/ \sum_{p=1}^{L}A_{kp}^2$$,

Note that $\beta_{x,k}$ is the ratio of the uncancelled to cancelled interference for the kth users. Similarly, we have

$$E\left\{r_{lk}^2\right\} = \frac{2\cdot\left[1+|\rho|^2\right]}{2N_I}\left\{A_l^2 A_k^2 + \left[\beta_{x,k} + \beta_{x,l} + \beta_{x,l}\beta_{x,k}\right]A_l^2 A_k^2\right\}$$

(38)

Now, neglecting the second order terms $\beta_{x,l}\beta_{x,k}$ and averaging over the users $\beta_x = E\{\beta_{x,l}\}$ we arrive at

$$I_{MUD} = \sum_{k=1,k\neq l}^{K_v} E\{(r_{lk} - \hat{r}_{lk})^2\}$$

$$= \frac{2 \cdot [1+|\rho|^2]}{2N_l} KA^2 \{(\alpha E_d^2 + E_c^2) + 2\beta_x(\alpha A_d^2 + A_c^2)\}$$

$$= \frac{2 \cdot [1+|\rho|^2]}{2N_l} KA^2 \{(\alpha + \beta_c^2)E_d^2 + 2\beta_x(\alpha + \beta_c^2)A^2\}$$

$$= \frac{2 \cdot [1+|\rho|^2]}{2N_l} KA^2 (\alpha + \beta_c^2)\{E_d^2 + 2\beta_x A^2\}$$

$$I_{MF} = \sum_{k=1,k\neq l}^{K_v} E\{r_{lk}^2\}$$

$$= \frac{2 \cdot [1+|\rho|^2]}{2N_l} KA^2 (\alpha + \beta_c^2)\{A^2 + 2\beta_x A^2\}$$

$$\beta_{MUD} = 1 - \frac{I_{MUD}}{I_{MF}} = 1 - \frac{E_d^2 + 2\beta_x A^2}{A^2 + 2\beta_x A^2} = 1 - \frac{1}{1+2\beta_x}\left[\left(\frac{E_d}{A}\right)^2 + 2\beta_x\right] \tag{39}$$

Note that β_x is the ratio of the uncancelled to cancelled interference.

In order to assess typical value for β_x multipath models [1][2][3] were used to generate random profiles. The models are based on data collected in four areas (A, B, C, and D) in the San Francisco-Oakland bay area. Table 1 below summarizes the key results. The table shows the β_x versus the number of multipath components L.

Table 1. Ratio (β_x) of the uncancelled to cancelled interference.

β_x	L = 8	L = 6	L = 4	L = 3	L = 2	L = 1
Area A	0.0019	0.0064	0.0481	0.0961	0.2376	0.5819
Area B	0.0012	0.0086	0.0404	0.1115	0.1416	0.5749
Area C	0.0004	0.0054	0.0291	0.0948	0.1649	0.6603
Area D	0.0039	0.0128	0.0430	0.0629	0.1435	0.4890

Suppose $\beta_x = 0.05$ and $(E_d/A)^2 = 0.51^2 = 0.260$. Without taking uncancelled multipath into account we found $\beta_{MUD} = 0.74$. Taking uncancelled multipath into account we find

$$\beta_{MUD} = 1 - \frac{1}{1+2\beta_x}\left[\left(\frac{E_d}{A}\right)^2 + 2\beta_x\right]$$

$$= 1 - \frac{1}{1+2(0.05)}[(0.51)^2 + 2(0.05)] \tag{40}$$

$$= 0.67$$

where a worst-case $\beta_x = 0.05$ is used.

8. Improved MUD Efficiency Due to Dropping Small Amplitudes

If small amplitude multipath components are not included in the cancellation the MUD efficiency is reduced slightly due to the additional uncancelled multipath interference, but it is also increased because of the absence error resulting from the inclusion of these small noisy estimates. The net effect is a substantial increase in the MUD efficiency. From Equation (30) we have

$$
\left(\frac{E_{d1}}{A}\right)^2 \equiv (1+f)\frac{K}{M \cdot PG}\left[1+\frac{\alpha}{\beta_c^2}\right]
$$

$$
= (1+0.35)\frac{(128)}{(18)(256)}\left[1+\frac{0.40}{(0.7333)^2}\right] \tag{41}
$$

$$
= 0.065
$$

where E_{d1}^2 is the error due to a single multipath (i.e. $L = 1$). From Equation (37) it is evident that if a particular multipath amplitude satisfies $A_{kp}^2 < E_{d1}^2$ then it is advantageous not to incorporate this amplitude into the cancellation since the error is greater than the amplitude. Table 2 shows the mean number of paths $E\{L\}$ which satisfy $A_{kp}^2 > E_{d1}^2$ and the ratio β_x of the uncancelled to cancelled interference if only these mulitpaths are cancelled. The MUD efficiency is then calculated using

$$
\beta_{MUD} = 1 - \frac{1}{1+2\beta_x}\left[E\{L\}\cdot\left(\frac{E_{d1}}{A}\right)^2 + 2\beta_x\right] \tag{42}
$$

Table 2. Improved MUD efficiency (β_{MUD}) due to dropping small amplitudes.

	$E\{L\}$	β_x	β_{MUD}
Area A	2.0300	0.0714	0.7638
Area B	2.4660	0.0691	0.7482
Area C	2.2970	0.0680	0.7564
Area D	2.0690	0.0625	0.7748
Mean	2.2155	0.0678	0.7608

9. Conclusions

This report represents a first-look at channel estimation and the effect of errors on the MUD efficiency. Only the case where all users are at the highest spreading factor has been examined. The initial results indicate that if the conventional channel estimates are used the MUD efficiency drops to 74% due to estimation errors. If the effect of uncancelled multipath interference is also considered the MUD efficiency drops down to 67%. If small amplitude multipath components are not included in the cancellation the MUD efficiency is reduced slightly due to the additional uncancelled multipath interference, but it is also increased because of the absence error resulting from the inclusion of these small noisy estimates. The net effect is a substantial increase in the

MUD efficiency, which is increased to 76%. The actual MUD efficiency will, of course, be less due to other factors which degrade efficiency. If an improved single-user channel estimation is used the MUD efficiency can be increased to 92%. This improved method requires knowledge of the pre-MRC matched-filter outputs. It is perhaps possible to further increase the MUD efficiency by employing multiuser channel estimation. These techniques also require knowledge of the pre-MRC matched-filter outputs. The above referenced MUD efficiency numbers are based on 128 users processed by the basestation. If fewer users are allowed access to the system in order to increase range the MUD efficiency is unchanged shine the total interference and noise remains unchanged.

References

[1] G. L. Turin, F. D. Clapp, T. L. Johnston, S. B. Fine, D. Lavry, "A statistical model of urban multipath propagation," IEEE Trans. on Vehicular Technology, vol. VT-21, No. 1, February 1972, pp. 1 – 9.

[2] H. Suzuki, "A statistical model for urban radio propagation," IEEE Trans. on Communications, vol. COM-25, No. 7, July 1977, pp. 673 – 680.

[3] H. Hashemi, "Simulation of the urban radio propagation channel," IEEE Trans. Vehicular Technology, vol. VT-28, No. 3, August 1979, pp. 213 – 225.

Appendix A

In order to estimate the variance of the channel amplitude estimate we need the second order statistics

$$E\left\{H_{lqkp} \cdot H^*_{l'q'k'p'}\right\}_{lq \neq kp} = \sum_m \sum_{m'} E\left\{C_{lkqp}[m] \cdot C^*_{l'k'q'p'}[m']\right\} \cdot E\left\{I_{lk}[m] \cdot I_{l'k'}[m']\right\}$$

$$= \sum_m \sum_{m'} \frac{1}{N_l} \delta_{ll'} \delta_{kk'} \delta_{qq'} \delta_{pp'} \delta_{mm'} \frac{N_{lkqp}[m']}{N_l} \cdot E\left\{I_{lk}[m] \cdot I_{l'k'}[m']\right\} \qquad (A1)$$

$$= \frac{1}{N_l} \delta_{ll'} \delta_{kk'} \delta_{qq'} \delta_{pp'} \sum_{m'} \frac{N_{lkqp}[m']}{N_l} E\left\{I^2_{lk}[m']\right\}$$

where we have used

$$E\left\{C_{lkqp}[m] \cdot C^*_{l'k'q'p'}[m']\right\} \cong \frac{1}{N_l} \cdot \delta_{ll'} \cdot \delta_{kk'} \cdot \delta_{qq'} \cdot \delta_{pp'} \cdot \delta_{mm'} \cdot \frac{N_{lkqp}[m']}{N_l} \qquad (A2)$$

which is derived in Appendix B assuming random codes. In order to evaluate $E\left\{I^2_{lk}[m']\right\}$ we consider two cases: 1) $k = l$, and 2) $k \neq l$. For $k = l$ we have

$$E\{I_{ll}^2[m']\} = \frac{1}{M^2} E\left\{ \sum_{m=1}^{M} \sum_{n=1}^{M} b_l[m] \cdot b_l[n] \cdot b_l[m-m'] \cdot b_l[n-m'] \right\}$$

$$= \frac{1}{M^2} \sum_{m=1}^{M} \sum_{n=1}^{M} [\delta_{m'0} + (1 - \delta_{m'0})\delta_{mn}]$$

$$= \delta_{m'0} + (1 - \delta_{m'0})\frac{1}{M}$$

$$= \delta_{m'0}\left(1 - \frac{1}{M}\right) + \frac{1}{M}$$

(A3)

whereas for $k \neq l$ we have

$$E\{I_{lk}^2[m']\} = \frac{1}{M^2} E\left\{ \sum_{m=1}^{M} \sum_{n=1}^{M} b_l[m] \cdot b_l[n] \cdot b_k[m-m'] \cdot b_k[n-m'] \right\}$$

$$= \frac{1}{M^2} \sum_{m=1}^{M} \sum_{n=1}^{M} \delta_{mn} \cdot \delta_{mn}$$

$$= \frac{1}{M}$$

(A4)

Hence, combining Equations (A3) and (A4) we have

$$E\{I_{lk}^2[m']\} = \delta_{kl} \cdot \delta_{m'0}\left(1 - \frac{1}{M}\right) + \frac{1}{M}$$

(A5)

Equation (A1) then becomes

$$E\{H_{lqkp} \cdot H_{l'q'k'p'}^*\}_{lq \neq kp} = \frac{1}{N_l} \delta_{ll'} \delta_{kk'} \delta_{qq'} \delta_{pp'} \sum_{m'} \frac{N_{lkqp}[m']}{N_l} E\{I_{lk}^2[m']\}$$

$$= \frac{1}{N_l} \delta_{ll'} \delta_{kk'} \delta_{qq'} \delta_{pp'} \sum_{m'} \frac{N_{lkqp}[m']}{N_l} \left\{ \delta_{kl} \cdot \delta_{m'0}\left(1 - \frac{1}{M}\right) + \frac{1}{M} \right\}$$

(A6)

$$= \frac{1}{N_l} \delta_{ll'} \delta_{kk'} \delta_{qq'} \delta_{pp'} \left\{ \delta_{kl} \cdot \frac{N_{lkqp}[0]}{N_l}\left(1 - \frac{1}{M}\right) + \frac{1}{M} \right\}$$

Now specializing Equation (A6) to the case where $k = l$

$$E\{|H_{lqlp}|^2\}_{q \neq p} = \frac{1}{N_l} \left\{ \frac{N_{llqp}[0]}{N_l}\left(1 - \frac{1}{M}\right) + \frac{1}{M} \right\}$$

(A7)

The above expression is further, simplified if we assume that users are approximately synchronous so that $N_{llqp}[0] \sim N_l$, which gives

$$E\{|H_{lqlp}|^2\}_{q \neq p} \cong \frac{1}{N_l}$$

(A8)

Similarly, specializing Equation (A6) to the case where $k \neq l$

$$E\left\{|H_{lqkp}|^2\right\}_{l \neq k} = \frac{1}{MN_l} \tag{A9}$$

Appendix B

In Appendix A we used the approximation

$$E\left\{C_{lkqp}[m] \cdot C_{l'k'q'p'}^*[m']\right\} \cong \frac{1}{N_l} \delta_{ll'} \cdot \delta_{kk'} \cdot \delta_{qq'} \cdot \delta_{pp'} \cdot \delta_{mm'} \cdot \frac{N_{lkqp}[m']}{N_l} \tag{B1}$$

under the restriction that $lq \neq kp$. We show here that this expression is exactly true for chip-synchronous users, and that the approximation is reasonably valid for chip-asynchronous users, particularly when differences in delay lag are greater than about 2 chips. The analysis is based on random user codes.

The user correlations can be explicitly related to the code correlations as follows

$$C_{lkqp}[m] = \frac{1}{2N_l} \sum_i \sum_j g[(i-j)N_c + mT + \tau_{lq} - \tau_{kp}] \cdot c_l^*[i] \cdot c_k[j]$$

$$= C_{lk}[\tau_{lkqp}[m]] \tag{B2}$$

$$C_{lk}[\tau] \equiv \frac{1}{2N_l} \sum_i \sum_j g[(i-j)N_c + \tau] \cdot c_l^*[i] \cdot c_k[j]$$

$$\tau_{lkqp}[m] \equiv mT + \tau_{lq} - \tau_{kp}$$

Consider two cases: 1) $l \neq k$, and 2) $l = k$.

Case 1

When $l \neq k$ the second-order statistics become

$$E\left\{C_{lk}[\tau] \cdot C_{l'k'}^*[\tau']\right\} = \frac{1}{4N_l N_{l'}} \sum_{iji'j'} g_{ij}[\tau] \cdot g_{i'j'}[\tau'] \cdot E\left\{c_l^*[i] \cdot c_{l'}[i'] \cdot c_k[j] \cdot c_k^*[j']\right\}$$

$$= \frac{1}{4N_l N_{l'}} \sum_{iji'j'} g_{ij}[\tau] \cdot g_{i'j'}[\tau'] \cdot 2\delta_{ll'} \delta_{ii'} \cdot 2\delta_{kk'} \delta_{jj'} \tag{B3}$$

$$= \frac{\delta_{ll'} \cdot \delta_{kk'}}{N_l^2} \sum_{ij} g_{ij}[\tau] \cdot g_{ij}[\tau']$$

$$g_{ij}[\tau] \equiv g[(i-j)N_c + \tau]$$

where we have used the assumption of random user codes, independent among the users. Note also that the summation over i is over the range where $c_l[i]$ is non-zero, and similarly the summation over j is over the range where $c_k[j]$ is non-zero.

Case 2

Now consider case 2 where $l = k$

$$E\{C_{ll}[\tau] \cdot C_{l'k}^*[\tau']\} = \frac{1}{4N_l N_{l'}} \sum_{ij i'j'} g_{ij}[\tau] \cdot g_{i'j'}[\tau'] \cdot E\{c_l^*[i] \cdot c_{l'}[i'] \cdot c_l[j] \cdot c_k^*[j']\}$$

$$= \frac{\delta_{l'k}}{4N_l N_{l'}} \sum_{ij i'j'} g_{ij}[\tau] \cdot g_{i'j'}[\tau'] \cdot E\{c_l^*[i] \cdot c_l[j] \cdot c_{l'}[i'] \cdot c_{l'}^*[j']\}$$
(B4)

When $l \neq l'$ we have

$$E\{C_{ll}[\tau] \cdot C_{l'k}^*[\tau']\} = \frac{\delta_{l'k}}{4N_l N_{l'}} \sum_{ij i'j'} g_{ij}[\tau] \cdot g_{i'j'}[\tau'] \cdot E\{c_l^*[i] \cdot c_l[j] \cdot c_{l'}[i'] \cdot c_{l'}^*[j']\}$$

$$= \frac{\delta_{l'k}}{4N_l N_{l'}} \sum_{ij i'j'} g_{ij}[\tau] \cdot g_{i'j'}[\tau'] \cdot 2\delta_{ij} \cdot 2\delta_{i'j'}$$
(B5)

$$= \frac{\delta_{l'k}}{N_l N_{l'}} \sum_{i i'} g[\tau] \cdot g[\tau']$$

$$= \delta_{l'k} \cdot g[\tau] \cdot g[\tau']$$

whereas when $l = l'$ we have

$$E\{C_{ll}[\tau] \cdot C_{lk}^*[\tau']\} = \frac{1}{4N_l^2} \sum_{ij i'j'} g_{ij}[\tau] \cdot g_{i'j'}[\tau'] \cdot E\{c_l^*[i] \cdot c_l[i'] \cdot c_l[j] \cdot c_k^*[j']\}$$

$$= \frac{\delta_{lk}}{4N_l^2} \sum_{ij i'j'} g_{ij}[\tau] \cdot g_{i'j'}[\tau'] \cdot E\{c_l^*[i] \cdot c_l[i'] \cdot c_l[j] \cdot c_l^*[j']\}$$

$$= \frac{\delta_{lk}}{4N_l^2} \left\{ \sum_{i \neq j, i'j'} g_{ij}[\tau] \cdot g_{i'j'}[\tau'] \cdot E\{c_l^*[i] \cdot c_l[i'] \cdot c_l[j] \cdot c_l^*[j']\} \right.$$
(B6a)

$$\left. + \sum_{i=j, i'j'} g_{ij}[\tau] \cdot g_{i'j'}[\tau'] \cdot E\{c_l^*[i] \cdot c_l[i'] \cdot c_l[j] \cdot c_l^*[j']\} \right\}$$

$$= \frac{\delta_{lk}}{4N_l^2} \left\{ \sum_{i \neq j, i'j'} g_{ij}[\tau] \cdot g_{i'j'}[\tau'] \cdot 2\delta_{ii'} \cdot 2\delta_{jj'} \right.$$

$$\left. + \sum_{i=j, i'j'} g[\tau] \cdot g_{i'j'}[\tau'] \cdot 2E\{c_l[i'] \cdot c_l^*[j']\} \right\}$$
(B6b)

$$= \frac{\delta_{lk}}{4N_l^2} \left\{ \sum_{ij i'j'} g_{ij}[\tau] \cdot g_{i'j'}[\tau'] \cdot 2\delta_{ii'} \cdot 2\delta_{jj'} - \sum_{i=j, i'j'} g_{ij}[\tau] \cdot g_{i'j'}[\tau'] \cdot 2\delta_{ii'} \cdot 2\delta_{jj'} \right.$$

$$\left. + \sum_{i=j, i'j'} g_{ij}[\tau] \cdot g_{i'j'}[\tau'] \cdot 2E\{c_l[i'] \cdot c_l^*[j']\} \right\}$$

$$= \frac{\delta_{lk\cdot}}{4N_l^2} \left\{ \sum_{ij} g_{ij}[\tau] \cdot g_{ij}[\tau'] \cdot 2 \cdot 2 - \sum_i g[\tau] \cdot g[\tau'] \cdot 2 \cdot 2 \right.$$

$$\left. + \sum_{i=j,i'j'} g_{ij}[\tau] \cdot g_{i'j'}[\tau'] \cdot 2 \cdot 2\delta_{i'j'} \right\}$$

(B6c)

$$= \frac{\delta_{rk\cdot}}{N_l^2} \left\{ \sum_{ij} g_{ij}[\tau] \cdot g_{ij}[\tau'] - N_l g[\tau] \cdot g[\tau'] + N_l^2 g[\tau] \cdot g[\tau'] \right\}$$

$$= \delta_{rk\cdot} g[\tau] \cdot g[\tau'] + \frac{\delta_{rk\cdot}}{N_l^2} \left\{ \sum_{ij} g_{ij}[\tau] \cdot g_{ij}[\tau'] - N_l g[\tau] \cdot g[\tau'] \right\}$$

Hence combining Equations (B5) and (B6c) we have

$$E\{C_{ll}[\tau] \cdot C_{rk\cdot}^*[\tau']\} = \delta_{rk\cdot} g[\tau] \cdot g[\tau'] + \frac{\delta_{ll'} \cdot \delta_{rk\cdot}}{N_l^2} \left\{ \sum_{ij} g_{ij}[\tau] \cdot g_{ij}[\tau'] - N_l g[\tau] \cdot g[\tau'] \right\}$$

(B7)

and combining cases for $l \neq k$ and $l = k$ we have

$$E\{C_{lk}[\tau] \cdot C_{rk\cdot}^*[\tau']\} = \delta_{lk} \cdot \delta_{rk\cdot} g[\tau] \cdot g[\tau'] + \frac{\delta_{lk} \cdot \delta_{ll'} \cdot \delta_{rk\cdot}}{N_l^2} \left\{ \sum_{ij} g_{ij}[\tau] \cdot g_{ij}[\tau'] - N_l g[\tau] \cdot g[\tau'] \right\}$$

$$+ (1 - \delta_{lk}) \frac{\delta_{ll'} \cdot \delta_{kk\cdot}}{N_l^2} \sum_{ij} g_{ij}[\tau] \cdot g_{ij}[\tau']$$

$$= \delta_{lk} \cdot \delta_{rk\cdot} g[\tau] \cdot g[\tau'] + \frac{\delta_{lk} \cdot \delta_{ll'} \cdot \delta_{rk\cdot}}{N_l^2} \left\{ \sum_{ij} g_{ij}[\tau] \cdot g_{ij}[\tau'] - N_l g[\tau] \cdot g[\tau'] \right\}$$

(B8)

$$+ \frac{\delta_{ll'} \cdot \delta_{kk\cdot}}{N_l^2} \sum_{ij} g_{ij}[\tau] \cdot g_{ij}[\tau'] - \frac{\delta_{lk} \cdot \delta_{ll'} \cdot \delta_{rk\cdot}}{N_l^2} \sum_{ij} g_{ij}[\tau] \cdot g_{ij}[\tau']$$

$$= \delta_{lk} \cdot \delta_{rk\cdot} g[\tau] \cdot g[\tau'] - \frac{\delta_{lk} \cdot \delta_{ll'} \cdot \delta_{rk\cdot}}{N_l} g[\tau] \cdot g[\tau'] + \frac{\delta_{ll'} \cdot \delta_{kk\cdot}}{N_l^2} \sum_{ij} g_{ij}[\tau] \cdot g_{ij}[\tau']$$

The above expression can be used to determine the second-order statistics for the general case of symbol-asynchronous and chip-asynchronous users with arbitrary spreading factors. In what follows we will be interested in approximating the above expression so as to get simple but meaningful results. In order to simplify the expressions we consider users all at the highest spreading factor, and we assume that certain small values are zero.

To assess the accuracy of channel estimation we need to determine the second order statistics

$$E\{C_{lkqp}[m] \cdot C_{rk\cdot q'p'}^*[m']\} = E\{C_{lk}[\tau_{lkqp}[m]] \cdot C_{rk\cdot}^*[\tau_{rk\cdot q'p'}[m']]\}$$

$$\tau_{lkqp}[m] \equiv mT + \tau_{lq} - \tau_{kp}$$

(B9)

with $lq \neq kp$. The function $g[\tau]g[\tau']$ in Equation (B8) above is small unless both τ and τ' are close to zero, and for the chip-asynchronous case function is exactly zero since unless both τ and τ' are equal to zero. Since for $lq \neq kp$ the probability that $\tau_{lkqp}[m]$ is close to zero is small a good approximation is to assume that these functions are zero. The third term can be written

$$E\left\{C_{lk}[\tau] \cdot C_{l'k'}^*[\tau']\right\} \cong \frac{\delta_{ll'}\delta_{kk'}}{N_l}\left\{\frac{1}{N_l}\sum_{ij} g_{ij}[\tau] \cdot g_{ij}[\tau']\right\} \tag{B10}$$

The double summation in the brackets

$$S_{lk}[\tau,\tau'] \equiv \frac{1}{N_l}\sum_{ij} g_{ij}[\tau] \cdot g_{ij}[\tau'] \tag{B11}$$

is plotted in Figure B1 for $N_l = N_k = 256$ versus $\tau - \tau'$ for $(\tau + \tau')/2 = 0$.

Figure B1. Plot of $S_{lk}[\tau,\tau']$ for $N_l = N_k = 256$
versus $\tau - \tau'$ for $(\tau + \tau')/2 = 0$.

The sharp localization around $\tau - \tau' = 0$ is valid for all values of $(\tau + \tau')/2$, except that for $(\tau + \tau')/2$ large peak value drops off due to the partial overlap of the codes. Hence for delay lag differences $\tau - \tau'$ greater than about 2 chips a good approximation is

$$S_{lk}[\tau,\tau'] \cong \delta_{\tau\tau'} \cdot S_{lk}[\tau,\tau] \tag{B12}$$

This approximation then gives

$$E\left\{C_{lk}[\tau] \cdot C_{l'k'}^*[\tau']\right\} \cong \frac{\delta_{ll'} \cdot \delta_{kk'}}{N_l} \cdot \delta_{\tau\tau'} \cdot S_{lk}[\tau,\tau] \tag{B13}$$

which implies

$$E\{C_{lkqp}[m] \cdot C_{l'k'q'p'}^{*}[m']\} \cong \frac{1}{N_l} \cdot \delta_{ll'} \cdot \delta_{kk'} \cdot \delta_{qq'} \cdot \delta_{pp'} \cdot \delta_{mm'} \cdot S_{lk}[\tau, \tau] \qquad (B14)$$

provided the delay spread is less than a symbol period. Now it can be shown that

$$\begin{aligned} S_{lk}[\tau_{lkqp}[m'], \tau_{lkqp}[m']] &= \frac{1}{N_l} \sum_{ij} g_{ij}^2 [\tau_{lkqp}[m']] \\ &\cong \frac{N_{lkqp}[m']}{N_l} \end{aligned} \qquad (B15)$$

where $N_{lkqp}[m']$ is the overlap between the user codes. Our final result is then

$$E\{C_{lkqp}[m] \cdot C_{l'k'q'p'}^{*}[m']\} \cong \frac{1}{N_l} \cdot \delta_{ll'} \cdot \delta_{kk'} \cdot \delta_{qq'} \cdot \delta_{pp'} \cdot \delta_{mm'} \cdot \frac{N_{lkqp}[m']}{N_l} \qquad (B16)$$

Computer Systems, Inc.
MERCURY
199 Riverneck Road
Chelmsford, MA 01824-2820
(978) 256-1300 • Fax (978) 256-3599
http://www.mc.com

Report

To: Wireless Communications Group

From: J. H. Oates

Subject: MUD interface to modem   Date: January 3, 2001

1. Multi-User Signal Model

The Rake receiver operation described in the next section is based a signal model. The MUD algorithm and implementation are based on the same model. This model is described below.

Figure 1 shows how the uplink complex spreading for the Dedicated Physical Data CHannels (DPDCHs) and the Dedicated Physical Control CHannel (DPCCH). There can be from 1 to 6 DPDCHs, denoted $DPDCH_k$, for k from 1 to 6. If there is more than one DPDCH, then the spreading factor for all DPDCHs must be equal to 4. For a single DPDCH ($DPDCH_1$) the spreading factor can vary from 4 to 256. The data bits for channel $DPDCH_1$ are spread by channelization code $c_{d,1} = C_{ch,SF,SF/4}$, where SF is the DPDCH spreading factor. These channelization codes are referred to as Orthogonal Variable Spreading Factor (OVSF) codes. They are equivalent to Hadamard codes, except for their ordering. When there are multiple DPDCHs then dedicated channels $DPDCH_k$, for k from 1 to 6 are spread by channelization codes $c_{d,k} = C_{ch,4,n}$, where the relationship between n and k is represented in Table 1.

Table 1. Relationship between n and k.

n	k
1	1,2
3	3,4
2	5,6

The data bits for the DPCCH are spread by code $c_c = C_{ch,256,0}$. The spreading factor for the DPCCH is always equal to 256. The multipliers β_c and β_d are constants used to select the relative amplitudes of the control and data channels. At least one of these constants must be equal to 1 for any given symbol period m.

Figure 1. Uplink complex spreading of DPDCHs and DPCCH

The uplink spreading for any one of the seven Dedicated CHannels (DCHs) above can be represented as shown in Figure 2.

Figure 2. A second representation of the uplink spreading for any one of the seven Dedicated CHannels (DCHs).

where the code $c[n]$ is given by

$$
c[n] = \begin{cases}
C_{ch,256,0}[n] \cdot jS_{sh}[n], & \text{DPCCH} \\
C_{ch,256,64}[n] \cdot S_{sh}[n], & \text{DPDCH}_1 \\
C_{ch,256,64}[n] \cdot jS_{sh}[n], & \text{DPDCH}_2 \\
C_{ch,256,192}[n] \cdot S_{sh}[n], & \text{DPDCH}_3 \\
C_{ch,256,192}[n] \cdot jS_{sh}[n], & \text{DPDCH}_4 \\
C_{ch,256,128}[n] \cdot S_{sh}[n], & \text{DPDCH}_5 \\
C_{ch,256,128}[n] \cdot jS_{sh}[n], & \text{DPDCH}_6
\end{cases} \tag{1}
$$

$$\beta = \begin{cases} \beta_c, & \text{DPCCH} \\ \beta_d, & \text{DPDCH}_{1-6} \end{cases} \tag{2}$$

For a DCH with a spreading factor less than 256 there are $J = 256/SF$ data bits transmitted during a single 256-chip symbol period (i.e. 1/15 ms). From a signal model perspective, the J data bits transmitted per symbol period can be viewed as arising from J virtual users, each transmitting a single bit per symbol period. The idea is illustrated in Figure 3.

Figure 3. *Transforming a single user with bit rate J bits per symbol period into J virtual users, each with bit rate 1 bit per symbol period.*

The codes for these virtual users are formed by extracting SF elements at a time out of the DCH code sequence to form J new codes. Each of the J codes is of length 256 chips, but with only SF non-zero chips. That is,

$$c_j[n] \equiv \begin{cases} c[n], & j \cdot SF \le n < (j+1) \cdot SF \\ 0, & \text{otherwise} \end{cases} \tag{3}$$

This code-partitioning concept is illustrated in Figure 4 for the case $SF = 64$ so that $J = 256/SF = 4$ codes are derived from the one DCH code.

Figure 4. Code partitioning concept illustrated for the case SF = 64, whereby J = 256/SF = 4 codes are derived from a single DCH code.

The control channel can also be viewed as a virtual user. Hence, for a given physical user with spreading factor SF there are $1 + 256N_D/SF$ virtual users, where N_D is the number of DPDCHs. (Recall that for $N_D > 1$, $SF = 4$.)

It turns out to be convenient to use a double indexing scheme to identify virtual users. Let paired indices kj represent the jth virtual user associated with the kth dedicated channel. Index j varies from $0 <= j < J_k = 256/SF_k$, where SF_k is the spreading factor for the kth dedicated channel. For the remainder of this section the spreading factors SF_k are assumed to be constant. In section 3 the equations are reformulated to allow for symbol-by-symbol changes in the spreading factor.

The transmitted signal for virtual user kj can be written

$$x_{kj}[t] = \beta_k \sum_m v_{kj}[t - mT]b_{kj}[m] \tag{4}$$

where t is the integer time sample index, $T = NN_c$ is the data bit duration, $N = 256$ is the short-code length, N_c is the number of samples per chip, $b_{kj}[m]$ are the data bits, and where $v_{kj}[t]$ is the transmit signature waveform for virtual user kj. This waveform is generated by passing the spread code sequence $c_{kj}[n]$ through a root-raised-cosine pulse-shaping filter $h[t]$

$$s_{kj}[t] = \sum_{p=0}^{N-1} h[t - pN_c]c_{kj}[p] \tag{5}$$

Note that $\beta_k = \beta_c$ if the kjth virtual user corresponds to a control channel. Otherwise $\beta_k = \beta_d$.

The total number of virtual users is denoted

$$K_v \equiv \sum_{k=1}^{K_D} \frac{256}{SF_k} \tag{6}$$

where K_D is the total number of dedicated channels. The baseband received signal after root-raised-cosine matched-filtering can be written

$$r[t] = \sum_{k=1}^{K_D} \sum_{j=0}^{J_k-1} \sum_m \tilde{s}_{kj}[t - mT]b_{kj}[m] + w[t] \tag{7}$$

where $w[t]$ is receiver noise with a raised-cosine power spectral density, and where $\tilde{s}_{kj}[t]$ is the channel-corrupted signature waveform for virtual user kj. For L multipath components the channel-corrupted signature waveform for virtual user kj is modeled as

$$\tilde{s}_{kj}[t] = \sum_{p=1}^{L} a_{kp} s_{kj}[t - \tau_{kp}] \tag{8}$$

where a_{kp} are the complex multipath amplitudes. The amplitude ratios β_k are incorporated into the amplitudes a_{kp}. Notice that if k and l are two dedicated channels corresponding to the same physical user then, aside from scaling the by β_k and β_l, a_{kp} and a_{lp}, are equal. This is due to the fact that the signal waveforms of all virtual users corresponding to the same physical user pass through the same channel. The waveform $s_{kj}[t]$ is referred to as the signature waveform for the $kjth$ virtual user. This waveform is generated by passing the spread code sequence $c_{kj}[n]$ through a raised cosine pulse-shaping filter $g[t]$

$$s_{kj}[t] = \sum_{p=0}^{N-1} g[t - pN_c]c_{kj}[p] \tag{9}$$

Note that for spreading factors less than 256 some of the chips $c_{kj}[p]$ are zero.

2. Rake Receiver Operation

This section describes the operation of a typical Rake receiver. Figure 1 shows a representation of the received antenna data that is delivered to the Rake receivers of all users.

One symbol (i.e. 256 chips)

Start of
buffer

User 1

τ_{lq}

Start of frame for user 1

T_{lq}

User k

τ_{kp}

Start of frame for user k

T_{kp}

Start of MUD
processing frame

Figure 5. Received antenna data delivered to the Rake receivers of all users.

The figure shows the received signals corresponding to users *l* and *k*. These signals are combined in free space so that the receivers gets one composite signal, which we denote *r[t]*. The buffer length is assumed to be an integral number of frames in length so that delay lag values T_{lq} are approximately constant with each new filling of the buffer. For each finger of each user there is a delay lag value T_{lq} indicating the start of frame for the *q*th multipath of the *l*th user. Lag values T_{lq} are assumed to be constant over a frame, but are allowed to change from frame to frame in response to the delay locked loop operation and in response to new searcher-receiver sweeps where new delay lags are found. The lower case values $\tau_{lq} = T_{lq}$ *mod 256N$_c$* denote the symbol-period offset relative to the start of an internal symbol period reference clock. Notice that the user spreading factors change on user frame boundaries. Since users are asynchronous it is impossible to have a MUD processing frame that corresponds to all user frame boundaries. Hence the MUD processing frame is matched as close as possible to the user frame boundaries, but does not necessarily correspond precisely to any user's frame boundary. Consequently there will be spreading factor changes that occur during a MUD processing frame. Handling these mid-frame changes is the subject of section 3 below.

The received signal above, which has been match-filtered to the chip pulse, must next be match-filtered by the user code-sequence filter. Since the spreading factor for the DPDCHs is not known, the Rake receiver performs an initial 4-chip despreading over all DPDCHs. The Fast Hadamard Transformation (FHT) can be used here to reduce the number of operations. The detection statistics for the multiple fingers and multiple antennas are maximal-ratio combined. Since the DPCCH is always spread with a spreading factor of 256 the DPCCH can be entirely despread during each symbol period. TFCI bits are extracted each slot from the DPCCH. After an entire frame is processed the TFCI is decoded and the spreading factor for that frame is determined. After spreading factor determination the final DPDCH despreading is performed. The resulting detection statistics are denoted here as $y_{kj}[m]$, the matched-filter output for the *kj*th virtual user for the *m*th symbol period. Since there are K_v codes, there are K_v such detection statistics,

which are collected into a column vector $y[m]$ for the mth symbol period. The matched-filter output $y_{li}[m]$, for the lth virtual user can be written

$$y_{li}[m] = \text{Re}\left\{ \sum_{q=1}^{L} \hat{a}_{lq}^{H} \cdot y_{li,q}[m] \right\}$$

$$y_{li,q}[m] \equiv \frac{1}{2N_{l}} \sum_{n} r[nN_{c} + \hat{\tau}_{lq} + mT] \cdot \overset{*}{c}_{li}[n]$$

(10)

where $\hat{a}_{lq}$ is the estimate of a_{lq}, $\hat{\tau}_{lq}$ is the estimate of τ_{lq}, and N_{l} is the (non-zero) length of codes $c_{li}[n]$ (i.e., the spreading factor for the lth dedicated channel). The intermediate result $y_{li,q}[m]$ represents the despread signal at the qth lag, and is here referred to the pre-MRC matched-filter output. When multiple antennas are employed, $r[t]$, $y_{li,q}[m]$ and $\hat{a}_{lq}$ are column vectors with one complex element per antenna.

The matched-filter detector estimates the transmitted data bits as $\hat{b}_{li}[m] \equiv sign\{y_{li}[m]\}$. Multiuser detection is considered in the next section.

3. Multiuser Detection Equations and Asynchronous Processing

As shown in Figure 5 a MUD processing interval must necessarily by asynchronous with most user's frame boundaries since the users are asynchronous. Because of this spreading factors will change during a MUD processing frame. When the spreading factor changes during the processing frame the MUD equations are modified. These modifications are considered in this section.

The modem delivers matched-filter data to the MUD function on a frame-by-frame basis. Let $N_{P}[r]$ represent the number of physical users accessing the system during frame r. For each frame the following data is received for physical users $p = 1$ to $N_{P}[r]$ and each dedicated channel l
- Number of DPDCHs, $N_{D,p}$
- Spreading factor, SF_{l}
- Amplitude ratios β_{d} and β_{c}
- Slot format
- Channel amplitude estimates a_{lq}
- Channel lag estimates T_{lq}
- Matched-filter outputs $f_{li}[m]$ for all DCHs
- Code numbers
- Gap information for compressed mode

Matched-filter outputs $f_{li}[m]$ correspond to the matched-filter outputs $y_{li}[m]$. If the lth dedicated channel is a DPCCH then matched-filter outputs are only received for the TPC, TFCI and FBI bits. The $f_{li}[m]$ values are mapped to the $y_{li}[m]$ values as described below. The mapping accounts for the frame offsets between the various users. The amount of matched-filter data received per physical user depends on the DPDCH spreading factor.

For each dedicated channel a symbol offset m_{l} is determined according to

$$m_l \equiv \left\{ \frac{1}{L} \sum_{q=1}^{L} T_{lq} \right\} \text{div} (256 N_c)$$ (11)

where *div* denotes integer division (i.e. with truncation). The symbol offset represents the fact that the users and hence the frame data are asynchronous. The y-data used for interference cancellation is derived from the frame data using

$$y_{li}[m] = f_{li}[m - m_l]$$ (12)

Figure 6 shows an example mapping of user data frames to MUD processing frames. To illustrate concepts the frames are each 16 symbol periods long rather than the actual 150 symbols for WCDMA. The height of the blocks represents the number of virtual users per physical user. For physical users 1 and 4 the spreading factor changes in going from data frame 1 to data frame 2. As shown in the figure this results in spreading factor changes within the MUD processing frame. The MUD function is designed to Calculate the C-matrix once per frame. Hence mid-frame changes to user spreading factors pose a problem which requires special treatment. It turns out, and will be shown below, that mid-frame changes to the spreading factor can be accommodated by performing modified calculations based on the minimum spreading factor over the MUD processing frame.

Figure 6. Mapping of user data frames to MUD processing frames.

First we develop the MUD matrix signal model which allows user spreading factors to change on a symbol-by-symbol basis. We then show how we can perform the processing based on the minimum user spreading factors over the MUD processing frame.

Let us reformulate the signal model presented in section 1 so as to allow spreading factors to change every symbol period. For every DCH *k*, there are $J_k[m]$ virtual users, where index *m* is the symbol period index. The number of DCHs $J_k[m]$ is

$$J_k[m] \equiv \frac{256}{SF_k[m]}$$ (13)

8

where $SF_k[m]$ is the spreading factor for the kth dedicated channel during the mth symbol period. The signature waveform for the jth virtual user of $J_k[m]$ total belonging to the kth DCH over the mth symbol period can be written

$$s_{kj,m}[t] = \sum_{p=0}^{N-1} g[t - pN_c]c_{kj,m}[p] \tag{14}$$

where the codes and hence the signature waveforms now include the symbol-period index m to account for symbol-by-symbol spreading factor changes. The channel-corrupted signature waveform is then

$$\tilde{s}_{kj,m}[t] = \sum_{p=1}^{L} a_{kp} s_{kj,m}[t - \tau_{kp}] \tag{15}$$

and thus the received signal corresponding to K_D dedicated channels is

$$r[t] = \sum_{k=1}^{K_D} \sum_{m} \sum_{j=0}^{J_k[m]-1} \tilde{s}_{kj,m}[t - mT]b_{kj}[m] + w[t] \tag{16}$$

The MUD matrix signal model proceeds from substituting the received signal $r[t]$ from Equation (16) into Equation (10) for the matched-filter outputs

$$y_{li}[m] \equiv \sum_{n} \sum_{k=1}^{K_D} \sum_{j=0}^{J_k[n]-1} \text{Re}\left\{\sum_{q=1}^{L} \hat{a}_{lq}^H \cdot \frac{1}{2N_l[m]} \sum_{r} \tilde{s}_{kj,n}[rN_c + \hat{\tau}_{lq} + (m-n)T] \cdot c_{li,m}^*[r]\right\} b_{kj}[n] + \eta_{li}[m]$$

$$= \sum_{n} \sum_{k=1}^{K_A} \sum_{j=0}^{J_k[n]-1} r_{likj}[m,n]b_{kj}[n] + \eta_{li}[m] \tag{17}$$

$$r_{likj}[m,n] = \sum_{q=1}^{L} \sum_{p=1}^{L} \text{Re}\left\{\hat{a}_{lq}^H a_{kp} \cdot C_{likjqp}[m,n]\right\}$$

$$C_{likjqp}[m,n] \equiv \frac{1}{2N_l[m]} \sum_{r} \sum_{s} g[(r-s)N_c + (m-n)T + \hat{\tau}_{lq} - \tau_{kp}]c_{li,m}^*[r] \cdot c_{kj,n}[s]$$

where $\eta_{li}[m]$ is the match-filtered receiver noise and $N_l[m] = SF_l[m]$. The terms for $m' <> 0$ result from asynchronous users.

The delay lags τ_{lq} for a given DCH l will under most circumstances be grouped within a range of from 4 to 8 µs. Under extreme conditions the delay spread will be as high as 20 µs. In any event, let τ_l represent the mean delay lag τ_{lq} over index q. According to Equation (10) above, the matched-filter detection statistic $y_{li}[0]$ is the result found by correlating the received signal starting roughly at delay lag τ_l, where τ_l is approximately in the range 0 to $256N_c$. If τ_l moves significantly outside this range an adjustment in the symbol period alignment will need to be made to restore τ_l back to within the desired range. More will be said about this below. Along the same lines, the detection statistic

$y_{li}[m]$ is the result found by correlating the received signal starting roughly at delay lag $\tau_l + mT$.

For efficient MUD processing it is important for the C-matrices to be constant over a 10 ms MUD processing frame. We now describe a method which operates on constant C-matrices. Handling changes to user spreading factors is relegated to the IC portion of the MUD processing. Let us define

$$J_k \equiv \max_m J_k[m] \qquad (18)$$

where the maximization is over symbol periods m that contribute to the current MUD processing frame. This includes not only symbol periods that fall within the MUD processing frame, but in addition a few symbol periods on either side due to asynchronous users. Note that the minimum spreading factor for the kth DCH is $SF_k = 256/J_k$. Now define the DCH *contraction factor* for the mth symbol period as

$$C_k[m] \equiv \frac{J_k}{J_k[m]} \qquad (19)$$

The DCH codes for a given symbol period can be expressed as a sum of the DCH codes corresponding to the minimum spreading factor. For the kth DCH there are at most J_k virtual users corresponding to the minimum spreading factor. Let the codes for these users be denoted $c_{kj}[r]$, $0 <= j < J_k$. The codes for the mth symbol period, where there might be fewer virtual users, are denoted $c_{kj,m}[r]$, $0 <= j < J_k[m]$, where

$$c_{kj,m}[r] = \sum_{j'=j \cdot C_k[m]}^{(j+1) \cdot C_k[m]-1} \mathbf{c}_{kj'}[r] \qquad (20)$$

With this result we are now able to represent the MUD signal model in terms of the C-matrix and R-matrix elements based on the codes corresponding to the minimum DCH spreading factors. The C-matrix in Equation () above becomes

$$C_{likjqp}[m,n] \equiv \frac{1}{2N_l[m]} \sum_r \sum_s g[(r-s)N_c + (m-n)T + \hat{\tau}_{lq} - \tau_{kp}]c_{li,m}^*[r] \cdot c_{kj,n}[s]$$

$$= \frac{1}{2N_l[m]} \sum_r \sum_s g[(r-s)N_c + (m-n)T + \hat{\tau}_{lq} - \tau_{kp}] \sum_{i'=i \cdot C_l[m]}^{(i+1) \cdot C_l[m]-1} \mathbf{c}_{li'}^*[r] \cdot \sum_{j'=j \cdot C_k[n]}^{(j+1) \cdot C_k[n]-1} \mathbf{c}_{kj'}[s]$$

$$= \frac{N_l}{N_l[m]} \sum_{i'=i \cdot C_l[m]}^{(i+1) \cdot C_l[m]-1} \sum_{j'=j \cdot C_k[n]}^{(j+1) \cdot C_k[n]-1} \frac{1}{2N_l} \sum_r \sum_s g[(r-s)N_c + (m-n)T + \hat{\tau}_{lq} - \tau_{kp}]c_{li'}^*[r] \cdot c_{kj'}[s]$$

$$= \frac{N_l}{N_l[m]} \sum_{i'=i \cdot C_l[m]}^{(i+1) \cdot C_l[m]-1} \sum_{j'=j \cdot C_k[n]}^{(j+1) \cdot C_k[n]-1} \mathbf{C}_{li'kj'qp}[m-n]$$

$$\mathbf{C}_{likjqp}[m-n] \equiv \frac{1}{2N_l} \sum_r \sum_s g[(r-s)N_c + (m-n)T + \hat{\tau}_{lq} - \tau_{kp}]\mathbf{c}_{li}^*[r] \cdot \mathbf{c}_{kj}[s]$$

$$\qquad (21)$$

where $N_l = min \ N_l[m] = SF_l$. Similarly, the R-matrix becomes

$$r_{likj}[m,n] = \sum_{q=1}^{L}\sum_{p=1}^{L} \text{Re}\{\hat{a}_{lq}^{H} a_{kp} \cdot C_{likjqp}[m,n]\}$$

$$= \frac{N_l}{N_l[m]} \sum_{i'=i \cdot C_l[m]}^{(i+1)\cdot C_l[m]-1} \sum_{j'=j \cdot C_k[n]}^{(j+1)\cdot C_k[n]-1} \sum_{q=1}^{L}\sum_{p=1}^{L} \text{Re}\{\hat{a}_{lq}^{H} a_{kp} \cdot C_{li'kj'qp}[m-n]\}$$

$$= \frac{N_l}{N_l[m]} \sum_{i'=i \cdot C_l[m]}^{(i+1)\cdot C_l[m]-1} \sum_{j'=j \cdot C_k[n]}^{(j+1)\cdot C_k[n]-1} \mathbf{r}_{li'kj'}[m-n] \tag{22}$$

$$\mathbf{r}_{likj}[m-n] \equiv \sum_{q=1}^{L}\sum_{p=1}^{L} \text{Re}\{\hat{a}_{lq}^{H} a_{kp} \cdot C_{likjqp}[m-n]\}$$

so that the matched-filter outputs become

$$y_{li}[m] \equiv \sum_{n}\sum_{k=1}^{K_D}\sum_{j=0}^{J_k[n]-1} r_{likj}[m,n]b_{kj}[n] + \eta_{li}[m]$$

$$= \sum_{n}\sum_{k=1}^{K_D}\sum_{j=0}^{J_k[n]-1} \left\{ \frac{N_l}{N_l[m]} \sum_{i'=i \cdot C_l[m]}^{(i+1)\cdot C_l[m]-1} \sum_{j'=j \cdot C_k[n]}^{(j+1)\cdot C_k[n]-1} \mathbf{r}_{li'kj'}[m-n] \right\} b_{kj}[n] + \eta_{li}[m] \tag{23}$$

This last equation can be written

$$y_{li}[m] = \sum_{n}\sum_{k=1}^{K_D}\sum_{j=0}^{J_k[n]-1} \left\{ \frac{N_l}{N_l[m]} \sum_{i'=i \cdot C_l[m]}^{(i+1)\cdot C_l[m]-1} \sum_{j'=j \cdot C_k[n]}^{(j+1)\cdot C_k[n]-1} \mathbf{r}_{li'kj'}[m-n] \right\} b_{kj}[n] + \eta_{li}[m]$$

$$= \frac{N_l}{N_l[m]} \sum_{i'=i \cdot C_l[m]}^{(i+1)\cdot C_l[m]-1} \mathbf{y}_{li'}[m] + \eta_{li}[m]$$

$$\tag{24}$$

$$\mathbf{y}_{li'}[m] \equiv \sum_{n}\sum_{k=1}^{K_D}\sum_{j=0}^{J_k[n]-1} \left\{ \sum_{j'=j \cdot C_k[n]}^{(j+1)\cdot C_k[n]-1} \mathbf{r}_{li'kj'}[m-n] \right\} b_{kj}[n]$$

$$= \sum_{n}\sum_{k=1}^{K_D}\sum_{j=0}^{J_k[n]-1} \left\{ \sum_{j'=j \cdot C_k[n]}^{(j+1)\cdot C_k[n]-1} \mathbf{r}_{li'kj'}[m-n] \cdot \mathbf{b}_{kj'}[n] \right\}$$

$$= \sum_{n}\sum_{k=1}^{K_D}\sum_{j'=0}^{J_k-1} \mathbf{r}_{li'kj'}[m-n] \cdot \mathbf{b}_{kj'}[n]$$

where we have defined $\mathbf{b}_{kj'}[n] = b_{kj}[n]$ for $jC_k[n] <= j' < (j + 1)C_k[n]$. Equation (24) is based entirely in terms of matrix elements corresponding to the minimum spreading factor for the MUD processing frame.

THIS PAGE BLANK (USPTO)

Computer Systems, Inc.

MERCURY

199 Riverneck Road
Chelmsford, MA 01824-2820
(978) 256-1300 • Fax (978) 256-3599
http://www.mc.com

Report

To: Wireless Communications Group

From: J. H. Oates

Subject: WCDMA Downlink MUD   Date: February 23, 2001

1. Introduction

MultiUser Detection (MUD) is most often thought of as a technique to improve either capacity or coverage for the *uplink*. A few reasons why MUD is uplink-focussed are
- Downlink MUD must be performed in the handsets, which are limited in processing power
- Each handset is interested in only one signal
- In the downlink users are separated by orthogonal codes

However, there is typically a greater demand for capacity in the downlink. If MUD is only applied in the uplink the imbalance is even greater. While in the downlink users are separated by orthogonal codes, because of multipath there is still significant intra-cell interfernece. Equalization has been suggested as a means of restoring orthogonality, however the computationally attractive linear equalization methods tend to amplify the othe-cell interference and noise.

A downlink MUD method is described in the next section which has reduced complexity. The Fast Hadamard Transform (FHT) is used to reduce complxity. The FHT is used in both the forward (demodulation) and backward (regeneration) directions.

2. The Method

The method proceeds according to the following steps
- Receive amplitude and delay information form the searcher receiver
- Start with the largest multipath
- Multiply the received signal by the conjugate of the scrambling code (512 chips at a time)
- Perform the FHT on the result (for multirate users, this is done in stages)
- Determine soft data estimates

- Set user-of-interest data symbols to zero.
- Do same for all multipaths
- Proceed till end of slot
- Estimate amplitudes and gain factors
- Diversity combine results and make hard decisions
- Use hard decisions, gain estimates and FHT to reconstruct chip sequence $c[n]$ (with user of interest nulled)
- Multiple $c[n]$ by $c_{sh}[n]$ to form $d[n]$ (with user of interest nulled)
- Use amplitude estimates, delay lag estimates (from searcher) and raised-cosine pulse to construct chip filter
- Pass $d[n]$ (with user of interest nulled) through chip filter to reconstruct interference signal
- Subtract interference signal from received signal
- Demodulate with conventional RAKE receiver

The WCDMA transmitted signal can be represented as

$$s[t] = \sum_n g[t - nN_c]d[n]$$

$$d[n] = \left\{ \sum_{k=1}^{K} G_k b_k[n \; div \; N_k] \cdot c_{ch,k}[n] \right\} \cdot c_{sh}[n] \qquad ()$$
$$= c[n] \cdot c_{sh}[n]$$

$$c[n] \equiv \sum_{k=1}^{K} G_k b_k[n \; div \; N_k] \cdot c_{ch,k}[n]$$

where $g[t]$ is the raised-cosine pulse[1], N_c is the number of samples per chip, and $d[n]$ is the composite chip sequence from all users. The received signal is then

$$r[t] = \sum_{q=1}^{L} a_q s[t - \tau_q]$$
$$= \sum_{q=1}^{L} a_q \sum_n g[t - \tau_q - nN_c]d[n] \qquad ()$$

The received signal advanced to the delay of interest is

---

[1] The chip-matched filter is artificially placed in the transmitter for simplicity of presentation

$$r[nN_c + \tau_p] = \sum_{q=1}^{L} a_q s[nN_c + \tau_p - \tau_q]$$

$$= \sum_{q=1}^{L} a_q \sum_m g[nN_c + \tau_p - \tau_q - mN_c]d[m] \qquad ()$$

$$= \sum_{q=1}^{L} a_q \sum_m g[\tau_p - \tau_q - mN_c]d[m+n]$$

The received signal multiplied by the conjugate of the scrambling codes is

$$r[nN_c + \tau_p] \cdot c_{sh}^*[n] = \sum_{q=1}^{L} a_q \sum_m g[\tau_p - \tau_q - mN_c]c[m+n]c_{sh}[m+n] \cdot c_{sh}^*[n]$$

$$= \left[\sum_{q=1}^{L} a_q g[\tau_p - \tau_q]\right] \cdot c[n] + w[n]$$

$$= \tilde{a}_p \cdot c[n] + w[n] \qquad ()$$

$$\tilde{a}_p \equiv \left[\sum_{q=1}^{L} a_q g[\tau_p - \tau_q]\right]$$

This result can now be demultiplexed using the 512 x 512 FHT. Since $512 = 2^9$, the FHT proceeds in 9 stages. After the first two stages the SF 4 symbols can be extracted. Similarly, after k stages the SF 2^k symbols can be extracted. The amplitudes $\tilde{a}_p$ can be determined from the embedded pilot symbols, or searcher-receiver estimates can be used. If embedded pilot symbols are used the measurements M_{pk} of the pth multipath of the kth user is in the form

$$M_{pk} = \tilde{a}_p G_k \qquad ()$$

which includes the user gain factor. After measurements are taken for all multipaths and all users for a given slot, the multipath amplitudes and user gains can be separated by determining the dominant left and right singular vectors of the rank-1 matrix M_{pk} (aside from an arbitrary scale factor which can be given to either amplitudes or the gains). One the approximate amplitudes $\tilde{a}_p$ are known the actual amplitudes a_p are determined by inverting the diagonally dominant system of equations

$$\tilde{a}_p = \sum_{q=1}^{L} a_q g[\tau_p - \tau_q]$$

$$= \sum_{q=1}^{L} g_{pq} a_q \qquad ()$$

$$g_{pq} \equiv g[\tau_p - \tau_q]$$

The chip filter h[t] for reconstructing the interference signal is

$$r[t] = \sum_{q=1}^{L} a_q s[t - \tau_q]$$

$$= \sum_{q=1}^{L} a_q \sum_n g[t - \tau_q - nN_c] d[n]$$

$$= \sum_n \left[\sum_{q=1}^{L} a_q g[t - \tau_q - nN_c] \right] d[n] \qquad ()$$

$$= \sum_n h[t - nN_c] d[n]$$

$$h[t] \equiv \sum_{q=1}^{L} a_q g[t - \tau_q]$$

Raceway DMA Engine

Raceway

Raceway
Protocol
Interface

Address Decode

DMA Command
Stack

FPGA Program
Interface

FPGA Program Da

DMA
State Machine

Receive FIFO
Interface

Receive Data

Transmit FIFO
Interface

Transmit Data

1

Possible DSP Raceway Architecture

2

3

4

Type	Memo
Project	MCW-DSP
Current Date	1/31/01
Author(s)	Paul Cantrell
Current Revision	0.1
File	

5
6
7
8
9

Revisions

10

Revision Date	Author	Version	Reason for changes
1/31/01	Paul Cantrell	0.1	Initial Revision

H.A. Bootstrap Functional Design Specification

11

12 ## **Table of Contents**

13

29

H.A. Bootstrap Functional Design Specification

30

1 Purpose

32   The purpose of this memo is to document parts of the discussion we have been
33 having on how the TI 6414 DSP may connect to the raceway.

34

35 2 Glossary

36   EMIF – A port on the DSP 6000 series peripheral bus which allows the
37   connection of memory devices.

38   SDRAM – In the context of this memo, means the main external memory of the
39   TI DSP – the one which contains the program and data.

40 3 Overview

41

42   So far, a proposed architecture is that we use the second EMIF (External
43   Memory Inter-Face) of the TI 6414 DSP to connect to a dual ported RAM.
44   Raceway transfers actually access the RAM, and then additional processing takes
45   place on the DSP to move the data to the correct place in SDRAM. In fact, if the
46   dualport RAM is not large enough to buffer an entire Raceway transfer, then there
47   will have to be a messaging protocol between the two endpoint DSPs wishing to
48   exchange messages (because the message will have to be fragmented in order to
49   not exceed the reserved buffer space).

50   An additional restriction of this design is that as more Raceway endpoints are
51   added, the size of the dualport RAM needs to be increased, or the maximum
52   fragment size needs to shrink, such that the RAM is big enough to contain at least
53      $2*F*N*P$ buffers of size F, where F is the size of the fragment, N is the number of
54   Raceway endpoints with which this DSP can exchange messages, P is the number
55   of parallel transfers which can be active on any endpoint at a time, and the
56   constant 2 represents double buffering so that one buffer can be transferred
57   to/from the Raceway, while a second buffer can be transferred to the DSP. The
58   constant becomes 4 if you want to be able to emulate a full duplex connection.
59   With a 4 node system, this might be $4*8K*4*4$ or 512K plus a little extra for
60   bookkeeping information. This probably means the minimum size is 1M bytes for
61   the dual port device.

62 4 Problem Identification

63   There are several characteristics of this architecture which could prove
64   problematic:

65 4.1 Requirement For A Fragment/Defragment Protocol

66   Raceway transfers can currently be very long. This architecture would require
67   a protocol for breaking transfers down into fragments. If the DSP is sourcing a
68   transfer greater than the fragment size, then it has to either dedicate itself for the
69   period of the transfer to programming the DMA engine, or it has to respond to
70   interrupts as each fragment is transferred. In either case, there is a substantial
71   performance impact above and beyond the normal performance hit due to
72   memory bandwidth utilization.

H.A. Bootstrap Functional Design Specification

73   If the DSP is on the receiving end of a Raceway transfer, a similar process has
74   to take place, except that there must be an interrupt to get the attention of the DSP
75   (polling would not be sufficient in such a case).

76   Beyond the performance hit such a protocol would impose on the DSP, there is
77   a major disadvantage in that only endpoints willing to implement this protocol can
78   exchange data with the DSP. It is in effect, defining a defacto standard subset of
79   Raceway. This is a major interoperability issue (you can no longer plug a board of
80   DSPs into a fabric and have them work as a standard Raceway Adjunct
81   Processor).

82   4.2   Requirement For The DSP To Be Running Code

83   If the DSP is involved in the Raceway transfers, then the DSP must already be
84   running in order to perform Raceway transfers. This will require that all nodes on
85   the Raceway be self booting.

86   4.3   Lower Transfer Rates

87   Raceway is less efficient with smaller transfer sizes. If the fragment size is kept
88   small to minimize dual port ram requirements, then aggregate Raceway transfer
89   rates will be lower because of less effiicient utilization of the fabric.

90   4.4   It Is Different

91   By changing the way Raceway works, we initiate a significant departure from
92   the way all current Mercury systems work. While there are many other possible
93   architectures which will perform well, it is inherently risky to change a
94   fundemental model of how our multiprocessors communicate.

95   5   An alternative Architecture

96   It may be possible to implement a different architecture which addresses some
97   of these shortcomings.

98

99

100

5.1 Architecture Description

101

102   The proposed architecture still has approximately the same hardware as the
103 existing architecture. The changes are in the way that the Raceway transfers move
104 between SDRAM and the Raceway.

105   In the proposed architecture, the FPGA connects to both the buffering device
106 (dual port RAM or FIFO) and the DSP. The connection to the buffering device
107 (hereafter FIFO) is used to move Raceway data to/from the FIFO.

108   The second connection is to the DSP Host Port. Dave currently believes this is
109 a moderately high performance interconnect – on the order of 75 Mbytes per
110 second. This interconnect could itself be used to move data to/from the DSP. The
111 host port can access data in the DSP on-chip memory, as well as any of the
112 peripheral devices, including the SDRAM. However, 75Mbytes per second is
113 pretty slow compared to normal Raceway bandwidth, and we think we can do
114 better.

115   The 6414 contains a second EMIF which can be attached to the FIFO (this is
116 similar to what the current architecture proposal intends). The difference in this
117 proposed architecture is that rather than have the DSP program the DMA engine

118 to move data between the FIFO and the DSP/SDRAM, we propose that the FPGA
119 can program the DMA engine directly via the Host Port.

120 The Host Port is a peripheral like the EMIF and the Serial Ports. The difference
121 is that the Host Port can master transfers into the DSP datapaths, i.e. it can read
122 and write any location in the DSP. Because the Host Port can access the DMA
123 Controller (we think), it can be used to initiate transfers via the DMA engine.

124 The advantage of this architecture is that Raceway transfers can be initiated
125 without the cooperation of the DSP. Thus, the DSP does not have to be self
126 booting. Performance is increased in two ways: the DSP is free to continue to
127 compute while Raceway transfers take place, and performance on the Racway is
128 increased because there is no need to fragment messages.

129 The internal datapaths of the DSP are flexible enough that we can control
130 which devices have priority access to memory and datapath. Specifically, we can
131 choose to give Raceway transfers priority over the CPU, or vice versa.

132 ### 5.2 Synchronization Issues

133 There is an issue to be solved in how we match data rates between Raceway
134 and the DSP. The EMIF looks to the DSP as if it were a memory, thus it is
135 reasonable for the DSP to assume it can get at the data it needs at any time.
136 However, if we indeed use a FIFO to buffer data, the implication is that there is a
137 way to hold off the DSP when we are waiting for the Raceway to empty or fill our
138 FIFO. A possibility is that the buffer device remains a dual port RAM rather than
139 a FIFO, and the FPGA actually does a fragment/defragment into the RAM, and
140 then programs the DMA engine to move that fragment into/out-of the DSP. This
141 starts to look somewhat like the original architecture, except that because the
142 FPGA performs the frag/defrag, the actual transfers over the Raceway can be
143 arbitrarily sized (assuming we can throttle the Raceway).

144 Synchronization remains one of the larger problems to be solved with this
145 proposed architecture.

146 ### 5.3 Sample Transfers

147 In order to illustrate how this architecture would work, two examples are
148 given. The first example is when the Raceway attempts to read data out of the
149 DSP memory.

150 5.3.1 Raceway Reading DSP Memory
151 In this example, we assume that another DSP is trying to read the SDRAM of
152 the local DSP.

153 1) The FPGA detects a Raceway packet arriving, and decodes that it is a read
154   of address 0x10000 (for instance).

155 2) The FPGA writes over the Host Port Interface in order to program the
156   DMA engine. It programs the DMA engine to transfer data starting at
157   location 0x10000 (a location in the primary EMIF corresponding to a
158   location in SDRAM) to a location in the secondary EMIF (the buffer

159   device/FIFO). As data arrives in the buffer device, the FPGA reads the
160   data out of the buffer device, and moves it onto the Raceway. When the
161   proper number of bytes have been moved, the DMA engine finishes the
162   transfer, and the FPGA finishes moving data from the FIFO to the
163   Raceway.

164 5.3.2 Raceway Writing DSP Memory
165   In this example, we assume that another DSP is trying to write to the SDRAM
166   of the local DSP.

167   1) The FPGA detects a Raceway packet arriving, and decodes that it is a
168   write of location 0x20000 (for instance).

169   2) The FPGA fills some amount of the buffer device with data from the
170   Raceway, and then:

171   3) The FPGA writes over the Host Port Interface in order to program the
172   DMA engine. It programs the DMA engine to transfer data from the buffer
173   device (secondary EMIF) and to write it to the primary EMIF at address
174   0x20000.

175   4) At the end of the transfer, we could either interrupt the DSP to signal that
176   a Raceway packet has arrived, or we can use the standard Mercury method
177   of polling a location in the SMB to see whether the transfer has completed
178   yet.

179 **5.4 *Additional Thoughts***

180   1) We need to verify that the Host Port Interface can program the DMA
181   engine. The documentation on the 6201 clearly states that it can write to
182   any location in internal memory, and to anywhere on the peripheral bus,
183   however the DMA engine/controller is the datapath controller for all that,
184   so it is always possible that there is a special case which does not allow
185   writing of the DMA engine/controller registers from HPI. The chance of
186   this being so is quite remote, but needs to be verified.

187   2) We need to understand the transfer rates and latencies of the HPI. This
188   architecture relies on fairly low latency access through the HPI, otherwise
189   more buffering space would be required, and at some point bandwidth
190   begins to be affected.

191   3) We need to understand the limitations of Raceway with respect to
192   throttling, etc. The best case would be that Raceway can provide data as
193   fast as the EMIF can take it (so we wouldn't worry about having data
194   ready when EMIF wanted it), and also for Raceway to be able to be
195   throttled so that it can take the data at the rate the EMIF can provide it.
196   The more the reality deviates from this best case scenerio, the more extra
197   logic is required in the FPGA until at some point complexity may prevent
198   the architecture from being viable.

199   4)   What we currently know about the 6414 is actually educated guesses
200   based on documentation of earlier DSPs. We are making some
201   assumptions about how TI will have enhanced their chip.

202   5)   If/when TI ever puts a RapidIO interface on their DSPs, it will almost
203   certainly look like a high speed HPI, i.e. it will sit on the peripheral bus,
204   have a separate datapath channel, data coming in will simply flow to the
205   correct addresses, and outgoing data transfers will happen by
206   programming the DMA engine to send data to the RapidIO peripheral
207   address. This proposed architecture looks almost exactly like that, and so
208   probably will not require major changes to use a RapidIO enhanced DSP.

209   6)   There are probably more thoughts.. but this is probably a good start...

210

211

212

213

6201 Design Options

Option 1 is the original proposal submitted at the DSP meeting Monday. Option 2 was created during the meeting.

The main shortfall in Option 1 is the sharing of the EMIF bus between the 6201 and the Raceway DMA FPGA. During DMA operations over the Raceway, the 6201 will not have access to the EMIF interface. Any data or _instruction_ fetches from SDRAM will stall. Given the relatively small size of the internal SRAM, this will impose a significant penalty to the operation of the 6201. Option 1 also requires the FPGA to take over SDRAM refresh operation when it takes control of the EMIF bus. This passing back and forth of the refresh task will not be clean.

Option 2 places a bi-directional transceiver between the 6201's EMIF bus and the Raceway SDRAM. This allows the 6201 to process data and fetch instructions without any interruption from it's local SDRAM while the DMA FPGA is accessing the Raceway SDRAM. The HPI interface is used by the 6201 to program the DMA engine and by the DMA engine to indicate the DMA complete status to the FPGA. Option 2 also lends itself to a dual 6201 node per raceway interface. Decode logic, controlling access to the Raceway SDRAM can be designed in a number/combination of ways:
>Total access to both 6201s
>Separate areas for each 6201
>Read but no write to the other 6201's memory space
>A separate common area accessible to both for message passing
>The ability of one 6201 to go through the transceiver to the others local SDRAM (not recommended)

For a migration story to the 6414, Option 2 is a better sell, Option 3 shows the 6414 design, the transceiver is stripped off and the Raceway SDRAM is connected to the second EMIF. The design will go to one DSP per raceway due to the increased in processing power of the 6414.

Option 3

RACEWAY

HPI

FPGA

EMIF

6414

EMIF

LOCAL SDRAM

RACE SDRAM

Computer Systems, Inc.

MERCURY

199 Riverneck Road
Chelmsford, MA 01824-2820
(978) 256-1300 • Fax (978) 256-3599
http://www.mc.com

Memorandum

To: Jonathan Schonfeld   Date: 23-FEB-2001

From: Nmf

Subject: An Efficient WCDMA Receiver Design based on   File Ref: mjv-019-
         the FFT   efficient_wcdma_receiver.doc

1. Introduction

Typical processing:

Signal is sampled at N samples per chip.
Despread by
upsampling chipping sequence by interpolating and using the RRC chip pulse matched filter as an
interpolation filter
Multiplying digitized receive signal by upsampled and interpolated chip sequence
Accumulate (integrate) results for an entire DPCCH symbol.
Repeat at the early lead and late lag sample offset values to calculate delay locked loop variables
Sweep the code correlator N*256 lags to determine code synchronization and channel response

Spreading sequence is 256 chips long
Typical filter is 12 chips long
typical oversampling rate on the receiver is N=8

Key calculations
Interpolation of the spreading code – precomputed and stored

Correlation process: N*256 CMAC
Correlation repeated for N*256 + 2 (DLL) times
Total CMACS: $N*256 * (N * 256 + 2) = N^2*65536 + 512 * N$
For N = 8, this results in: 4,198,400 CMAC
1 CMAC = 4 RMUL + 2 RADD = 6 ROP

Results in 25,190,400 Real operations
At 15000 Hz symbol rate, need: 378 GOP/s

2. A New Design

Use of FFT to perform efficient circular convolution of spreading code sequence

Results in
Short code synchronization (chip sync only, not slot or frame)
DPCCH demodulation
Early and late Delay Locked Loop variables
Rough channel estimate values for an entire symbol worth of differential delay

Polyphase signal processing

Digitize the signal at an Nx oversample rate and filter with the RRC filter and split into N streams at the 1x rate.

Compute the complex conjugate of the FT of the spreading code sequence at the chip rate – precomputed and stored

Computation:
Filter data at Nx oversample rate and split into N streams at 1x rate.

For each stream,
    Compute 256 point FFT
    Complex multiply FFT with stored FFT values of spreading code
    Inverse 256-point FFT

Ops calculation:
Input filter: could be done using FFT as well.
but for time domain processing: 8*256 points, filter length 96 =>
96 RMUL per point, 95 RADD per point,
Total of 19608 RMUL, 194,560 RADD per symbol == > 391,168 ROP per symbol
I and Q streams, => 782336 ROP

Stream processing (8 streams)
    Radix 4 FFT: 256*4*(4 CMUL + 8 CADD) = 34,816 ROP
    256 CMUL = 1536 ROP
    Radix 4 IFFT: 256*4*(4 CMUL + 8 CADD) = 34,816 ROP
    TOTAL per stream: 71168 ROP

Total stream calcs: 569,344 ROP

Total ops per second at 15000 Hz symbol rate is: 20.3 GOPS
more than 18 times more efficient than traditional approach.

Also, the DLL circuitry can be eliminated since the entire channel response is calculated at the symbol rate.

FFT numbers may be off by a factor of 2 larger in the number of complex multiplications needed.

3. References:

Scholtz, et. al. <u>Spread Spectrum Handbook</u>.

Proakis and Manolakis. <u>Introduction to Digital Signal Processing</u>. Macmillian, 1988.

Mapping to Processors

Practical Implementation of an Iterative Hard-Decision MUD Algorithm for the UMTS FDD Uplink

John H. Oates
Mercury Computer Systems, Inc.
Wireless Communications Group
199 Riverneck Road
Chelmsford, MA 01824-2820 USA
Tel: 978-256-0052 x 1659
FAX: 978-256-8596
E-mail: joates@mc.com
Technical Area: 03

Introduction

Multi-User Detection (MUD) has been shown to provide a number of significant benefits[1][2]. These include increased system capacity, increased range, enhanced Quality of Service (QoS), improved near-far resistance, extended battery life, and reduced handset transmit power. This paper describes the practical implementation of Multi-User Detection (MUD) for the UMTS uplink using short codes. The focus is on practical implementation details such as efficient implementation of the calculations, processing requirements, latencies, MUD efficiency, and mapping to hardware.

The use of short codes allows MUD to be performed at the symbol rate. As such MUD can be introduced into a conventional Base-Transceiver-Station (BTS) as an enhancement to the Matched-Filter (MF) RAKE receiver. The MUD processing takes the MF detection statistics, performs interference cancellation, and then delivers improved hard or soft-decision symbol estimates to the symbol-rate BTS processing functions. The MUD processing introduces only a few milliseconds latency. Because of the reduced computational complexity of MUD operating at the symbol rate the entire MUD functionality can be implemented in software on a single card or daughter card populated with a minimal number of processors. We present here an implementation of an iterative hard-decision Interference Cancellation (IC) algorithm on four Power PC 7410 processors. The processors are connected together with a high-bandwidth RACE++ interconnect fabric.

In order to perform MUD at the symbol rate the correlation between the user channel-corrupted signature waveforms must be calculated. These correlations are stored as elements of matrices, here referred to as the R-matrices. Since the channel is continually changing these correlations must be updated in real time. There are two elements to updating the R-matrices. The first part is based on the user code correlations. These depend on the relative lag between the various user multipath components. It is assumed that these lags change with a time constant of about 400 ms. The second part is due to the fast variation of the Rayleigh-fading multipath amplitudes. It is assumed that these amplitudes are changing with a time constant of about 1.33 ms. The R-matrices are used to cancel the multiple access interference through the Multi-stage Decision-Feedback Interference Cancellation (MDFIC) technique.

UMTS Uplink Multi-rate Signal Model and RAKE Processing

We derive here the equations describing the MF outputs based on the WCDMA transmitted waveform. The users accessing the system will hereafter be referred to as *physical users*. Each physical user is regarded as a composition of *virtual users*. Each virtual user transmits a single bit per symbol period, where by *symbol period* we mean a time duration of 256 chips (i.e. 1/15 ms). The number of virtual users, then, for a given physical user is equal to the number of bits transmitted in a symbol period. At a minimum each active physical user is composed of two virtual users, one for the Dedicated Physical Control Channel

(DPCCH)[3] and one for the Dedicated Physical Data CHannel (DPDCH). If the physical user is a data user with Spreading Factor (SF) less than 256 then there are $J = 256/SF$ data bits and one control bit transmitted per symbol period. Hence for the rth physical user with data-channel spreading factor SF_r, there are a total of $1 + 256/SF_r$, virtual users. The total number of virtual users is denoted

$$K_v \equiv \sum_{r=1}^{K} \left[1 + \frac{256}{SF_r} \right] \tag{1}$$

The transmitted waveform for the rth physical user can be written as

$$x_r[t] = \sum_{k=1}^{1+J_r} \beta_k \sum_m s_k[t - mT]b_k[m] \tag{2}$$

$$s_k[t] \equiv \sum_{p=0}^{N-1} h[t - pN_c]c_k[p]$$

where t is the integer time sample index, $T = NN_c$ is the data bit duration, $N = 256$ is the short-code length, N_c is the number of samples per chip, and where $\beta_k = \beta_c$ if the kth virtual user is a control channel and $\beta_k = \beta_d$ if the kth virtual user is a data channel. The multipliers β_c and β_d are constants used to select the relative amplitudes of the control and data channels. At least one of these constants must be equal to 1 for any given symbol period m. The waveform $s_k[t]$ is referred to as the transmitted signature waveform for the kth virtual user. This waveform is generated by passing the spread code sequence $c_k[n]$ through a root-raised-cosine pulse shaping filter $h[t]$. If the kth virtual user corresponds to a data user with spreading factor less than 256 then the code $c_k[n]$ still has length 256, but only N_k of the 256 elements are non-zero, where N_k is the spreading factor for the kth virtual user. The non-zero values are extracted from the code $C_{ch,256,64}$ $S_{sh}[n]$[3]. The W-CDMA standard actually allows for up to six DPDCHs to be multiplexed with a single DPCCH. This functionality is not presently incorporated in the MUD algorithms described below.

The baseband received signal can be written

$$r[t] = \sum_{k=1}^{K_v} \sum_m \tilde{s}_k[t - mT]b_k[m] + w[t] \tag{3}$$

$$s_k[t] \equiv \sum_{q'=1}^{L} a_{kq'} s_k[t - \tau_{kq'}]$$

where $w[t]$ is receiver noise, $\tilde{s}_k[t]$ is the channel-corrupted signature waveform for virtual user k, L is the number of multipath components, and $a_{kq'}$ are the complex multipath amplitudes. The amplitude ratios β_k are incorporated into the amplitudes $a_{kq'}$. Notice that if k and l are two virtual users corresponding to the same physical user then, aside from scaling the by β_k and β_l, $a_{kq'}$ and $a_{lq'}$, are equal. This is due to the fact that the signal waveforms of all virtual users corresponding to the same physical user pass through the same channel. The waveform $s_k[t]$ is now the received signature waveform for the kth virtual user. This waveform is identical to the transmitted signature waveform given in Equation (2) except that the root-raised-cosine pulse $h[t]$ is replaced with the raised-cosine pulse $g[t]$.

Thus far the received signal has been match-filtered to the chip pulse. It must next be match-filtered by the user code-sequence filter. The resulting detection statistic is denoted here as y_k, the matched-filter output for the kth virtual user. Since there are K_v codes, there are K_v such detection statistics, which are collected into a column vector $y[m]$ for the mth symbol period. The matched-filter output $y_l[m]$, for the lth virtual user can be written

$$y_l[m] \equiv \text{Re} \left\{ \sum_{q=1}^{L} \hat{a}_{lq}^* \cdot \frac{1}{2N_l} \sum_n r[nN_c + \hat{\tau}_{lq} + mT] \cdot c_l^*[n] \right\} \tag{4}$$

where $\hat{a}_{lq}^{*}$ is the estimate of a_{lq}^{*}, $\hat{\tau}_{lq}$ is the estimate of τ_{lq}, N_l is the (non-zero) length of code $c_l[n]$, and $\eta_l[m]$ is the match-filtered receiver noise. Substituting $r[t]$ from Equation (3) above gives

$$y_l[m] \equiv \sum_{m'} \sum_{k=1}^{K_v} \mathrm{Re}\left\{\sum_{q=1}^{L} \hat{a}_{lq}^{*} \cdot \frac{1}{2N_l} \sum_{n} \tilde{s}_k[nN_c + \hat{\tau}_{lq} + m'T] \cdot c_l^{*}[n]\right\} b_k[m-m'] + \eta_l[m]$$

$$= \sum_{m'} \sum_{k=1}^{K_v} r_{lk}[m'] b_k[m-m'] + \eta_l[m]$$

$$r_{lk}[m'] \equiv \mathrm{Re}\left\{\sum_{q=1}^{L} \hat{a}_{lq}^{*} \cdot \frac{1}{2N_l} \sum_{n} \tilde{s}_k[nN_c + \hat{\tau}_{lq} + m'T] \cdot c_l^{*}[n]\right\}$$

$$(5)$$

$$= \sum_{q=1}^{L} \sum_{q'=1}^{L} \mathrm{Re}\left\{\hat{a}_{lq}^{*} a_{kq'} \cdot \frac{1}{2N_l} \sum_{n} s_k[nN_c + m'T + \hat{\tau}_{lq} - \tau_{kq'}] \cdot c_l^{*}[n]\right\}$$

$$= \sum_{q=1}^{L} \sum_{q'=1}^{L} \mathrm{Re}\left\{\hat{a}_{lq}^{*} a_{kq'} \cdot \frac{1}{2N_l} \sum_{n} \sum_{p} g[(n-p)N_c + m'T + \hat{\tau}_{lq} - \tau_{kq'}] c_k[p] \cdot c_l^{*}[n]\right\}$$

The terms for $m' \neq 0$ result from asynchronous users.

MUD Algorithm and Functions

A vast number of MUD algorithms have been proposed [1][2]. Many of these are too computationally complex to be implemented with current technology. The linear-iterative class of MUD algorithms [4][5][6] are the least computationally complex. For this class of algorithms software implementation is feasible. The hard-decision variants of these algorithms also enjoy a significant performance advantage in that they do not tend to amplify other-cell interference. The down side is that performance degrades under high input BER. Since channel decoding reduces the BER by orders of magnitude, it is possible to be operating with raw channel BERs as high as 10%. A number of methods have been proposed to address this issue, including the null-zone detector [4], and partial interference cancellation [4][5][6]. We employ partial interference cancellation in conjunction with a new thresholding technique which reduces computational complexity. Our method provides excellent performance under high input BER.

The implementation of MUD at the symbol rate can be divided into two functions. The first function is the calculation of the R-matrix elements. The second function is interference cancellation, which relies on knowledge of the R-matrix elements. The calculation of these elements and the computational complexity are described in the following section. Computational complexity is expressed in Giga Operations Per Second (GOPS). The subsequent section describes the MUD IC function. The method of interference cancellation employed is Multistage Decision Feedback IC (MDFIC)[2][7].

R-matrix

From Equation (5) above, the R-matrix calculations can be divided into three separate calculations, each with an associated time constant for real-time operation, as follows

$$r_{lk}[m'] = \sum_{q=1}^{L}\sum_{q'=1}^{L}\text{Re}\left\{a_{lq}^*a_{kq'} \cdot \frac{1}{2N_I}\sum_n\sum_p g[(n-p)N_c + m'T + \tau_{lq} - \tau_{kq'}]c_k[p] \cdot c_l^*[n]\right\}$$

$$= \sum_{q=1}^{L}\sum_{q'=1}^{L}\text{Re}\left\{a_{lq}^*a_{kq'} \cdot C_{lkqq'}[m']\right\}$$

(6)

$$C_{lkqq'}[m'] \equiv \frac{1}{2N_I}\sum_n\sum_p g[(n-p)N_c + m'T + \tau_{lq} - \tau_{kq'}]c_k[p] \cdot c_l^*[n]$$

$$= \frac{1}{2N_I}\sum_m g[mN_c + m'T + \tau_{lq} - \tau_{kq'}]\sum_n c_k[n-m] \cdot c_l^*[n]$$

$$= \frac{1}{2N_I}\sum_m g[mN_c + m'T + \tau_{lq} - \tau_{kq'}]\Gamma_{lk}[m]$$

$$\Gamma_{lk}[m] \equiv \sum_n c_k[n-m] \cdot c_l^*[n]$$

where we have omitted the hats indicating parameter estimates. Hence we must calculate the R-matrices, which depend on the C-matrices ($C_{lkqq'}[m']$), which depend on the Γ-matrix ($\Gamma_{lk}[m]$). The Γ-matrix has the slowest time constant. This matrix represents the user code correlations for all values of offset m. For the case of 100 voice users the total memory requirement is 21 MB based on two bytes (real and imaginary parts) per element. This matrix is updated only when new codes (new users) are added to the system. Hence this is essentially a static matrix. The computational requirements are negligible. The most efficient method of calculation depends on the non-zero length of the codes. For high data-rate users the non-zero length of the codes is only 4 chips long. For these codes a direct convolution is the most efficient method to calculation the elements. For low data-rate users it is more efficient to calculation the elements using the FFT to perform the convolutions in the frequency domain.

The C-matrix is calculated from the Γ-matrix. These elements must be calculated whenever a users delay lag changes. For now assume that on average each multipath component changes every 400 ms. The length of the $g[]$ function is 48 samples. Since we are oversampling by 4, there are 12 multiply-accumulations (real x complex) to be performed per element, or 48 operations per element. When there are 100 low-rate users on the system (200 virtual users) and a single multipath lag (of 4) changes for one user a total of $(1.5)(2)K_vLN_v$ elements must be calculated. The factor of 1.5 comes from the 3 C-matrices ($m' = -1, 0, 1$), reduced by a factor of 2 due to a conjugate symmetry condition. The factor of 2 results because both rows and columns must be updated. The factor N_v is the number of virtual users per physical user, which for the lowest rate users is $N_v = 2$. In total then this amounts to 230400 operations per multipath component per physical user. Assuming 100 physical users with 4 multipath components per user, each changing once per 400 ms gives 230 MOPS.

The R-matrices are calculated from the C-matrices. From Equation (6) above the R-matrix elements are

$$r_{lk}[m'] = \sum_{q=1}^{L}\sum_{q'=1}^{L}\text{Re}\left\{a_{lq}^*a_{kq'} \cdot C_{lkqq'}[m']\right\} = \text{Re}\left\{a_l^H \cdot C_{lk}[m'] \cdot a_k\right\}$$

(7)

where a_k are $L \times 1$ vectors, and $C_{lk}[m']$ are $L \times L$ matrices. The rate at which these calculations must be performed depends on the velocity of the users. The selected update rate is 1.33 ms. If the update rate is too slow such that the estimated R-matrix values deviate significantly from the actual R-matrix values then there is a degradation in the MUD efficiency. Figure 1 below shows the degradation in MUD efficiency versus user velocity for an update rate of 1.33 ms, which corresponds to two WCDMA time slots. The plot indicates that there is high MUD efficiency for users with velocity less than about 100 km/hr. The plot indicates that the interference corresponding to fast users is not cancelled as effectively as the interference due to slow users. For a system with a mix of fast and slow users the resulting MUD efficiency is a average of the MUD efficiency for the various user velocities.

Figure 1. MUD efficiency versus user velocity in km/hr

From Equation (7) the calculation of the R-matrix elements can be calculated in terms of an X-matrix which represents amplitude-amplitude multiplies

$$r_{lk}[m'] = \text{Re}\{tr[a_l^H \cdot C_{lk}[m'] \cdot a_k]\} = \text{Re}\{tr[C_{lk}[m'] \cdot a_k \cdot a_l^H]\} \equiv \text{Re}\{tr[C_{lk}[m'] \cdot X_{lk}]\}$$
$$= tr[C_{lk}^R[m'] \cdot X_{lk}^R] - tr[C_{lk}^I[m'] \cdot X_{lk}^I] \tag{8}$$

$$X_{lk} \equiv a_k \cdot a_l^H \equiv X_{lk}^R + jX_{lk}^I$$
$$C_{lk}[m'] \equiv C_{lk}^R[m'] + jC_{lk}^I[m']$$

The advantage of this approach is that the X-matrix multiplies can be reused for all virtual users associated with a physical user and for all m' (i.e. $m' = 0, 1$). Hence these calculations are negligible when amortized. The remaining calculations can be expressed as a single real dot product of length $2L^2 = 32$. The calculations are be performed in 16-bit fixed-point math. The total operations is thus $1.5(4)(K,L)^2 = 3.84$ Mops. The processing requirement is then 2.90 GOPS. The X-matrix multiplies when amortized amount to an additional 0.7 GOPS. The total processing requirement is then 3.60 GOPS.

MDFIC

From Equation (5) above the matched-filter outputs are given by

$$y_l[m] = r_{ll}[0]b_l[m] + \sum_{k=1}^{K_v} r_{lk}[-1]b_k[m+1] + \sum_{k=1}^{K_v} [r_{lk}[0] - r_{ll}[0]\delta_{lk}]b_k[m] + \sum_{k=1}^{K_v} r_{lk}[1]b_k[m-1] + \eta_l[m] \tag{9}$$

The first term represents the signal of interest. All the remaining terms represent Multiple Access Interference (MAI) and noise. The MDFIC algorithm iteratively solves for the symbol estimates $\hat{b}_l[m]$ using

$$\hat{b}_i[m] = sign\left\{ y_i[m] - \sum_{k=1}^{K_v} r_{ik}[-1]\hat{b}_k[m+1] - \sum_{k=1}^{K_v} [r_{ik}[0] - r_{ii}[0]\delta_{ik}]\hat{b}_k[m] - \sum_{k=1}^{K_v} r_{ik}[1]\hat{b}_k[m-1] \right\} \qquad (10)$$

with initial estimates given by hard decisions on the matched-filter detection statistics, $\hat{b}_i[m] = sign\{y_i[m]\}$. The MDFIC [7] technique is closely related to the SIC and PIC technique. Notice that new estimates $\hat{b}_i[m]$ are immediately introduced back into the interference cancellation as they are calculated. Hence at any given cancellation step the best available symbol estimates are used. This idea is analogous to the Gauss-Siedel method for solving diagonally dominant linear systems.

The above iteration is performed on a block of 20 symbols, for all users. The 20-symbol block size represents two WCDMA time slots. The R-matrices are assumed to be constant over this period. Performance is improved under high input BER if the *sign* detector in Equation (10) is replaced by the hyperbolic tangent detector [6]. This detector has a single slope parameter which is variable from iteration to iteration.

The three R-matrices (R[-1], R[0] and R[1]) are each $K_v \times K_v$ in size. The total number of operation then is $6K_v^2$ per iteration. The computational complexity of the MDFIC algorithm depends on the total number of virtual users, which depends on the mix of users at the various spreading factors. For $K_v = 200$ users (e.g. 100 low-rate users) this amounts to 240,000 operations. In the current implementation two iterations are used, requiring a total of 480,000 operation. For real-time operation these operations must be performed in 1/15 ms. The total processing requirement is then 7.2 GOPS. Computational complexity is markedly reduced if a threshold parameter is set such that IC is performed only for values $|y_i[m]|$ below the threshold. The idea is that if $|y_i[m]|$ is large there is little doubt as to the sign of $b_i[m]$, and IC need not be performed. The value of the threshold parameter is variable from stage to stage.

Mapping to Hardware

The above calculations are performed on a single 9"x6" card populated with four Power PC 7410 processors. These processors employ the AltiVec SIMD vector arithmetic-logic unit, which has 32 128-bit vector registers. These registers can hold either 4 32-bit floats, 4 32 bit ints, 8 16-bit shorts, or 16 8-bit chars. Two vector SIMD operation (multiply and accumulate) can be performed by clock. The clock rate used for the current implementation is 400 MHz. The processors, however, can be operated at 500 MHz with higher clock speeds in the near future. Each processor has 32KB of L1 cache and 2MB of 266MHz L2 cache. The maximum theoretical performance of these processors is thus 3.2 GFLOPS, 6.4 GOPS (16-bit), or 12.8 GOPS (8-bit). The current implementation used a combination of floating-point, 16-bit fixed-point and 8-bit fixed-point calculations.

The four PPC7410 processors are interconnected with a RACE++ 266MB/s 8-port switched fabric as shown in Figure 2. The high bandwidth fabric allows transfer of large amounts of data with very low latency so as to achieve efficient parallelism of the four processors. The maximum theoretical performance of the card is thus 51.2 GOPS.

Figure 2. Partitioning of MUD functions across four processors

As shown in Figure 2 the MDFIC and C-matrix calculations are allocated to a single processor. The other three processors are given to the R-matrix calculations which are considerably more complex.

MUD BER Performance

A sample of the Bit Error Rate (BER) performance of the MUD algorithm is shown in Figure 3. For comparison the matched-filter BER is also shown. The figure shows that MUD doubles system capacity.

Figure 3. Log10 bit error rate versus system capacity for matched filter (blue) and multiuser detection (red)

The above performance is based on the following assumptions:
- A single receive antenna is used
- The target BER is 0.001

- The percentage of systems users in handoff is 30%
- Other-cell interference is 35% of intra-cell interference. This is lower than the typical value (0.60) used. The reason is that the other-cell users in handoff with the cell of interest are included in the intra-cell interference. This is because the cell of interest is processing these users and hence can cancell there interference using MUD.
- A 4-tap multipath channel is used. Each tap is Rayleigh fading. The composite power of all paths is perfectly power controlled.
- The channel amplitude estimation error is 10%
- The channel delay estimation is ¼ chip
- The activity factor for voice is 0.40
- The relative amplitude of the control channel is $\beta_c = 0.5333$

Conclusions

The current state of processor technology is such that iterative hard-decision MUD for the UMTS uplink can be implemented in software on a single card or daughter card populated with four Power PC 7410 processors, connected together with a high-bandwidth RACE++ interconnect fabric. The use of short codes allows MUD to be performed at the symbol rate. The advantage of symbol-rate processing is that MUD can be introduced into a BTS as an enhancement to the conventional RAKE receiver. The MUD processing takes the MF detection statistics, performs interference cancellation, and then delivers improved hard or soft-decision symbol estimates to the symbol-rate BTS processing functions. The latency introduced is only a few milliseconds. In order to perform MUD at the symbol rate the R-matrices must be updated in real time. There is a minimal degradation in MUD efficiency if these elements are updated at a rate of once per 1.33 ms. The R-matrices are used to cancel the multiple access interference through the MDFIC interference cancellation technique. At a BER of 0.001 the use of the above MUD technique doubles system capacity.

References

[1] A. Duel-Hallen, J. Holtzman, and Z. Zvonar. Multiuser detection for CDMA systems. IEEE Personal Communications, 2(2):46-58, April 1995.

[2] S. Moshavi. Multi-user detection for DS-CDMA communications. IEEE Communications Magazine, pages 124-136, October 1996.

[3] 3G TS 25.213: "Spreading and modulation (FDD)"; 3GPP

[4] D. Divsalar and M.K. Simon. Improved CDMA performance using parallel interference cancellation. IEEE MILCOM, pages pp. 911-917, October 1994.

[5] D. Divsalar, M. Simon, and D. Raphaeli. A new approach to parallel interference cancellation for CDMA. IEEE Global Telecommunications Conference, pages 1452-1457, 1996.

[6] D. Divsalar, M.K. Simon, and D. Raphaeli. Improved parallel interference cancellation for CDMA. IEEE Trans. Commun., 46(2):258-268, February 1998.

[7] T.R. Giallorenzi and S.G. Wilson. Decision feedback multiuser receivers for asynchronous CDMA systems. IEEE Global Telecommunications Conference, pages 1677-1682, June 1993.

Computer Systems, Inc.
MERCURY
199 Riverneck Road
Chelmsford, MA 01824-2820
(978) 256-1300 • Fax (978) 256-3599
http://www.mc.com

Report

To: Wireless Communications Group

From: J. H. Oates

Subject: Long-Code MUD   Date: November 3, 2000

1. Introduction

This report briefly describes long-code Multi-User Detection (MUD). Section 2 describes the long-code signal model, which is different from the short-code model. Section 3 describes the matched-filtering operation for long codes and gives a lower bound on the GOPS required for long-code symbol-rate MUD. The lower bound is 19.7 TOPS (i.e. Tera Operations Per Second; 1 TOPS = 1000 GOPS). Because of the extreme computational complexity of symbol-rate MUD for long codes regenerative MUD is examined. It is shown in Section 4 that although regenerative MUD operates at the chip rate, the overall complexity is lower for long codes. Two methods are examined. The first method is a somewhat straight-forward implementation of regenerative MUD. The required computational complexity is shown to be 774.6 GOPS for 100 users. The second method is based on combining impluse trains and subsequently raised-cosine filtering the composite signal. The total computational complexity is shown to be 109.6 GOPS for 100 users. Regenerative MUD is linear in the number of users, so that if the number of users is reduced to 64 the complexity drops to 70.1 GOPS. The complexity is also linear in the number of multipaths subtracted, so that if the number of multipaths subtracted is reduced from 4 to 2 the complexity drops to 35.1 GOPS. It may be desirable for MUD performance to subtract only the two largest multipaths due channel amplitude estimation errors. The above complexity figures are for a single interference cancellation stage. For two stages the computation is doubled. To perform regenerative MUD the baseband antenna stream data must be brought onto the MUD board. The required bandwidth is 123 MB/s. Note that the figures given above can perhaps be reduced through a clever implementation. A block diagram of regenerative MUD is shown to facilitate an investigation into the feasibility of an FPGA or ASIC implementation.

2. Signal Model

The received signal model for short-code WCDMA is given in [1]. When long codes are used the signal model is different since effectively the codes change from symbol to symbol. We present here the WCDMA signal model for long codes. The baseband received signal can be written

$$r[t] = \sum_{k=1}^{2K} \sum_m \tilde{s}_{km}[t - mT_k] b_k[m] + w[t] \tag{1}$$

where t is the integer time sample index, $T_k = N_k N_c$ is the data bit duration, which depends on the user spreading factor, N_k is the spreading factor for the kth virtual user, N_c is the number of samples per chip, K is the total number of physical users, $w[t]$ is receiver noise, and where $\tilde{s}_{km}[t]$ is the channel-corrupted signature waveform for the kth virtual user over the mth symbol period. The concept of virtual users is used to account for both the DPDCH and the DPCCH. Hence if there are K physical users, then there are $K_v = 2K$ virtual users. The user signature waveform and hence the channel-corrupted signature waveform vary from symbol period to symbol period since long codes by definition extend over many symbol periods. For L multipath components the channel-corrupted signature waveform for virtual user k is modeled as

$$\tilde{s}_{km}[t] = \sum_{p=1}^{L} a_{kp} s_{km}[t - \tau_{kp}] \tag{2}$$

where a_{kp} are the complex multipath amplitudes. The amplitude ratios β_k are incorporated into the amplitudes a_{kp}. Notice that if k and l are virtual users corresponding to the DPCCH and the DPDCH of the same physical user then, aside from scaling the by β_k and β_l, a_{kp} and a_{lp}, are equal. This is due to the fact that the signal waveforms for both the DPCCH and the DPDCH pass through the same channel.

The waveform $s_{km}[t]$ is referred to as the signature waveform for the kth virtual user over the mth symbol period. This waveform is generated by passing the spreading code sequence $c_{km}[n]$ through a pulse-shaping filter $g[t]$

$$\begin{aligned} s_{km}[t] &= \sum_{r=0}^{N_k-1} g[t - rN_c] c_{km}[r] \\ &= \sum_{r=0}^{N_k-1} g[t - rN_c] c_k[r + mN_k] \end{aligned} \tag{3}$$

where $g[t]$ is the raised-cosine pulse shape. Since $g[t]$ is a raised-cosine pulse as opposed to a root-raised-cosine pulse, the received signal $r[t]$ represents the baseband signal after filtering by the matched chip filter.

3. Matched filter

The received signal above, which has been match-filtered to the chip pulse, must next be match-filtered by the user code-sequence filter. The resulting detection statistic is

denoted here as $y_k[m]$, the matched-filter output for the *kth* virtual user over the *m*th symbol period. Since there are K_v codes, there are K_v such detection statistics, which are collected into a column vector $y[m]$. The matched-filter output $y_l[m]$, for the *l*th virtual user can be written

$$y_l[m] \equiv \text{Re}\left\{\sum_{q=1}^{L} \hat{a}_{lq}^{H} \cdot \frac{1}{2N_l} \sum_{n=0}^{N_l-1} r[nN_c + \hat{\tau}_{lq} + mT_l] \cdot c_{lm}^*[n]\right\} \tag{4}$$

where $\hat{a}_{lq}^{H}$ is the estimate of a_{lq}^{H}, $\hat{\tau}_{lq}$ is the estimate of τ_{lq}, and $\eta_l[m]$ is the match-filtered receiver noise. Substituting $r[t]$ from Equation (1) above gives

$$y_l[m] \equiv \text{Re}\left\{\sum_{q=1}^{L} \hat{a}_{lq}^{H} \cdot \frac{1}{2N_l} \sum_{n=0}^{N_l-1} \left[\sum_{k=1}^{2K} \sum_{m'} \sum_{p=1}^{L} a_{kp} s_{km}[nN_c + \tau_{lkqp}[m,m']] b_k[m'] \right.\right.$$

$$\left.\left. + w[nN_c + \hat{\tau}_{lq} + mT_l]\right] c_{lm}^*[n]\right\}$$

$$= \text{Re}\left\{\sum_{q=1}^{L} \hat{a}_{lq}^{H} \cdot \frac{1}{2N_l} \sum_{n=0}^{N_l-1} \left[\sum_{k=1}^{2K} \sum_{m'} \sum_{p=1}^{L} a_{kp} s_{km}[nN_c + \tau_{lkqp}[m,m']] b_k[m'] \right] \cdot c_{lm}^*[n]\right\} + \eta_l[m]$$

$$= \sum_{k=1}^{2K} \text{Re}\left\{\sum_{q=1}^{L} \sum_{p=1}^{L} \hat{a}_{lq}^{H} a_{kp} \cdot \sum_{m'} \left[\frac{1}{2N_l} \sum_{n=0}^{N_l-1} s_{km}[nN_c + \tau_{lkqp}[m,m']] \cdot c_{lm}^*[n]\right] \cdot b_k[m']\right\} + \eta_l[m]$$

$$= \sum_{m'} \sum_{k=1}^{2K} \text{Re}\left\{\sum_{q=1}^{L} \sum_{p=1}^{L} \hat{a}_{lq}^{H} a_{kp} \cdot C_{lkqp}[m,m']\right\} \cdot b_k[m'] + \eta_l[m]$$

$$C_{lkqp}[m,m'] \equiv \frac{1}{2N_l} \sum_{n=0}^{N_l-1} s_{km}[nN_c + \tau_{lkqp}[m,m']] \cdot c_{lm}^*[n]$$

$$\eta_l[m] \equiv \text{Re}\left\{\sum_{q=1}^{L} \hat{a}_{lq}^{H} \cdot \frac{1}{2N_l} \sum_{n=0}^{N_l-1} w[nN_c + \hat{\tau}_{lq} + mT_l] \cdot c_{lm}^*[n]\right\}$$

$$\tau_{lkqp}[m,m'] \equiv \hat{\tau}_{lq} - \tau_{kp} + mT_l - m'T_k \tag{5}$$

In order to subtract interference we must, at a minimum, calculate $C_{lkqp}[m,m']$ for all virtual users and for all multipath components. A lower bound on the computational complexity can be determined by considering the above calculations for synchronous users. For synchronous users, all at the highest spreading factor, the required number of operations to calculate $C_{lkqp}[m,m']$ is $8(256)(2KL)^2 = 1.31$ Gops for $K = 100$ and $L = 4$. For real time operation 15000 such computations must be performed every second. This amounts to 19.7 TOPS (i.e. Tera Operations Per Second).

4. Regenerative MUD

Because of the extreme computational complexity of symbol-rate MUD for long codes it is advantageous to resort to regenerative MUD when long codes are used. Although regenerative MUD operates at the chip rate, the overall complexity is lower for long codes. For regenerative MUD the signal waveforms of interferers are regenerated at the sample rate and effectively subtracted from the received signal. A second pass through the matched filter then yields improved performance. It turns out that the computational complexity of regenerative MUD is linear in the number of users.

The received signal can be written

$$r[t] = \sum_{k=1}^{2K} \sum_{m} \sum_{p=1}^{L} a_{kp} s_{km}[t - \tau_{kp} - mT_k] b_k[m] + w[t]$$

$$= \sum_{k=1}^{2K} r_k[t] + w[t] \tag{6}$$

$$r_k[t] \equiv \sum_{m} \sum_{p=1}^{L} a_{kp} s_{km}[t - \tau_{kp} - mT_k] b_k[m]$$

Subtracting interference gives a cleaned-up signal $x_l[t]$

$$x_l[t] = r[t] - \sum_{k=1, k \neq l}^{2K} \hat{r}_k[t]$$

$$= r[t] - \sum_{k=1}^{2K} \hat{r}_k[t] + \hat{r}_l[t]$$

$$= r[t] - \hat{r}[t] + \hat{r}_l[t]$$

$$= \hat{r}_l[t] + r_{res}[t] \tag{7}$$

$$r_{res}[t] \equiv r[t] - \hat{r}[t]$$

$$\hat{r}[t] \equiv \sum_{k=1}^{2K} \hat{r}_k[t]$$

$$\hat{r}_k[t] \equiv \sum_{m} \sum_{p=1}^{L} \hat{a}_{kp} s_{km}[t - \hat{\tau}_{kp} - mT_k] \hat{b}_k[m]$$

Two methods are presented below for performing regenerative MUD.

First Method

In order to subtract interference we must reconstruct (regenerate) the waveform $s_{km}[t]$ as given in Equation (3). The waveform can be reconstructed using

$$s_{km}[t] = \sum_{r=0}^{N_k-1} g[t - rN_c]c_{km}[r]$$

$$= \sum_{p=0}^{N_k/4-1} \sum_{j=0}^{3} g[t - (4p + j)N_c]c_{km}[4p + j]$$

$$= \sum_{p=0}^{N_k/4-1} \sum_{j=0}^{3} g[t - 4pN_c - jN_c]c_{kmp}[j]$$

$$= \sum_{p=0}^{N_k/4-1} s_{kmp}[t - 4pN_c] \qquad (8)$$

$$s_{kmp}[t] \equiv \sum_{j=0}^{3} g[t - 4pN_c - jN_c]c_{kmp}[j]$$

$$c_{kmp}[j] \equiv c_{km}[4p + j]$$

The idea is that $s_{km}[t]$ can be represented as a summation of shifted waveforms $s_{kmp}[t]$, which are entirely specified by the 8 binary numbers comprising the complex sequence $c_{kmp}[j]$ of length 4. Hence there are only $2^8 = 256$ such waveforms. For what follows we assume that the signals are sampled at $N_c = 8$ samples per chip. Each is of length 96 + 3(4) = 108 samples assuming that $g[t]$ is of length 96. For 2 bytes per sample (real and imaginary parts) the total memory requirement is 216*256 = 55296 bytes, which spills out of L1 cache, but fits entirely in L2 cache.

To generate $\hat{r}_k[t]$ for a single symbol period, 64 of these waveforms must be read from memory. For each of these 64 waveforms L complex macs are required per sample per symbol period. Hence 64(8L)(108) operations are required per symbol period. For $L = 4$ this amounts to 64(32)(108) = 221184 operations per symbol period (1/15 ms), or 3.32 GOPS. The formation of $r_{res}[t]$ then requires $2K$ times this, or 3.32(200) = 664 GOPS for K = 100 physical users. To form $\hat{r}_l[t] + r_{res}[t]$ requires an additional 2(96+255*4) = 2232 operations per symbol period per virtual user, or another 6.7 GOPS. Finally, the matched filter operation needs to be performed for each user, which from Equation (4) requires NLK complex macs ($N = 256$), or 256(4)(100)(8)*15000 = 12.3 GOPS. The GOPS figures above are for a single antenna. For two antennas the operations are doubled. Hence the total computational complexity is 2(664 + 6.7 + 12.3) = 1.37 TOPS. This is for a single-stage MPIC algorithm. For two stages the computation is doubled.

To perform regenerative MUD the baseband antenna stream data must be brought onto the MUD board. The required bandwidth is

[2 Bytes(complex)/Sa/Ant][2 Ant][8 Sa/chip][3.84 Mchips/ second] = 123 MB/s

Second Method
The second method is to represent the waveform for each multipath for each user as a complex impulse train with $N_c = 8$ samples per impulse. The complex amplitude of each impulse is the product of the complex chip, complex multipath amplitude and the binary (real) data bit estimate. These $2KL$ complex streams (times 2 for 2 antennas) are added to form a composite signal. Since this composite signal is a sum many impulse trains, all

asynchronous, the composite signal is a dense (i.e. no systematic zeros) signal at the sample rate. A block diagram of the processing is shown in Figure 1.

Figure 1. A block diagram of the long-code MUD processing

From Equations (7) and (8)

$$r_{res}[t] \equiv r[t] - \hat{r}[t]$$

$$\hat{r}[t] \equiv \sum_{k=1}^{2K} \hat{r}_k[t]$$

$$= \sum_{k=1}^{2K} \sum_{m} \sum_{p=1}^{L} \hat{a}_{kp} s_{km}[t - \hat{\tau}_{kp} - mT_k] \hat{b}_k[m]$$

$$= \sum_{k=1}^{2K} \sum_{p=1}^{L} \hat{a}_{kp} \sum_{m} \sum_{r=0}^{N_k-1} g[t - \hat{\tau}_{kp} - mT_k - rN_c] c_{km}[r] \hat{b}_k[m]$$

$$= \sum_{k=1}^{2K} \sum_{p=1}^{L} \hat{a}_{kp} \sum_{m} \sum_{r=0}^{N_k-1} g[t - \hat{\tau}_{kp} - (r + mN_k)N_c] c_k[r + mN_k] \hat{b}_k[\lfloor (r + mN_k)/N_k \rfloor]$$

$$= \sum_{k=1}^{2K} \sum_{p=1}^{L} \hat{a}_{kp} \sum_{n} g[t - \hat{\tau}_{kp} - nN_c] c_k[n] \hat{b}_k[\lfloor n/N_k \rfloor]$$

$$= \sum_{k=1}^{2K} \sum_{p=1}^{L} \hat{a}_{kp} \sum_{r} \sum_{n} g[r] \delta[t - r - \hat{\tau}_{kp} - nN_c] c_k[n] \hat{b}_k[\lfloor n/N_k \rfloor]$$

$$= \sum_{k=1}^{2K} \sum_{r} g[r] \sum_{p=1}^{L} \sum_{n} \delta[t - r - \hat{\tau}_{kp} - nN_c] \cdot \hat{a}_{kp} \cdot c_k[n] \cdot \hat{b}_k[\lfloor n/N_k \rfloor]$$

$$= \sum_{r} g[r] \alpha[t - r]$$

(9)

$$\alpha[t] \equiv \sum_{k=1}^{2K} \sum_{p=1}^{L} \sum_{n} \delta[t - \hat{\tau}_{kp} - nN_c] \cdot \hat{a}_{kp} \cdot c_k[n] \cdot \hat{b}_k[\lfloor n/N_k \rfloor]$$

where $\alpha[t]$ is the composite signal. For each symbol period this requires 256(10)(2KL) operations per antenna. For two antennas this amounts to 5120(200)(4) = 4096000 operations per symbol period, or 61.4 GOPS.

The estimate of the received signal is then determined by passing the composite signal through the raised-cosine filter $g[t]$ of length 96, which requires 96 real macs, or 192 real operations, per sample per real stream. There are a total of 4 real streams (2 antennas, real and imaginary streams). The total GOPS then for $N_c = 8$ samples per chip is $192(4)(8)(3.84M) = 23.6$ GOPS.

The final step is to pass the cleaned-up signal $x_l[t] = \hat{r}_l[t] + r_{res}[t]$ through the matched-filter (i.e. rake receiver) which gives the improved detection statistic

$$y_l^{(1)}[m] \equiv \mathrm{Re}\left\{ \sum_{q=1}^{L} \hat{a}_{lq}^H \cdot \frac{1}{2N_l} \sum_{n=0}^{N_l-1} x_l[nN_c + \hat{\tau}_{lq} + mT_l] \cdot c_{lm}^*[n] \right\}$$

$$= \mathrm{Re}\left\{ \sum_{q=1}^{L} \hat{a}_{lq}^H \cdot \frac{1}{2N_l} \sum_{n=0}^{N_l-1} \hat{r}_l[nN_c + \hat{\tau}_{lq} + mT_l] \cdot c_{lm}^*[n] \right\}$$

$$+ \mathrm{Re}\left\{ \sum_{q=1}^{L} \hat{a}_{lq}^H \cdot \frac{1}{2N_l} \sum_{n=0}^{N_l-1} r_{res}[nN_c + \hat{\tau}_{lq} + mT_l] \cdot c_{lm}^*[n] \right\}$$

$$= \mathrm{Re}\left\{ \sum_{q=1}^{L} \hat{a}_{lq}^H \cdot \frac{1}{2N_l} \sum_{n=0}^{N_l-1} \left[\sum_{m'} \sum_{q'=1}^{L} \hat{a}_{lq'} s_{lm'}[nN_c + \hat{\tau}_{lq} - \hat{\tau}_{lq'} + (m-m')T_l] \hat{b}_l[m'] \right] \cdot c_{lm}^*[n] \right\} + y_{l,res}^{(1)}[m]$$

$$\cong \mathrm{Re}\left\{ \sum_{q=1}^{L} \hat{a}_{lq}^H \cdot \frac{1}{2N_l} \sum_{n=0}^{N_l-1} \left[\sum_{q'=1}^{L} \hat{a}_{lq'} s_{lm}[nN_c + \hat{\tau}_{lq} - \hat{\tau}_{lq'}] \right] \cdot c_{lm}^*[n] \right\} \cdot \hat{b}_l[m] + y_{l,res}^{(1)}[m]$$

$$= \mathrm{Re}\left\{ \sum_{q=1}^{L} \sum_{q'=1}^{L} \hat{a}_{lq}^H \hat{a}_{lq'} \cdot \frac{1}{2N_l} \sum_{n=0}^{N_l-1} s_{lm}[nN_c + \hat{\tau}_{lq} - \hat{\tau}_{lq'}] \cdot c_{lm}^*[n] \right\} \cdot \hat{b}_l[m] + y_{l,res}^{(1)}[m]$$

$$\cong \mathrm{Re}\left\{ \sum_{q=1}^{L} \hat{a}_{lq}^H \hat{a}_{lq} \right\} \cdot \hat{b}_l[m] + y_{l,res}^{(1)}[m]$$

$$= A_l^2 \cdot \hat{b}_l[m] + y_{l,res}^{(1)}[m]$$

$$A_l^2 \equiv \mathrm{Re}\left\{ \sum_{q=1}^{L} \hat{a}_{lq}^H \hat{a}_{lq} \right\} \tag{10}$$

$$y_{l,res}^{(1)}[m] \equiv \mathrm{Re}\left\{ \sum_{q=1}^{L} \hat{a}_{lq}^H \cdot \frac{1}{2N_l} \sum_{n=0}^{N_l-1} r_{res}[nN_c + \hat{\tau}_{lq} + mT_l] \cdot c_{lm}^*[n] \right\}$$

The matched filter operation requires NLK complex macs, or $256(4)(100)(8)*15000 = 12.3$ GOPS. The GOPS figures above are for a single antenna. For two antennas the operations are doubled, giving 24.6 GOPS. The total computational complexity for the second method is then $61.4 + 23.6 + 24.6 = 109.6$ GOPS.

References

[1] J. H. Oates, "MUD Algorithms," Mercury Wireless Communication Group Report, August 22, 2000.

MUD Functions

From modem card

τ_{kq} $\hat{a}_{kq}$ (y_{kq}) y_k

User codes, ...

R-Matrix Calculation

R[1],R[0],R[-1]

Interference Cancellation

MUD Daughter Card

$\hat{b}_k$

- R-matrix calculation

  – User code correlations

    • C-matrices (1.9 MB)

    • τ_{kq} change ~ every 100 ms

  – R-matrices

    • a_{kq} change ~ every 1.33 ms

- Interference cancellation

  – Must be performed in 10 symbol periods (0.667 ms) for real-time operation

- Total latency: 10 ms

  $\hat{b}_k$ To symbol processing

R-matrix Calculation

$\hat{\tau}_{kq}$

$\hat{a}_{kq}$

Determine which $\hat{\tau}_{kq}$ have changed

$\{k,q\}$

Update $C_{lkqq'}[m']$

Calculate $r_{lk}[m']$

1.9 MB array split over 3 processors: 640K per processor, L2 cache resident

$$r_{lk}[m'] = \rho_{lk}[m']A_l A_k \equiv \sum_{q=1}^{L}\sum_{q'=1}^{L}\text{Re}\{\hat{a}_{lq}^H \hat{a}_{kq'} \cdot C_{lkqq'}[m']\}$$

$$C_{lkqq'}[m'] \equiv \frac{1}{2N_l}\sum_n s_k[nN_c + m'T + \hat{\tau}_{lq} - \hat{\tau}_{kq'}] \cdot c_l^*[n]$$

Computer Systems, Inc.

MERCURY

199 Riverneck Road
Chelmsford, MA 01824-2820
(978) 256-1300 • Fax (978) 256-3599
http://www.mc.com

Report

To: Wireless Communications Group

From: J. H. Oates

Subject: R-matrix GOPS   Date: June 21, 2000

1. Introduction

This report investigates a number of different methods for calculating the R-matrix elements. There are two parts to the calculation. First is the calculation of the user code correlations at lag offsets determined by the searcher receivers. This calculation must be performed every time a multipath component changes to a new lag. The assumption used here is that every 100 ms one multipath component changes to a new lag for each user. Hence, if each user has 4 multipath lags, then all R-matrix elements will have changed after 400 ms. The validity of this assumption will have to be tested with measured data. Note that the WCDMA standard call out a test with 2 multipath components, where one lag changes every 191 ms [1]. The second part is the actual calculation of the R-matrix elements, which requires a double summation of code correlations over all multipath components, with each term scaled by the Rayleigh-fading multipath amplitudes. The maximum time period to perform this calculation is about 1.33 ms. Hence there are two parts to the calculation, each with a different update rate.

Section 2 is devoted the first part of the calculation, the code correlations. Section 3 covers the actual calculation of the R-matrix elements.

1

2. Calculation of User Code Correlations

The R-matrix elements can be expressed as [2]

$$\hat{\rho}_{lk}[m']A_k = \sum_{q=1}^{L}\sum_{q'=1}^{L} \mathrm{Re}\{\hat{a}_{lq}^{*}\hat{a}_{kq'} \cdot C_{lkqq'}[m']\}$$

$$C_{lkqq'}[m'] \equiv \frac{1}{2N_l}\sum_{n} s_k[nN_c + m'T + \hat{\tau}_{lq} - \hat{\tau}_{kq'}] \cdot c_l^{*}[n] \qquad (1)$$

$$= \frac{1}{2N_l}\sum_{n}\sum_{p} g[(n-p)N_c + m'T + \hat{\tau}_{lq} - \hat{\tau}_{kq'}]c_k[p] \cdot c_l^{*}[n]$$

where $C_{lkqq'}[m']$ is a five-dimensional matrix of code correlations. Both l and k range from 1 to K_v, where K_v is the number of virtual users. If there are K physical users, all operating at the highest spreading factor, then there are $K_v = 2K$ virtual users. For now consider $K = 128$ so that $K_v = 256$. The indices q and q' range from 1 to L, the number of multipath components, which for this report is assumed to be equal to 4. The symbol period offset m' ranges from -1 to 1. The total number of matrix elements to be calculated is then $N_c = 3(K_v L)^2 = 3(1024)^2 = 3M$ complex elements, or 24 MB if each element is a float. This number is reduced, however, due to the symmetries

$$C_{klq'q}[-m'] = \frac{1}{2N_k}\sum_{n}\sum_{p} g[(n-p)N_c - m'T + \hat{\tau}_{kq'} - \hat{\tau}_{lq}]c_l[p] \cdot c_k^{*}[n]$$

$$= \frac{1}{2N_k}\sum_{p}\sum_{n} g[-(n-p)N_c - m'T - \hat{\tau}_{lq} + \hat{\tau}_{kq'}]c_l[n] \cdot c_k^{*}[p] \qquad (2)$$

$$= \frac{1}{2N_k}\sum_{p}\sum_{n} g[(n-p)N_c + m'T + \hat{\tau}_{lq} - \hat{\tau}_{kq'}]c_k^{*}[p] \cdot c_l[n]$$

$$= \frac{N_l}{N_k}C_{lkqq'}^{*}[m']$$

so that it is sufficient to store elements for offsets $m' = 0,1$. The memory requirement is then 16 MB if each element is a float. If the elements are stored as bytes the requirement is reduced to 4 MB.

Referring to Equation 1, line 2, it is evident that each element of $C_{lkqq'}$ $[m']$ is a complex dot product between a code vector c_l and a waveform vector $s_{kqq'}$. The length of the code vector is 256. The length of the waveform vector is $L_g + 255N_c$, where L_g is the length of the raised-cosine pulse vector $g[t]$ and N_c is the number of samples per chip. The values for these parameters as currently implemented are $L_g = 48$ and $N_c = 4$. The length of the waveform vector is then 1068, but for the dot product it is accessed at a stride of $N_c = 4$, which gives effectively a length of 267. Note that the code and waveform vectors in general do not entirely overlap. Also note that an increment or decrement in the symbol offset index m' slides the waveform vector 256 elements to the left or right respectively. Figure 1 shows that the total number of complex macs (cmacs) for all three ($m' = -1, 0, 1$) dot products is 267, irrespective of any relative offset.

Figure 1. Overlap of waveform and code vectors. The total number of complex macs (cmacs) for all three (m' = -1, 0, 1) dot products is 267, irrespective of any relative offset.

Hence for any given combination of indices $lkqq'$ the three elements $C_{lkqq'}$ $[m']$, corresponding to $m' = -1$, 0 and 1 require 267 cmacs to calculate all three. Since there are $(K_v L)^2$ combinations of indices, the calculation of all elements $C_{lkqq'}$ $[m']$ requires $(K_v L)^2$ (267) cmacs. Given the symmetry condition, only half of the elements need to be calculated, and noting that each cmac requires 8 operation to perform, the total number of operations required is

$$N_{ops} = \tfrac{1}{2}(K_v L)^2 (267)(8) = \tfrac{1}{2}(1024)^2 (267)(8) = 1.12\ G\ ops \tag{3}$$

The total number of GOPS (Giga Operations Per Second), then, given the 400 ms update rate is

$$N_{GOPS} = \frac{\tfrac{1}{2}(K_v L)^2 (267)(8) ops}{400ms} = \frac{\tfrac{1}{2}(1024)^2 (267)(8) ops}{400ms} = 2.80\ GOPS \tag{4}$$

The next section addresses the calculation of the R-matrix elements.

3. Calculation of R-matrix Elements

Consider the calculation of the R-matrix elements

$$\hat{\rho}_{lk}[m']A_k = \sum_{q=1}^{L}\sum_{q'=1}^{L}\text{Re}\{\hat{a}_{lq}^{*}\hat{a}_{kq'}\cdot C_{lkqq'}[m']\}$$ (5)

The total number of matrix elements to be calculated is $N_\rho = 3K_v^2$. This number is reduced, however, due to the symmetries

$$\hat{\rho}_{kl}[-m']A_l = \sum_{q=1}^{L}\sum_{q'=1}^{L}\text{Re}\{\hat{a}_{kq}^{*}\hat{a}_{lq'}\cdot C_{klqq'}[-m']\} = \sum_{q=1}^{L}\sum_{q'=1}^{L}\text{Re}\left\{\hat{a}_{lq}\hat{a}_{kq'}^{*}\cdot\frac{N_l}{N_k}C_{lkqq'}^{*}[m']\right\}$$ (6)

$$= \frac{N_l}{N_k}\sum_{q=1}^{L}\sum_{q'=1}^{L}\text{Re}\{\hat{a}_{lq}^{*}\hat{a}_{kq'}\cdot C_{lkqq'}[m']\}\} = \frac{N_l}{N_k}\hat{\rho}_{lk}[m']A_k$$

so that the total number of matrix elements to be calculated is $N_\rho = \frac{3}{2}K_v^2$.

Now let us consider the operations per element. Dropping explicit reference to the symbol period offset [m'], the matrix elements are

$$\hat{\rho}_{lk}A_k = \sum_{q=1}^{L}\sum_{q'=1}^{L}\text{Re}\{\hat{a}_{lq}^{*}\cdot\hat{a}_{kq'}\cdot C_{lkqq'}\}$$ (7)

A brute-force calculation requires $L^2(6 + 3 + 1)$ operations (1 complex multiply, one half-complex multiply -- i.e. the real part -- and one real add, or 6 real multiplies and 4 real adds). The total operations is then

$$N_{ops} = \frac{3}{2}(K_v L)^2(10)$$ (8)

For a vehicular speed of 120 km/h the Doppler frequency is 216.67 Hz for a user at frequency 1950 MHz. The coherence bandwidth is thus 433.33 MHz, and the corresponding coherence time is about 2.3 ms. Hence the multipath amplitudes are changing with a time constant of about 2 ms, and consequently the second part of the calculation must be updated at least every 2 ms. The channel amplitudes are calculated on a time slot by time slot basis. Each time slot is $10/15 = 2/3 = 0.67$ ms. Hence 2 ms equals 3 time slots, whereas two slots equals 1.33 ms. Figures 2 and 3 below show the MUD efficiency versus user velocity for 2 ms and 1.33 ms update times respectively. The plots show that to be able to effectively handle high velocity users the update time should be 1.33 ms. When users are at various speeds the interference from low speed users is cancelled more effectively than the interference from high speed users. The MUD efficiency

will then be an average of the MUD efficiency corresponding to each user's speed.

Figure 2. MUD efficiency versus user velocity for a
2 ms R-matrix update time.

Figure 3. MUD efficiency versus user velocity for a
1.33 ms R-matrix update time.

The calculations below are based on a 1.33 ms update time. Note that most of the capacity and coverage benefits calculated for MUD so far have assumed

70% MUD efficiency. The 1.33 ms update time is sufficient to achieve 70% MUD efficiency. The total GOPS are then,

$$N_{GOPS} = \frac{\frac{3}{2}(K_v L)^2 (10)}{1.33\,ms} = \frac{1.5(256 \cdot 4)^2 (10)}{1.33\,ms} = 11.8\,GOPS \qquad (9)$$

where we have assumed $L = 4$ multipath components. A better way to perform this operation is

$$\hat{\rho}_{lk} A_k = \sum_{q=1}^{L} \text{Re}\left\{ \hat{a}_{lq}^* \sum_{q'=1}^{L} C_{lkqq'} \cdot \hat{a}_{kq'} \right\} \qquad (10)$$

The inner sum is a matrix-vector multiply, hence requiring L^2 cmacs, and the outer sum is the real part of a compex dot product, which requires L half-cmacs. The total is then $(L^2 + L/2) = 1.125\,L^2$ cmacs (for $L = 4$) times 8 operations per cmac, or $9L^2$ operations, which gives

$$N_{GOPS} = \frac{\frac{3}{2}(K_v L)^2 (9)}{1.33\,ms} = \frac{1.5(256 \cdot 4)^2 (9)}{1.33\,ms} = 10.6\,GOPS \qquad (11)$$

The above calculations are represented in terms of complex numbers, which are not directly calculable. To express the above equations explicitly in terms of real numbers it is convenient to cast the calculations into matrix form

$$\hat{\rho}_{lk} A_k = \sum_{q=1}^{L} \sum_{q'=1}^{L} \text{Re}\left\{ \hat{a}_{lq}^* \hat{a}_{kq'} \cdot C_{lkqq'} \right\}$$

$$= \text{Re}\left\{ \begin{bmatrix} \hat{a}_{l1}^* & \hat{a}_{l2}^* & \cdots & \hat{a}_{lL}^* \end{bmatrix} \begin{bmatrix} C_{lk11} & C_{lk12} & \cdots & C_{lk1L} \\ C_{lk21} & C_{lk22} & \cdots & C_{lk2L} \\ \vdots & \vdots & \ddots & \vdots \\ C_{lkL1} & C_{lkL2} & \cdots & C_{lkLL} \end{bmatrix} \begin{bmatrix} \hat{a}_{k1} \\ \hat{a}_{k2} \\ \vdots \\ \hat{a}_{kL} \end{bmatrix} \right\}$$

$$\equiv \text{Re}\left\{ a_l^H \cdot C_{lk} \cdot a_k \right\}$$

$$(12)$$

$$a_k \equiv \begin{bmatrix} \hat{a}_{k1} \\ \hat{a}_{k2} \\ \vdots \\ \hat{a}_{kL} \end{bmatrix}, \qquad C_{lk} \equiv \begin{bmatrix} C_{lk11} & C_{lk12} & \cdots & C_{lk1L} \\ C_{lk21} & C_{lk22} & \cdots & C_{lk2L} \\ \vdots & \vdots & \ddots & \vdots \\ C_{lkL1} & C_{lkL2} & \cdots & C_{lkLL} \end{bmatrix}$$

The quadratic form $a_l^H C_{lk} a_k$ can be expressed

$$\text{Re}\{a_l^H \cdot C_{lk} \cdot a_k\} = \text{Re}\{[a_r^T - ja_i^T] \cdot [C_r + jC_i] \cdot [b_r + jb_i]\}$$

$$= \text{Re}\{[a_r^T - ja_i^T] \cdot [C_r b_r - C_i b_i + j(C_r b_i + C_i b_r)]\}$$

$$= \text{Re}\left\{ \begin{matrix} a_r^T C_r b_r - a_r^T C_i b_i + a_i^T C_r b_i + a_i^T C_i b_r \\ + j(a_r^T C_r b_i + a_r^T C_i b_r - a_i^T C_r b_r + a_i^T C_i b_i) \end{matrix} \right\}$$

$$= \text{Re}\left\{ \begin{bmatrix} a_r^T & a_i^T \end{bmatrix} \begin{bmatrix} C_r & -C_i \\ C_i & C_r \end{bmatrix} \begin{bmatrix} b_r \\ b_i \end{bmatrix} + j \begin{bmatrix} a_r^T & a_i^T \end{bmatrix} \begin{bmatrix} C_i & C_r \\ -C_r & C_i \end{bmatrix} \begin{bmatrix} b_r \\ b_i \end{bmatrix} \right\}$$

$$= \begin{bmatrix} a_r^T & a_i^T \end{bmatrix} \begin{bmatrix} C_r & -C_i \\ C_i & C_r \end{bmatrix} \begin{bmatrix} b_r \\ b_i \end{bmatrix}$$

$$\equiv a^T \cdot C \cdot b \tag{13}$$

The matrix-vector multiplication requires $(2L)^2$ macs. The dot product adds $(2L)$ macs so that the total is $(2L)^2 + (2L)$ macs. For $L = 4$ we have $1.125(2L)^2$ macs = $4.5L^2$ macs = $9L^2$ operations. The total GOPS are then

$$N_{GOPS} = \frac{\frac{3}{2}(K_v L)^2 (9)}{1.33 \, ms} = \frac{1.5(256 \cdot 4)^2 (9)}{1.33 \, ms} = 10.6 \, GOPS \tag{14}$$

Now consider a different formulation which attempts to reuse the amplitude-amplitude multiplications. Consider the calculation $a^T \cdot C \cdot b$

$$a^T \cdot C \cdot b = tr[a^T \cdot C \cdot b] = tr[C \cdot (ba^T)] = tr[C \cdot X] \tag{15}$$

$$X \equiv ba^T$$

The calculations to produce matrix X are pure multiplications, but the elements, once calculated, can be reused for the other virtual users corresponding to the same physical users. For voice-only users there are 2 virtual users per physical user. For data users there can be up to 65 virtual users per physical user. For now, however, we stay with our 128 voice-user scenario. To calculate X, then, requires $(2L)^2 = 4L^2$ multiplications. This calculation is performed once per pair of physical users, so the total number of operations is

$$N_{ops} = (KL)^2 (4) = (K_v L)^2 (1) = \frac{3}{2}(K_v L)^2 (\frac{2}{3}) \tag{16}$$

Effectively, then, X requires $(2/3)L^2$ operations. The details to calculate $a^T \cdot C \cdot b$ are

$$a^T \cdot C \cdot b = tr[C \cdot X] = tr\left\{\begin{bmatrix} c_1 \\ c_2 \\ \vdots \\ c_L \end{bmatrix} \cdot \begin{bmatrix} x_1 & x_2 & \cdots & x_L \end{bmatrix}\right\} = \sum_{i=1}^{2L} c_i \cdot x_i \qquad (17)$$

where c_i is the ith row of C and x_i is the ith column of X. Hence we have $2L$ dot products of length $2L$, which require $(2L)^2$ macs $= 8L^2$ operations. To calculate $a^H \cdot C \cdot b$ then requires $8L^2 + (2/3)L^2 = 8.67L^2$ operations, which gives

$$N_{GOPS} = \frac{\frac{3}{2}(K_v L)^2 (8.67)}{1.33\,ms} = \frac{1.5(256 \cdot 4)^2 (8.67)}{1.33\,ms} = 10.3\,GOPS \qquad (18)$$

A better way to perform this calculation is as follows

$$\rho = \sum_{q=1}^{L} \sum_{q'=1}^{L} \mathrm{Re}\{a_q^* \cdot a_{q'} \cdot C_{qq'}\} = \sum_{q=1}^{L} \sum_{q'=1}^{L} \mathrm{Re}\{X_{qq'}^* \cdot C_{qq'}\}$$

$$= \sum_{q=1}^{L} \sum_{q'=1}^{L} \mathrm{Re}\{(X_{qq'}^r - jX_{qq'}^i) \cdot (C_{qq'}^r + jC_{qq'}^i)\}$$

$$= \sum_{q=1}^{L} \sum_{q'=1}^{L} (X_{qq'}^r \cdot C_{qq'}^r + X_{qq'}^i \cdot C_{qq'}^i) \qquad (19)$$

$$X_{qq'} \equiv a_q \cdot a_{q'}^* = (a_q^r + ja_q^i) \cdot (a_{q'}^r - ja_{q'}^i) \equiv X_{qq'}^r + jX_{qq'}^i$$
$$X_{qq'}^r = a_q^r \cdot a_{q'}^r + a_q^i \cdot a_{q'}^i$$
$$X_{qq'}^i = a_q^i \cdot a_{q'}^r - a_q^r \cdot a_{q'}^i$$

where for convenience we have dropped A_k, the lk subscripts and the hat symbols. The calculation of X requires

$$N_{ops} = (KL)^2 (6) = (K_v L)^2 (6/4) = \tfrac{3}{2}(K_v L)^2 (1) \qquad (20)$$

operations. Note that, once the X values are calculated, the remainder of the calculation is a long dot product of length $2L^2$, hence requiring $2L^2$ macs, or $4L^2$ operations, which gives

$$N_{GOPS} = \frac{\frac{3}{2}(K_v L)^2(5)}{1.33 \, ms} = \frac{1.5(256 \cdot 4)^2(5)}{1.33 \, ms} = 5.9 \, GOPS \qquad (21)$$

Dual Diversity Antennas

When dual diversity antennas are employed, the calculation of the R-matrix elements becomes

$$\rho = \sum_{q=1}^{L}\sum_{q'=1}^{L} \text{Re}\left\{\left(a_{1q}^* \cdot a_{1q'} + a_{2q}^* \cdot a_{2q'}\right) \cdot C_{qq'}\right\} = \sum_{q=1}^{L}\sum_{q'=1}^{L} \text{Re}\left\{\left(X_{1qq'}^* + X_{2qq'}^*\right) \cdot C_{qq'}\right\}$$

$$= \sum_{q=1}^{L}\sum_{q'=1}^{L}\left[\left(X_{1qq'}^r + X_{2qq'}^r\right) \cdot C_{qq'}^r + \left(X_{1qq'}^i + X_{2qq'}^i\right) \cdot C_{qq'}^i\right]$$

$$\tag{22}$$

$$= \sum_{q=1}^{L}\sum_{q'=1}^{L}\left[X_{qq'}^r \cdot C_{qq'}^r + X_{qq'}^i \cdot C_{qq'}^i\right]$$

$$X_{qq'}^r \equiv X_{1qq'}^r + X_{2qq'}^r$$
$$X_{qq'}^i \equiv X_{1qq'}^i + X_{2qq'}^i$$

To calculate X for dual diversity antennas, then, requires

$$N_{ops} = (KL)^2(14) = (K_v L)^2(14/4) = \tfrac{3}{2}(K_v L)^2(7/3) = \tfrac{3}{2}(K_v L)^2(2.33) \qquad (23)$$

operations. The remainder of the calculation is again a long dot product of length $2L^2$ requiring $4L^2$ operations, which gives

$$N_{GOPS} = \frac{\frac{3}{2}(K_v L)^2(6.33)}{1.33 \, ms} = \frac{1.5(256 \cdot 4)^2(6.33)}{1.33 \, ms} = 7.5 \, GOPS \qquad (24)$$

Reuse of C data

So far we have not addressed the problem associated with a lack of data reuse, which renders our calculations I/O limited. The C data can be reused by introducing extra latency into the calculations. For a given user, a single multipath component changes on average once every 100 ms, or once every 150 slots. Suppose we collect and save in cache 4 amplitude estimate vectors $a_k[q]$,

where q is the 2 ms update index. The total latency is then 8 ms = 12 time slots. During this time the probability that a multipath lag changes is (8 ms)/(100 ms) = .08. The probability that the matrix C_{lk} changes is then = $1-(1-0.08)^2$ = 0.15. Hence for most matrices C_{lk} we will be able to calculate

$$a_l^H[q] \cdot C_{lk} \cdot a_k[q] \qquad (25)$$

for 12 time slots q for only one read of C_{lk} from memory. The penalty for this reuse is the 8 ms of latency incurred.

References

[1] "3rd Generation Partnership Project (3GPP) Technical Specification Group (TSG) RAN WG4 UE Radio transmission and Reception (FDD)", TS 25.101 V3.1.0 (1999-12), Annex B.

[2] J. H. Oates, "MUD Algorithms," Mercury Wireless Communications Group Report, April 25, 2000.

Computer Systems. Inc.

MERCURY

Memorandum

To: John Oates, John Greene, Alden Fuchs, Frank Lauginiger   Date: 31-AUG-2000

From: Mike Vinskus

Subject: Theoretically optimum load balancing for the R matrix calculations   File Ref: mjv-9.doc

This memo describes the calculation of optimum R matrix partitioning points in normalized virtual user space. These partitioning points provide an equal, and hence balanced, computation load per processor. The computational model of the R matrix calculations does not include any data access overhead or caching effects. It is shown that a closed form recursive solution exists that can be solved for an arbitrary number of processors.

Although three R matrices are output from the R matrix calculation function, only half of the elements are explicitly calculated. This is due to the symmetry condition that exists between R matrices:

$$R_{l,k}(m) = \xi \, R_{k,l}(-m) \, .$$

In essence, only two matrices need to be calculated. The first one is a combination of R(1) and R(-1). The second is the R(0) matrix. In this case, the essential R(0) matrix elements have a triangular structure to them. The number of computations performed to generate the raw data for the R(1)/R(-1) and R(0) matrices are combined and optimized as a single number. This is due to the reuse of the X matrix outer product values across the two R matrices. Since the bulk of the computations involve combining the X matrix and correlation values, they dominate the processor utilization. These computations are used as a cost metric in determining the optimum loading of each processor.

The optimization problem is formulated as an equal area problem, where the solution results in each partition area to be equal. Since the major dimensions of the R matrices are in terms of the number of active virtual users, the solution space for this problem is in terms of the number of virtual users per processor. By normalizing the solution space by the number of virtual users, the solution is applicable for an arbitrary number of virtual users.

Figure 1: Normalized R matrix computation model.

Figure 1 shows the model of the normalized optimization problem. The computations for the R(1)/R(-1) matrix are represented by the square HJKM, while the computations for the R(0) matrix are represented by the triangle ABC. From geometry, the area of a rectangle of length b and height h is

$$A_r = bh.$$

For a triangle with a base width b and height h, the area is calculated by

$$A_t = \frac{1}{2} bh.$$

When combined with a common height a_i, the formula for the area becomes

$$A_i = A_{ri} + A_{ti}$$

$$= a_i a_3 + \frac{1}{2} a_i^2.$$

$$= a_i + \frac{1}{2} a_i^2$$

The formula for A_i gives the area for the total region below the partition line. For example, the formula for A2 gives the area within the rectangle HQRM plus the region within triangle AFG. For the cost function, the difference in successive areas is used. That is

$$B_i = A_i - A_{i-1}$$

$$= \frac{1}{2} a_i^2 + a_i - \frac{1}{2} a_{i-1}^2 - a_{i-1}$$

For an optimum solution, the B_i must be equal for $i = 1, 2, ..., N$, where N is the number of processors performing the calculations. Because the total normalized load is equal to A_N, the loading per processor load is equal to A_N/N.

$$B_i = \frac{A_N}{N} = \frac{A_3}{3} = \frac{3}{2N}, \text{ for } i = 1, 2, ..., N.$$

By combining the two equation for B_i, the solution for a_i is found by finding the roots of the equation:

$$\frac{1}{2}a_i^2 + a_i - \frac{1}{2}a_{i-1}^2 - a_{i-1} - \frac{3}{2N} = 0.$$

The solution for a_i is:

$$a_i = -1 \pm \sqrt{1 + a_{i-1}^2 + 2a_{i-1} + \frac{3}{N}}, \text{ for } i = 1, 2, ..., N.$$

Since the solution space must fall in the range [0, 1], negative roots are not valid solutions to the problem. On the surface, it appears that the a_i must be solved by first solving for case where $i = 1$. However, by expanding the recursions of the a_i and using the fact that a_0 equals zero, a solution that does not require previous a_i, $i = 0, 1, ..., n-1$ exists. The solution is:

$$a_i = -1 + \sqrt{1 + \frac{3i}{N}}$$

Table 1 shows the normalized partition values for two, three, and four processors. To calculate the actual partitioning values, the number of active virtual users is multiplied by the corresponding table entries. Since a fraction of a user cannot be allocated, a ceiling operation is performed that biases the number of virtual users per processor towards the processors whose loading function is less sensitive to perturbations in the number of users.

Table 1: Normalized partition locations for two, three, and four processors.

Location	Two processors	Three processors	Four processors
a_1	$-1 + \sqrt{\frac{5}{2}}$ (0.5811)	$-1 + \sqrt{2}$ (0.4142)	$-1 + \sqrt{\frac{7}{4}}$ (0.3229)
a_2	--	$-1 + \sqrt{3}$ (0.7321)	$-1 + \sqrt{\frac{5}{2}}$ (0.5811)
a_3	--	--	$-1 + \sqrt{\frac{13}{4}}$ (0.8028)

Computer Systems, Inc.

MERCURY

199 Riverneck Road
Chelmsford, MA 01824-2820
(978) 256-1300 • Fax (978) 256-3599
http://www.mc.com

Memorandum

To: Jonathan Schonfeld   Date: 23-FEB-2001

From: Nmf

Subject: Degraded mode of operation for the MUD   File Ref: mjv-018-
         algorithm   degraded_mode_desc.doc

Reference [1] showed that the load balancing for the R matrix calculations resulted in a non-uniform partitioning of the rows of the final R matrices over a number of processors. In summary, the partition sizes increase as the partition starting user index increases.

When the system is running at full capacity (i.e. the maximum number of users is processed while still within the bounds of real-time operation) and a computational node has a failure, the impact can be significant.

This impact can be minimized by allocating the first user partition to the disabled node. Also the values that would have been calculated by that node are set to zero. This reduces the effects of the failed node. Also, by changing which user data is set to zero (i.e. which users are assigned to the failed node) the overall errors due to the lack of non-zero output data for that node are averaged over all of the users, providing a "soft" degradation.

References:

[1] M. Vinskus. "mjv-009: Theoretically optimum load balancing for the R matrix calculations." 31-AUG-2000.
[2] M. Vinskus. "mjv-010: Preliminary degraded MUD operation results." 19-OCT-2000.
[3] J. Oates. "jho-001: MUD Algorithms", 25-APR-2000

Computer Systems, Inc.

MERCURY

199 Riverneck Road
Chelmsford, MA 01824-2820
(978) 256-1300 • Fax (978) 256-3599
http://www.mc.com

Report

To: Wireless Communications Group

From: J. H. Oates

Subject: Methods for Calculating the C-matrix Elements   Date: November 13, 2000

1. Direct Method

The direct method for calculating the C-matrix elements is

$$\hat{r}_{lk}[m'] = \sum_{q=1}^{L}\sum_{q'=1}^{L} \mathrm{Re}\left\{\hat{a}_{lq}^{*}\hat{a}_{kq'} \cdot C_{lkqq'}[m']\right\}$$

(1)

$$C_{lkqq'}[m'] \equiv \frac{1}{2N_l}\sum_{n} s_k[nN_c + m'T + \hat{\tau}_{lq} - \hat{\tau}_{kq'}] \cdot c_l^{*}[n]$$

Symmetry

$$C_{klq'q}[-m'] = \frac{N_l}{N_k} C_{lkqq'}^{*}[m']$$

(2)

Due to symmetry there are *1.5(K$_v$L)^2* elements to calculate. Assuming all users are at SF 256, each calculation requires 256 cmacs, or 2048 operations. The probability that a multipath changes in a 10 ms time period is approximately 10/200 = 0.05 if all users are at 120 kmph. Assuming a mix of user velocities, let's say the probability is 0.025. Since the C-matrix elements represent the interaction between two users, the probability that C-matrix elements change in a 10 ms time period is approximately 0.10 for all users are at 120 kmph, or 0.05 for a mix of user velocities. The GOPS are tabulated in Table 1 below.

The C-matrix elements also need to be updated when the spreading factor changes. The spreading factor can change due to
- AMR codec rate changes
- Multiplexing of DCCH
- Multiplexing data services

For lack of a better number, assume that 5% of the users, hence 10% of the elements change rate every 10 ms.

Table 1. GOPS to update C-matrix elements using the direct method.

K_v	High velocity users	$1.5(K_vL)^2$	Gops	Percentage change	GOPS
200	100%	960,000	1.966	20	39.3
200	50%	960,000	1.966	15	29.5
128	100%	393,216	0.805	20	16.1
128	50%	393,216	0.805	15	12.1

2. FFT Method

The FFT can be used to calculate the correlations for a range of offsets τ using

$$C_{lkqq'}[m'] \equiv \frac{1}{2N_l} \sum_n s_k[nN_c + m'T + \hat{\tau}_{lq} - \hat{\tau}_{kq'}] \cdot c_l^*[n]$$

$$= C_{lk}[\tau_{lkqq'}[m']]$$

(3)

$$C_{lk}[\tau] \equiv \frac{1}{2N_l} \sum_n s_k[nN_c + \tau] \cdot c_l^*[n]$$

$$\tau_{lkqq'}[m'] \equiv m'T + \hat{\tau}_{lq} - \hat{\tau}_{kq'}$$

The length of the waveform $s_k[t]$ is $L_g + 255N_c = 1068$ for $L_g = 48$ and $N_c = 4$. This is represented as N_c waveforms of length $L_g/N_c + 255 = 267$.

One advantage of this approach is that elements can be stored for a range of offsets τ so that calculations do not need to be performed when lags change. For delay spreads of about 4μs 32 samples need to be stored for each m'.

3. Using Code Correlations

The C-matrix elements can be represented in terms of the underlying code correlations using

$$C_{lkqq'}[m'] \equiv \frac{1}{2N_l} \sum_n s_k[nN_c + m'T + \hat{\tau}_{lq} - \hat{\tau}_{kq'}] \cdot c_l^*[n]$$

$$= \frac{1}{2N_l} \sum_n \sum_p g[(n-p)N_c + m'T + \hat{\tau}_{lq} - \hat{\tau}_{kq'}] \cdot c_k[p] \cdot c_l^*[n]$$

$$= \frac{1}{2N_l} \sum_n \sum_m g[mN_c + \tau] \cdot c_k[n-m] \cdot c_l^*[n]$$

$$= \sum_m g[mN_c + \tau] \cdot \frac{1}{2N_l} \sum_n c_l^*[n] \cdot c_k[n-m] \qquad (4)$$

$$= \sum_m g[mN_c + \tau] \cdot \Gamma_{lk}[m]$$

$$\Gamma_{lk}[m] \equiv \frac{1}{2N_l} \sum_n c_l^*[n] \cdot c_k[n-m]$$

$$\tau \equiv m'T + \hat{\tau}_{lq} - \hat{\tau}_{kq'}.$$

If the length of $g[t]$ is $L_g = 48$ and $N_c = 4$, then the summation over m requires 48/4 =12 macs for the real part and 12 macs for the imaginary part. The total ops is then 48 ops per element. (Compare with 2048 operations for the direct method.) Hence for the case where there are 200 virtual users and 20% of the C-matrix needs updating every 10 ms the required complexity is (960000 el)(48 ops/el)(0.20)/(0.010 sec) = 921.6 MOPS. This is the required complexity to compute the C-matrix from the Γ-matrix. The cost of computing the Γ-matrix must also be considered. There is reason to hope that the Γ-matrix can be efficiently computed since the fundamental operation is a convolution of codes with elements constrained to be +/-1 +/-j.

The Γ-matrix elements can be calculated using
* the FFT
* Modulo-2 arithmetic
* . Hardware XOR
* Short-code generator(?)

4. Using Fundamental Correlations

The waveform $s_k[t]$ can be decomposed into fundamental waveforms corresponding to 4-chip segments of the corresponding complex user codes. There are $2^8 = 256$ such waveforms. Each of these can be correlated with another 256 possible 4-chip code segments. For each correlation there are about 64 offsets that produce a non-zero correlation. Hence all correlation calculations can be represented in terms of $256(256)(64) = 4M$ fundamental complex correlations. The C-matrix elements are then

$$C_{lkqq'}[m'] \equiv \frac{1}{2N_l} \sum_n s_k[nN_c + m'T + \hat{\tau}_{lq} - \hat{\tau}_{kq'}] \cdot c_l^*[n]$$

$$= C_{lk}[\tau_{lkqq'}[m']]$$

$$C_{lk}[\tau] \equiv \frac{1}{2N_l} \sum_n s_k[nN_c + \tau] \cdot c_l^*[n]$$

$$\tau_{lkqq'}[m'] \equiv m'T + \hat{\tau}_{lq} - \hat{\tau}_{kq'}$$

$$C_{lk}[\tau] \equiv \sum_{i=0}^{63} \sum_{j=0}^{63} \frac{1}{2N_l} \sum_{n=0}^{3} s_{kj}[nN_c + \tau] \cdot c_{li}^*[n]$$

$$= \sum_{i=0}^{63} \sum_{j=0}^{63} C_{n_{kj}n_{li}}[\tau]$$

$$C_{n_{kj}n_{li}}[\tau] \equiv \frac{1}{2N_l} \sum_{n=0}^{3} s_{n_{kj}}[nN_c + \tau] \cdot c_{n_{li}}^*[n] \tag{5}$$

Using the above, each C-matrix element requires $64(64) = 4096$ complex adds, or 8192 operations to calculate. (Compare with 2048 operations for the direct method.)

Alternately, the calculations can be represented in terms of 4-chip real code segments and the corresponding waveforms. Hence all correlation calculations can be represented in terms of $16(16)(64) = 16K$ fundamental real correlations.

Computer Systems, Inc.

MERCURY

199 Riverneck Road
Chelmsford, MA 01824-2820
(978) 256-1300 • Fax (978) 256-3599
http://www.mc.com

Report

To: Wireless Communications Group

From: J. H. Oates

Subject: Calculation of C-matrix Elements   Date: August 10, 2000

1. Introduction

The C-matrix elements are used to calculate the R-matrices, which are used by the MDF interference cancellation routine. Each C-matrix element can be calculated as a dot product between the kth user's waveform and the lth user's code stream, each offset by some multipath delay. For this method of calculation, each time a user's multipath profile changes all C-matrix elements associated with the changed profile must be recalculated. It is estimated that a user profile changes every 100 ms. This number, however, is based on very little data, and there is considerable risk that profiles may change more rapidly and compromise real-time operation. In addition, there is a large amount of overhead that must be performed before each dot product. In a recent benchmark the overhead consumed nearly all of the time allocated for the entire C-matrix update. Finally, if the C-matrix is calculated as described above then an entire processor must be allocated for this calculation.

In view of the above observations a better approach is to pre-calculate the code correlations up-front when a user is added to the system. This calculation is performed over all possible code offsets and the calculations are stored in a large array, approximately 21 Mbytes in size. We will henceforth refer to this large matrix as the Γ matrix. The C-matrix elements are updated when a profile changes by extracting the appropriate elements from the Γ matrix and performing minor calculations. Since the Γ matrix elements are calculated for all code offsets the FFT can be effectively used to speed up the calculations. Since all code offsets are pre-calculated, there is no risk associated with rapidly changing multipath profiles. Under normal operating conditions when the number of users accessing system is constant the resources which must be allocated to extracting the C-matrix elements are minimal, and so extra resources may be allocated to the R-matrix calculation.

Section 2 below outlines the calculation of the Γ matrix elements. It is shown that the Γ matrix elements are given in terms of a convolution. Section 3 shows how to calculate the Γ matrix elements using the FFT. Section 4 describes how the Γ-matrix elements might be

1

accessed from SDRAM. In section 5 various processing times are estimated, and a summary with conclusions is given in section 6.

2. C-matrix Elements Expressed in Terms of Code Correlations

The R-matrix elements are given in terms of the C-matrix elements as [1]

$$\hat{\rho}_{lk}[m']A_l A_k = \sum_{q=1}^{L}\sum_{q'=1}^{L}\text{Re}\{\hat{a}_{lq}^* \hat{a}_{kq'} \cdot C_{lkqq'}[m']\}$$

(1)

$$C_{lkqq'}[m'] \equiv \frac{1}{2N_l}\sum_{n} s_k[nN_c + m'T + \hat{\tau}_{lq} - \hat{\tau}_{kq'}] \cdot c_l^*[n]$$

where $C_{lkqq'}[m']$ is a five-dimensional matrix of code correlations. Both l and k range from 1 to K_v, where K_v is the number of virtual users. The indices q and q' range from 1 to L, the number of multipath components, which is assumed to be equal to 4. The symbol period offset m' ranges from -1 to 1. The total number of matrix elements to be calculated is then $N_c = 3(K_v L)^2 = 3(800)^2 = 1.92M$ complex elements, or 3.84 MB if each element is a byte. This number is cut in half, however, due to the symmetries [2]

$$C_{klq'q}[-m'] = \frac{N_l}{N_k}C_{lkqq'}^*[m']$$

(2)

The memory requirement is then 1.92 MB.

Referring to Equation (1) it is evident that each element of $C_{lkqq'}[m']$ is a complex dot product between a code vector c_l and a waveform vector $s_{kqq'}$. The length of the code vector is 256. The waveform $s_k[t]$ is referred to as the signature waveform for the kth virtual user. This waveform is generated by passing the spread code sequence $c_k[n]$ through a pulse-shaping filter $g[t]$

$$s_k[t] = \sum_{p=0}^{N-1} g[t - pN_c]c_k[p]$$

(3)

where $N = 256$ and $g[t]$ is the raised-cosine pulse shape. Since $g[t]$ is a raised-cosine pulse as opposed to a root-raised-cosine pulse, the signature waveform $s_k[t]$ includes the effects of filtering by the matched chip filter. Note that for spreading factors less than 256 some of the chips $c_k[p]$ are zero. The length of the waveform vector is $L_g + 255N_c$, where L_g is the length of the raised-cosine pulse vector $g[t]$ and N_c is the number of samples per chip. The values for these parameters as currently implemented are $L_g = 48$ and $N_c = 4$. The length of the waveform vector is then 1068, but for the dot product it is accessed at a stride of $N_c = 4$, which gives effectively a length of 267.

The raised-cosine pulse vector $g[t]$ is defined to be non-zero from $t = -L_g/2 + 1:L_g/2$, with $g[0] = 1$. With this definition the waveform $s_k[t]$ is non-zero from $t = -L_g/2 + 1: L_g/2 + 255N_c$.

By combining Equations (1) and (3) the calculation of the C-matrix elements can be expressed directly in terms of the user code correlations. These correlations can be calculated up front and stored in SDRAM. The C-matrix elements expressed in terms of the code correlations $\Gamma_{lk}[m]$ are

$$C_{lkqq'}[m'] \equiv \frac{1}{2N_l} \sum_n s_k[nN_c + m'T + \hat{\tau}_{lq} - \hat{\tau}_{kq'}] \cdot c_l^*[n]$$

$$= \frac{1}{2N_l} \sum_n \sum_p g[(n-p)N_c + m'T + \hat{\tau}_{lq} - \hat{\tau}_{kq'}] \cdot c_k[p] \cdot c_l^*[n]$$

$$= \frac{1}{2N_l} \sum_n \sum_m g[mN_c + \tau] \cdot c_k[n-m] \cdot c_l^*[n]$$

$$= \sum_m g[mN_c + \tau] \cdot \frac{1}{2N_l} \sum_n c_l^*[n] \cdot c_k[n-m] \qquad (4)$$

$$= \sum_m g[mN_c + \tau] \cdot \Gamma_{lk}[m]$$

$$\Gamma_{lk}[m] \equiv \frac{1}{2N_l} \sum_n c_l^*[n] \cdot c_k[n-m]$$

$$\tau \equiv m'T + \hat{\tau}_{lq} - \hat{\tau}_{kq'}$$

Since the pulse shape vector $g[n]$ is of length L_g there are at most $2L_g/N_c = 24$ real macs to be performed to calculate each element $C_{lkqq'}[m']$. (The factor of 2 is because the code correlations $\Gamma_{lk}[m]$ are complex.) Given τ it is important to be able to efficiently calculate the range of values m for which $g[mN_c + \tau]$ is non-zero. The minimum value of m is given by $m_{min1}N_c + \tau = -L_g/2 + 1$. Now τ is given by $\tau = m'NN_c + \tau_{lq} - \tau_{kq'}$. If each τ value is decomposed $\tau_{lq} = n_{lq}N_c + p_{lq}$, then $m_{min1} = \text{ceil}[\ (-\tau - L_g/2 + 1)/N_c\ ] = -m'N - n_{lq} + n_{kq'} - L_g/(2N_c) + \text{ceil}[\ (p_{kq'} - p_{lq} + 1)/N_c\ ]$. Now $\text{ceil}[\ (p_{kq'} - p_{lq} + 1)/N_c\ ]$ will be either 0 or 1. It is convenient to set this to 0. In order that we do not access values outside the allocation for $g[n]$ we must set $g[n] = 0.0$ for $n = -L_g/2 : -L_g/2 - (N_c - 1)$. Note that of the N_c^2 possible values for $\text{ceil}[\ (p_{kq'} - p_{lq} + 1)/N_c\ ]$, all but one are 0. Hence we have

$$m_{min1} = -m'N - n_{lq} + n_{kq'} - L_g/(2N_c) \qquad (5)$$

Note that L_g must be divisible by $2N_c$, and that $L_g/(2N_c)$ should be a system constant.

The maximum value of m is given by $m_{max1}N_c + \tau = L_g/2$. This gives $m_{max1} = \text{floor}[\ (-\tau + L_g/2)/N_c\ ] = -m'N - n_{lq} + n_{kq'} + L_g/(2N_c) + \text{floor}[\ (p_{kq'} - p_{lq})/N_c\ ]$. Now $\text{floor}[\ (p_{kq'} - p_{lq})/N_c\ ]$ will be either -1 or 0. It is convenient to set this to 0. In order that we do not access values outside the allocation for $g[n]$ we must set $g[n] = 0.0$ for $n = -L_g/2 + 1 : L_g/2 + N_c$. Note that of the N_c^2 possible values for $\text{floor}[\ (p_{kq'} - p_{lq})/N_c\ ]$, about half are 0. Hence we have

$$m_{max1} = -m'N - n_{lq} + n_{kq'} + L_g/(2N_c) \qquad (6)$$

These values are quickly calculable.

The Γ matrix is calculated in the next section for all values m by exploiting the FFT. Notice that the calculation of the C-matrix elements requires only a small subset of the Γ matrix elements.

3. Using the FFT to Calculate the Γ-matrix Elements

In the previous section it was shown that the Γ-matrix elements can be represented as a convolution. This fact is here exploited to calculate the Γ-matrix elements using the FFT convolution theorem. From Equation (4) the Γ-matrix elements are

$$\Gamma_{lk}[m] \equiv \frac{1}{2N_l} \sum_{n=0}^{N-1} c_l^*[n] \cdot c_k[n-m] \tag{7}$$

where $N = 256$. Three streams are related by this equation. In order to apply the convolution theorem all three streams must be defined over the same time interval. The code streams $c_k[n]$ and $c_l[n]$ are non-zero from $n = 0:255$. These intervals are based on the maximum spreading factor. For higher data-rate users the intervals over which the streams are non-zero are reduced further. We are concerned here, however, with the intervals derived from the highest spreading factor since these will be the largest intervals and we wish to define a common interval for all streams. The common interval allows the FFTs to be reused for all user interactions.

Figure 1. Interval for FFT calculation of the Γ matrix elements. Shown For the case where $N_k = 256$ and $N_l = 128$.

The range of values m for which $\Gamma_{lk}[m]$ is non-zero can be derived from the above intervals. The maximum value of m is limited by $n - m \geq 0$, which gives

$$255 - m_{max} = 0 \quad \Rightarrow \quad m_{max} = 255 \tag{8}$$

and the minimum value is limited by $n - m \leq 255$, which gives

$$0 - m_{min} = 255 \quad \Rightarrow \quad m_{min} = -255 \tag{9}$$

To achieve a common interval for all three streams we select the interval $m = -M/2: M/2 - 1, M = 512$. Where necessary the streams are zero-padded to fill up the interval.

Now, the DFT and IDFT of the streams are

$$C_l[r] = \sum_{n=-\frac{M}{2}}^{\frac{M}{2}-1} c_l[n] \cdot e^{-j2\pi nr/M}$$

$$c_l[n] = \frac{1}{M} \sum_{r=-\frac{M}{2}}^{\frac{M}{2}-1} C_l[r] \cdot e^{j2\pi nr/M}$$

(10)

which gives

$$\Gamma_{lk}[m] \equiv \frac{1}{2N_l} \sum_{n=-\frac{M}{2}}^{\frac{M}{2}-1} c_k[n-m] \cdot c_l^*[n]$$

$$= \frac{1}{2N_l M^2} \sum_{n=-\frac{M}{2}}^{\frac{M}{2}-1} \sum_{r=-\frac{M}{2}}^{\frac{M}{2}-1} C_k[r] \cdot e^{j2\pi(n-m)r/M} \sum_{r'=-\frac{M}{2}}^{\frac{M}{2}-1} C_l^*[r'] \cdot e^{-j2\pi nr'/M}$$

(11)

$$= \frac{1}{2N_l M^2} \sum_{r=-\frac{M}{2}}^{\frac{M}{2}-1} C_k[r] \cdot e^{-j2\pi mr/M} \sum_{r'=-\frac{M}{2}}^{\frac{M}{2}-1} C_l^*[r'] \sum_{n=-\frac{M}{2}}^{\frac{M}{2}-1} e^{j2\pi n(r-r')/M}$$

$$= \frac{1}{2N_l M} \sum_{r=-\frac{M}{2}}^{\frac{M}{2}-1} C_k[r] \cdot C_l^*[r] e^{-j2\pi mr/M}$$

Hence $\Gamma_{lk}[m]$ can be calculated using the FFTs. Notice that the FFT gives values for all m. From the analysis above we know that many of these values will be zero for high data rate users. To conserve memory we wish to store only the non-zero values. The values of m for which $\Gamma_{lk}[m]$ is non-zero can be determined analytically. This subject is treated in the next section where the storage and retrieval of the Γ-matrix elements is considered.

4. Storage and Retrieval of Γ-matrix Elements

In order to efficiently store the Γ-matrix elements we must determine which values are non-zero. For high data rate users certain elements $c_l[n]$ are zero, even within the interval $n = 0:N-1$, $N = 256$. These zero values reduce the interval over which $\Gamma_{lk}[m]$ is non-zero. In order to determine the interval for non-zero values consider

$$\Gamma_{lk}[m] \equiv \frac{1}{2N_l} \sum_{n=0}^{N-1} c_l^*[n] \cdot c_k[n-m]$$

(12)

Define index j_l for the lth virtual user such that $c_l[n]$ is non-zero only over the interval $n = j_l N_l : j_l N_l + N_l - 1$. Correspondingly, the vector $c_k[n]$ is non-zero only over the interval $n = j_k N_k : j_k N_k + N_k - 1$. Given these definitions $\Gamma_{lk}[m]$ can be rewritten as

$$\Gamma_{lk}[m] \equiv \frac{1}{2N_l} \sum_{n=0}^{N_l-1} c_l^*[n + j_l N_l] \cdot c_k[n + j_l N_l - m] \qquad (13)$$

The minimum value of m for which $\Gamma_{lk}[m]$ is non-zero is

$$m_{\min 2} = -j_k N_k + j_l N_l - N_k + 1 \qquad (14)$$

and the maximum value of m for which $\Gamma_{lk}[m]$ is non-zero is

$$m_{\max 2} = N_l - 1 - j_k N_k + j_l N_l \qquad (15)$$

The total number of non-zero elements is then

$$m_{total} \equiv m_{\max 2} - m_{\min 2} + 1 \qquad (16)$$

$$= N_l + N_k - 1$$

Table 1 below gives the number of bytes per l,k virtual-user pair based on 2 bytes per element — one byte for the real part and one byte for the imaginary part.

Table 1. Number of bytes per l,k virtual user pair based on 2 bytes per element.

	$N_k = 256$	128	64	32	16	8	4
$N_l = 256$	1022	766	638	574	542	526	518
128	766	510	382	318	286	270	262
64	638	382	254	190	158	142	134
32	574	318	190	126	94	78	70
16	542	286	158	94	62	46	38
8	526	270	142	78	46	30	22
4	518	262	134	70	38	22	14

Now we are in a position to determine the memory requirements for the Γ matrix for a given number of users at each spreading factor. Let there be K_q virtual users at spreading factor $N_q \equiv 2^{8-q}$, $q = 0:6$, where K_q is the qth element of the vector K. Note that some elements of K may be zero. Let Table 1 above be stored in matrix M with elements $M_{qq'}$. For example, $M_{00} = 1022$, and $M_{01} = 766$. The total memory required by the Γ matrix in bytes is then

$$M_{bytes} = \sum_{q=0}^{6} \left\{ \frac{K_q(K_q + 1)}{2} M_{qq} + \sum_{q'=q+1}^{6} K_q K_{q'} M_{qq'} \right\} \qquad (17)$$

$$= \frac{1}{2} \sum_{q=0}^{6} \left\{ K_q M_{qq} + \sum_{q'=0}^{6} K_q K_{q'} M_{qq'} \right\}$$

For example, for 200 virtual users at spreading factor $N_0 = 256$ we have $K_q = 200\delta_{q0}$, which gives $M_{bytes} = \frac{1}{2}K_0(K_0 + 1)M_{00} = 100(201)(1022) = 20.5$ MB.

For 10 384 Kbps users we have $K_q = K_0\delta_{q0} + K_6\delta_{q6}$ with $K_0 = 10$ and $K_6 = 640$. This gives $M_{bytes} = \frac{1}{2}K_0(K_0 + 1)M_{00} + K_0K_6M_{06} + \frac{1}{2}K_6(K_6 + 1)M_{66} = 5(11)(1022) + 10(640)(518) + 320(641)(14) = 6.2$ MB.

Now consider addressing, storing and accessing the Γ-matrix data. For each pair (l,k), $k >= l$ we have 1 complex value $\Gamma_{lk}[m]$ value for each value of m, where m ranges from m_{min2} to m_{max2}, and the total number of non-zero elements is $m_{total} = m_{max2} - m_{min2} + 1$. Hence for each pair (l,k), $k >= l$ we have $2m_{total}$ time-contiguous bytes. To access the data, create an array of structures:

```
struct {
        int m_min2;
        int m_max2;
        int m_total;
        char * Glk;
} G_info[N_VU_MAX][ N_VU_MAX];
```

The C-matrix data is then retrieved using something like:

```
mmin2 = G_info[l][k].m_min2
mmax2 = G_info[l][k].m_max2
Ng = Lg/Nc
N1 = m'*N – Lg/(2Nc)
for m' = 0:1
        for q = 0:L –1
                for q' = 0:L –1
                        τ = m'T + τlq – τkq'
                        mmin1 =  N1 – nlq + nkq'
                        mmax1 = mmin1 + Ng
                        mmin = max[ mmin1 , mmin2 ]
                        mmax = min[ mmax1 , mmax2 ]
                        if mmax >= mmin
                                mspan = mmax – mmin + 1
                                sum1 = 0.0;
                                ptr1 = &G_info[l][k].Glk[mmin]
                                ptr2 = &g[ mmin * Nc + τ ]
                                while mspan > 0
                                        sum1 += ( *ptr1++ ) * ( *ptr2++ )
                                        mspan—
                                end
                                C[m'][l][k][q][q'] = sum1
                        end
                end
        end
end
```

5. Estimated Processing Times

The following processing times are estimated below:
- Calculate Γ-matrix elements
- Write to Γ-matrix elements to SDRAM
- Pack Γ-matrix elements in SDRAM
- Extract Γ-matrix elements/Form C-matrix from SDRAM
- Write C-matrix elements to L2 cache
- Pack C-matrix elements in L2 cache

Processing times are calculated for two cases of interest. The first case is where $K = 100$ users ($K_v = 200$ virtual users) are accessing the system and a voice user is added to the system. Not all of these users are active. The control channels are always active, but the data channels have activity factor AF = 0.4. The mean number of active virtual users is then $K + AF*K = 140$. The standard deviation is $\sigma = \sqrt{K \cdot AF \cdot (1 - AF)} = 4.90$. With high probability, then, we have $K_v < 140 + 3\sigma < 155$ active users.

The second case is the worst case scenario. This occurs when a number of voice users are accessing the system and a single 384 Kbps data user is added. A single 384 Kbps data user adds interference equal to $(.25 + 0.125*100)/(.25 + 0.400*1) \sim = 20$ voice users. Hence, the number of voice users accessing the system must be reduced to approximately $K = 100 - 20 = 80$ ($K_v = 160$). The 3σ number of active virtual users is then $80 + (0.125)80 + 3(3.0) = 99$ active virtual users. The reason this scenario is stressful is that when a single 384 Kbps data user is added to the system, $J + 1 = 64 + 1 = 65$ virtual users are added to the system.

Calculate Γ-matrix elements

The Γ-matrix elements can be calculated in one of two ways. The first is using the SAL zconvx to perform the direct convolution. The second is using the SAL fft_zipx to perform the calculation via the FFT. The first method is preferable when the vector lengths are small. SAL timing are given in Table 2. These timings are based on a 400 MHz PPC7400 with 160MHz, 2MB L2 cache. The data is assumed resident in L1 cache. The performance loss for data L2 cache resident is not severe.

Table 2. SAL timings and GFLOPS for zconvx function

M_{total}	N_i	Timing (μs)	GFLOPS
1024	4	19.33	1.70
1024	8	29.73	2.20
1024	16	50.55	2.59
1024	32	92.32	2.84
1024	64	176.53	2.97
1024	128	346.80	3.47

The time to perform a 512 complex FFT, with in-place calculation (fft_zipx), on a 400 MHz PPC7400 with 160MHz, 2MB L2 cache is 10.94 μs for data L1 resident. Prior to

performing the (final) FFT we must perform a complex vector multiply of length 512. The SAL timings for zvmulx are given in Table 3.

Table 3. SAL timings and GFLOPS for zvmulx function

Length	Location	Timing (µs)	GFLOPS
1024	L1	4.46	1.38
1024	L2	24.27	0.253
1024	DRAM	61.49	0.100

We will also be interested in the time to move data. Hence the SAL timings for zvmovx are given in Table 4.

Table 4. SAL timings for zvmovx function

Length	Location	Timing (µs)
1024	L1	1.20
1024	L2	15.34
1024	DRAM	30.05

Figure 2 shows the elements that must be calculated (in gray) when a physical user is added to the system. When a physical user is added to the system there are $1 + J$ virtual users added to the systems: that is, 1 control channel $+ J = 256/SF$ data channels. The number K_v represents the number of virtual users that are using the system to begin with.

Figure 2. Elements that must be calculated (in gray)
when a physical user is added to the system.

Hence there are $(K_v + 1)$ elements added due to the control channel, and $J(K_v + 1) + J(J + 1)/2$ elements added due to the data channels. The total number of elements added is then $(J + 1)[K_v + 1 + J/2]$.

Suppose that the FFT is used to perform the calculations. The total number of FFTs to perform is $(J + 1) + (J + 1)[K_v + 1 + J/2]$. The first term represents the FFTs to transform $c_k[n]$, and the second term represents the $(J + 1)[K_v + 1 + J/2]$ inverse FFTs of $FFT\{c_k[n]\}^*FFT\{c_i[n]\}$. The time to perform the complex 512 FFTs is 10.94 μs, whereas the time to perform the complex vector multiply and the complex 512 FFT is 24.27/2 + 10.94 = 23.08 μs.

For the first scenario there are $K_v = 200$ virtual users accessing the system and a voice user is added to the system $(J = 1)$. The total time to add the voice user is then $(1 + 1)(10.94 \ \mu s) + (1 + 1)[200 + 1 + 1/2](23.08 \ \mu s) = 9.3$ ms.

For the second scenario there are $K_v = 160$ virtual users accessing the system and a 384 Kbps data user is added to the system $(J = 64)$. The total time to add the 384 Kbps user is then $(64 + 1)(10.94 \ \mu s) + (64 + 1)[160 + 1 + 64/2](23.08 \ \mu s) = 290$ ms! This number is way too big and hence for high data-rate users, at least, the Γ-matrix elements must be calculated via convolutions.

The direct method to calculate the Γ-matrix elements is to use the SAL zconvx function to perform the convolution

$$\Gamma_{lk}[m] \equiv \frac{1}{2N_l} \sum_{n=0}^{N_l-1} c_l^*[n + j_l N_l] \cdot c_k[n + j_l N_l - m]$$

$$= \frac{1}{2N_l} \sum_{n=0}^{N_k-1} c_l^*[n + j_k N_k + m] \cdot c_k[n + j_k N_k]$$

(18)

For each value of m there are $N_{min} = \min\{N_l, N_k\}$ complex macs (cmacs). Each cmac requires 8 flops, and there are $m_{total} = N_l + N_k - 1$ m-values to calculate. Hence the total number of flops is $8N_{min}(N_l + N_k - 1)$. For what follows we assume the convolution calculation is performed at 1.50 GOPs = 1500 ops/μs. The calculation time to perform the convolutions is presented in Table 5.

Table 5. Calculation time(μs) to perform the Γ-matrix convolutions.

	$N_k = 256$	128	64	32	16	8	4
$N_l = 256$	697.69	261.46	108.89	48.98	23.13	11.22	5.53
128	261.46	174.08	65.19	27.14	12.20	5.76	2.79
64	108.89	65.19	43.35	16.21	6.74	3.03	1.43
32	48.98	27.14	16.21	10.75	4.01	1.66	0.75
16	23.13	12.20	6.74	4.01	2.65	0.98	0.41
8	11.22	5.76	3.03	1.66	0.98	0.64	0.23
4	5.53	2.79	1.43	0.75	0.41	0.23	0.15

The shaded cells indicate times faster than the 23.08 μs FFT time. Equation 17 gives the size of the Γ-matrix in bytes. Similarly, the total time to calculate the Γ-matrix is

$$T_{\Gamma}(K) = \sum_{q=0}^{6} \left\{ \frac{K_q(K_q+1)}{2} T_{qq} + \sum_{q'=q+1}^{6} K_q K_{q'} T_{qq'} \right\}$$

$$= \frac{1}{2} \sum_{q=0}^{6} \left\{ K_q T_{qq} + \sum_{q'=0}^{6} K_q K_{q'} T_{qq'} \right\} \qquad (19)$$

$$= \frac{1}{2} \left[K \cdot diag(T) + K^T \cdot T \cdot K \right]$$

where T_{qq} are the elements in Table 5. Now suppose $K' = K + \Delta$, where $\Delta_q = J_x \delta_{qx} + J_y \delta_{qy}$, where x and y are not equal. Then

$$\Delta T_{\Gamma} \equiv T_{\Gamma}(K') - T_{\Gamma}(K)$$

$$= \frac{1}{2} J_x (J_x+1) T_{xx} + \frac{1}{2} J_y (J_y+1) T_{yy} + J_x J_y T_{xy} + \sum_{q=0}^{6} K_q \left\{ J_x T_{xq} + J_y T_{yq} \right\} \qquad (20)$$

For the first scenario there are $K_v = 200$ virtual users accessing the system and a voice user is added to the system ($J = 1$). Hence we have $K_q = K_v \delta_{q0}$ (SF = 256), $K_v = 200$, $J_x = J = 2$ and $J_y = 0$. The total time is then

½$J(J + 1)T_{00} + JK_vT_{00} = (0.5)(2)(3)(0.70 \text{ ms}) + (2)(200)(0.70 \text{ ms}) = 283 \text{ ms}$

This number is way too big and hence for voice users, at least, the Γ-matrix elements must be calculated via FFTs.

For the second scenario there are $K_v = 160$ virtual users accessing the system and a 384 Kbps data user is added to the system ($J = 64$). Hence we have $K_q = K_v \delta_{q0}$ (SF = 256), $K_v = 160$, $J_x = 1$ (control) and $J_y = J = 64$ (data). The total time is then

$(K_v + 1)T_{00} + J(K_v + 1)T_{06} + (J + 1)(J/2)T_{66}$
$= (161)(697.7 \text{ μs}) + (64)(161)(5.53 \text{ μs}) + (65)(32)(0.15 \text{ μs}) =$
$112.33 \text{ ms} + 56.98 \text{ ms} + 0.31 \text{ ms} = 169.62 \text{ ms}$

Since $T_{00} = 697.7$ μs is so large, these calculations should be performed using the FFT, which costs 23.08 μs per convolution. We also have 1 FFTs to compute FFT{$c_k[n]$}) for the single control channel. This costs an additional 10.94 μs. The total time, then, to add the 384 Kbps user is

$10.94 \text{ μs} + (161)(23.08) \text{ μs} + (64)(161)(5.53) \text{ μs} + (65)(32)(0.15) \text{ μs} =$
$= 61.02 \text{ ms}$

Write to Γ-matrix elements to SDRAM

The numbers in Table 1 represent the $2m_{total}$ bytes per Γ-matrix element. Recall that the size of the Γ-matrix in bytes from Equation 17 is

$$M_b(K) = \sum_{q=0}^{6} \left\{ \frac{K_q(K_q+1)}{2} M_{qq} + \sum_{q'=q+1}^{6} K_q K_{q'} M_{qq'} \right\}$$

$$= \frac{1}{2} \sum_{q=0}^{6} \left\{ K_q M_{qq} + \sum_{q'=0}^{6} K_q K_{q'} M_{qq'} \right\} \qquad (21)$$

$$= \frac{1}{2} \left[K \cdot diag(M) + K^T \cdot M \cdot K \right]$$

Now suppose $K' = K + \Delta$, where $\Delta_q = J_x \delta_{qx} + J_y \delta_{qy}$, where x and y are not equal. Then

$$\Delta M_b \equiv M_b(K') - M_b(K)$$

$$= \frac{1}{2} J_x (J_x + 1) M_{xx} + \frac{1}{2} J_y (J_y + 1) M_{yy} + J_x J_y M_{xy} \qquad (22)$$

$$+ \sum_{q=0}^{6} K_q \left\{ J_x M_{xq} + J_y M_{yq} \right\}$$

Consider the first scenario where $K_q = 200\delta_{q0}$ (SF = 256) and that a single voice user is added to the system: $J_x = 2$ (data plus control), and $J_y = 0$. The total number of bytes is then $0.5(2)(3)(1022) + 200(2)(1022) = 0.412$ MB. The SDRAM write speed is 133MHz*8 bytes * 0.5 = 532 MB/s. The time to write to SDRAM is then 0.774 ms.

Now for the second scenario $K_q = 160\delta_{q0}$ (SF = 256), and that a single 384 Kbps (SF = 4) user is added to the system: $J_x = 1$ (control) and $J_y = 64$ (data). The total number of bytes is then $0.5(1)(2)(1022) + 0.5(64)(65)(14) + 160\{1(1022) + 64(518)\} = 5.498$ MB. The SDRAM write speed is 133MHz*8 bytes * 0.5 = 532 MB/s. The time to write to SDRAM is then 10.33 ms.

Pack Γ-matrix elements in SDRAM

The maximum total size of the Γ-matrix is 20.5 MB. Suppose that in order to pack the matrix every element must be moved. This is the worst case. The SDRAM speed is 133MHz*8 bytes * 0.5 = 532 MB/s. The move time is then 2(20.5 MB)/(532 MB/s) = 77.1 ms. If the Γ-matrix is divided over three processors this time is reduced by a factor of 3. The packing can be done incrementally, so there is no strict time limit.

Extract Γ-matrix elements/Form C-matrix from SDRAM

Recall that the C-matrix data is retrieved using something like:

$m_{min2} = G\_info[l][k].m\_min2$
$m_{max2} = G\_info[l][k].m\_max2$
$N_g = L_g/N_c$
$N1 = m'^*N - L_g/(2N_c)$
for $m' = 0:1$
      for $q = 0:L -1$
            for $q' = 0:L -1$
                 $\tau = m'T + \tau_{lq} - \tau_{kq'}$
                 $m_{min1} = N1 - n_{lq} + n_{kq'}$
                 $m_{max1} = m_{min1} + N_g$
                 $m_{min} = \max[m_{min1}, m_{min2}]$
                 $m_{max} = \min[m_{max1}, m_{max2}]$
                 if $m_{max} >= m_{min}$
                       $m_{span} = m_{max} - m_{min} + 1$
                       $sum1 = 0.0;$
                       $ptr1 = \&G\_info[l][k].Glk[m_{min}]$
                       $ptr2 = \&g[m_{min} * N_c + \tau]$
                       while $m_{span} > 0$
                           $sum1 += (^*ptr1++) ^* (^*ptr2++)$
                           $m_{span}-$
                     end
                     $C[m'][l][k][q][q'] = sum1$
             end
         end
     end
end

Time to extract elements when a new user is added to the system

We calculated above the time to calculate the Γ-matrix elements when a new user is added to the system. Here we consider the time to extract the corresponding C-matrix elements.

Notice that $Glk[m]$ are accessed from SDRAM. Values will almost certainly *not* be in either L1 or L2 cache. For a given (l,k) pair, however, the spread in τ will for most cases be less than 8 μs (i.e for a 4 μs delay spread), which equates to (8 μs)(4 chips/μs)(2 bytes/chip) = 64 bytes, or 2 cache lines. Since data must be read in for two values of m' a total of 4 cache lines must be read. This will require 16 clocks, or about 16/133 = 0.12 μs. However, measured results for zvmovx indicate that accesses to SDRAM are performed at about 50% efficiency so that the required time is about 0.24 μs.

Now suppose, for example, user $l = x$ is added to the system. We must fetch the elements $C[m'][x][k][q][q']$ for all m', k, q and q'. As indicated above, all the m', q and q' values will be contained typically in 4 cache lines. Hence if there are K_v virtual users we must read in $4K_v$ cache lines, or $32K_v$ clocks, where we have doubled the clocks to account for the 50%

efficiency. In general $J + 1$ virtual users are added to the system at a time. This will require $32K_v(J + 1)$ clocks.

For the first case where we have 155 active virtual users and a new voice user is added to the system, the time required to read in the C-matrix elements will be $32(155)(1 + 1)$ clocks/(133 clocks/μs) = 74.6 μs. The industry standard hold time t_h for a voice call is 140 s. The average rate λ of users added to the system can be determined from $\lambda t_h = K$, where K is the average number of users using the system. For $K = 100$ users we have $\lambda = 100/140$ s = 1 users added per 1.4 s.

For the case where we have 99 active virtual users and a 384 Kbps user is added to the system, the time required to read in the C-matrix elements will be $32(99)(64 + 1)$ clocks/(133 clocks/μs) = 1.55 ms. However data users presumably will be added to the system more infrequently than voice users.

Time to extract elements when τ_{xy} changes

Now suppose, for example, user $I = x$ lag $q = y$ changes. Then we must fetch the elements $C[m'][x][k][y][q']$ for all m', k and q'. All the q' values will be contained typically in 1 cache line. Hence we must read in $2(K_v)(1) = 2K_v$ cache lines, or $16K_v$ clocks, where we have doubled the clocks to account for the 50% efficiency. In general, when a lag changes there are $J + 1$ virtual users for which the C-matrix elements must be updated. This will require $16K_v(J + 1)$ clocks.

For the first case where we have 155 active virtual users and a voice user's profile (one lag) changes, the time required to read in the C-matrix elements will be $16(155)(1 + 1)$ clocks/(133 clocks/μs) = 37.3 μs. Recall that for high mobility users such changes should occur at a rate of about 1 per 100 ms per physical user. This equates to about once per 1.33 ms processing interval if there are 100 physical users so that approximately 37.3 μs will be required every 1.33 ms.

For the case where we have 99 virtual users and a 384 Kbps data user's profile (one lag) changes, the time required to read in the C-matrix elements will be $16(99)(64 + 1)$ clocks/(133 clocks/μs) = 0.774 ms. However data users will have lower mobility and hence such changes should occur infrequently.

Write C-matrix elements to L2 cache

Time to write elements when a new user is added to the system

Consider again the case where user $I = x$ is added to the system. We must write elements $C[m'][x][k][q][q']$ for all m', k, q and q'. If there are K_v active virtual users we must write $4K_vL^2$ bytes, where we have doubled the bytes since the elements are complex. In general $J + 1$ virtual users are added to the system at a time. This will require $4K_vL^2(J + 1)$ bytes to be written to L2 cache.

For the first case where we have 155 active virtual users and a new voice user is added to the system, the time required to write the C-matrix elements will be $4(155)(16)(1 + 1)$ bytes/(2128 bytes/μs) = 9.3 μs.

For the second case where we have 99 active virtual users and a 384 Kbps user is added to the system, the time required to write the C-matrix elements will be 4(99)(16)(64 + 1) bytes/(2128 bytes/μs) = 193.5 μs. Recall, however, that data users presumably will be added to the system more infrequently than voice users.

Time to extract elements when τ_{xy} changes

Now suppose, for example, user $l = x$ lag $q = y$ changes. We must write elements $C[m'][x][k][q][q']$ for all m', k and q'. If there are K_v active virtual users we must write $4K_vL$ bytes, where we have doubled the bytes since the elements are complex. In general $J + 1$ virtual users are added to the system at a time. This will require $4K_vL(J + 1)$ bytes to be written to L2 cache.

For the first case where we have 155 active virtual users and a voice user's profile (one lag) changes, the time required to write the C-matrix elements will be 4(155)(4)(1 + 1) bytes/(2128 bytes/μs) = 2.33 μs.

For the second case where we have 99 active virtual users and a 384 Kbps data user's profile (one lag) changes, the time required to write the C-matrix elements will be 4(99)(4)(64 + 1)bytes/(2128 bytes/μs) = 48.4 μs. However data users will have lower mobility and hence such changes should occur infrequently.

Pack C-matrix elements in L2 cache

The C-matrix elements will need to be packed in memory every time a new user is added to or deleted from the system and every time a new user becomes active or inactive. The size of the C-matrix is $2(3/2)(K_vL)^2 = 3(K_vL)^2$ bytes, however, divided over three processors this becomes $(K_vL)^2$ bytes per processor. Assume that the entire matrix must be moved. The move is within L2 cache. Hence the total move time is $2(K_vL)^2$ bytes/(2128 bytes/μs), where the factor of 2 accounts for read and write.

For the first case where we have 155 active virtual users the time required to move the C-matrix elements will be $2(155*4)^2$ bytes/(2128 bytes/μs) = 0.361 ms.

For the first case where we have 99 active virtual users the time required to move the C-matrix elements will be $2(99*4)^2$ bytes/(2128 bytes/μs) = 0.147 ms.

These events will occur typically once every 10 ms, that is, once per frame.

6. Summary and Conclusions

In summary, we have determined
- The Γ-matrix will require approximately 20.5 MB of SDRAM
- To efficiently calculate the Γ-matrix elements will require both direct convolution and FFT calculations
- To pack the Γ matrix in SDRAM will require approximately 77.1 ms

The following processing times are estimated:

Estimated Processing Times	Case 1 (voice user added)	Case 2 (384 Kbps user added)
Calculate Γ-matrix elements	9.3 ms	61.0 ms
Write Γ-matrix elements to SDRAM	0.77 ms	10.3 ms
Extract C-matrix elements when		
New user added	75 μs	1.6 ms
Multipath profile changes	37 μs	0.77 ms
Write C-matrix elements to L2 when		
New user added	9.3 μs	194 μs
Multipath profile changes	2.3 μs	48 μs
Pack C-matrix elements in L2 cache	361 μs	147 μs

These times are based on a single but devoted G4 allocated to perform the calculations.

References

[1] J. H. Oates, "MUD Algorithms," Mercury Wireless Communications Group Report, April 25, 2000.

[2] J. H. Oates, "R-matrix GOPS," Mercury Wireless Communications Group Report, June 21, 2000.

Computer Systems, Inc.

MERCURY

199 Riverneck Road
Chelmsford, MA 01824-2820
(978) 256-1300 • Fax (978) 256-3599
http://www.mc.com

Report

To: Wireless Communications Group

From: J. H. Oates

Subject: Hardware Calculation of Γ-matrix Elements   Date: November 13, 2000

The C-matrix elements can be represented in terms of the underlying code correlations using

$$C_{lkqq'}[m'] \equiv \frac{1}{2N_l} \sum_n s_k[nN_c + m'T + \hat{\tau}_{lq} - \hat{\tau}_{kq'}] \cdot c_l^*[n]$$

$$= \frac{1}{2N_l} \sum_n \sum_p g[(n-p)N_c + m'T + \hat{\tau}_{lq} - \hat{\tau}_{kq'}] \cdot c_k[p] \cdot c_l^*[n]$$

$$= \frac{1}{2N_l} \sum_n \sum_m g[mN_c + \tau] \cdot c_k[n-m] \cdot c_l^*[n]$$

$$= \sum_m g[mN_c + \tau] \cdot \frac{1}{2N_l} \sum_n c_l^*[n] \cdot c_k[n-m] \qquad (1)$$

$$= \sum_m g[mN_c + \tau] \cdot \Gamma_{lk}[m]$$

$$\Gamma_{lk}[m] \equiv \frac{1}{2N_l} \sum_n c_l^*[n] \cdot c_k[n-m]$$

$$\tau \equiv m'T + \hat{\tau}_{lq} - \hat{\tau}_{kq'}$$

The Γ-matrix represents the correlation between the complex user codes. The complex code for user l is assumed to be infinite in length, but with only N_l non-zero values. The non-zero values are constrained to be $\pm 1 \pm j$. The Γ-matrix can represented in terms of the real and imaginary parts of the complex user codes becomes

$$\Gamma_{lk}[m] \equiv \frac{1}{2N_l}\sum_n c_l^*[n]\cdot c_k[n-m]$$

$$=\frac{1}{2N_l}\sum_n \left\{c_l^R[n]-jc_l^I[n]\right\}\cdot\left\{c_k^R[n-m]+jc_k^I[n-m]\right\}$$

$$=\frac{1}{2N_l}\sum_n \left\{c_l^R[n]\cdot c_k^R[n-m]+c_l^I[n]\cdot c_k^I[n-m]\right.$$

$$\left.+jc_l^R[n]\cdot c_k^I[n-m]-jc_l^I[n]\cdot c_k^R[n-m]\right\} \tag{2}$$

$$=\Gamma_{lk}^{RR}[m]+\Gamma_{lk}^{II}[m]+j\left\{\Gamma_{lk}^{RI}[m]-\Gamma_{lk}^{IR}[m]\right\}$$

where

$$\Gamma_{lk}^{RR}[m]\equiv\frac{1}{2N_l}\sum_n c_l^R[n]\cdot c_k^R[n-m]$$

$$\Gamma_{lk}^{II}[m]\equiv\frac{1}{2N_l}\sum_n c_l^I[n]\cdot c_k^I[n-m]$$

$$\Gamma_{lk}^{RI}[m]\equiv\frac{1}{2N_l}\sum_n c_l^R[n]\cdot c_k^I[n-m] \tag{3}$$

$$\Gamma_{lk}^{IR}[m]\equiv\frac{1}{2N_l}\sum_n c_l^I[n]\cdot c_k^R[n-m]$$

Consider any one of the above real correlations, denoted

$$\Gamma_{lk}^{XY}[m]\equiv\frac{1}{2N_l}\sum_n c_l^X[n]\cdot c_k^Y[n-m] \tag{4}$$

where X and Y can be either R or I. Since the elements of the codes are now constrained to be ± 1 or 0, we can define

$$c_l^X[n]=\left(1-2\gamma_l^X[n]\right)\cdot m_l^X[n] \tag{5}$$

where $\gamma_l^X[n]$ and $m_l^X[n]$ are both either zero or one. The sequence $m_l^X[n]$ is a mask used to account for values of $c_l^X[n]$ that are zero. With these definitions Equation (4) becomes

$$\Gamma_{lk}^{XY}[m] \equiv \frac{1}{2N_I} \sum_n \left(1 - 2\gamma_l^X[n]\right) \cdot m_l^X[n] \cdot \left(1 - 2\gamma_k^Y[n-m]\right) \cdot m_k^Y[n-m]$$

$$= \frac{1}{2N_I} \sum_n \left(1 - 2\gamma_l^X[n]\right) \cdot \left(1 - 2\gamma_k^Y[n-m]\right) \cdot m_l^X[n] \cdot m_k^Y[n-m]$$

$$= \frac{1}{2N_I} \sum_n \left[1 - 2\left(\gamma_l^X[n] \oplus \gamma_k^Y[n-m]\right)\right] \cdot m_l^X[n] \cdot m_k^Y[n-m]$$

$$= \frac{1}{2N_I} \left\{ \sum_n \cdot m_l^X[n] \cdot m_k^Y[n-m] \right.$$

$$\left. - 2\sum_n \left(\gamma_l^X[n] \oplus \gamma_k^Y[n-m]\right) \cdot m_l^X[n] \cdot m_k^Y[n-m] \right\} \qquad (6)$$

$$= \frac{1}{2N_I} \left\{ M_{lk}^{XY}[m] - 2N_{lk}^{XY}[m] \right\}$$

$$M_{lk}^{XY}[m] \equiv \sum_n \cdot m_l^X[n] \cdot m_k^Y[n-m]$$

$$N_{lk}^{XY}[m] \equiv \sum_n \left(\gamma_l^X[n] \oplus \gamma_k^Y[n-m]\right) \cdot m_l^X[n] \cdot m_k^Y[n-m]$$

where $\oplus$ indicates modulo-2 addition (or logical XOR).

The hardware to perform these operations is shown in Figures 1 – 3. Figure 1 shows the initial register configuration after loading code and mask sequences. The boolean functions are shown in Figure 2, and Figure 3 shows the register configuration after a number of shifts.

Figure 1. Initial register configuration after loading code and mask sequences.

Figure 2. Boolean functions.

Figure 3. Register configuration after a number of shifts.

The above hardware calculates the functions $M_{lk}^{XY}[m]$ and $N_{lk}^{XY}[m]$. The remaining calculations to form $\Gamma_{lk}^{XY}[m]$ and subsequently $\Gamma_{lk}[m]$ can be performed in software. Note that the four functions $\Gamma_{lk}^{XY}[m]$ corrsponding to $X, Y = R, I$ which are components of $\Gamma_{lk}[m]$ can be calculated in parallel. For $K_v = 200$ virtual users, and assuming that 10% of all (l, k) pairs must be calculated in 2 ms, then for real-time operation we must calculate $0.10(200)^2 = 4000\ \Gamma_{lk}[m]$ elements (all shifts) in 2 ms, or about 2M elements (all shifts) per second. For $K_v = 128$ virtual users the requirement drops to 0.8192M elements (all shifts) per second.

In what has been presented the $\Gamma_{lk}[m]$ elements are calculated for all 512 shifts. Not all of these shifts are needed, so it is possible to reduce the number of calculations per $\Gamma_{lk}[m]$ elements. The cost is increased design complexity.

Mask k
Code k

Load zeros in from left

Shift mask & code right
1 chip at a time

Perform a total of 512 shifts,
shifting mask k and code k
out of registers at right.

Mask l
code l

Sum

Output

Mask k
Code k

Load mask & code for
user k here (256 chips)

Mask l
Code l

Load mask & code for
user l here (256 chips)

Sum

Initialize with
all zeros

Boolean operations

Output

Mask 1
Code 1

Mask k
Code k

To summing
function

This line shifts with
the code

code l

Code k

Cyclicly shift code right
1 chip at a time

Perform a total of 256 shifts,
cyclicly shifting code k

Sum

Output

Sum

Output

Boolean XOR operations

Two ouiputs representing code correlation at offsets separated by 256 chips are produced
every clock cycle. This idea can be extended to handle virtual-user code correlations, in
which case many outputs are produced every clock cycle.

Hardware vs. Software Calculation of G-matrix Elements

- Calculation of G-matrix elements
  - Requires performing XOR, bit-sum, bit-masking and bit-shifting operations on 256-bit registers
  - Approximately one million elements must be calculated every second

- Problems with using the AltiVec
  - The AltiVec solution is approximately 40 times slower than the FPGA solution because:
    - The AltiVec does not have a bit-sum instruction
    - Two 128-bit AltiVec registers are required to represent a 256 bit register
  - The PPC/AltiVec processor draws from 8 to 10 Watts

- Advantages of an FPGA implementation
  - XOR, bit-sum, bit-masking and bit-shifting operations are ideally suited for FPGA implementation
  - The G-matrix calculations are fundamental to MUD operation and will be identical for any variations in MUD algorithm
  - The FPGA implementation will run real-time with a single FPGA
  - The FPGA draws only 2 to 3 Watts
  - The slower FPGA clock speed can be counterbalanced by implementing multiple calculation functions in parallel

Makefile

```
#
.SUFFIXES: .a .c .mac .o .S

ARCH = ppc7400
MUDLIB = mudlib.a

###CFLAGS = -Ot -t ${ARCH} -I. -DCOMPILE_C
CFLAGS = -Ot -t ${ARCH} -I.
ASFLAGS = -t ${ARCH} -DBUILD_MAX -I.


#
# Make object files
#
.c.o:
        ccmc ${CFLAGS} -o $*.o -c $*.c


#
#       Make ASM
#
.mac.o:
        rm -f $*.S
        cp $*.mac $*.S
        ccmc ${ASFLAGS} -o $*.o -c $*.S
        rm -f $*.S

OBJS = \
        get sizes.o \
        get sizes v.o \
        reformat corr.o \
        rmats.o \
        reformat_r.o \
        mpic.o \
        gen x row.o \
        gen r sums.o \
        gen r sums2.o \
        gen r matrices.o \
        mtrans32 8bit.o \
        mtriangle 8bit.o \
        dotpr3 8bit.o \
        dotpr6 8bit.o \
        dotpr9 8bit.o \
        sve3 8bit.o \
        fixed cdotpr.o \
        zdotpr4 vmx.o \
        zdotpr_vmx.o

${MUDLIB}: Makefile ${OBJS}
        armc -c $@ ${OBJS}


#
# Cleanup
#
clean:
        rm -f ${OBJS} *.S ${MUDLIB}

get sizes.o: mudlib.h get_sizes.c
reformat_corr.o: mudlib.h reformat_corr.c
rmats.o: mudlib.h rmats.c \
                gen x row.mac gen r_sums.mac gen_r_sums2.mac
                gen r matrices.mac
reformat r.o: mudlib.h reformat_r.c
mpic.o: mudlib.h mpic.c \
                dotpr3 8bit.mac dotpr6_8bit.mac dotpr9_8bit.mac
                sve3_8bit.mac

dotpr3 8bit.o: dotpr3 8bit.mac salppc.inc
dotpr6_8bit.o: dotpr6_8bit.mac salppc.inc
```

1

Makefile

```
dotpr9 8bit.o: dotpr9 8bit.mac salppc.inc
sve3 8bit.o: sve3 8bit.mac salppc.inc
fixed cdotpr.o: zdotpr4 vmx.mac salppc.inc
zdotpr4_vmx.o: zdotpr4_vmx.mac zdotpr4_vmx.k salppc.inc
```

2

```
#include "mudlib.h"

#define   DO CALC STATS   0
#define   DO TRUNCATE   1
#define   DO SATURATE   1
#define   DO_SQUELCH   0

#define   SQUELCH THRESH   1.0
#define   TRUNCATE_BIAS   0.0

#if DO TRUNCATE
#define SATURATE_THRESH   (128.0 + TRUNCATE_BIAS)
#else
#define SATURATE_THRESH   127.5
#endif

#define SATURATE( f ) \
   { \
     if ( (f) >= SATURATE THRESH ) f = (SATURATE THRESH - 1.0); \
     else if ( (f) < -SATURATE_THRESH ) f = -SATURATE_THRESH; \
   }

#if DO_TRUNCATE
#if 0
#define   BF8_FIX( f )   ((BF8) (FABS(f) <= TRUNCATE BIAS) ? 0 : \
                          (((f) > 0.0) ? ((f) - TRUNCATE BIAS) : \
                                      ((f) + TRUNCATE_BIAS)))
#define   BF8_FIX( f )   ((BF8)(f))
#else
#define   BF8_FIX( f )   ((BF8)(((((f) < 0.0)) && ((f) == (float)((int)(f)))) ? \
                          ((f) + 1.0) : (f)))
#endif

#else
#define   BF8_FIX( f )   ((BF8)(((f) >= 0.0) ? ((f)+0.5) : ((f)-0.5)))
#endif

#define   UPDATE MAX( f, max ) \
   if ( FABS( f ) > max ) max = FABS( f );

#define uchar   unsigned char
#define ushort   unsigned short
#define ulong   unsigned long

#if DO_CALC STATS
static float   max_R_value;
#endif

void   gen X row (
         COMPLEX BF16   *mpath1 bf,
         COMPLEX BF16   *mpath2_bf,
         COMPLEX BF16   *X_bf,
         int   phys index,
         int   tot_phys_users
      );

void   gen R sums (
         COMPLEX BF16   *X bf,
         COMPLEX BF8   *corr_bf,
         uchar   *ptov map,
         BF32   *R sums,
         int   num_phys_users
      );

void   gen_R_sums2 (
```

1

```
        COMPLEX BF16   *X bf,
        COMPLEX BF8    *corra bf,
        COMPLEX BF8    *corrb_bf,
        uchar   *ptov map,
        BF32    *R sumsa,
        BF32    *R sumsb,
        int   num_phys_users
    );

void  gen R matrices (
        BF32    *R sums,
        float   *bf scalep,
        float   *inv scalep,
        float   *scalep,
        BF8     *no scale row bf,
        BF8     *scale row bf,
        int   num_virt_users
    );

void  mudlib gen R (
        COMPLEX BF16   *mpath1 bf,
        COMPLEX BF16   *mpath2 bf,
        COMPLEX BF8    *corr 0 bf,    /* adjusted for starting physical user */
        COMPLEX BF8    *corr_1_bf,    /* adjusted for starting physical user */
        uchar   *ptov map,           /* no more than 256 virts. per phys */
        float   *bf scalep,          /* scalar: always a power of 2 */
        float   *inv scalep,         /* start at 0'th physical user */
        float   *scalep,             /* start at 0'th physical user */
        char    *L1 cachep,          /* temp: 32K bytes, 32-byte aligned */
        BF8     *R0 upper bf,
        BF8     *R0 lower bf,
        BF8     *R1 trans_bf,
        BF8     *R1m bf,
        int   tot phys users,
        int   tot virt users,
        int   start phys user,       /* zero-based starting row (inclusive) */
        int   start virt user,       /* relative to start phys user */
        int   end phys user,         /* zero-based ending row (inclusive) */
        int   end_virt_user          /* relative to end_phys_user */
    )
{
  COMPLEX BF16   *X bf;
  BF32   *R sums0, *R sums1;
  uchar  *R0_ptov_map;

  int  bump, byte offset, i, iv, last virt user;
  int  R0_align, R0_skipped_virt_users, R0_tcols, R0_virt_users, R1_tcols;

#if DO CALC STATS
  max R_value = 0.0;
#endif

  X_bf = (COMPLEX_BF16 *)L1_cachep;

  byte offset = tot phys users * NUM FINGERS SQUARED * sizeof(COMPLEX BF16);
  R_sums0 = (BF32 *)(((ulong)X bf + byte_offset + R_MATRIX_ALIGN_MASK) &
          ~R_MATRIX_ALIGN_MASK);

  byte offset = tot virt users * sizeof(BF32);
  R_sums1 = (BF32 *)(((ulong)R sums0 + byte_offset + R_MATRIX_ALIGN_MASK) &
          ~R_MATRIX_ALIGN_MASK);

  R0_ptov_map = (uchar *)(((ulong)R sums1 + byte offset +
                R_MATRIX_ALIGN_MASK) & ~R_MATRIX_ALIGN_MASK);

  R1_tcols = (tot_virt_users + R_MATRIX_ALIGN_MASK) & ~R_MATRIX_ALIGN_MASK;
```

2

rmats.c

```
RO virt_users = 0;
for ( i = start_phys user; i < tot phys_users; i++ ) {
  RO virt users += (int)ptov map[i];
  RO_ptov_map[i] = ptov_map[i];
}

RO ptov map[start phys user] -= start virt user;
RO skipped virt users = tot virt users - RO_virt_users + start_virt_user;
RO_virt_users -= (start_virt_user + 1);

--inv_scalep;              /* predecrement to allow for common indexing */

for ( i = start_phys_user; i <= end_phys_user; i++ ) {

  gen X row (
    mpath1 bf,
    mpath2_bf,
    X bf,
    i,
    tot_phys_users
  );

  --RO_ptov_map[i];                      /* excludes RO diagonal */

  last_virt_user = (i < end_phys_user) ? ((int)ptov map[i] - 1) :
                                          end_virt_user;

  for ( iv = start_virt_user; (iv + 1) <= last_virt_user; iv += 2 ) {

    gen R sums2 (
      X bf + (i * NUM_FINGERS_SQUARED),
      corr 0 bf,
      corr 0 bf + ((RO_virt_users - 1) * NUM_FINGERS_SQUARED),
      RO ptov_map + i,
      R sums0 + (RO skipped virt users + 1),
      R sums1 + (RO skipped_virt_users + 1),
      tot_phys_users - i
    );

    RO tcols = R1 tcols - (RO skipped_virt users & ~R MATRIX_ALIGN_MASK);
    RO_align = (RO_skipped_virt_users & R_MATRIX_ALIGN_MASK) + 1;

    gen R matrices (
      R sums0 + (RO_skipped_virt_users + 1),
      bf scalep,
      inv scalep + (RO skipped virt users + 1),
      scalep + (RO skipped virt_users + 1),
      RO lower bf + RO align,
      RO upper bf + RO_align,
      RO_virt_users
    );

    RO_upper_bf[ RO_align - 1 ] = 0;   /* zero diagonal element */

    RO lower bf += RO tcols;
    RO_upper_bf += RO_tcols;

    RO_tcols = R1_tcols - ((RO skipped virt users + 1) &
                    ~R MATRIX ALIGN MASK);
    RO_align = ((RO_skipped_virt_users + 1) & R_MATRIX_ALIGN_MASK) + 1;

    gen R matrices (
      R sums1 + (RO_skipped_virt_users + 2),
      bf scalep,
      inv scalep + (RO skipped virt users + 2),
      scalep + (RO skipped virt_users + 2),
      RO_lower_bf + RO_align,
```

3

```
        R0 upper bf + R0 align,
        R0_virt_users - 1
    );

    R0_upper_bf[ R0_align - 1 ] = 0;   /* zero diagonal element */

    R0 lower bf += R0 tcols;
    R0_upper_bf += R0_tcols;

    /*
     *  create ptov map[i] number of 32-element dot products involving
     *  X_bf[i] and corr_1_bf[i][j] where 0 < j < ptov_map[i]
     */
    gen R sums2 (
        X bf,
        corr 1 bf,
        corr 1 bf + (tot_virt_users * NUM_FINGERS_SQUARED),
        ptov map,
        R sums0,
        R sums1,
        tot_phys_users
    );

    /*
     *  scale the results and create two output rows (1 per matrix)
     */
    gen R matrices (
        R sums0,
        bf scalep,
        inv scalep + (R0_skipped_virt_users + 1),
        scalep,
        R1 trans_bf,
        R1m bf,
        tot_virt_users
    );

    R1 trans bf += R1 tcols;
    R1m_bf += R1_tcols;

    gen R matrices (
        R sums1,
        bf scalep,
        inv scalep + (R0_skipped_virt_users + 2),          (
        scalep,
        R1 trans_bf,
        R1m bf,
        tot_virt_users
    );

    R1 trans bf += R1 tcols;
    R1m_bf += R1_tcols;

    corr 0 bf += (((2 * R0 virt users) - 1) * NUM FINGERS SQUARED);
    corr 1 bf += ((2 * tot_virt_users) * NUM_FINGERS_SQUARED);
    R0 ptov map[i] -= 2;
    R0 virt users -= 2;
    R0_skipped_virt_users += 2;
}

if ( iv <= last_virt_user ) {

    bump = R0 ptov_map[ i ] ? 0 : 1;
    gen R sums (
        X bf + ((i + bump) * NUM_FINGERS_SQUARED),
        corr 0 bf,
        R0 ptov_map + i + bump,
        R_sums0 + (R0_skipped_virt_users + 1),
```

4

```
        tot_phys_users - i - bump
    );

    R0_tcols = R1_tcols - (R0_skipped_virt_users & ~R_MATRIX_ALIGN_MASK);
    R0_align = (R0_skipped_virt_users & R_MATRIX_ALIGN_MASK) + 1;

    gen_R_matrices (
      R_sums0 + (R0_skipped_virt_users + 1),
      bf_scalep,
      inv_scalep + (R0_skipped_virt_users + 1),
      scalep + (R0_skipped_virt_users + 1),
      R0_lower_bf + R0_align,
      R0_upper_bf + R0_align,
      R0_virt_users
    );

    R0_upper_bf[ R0_align - 1 ] = 0;  /* zero diagonal element */

    R0_lower_bf += R0_tcols;
    R0_upper_bf += R0_tcols;

    /*
     *  create ptov_map[i] number of 32-element dot products involving
     *  X_bf[i] and corr_1_bf[i][j] where 0 < j < ptov_map[i]
     */
    gen_R_sums (
      X_bf,
      corr_1_bf,
      ptov_map,
      R_sums0,
      tot_phys_users
    );

    /*
     *  scale the results and create two output rows (1 per matrix)
     */
    gen_R_matrices (
      R_sums0,
      bf_scalep,
      inv_scalep + (R0_skipped_virt_users + 1),
      scalep,
      R1_trans_bf,
      R1m_bf,
      tot_virt_users
    );

    R1_trans_bf += R1_tcols;
    R1m_bf += R1_tcols;

    corr_0_bf += (R0_virt_users * NUM_FINGERS_SQUARED);
    corr_1_bf += (tot_virt_users * NUM_FINGERS_SQUARED);
    R0_ptov_map[i] -= 1;
    R0_virt_users -= 1;
    R0_skipped_virt_users += 1;
  }
  start_virt_user = 0;                    /* for all subsequent passes */
}

#if DO_CALC_STATS
  printf( "max R value = %f\n", max_R_value );
  if ( max_R_value > 127.0 )
    printf ( "***** OVERFLOW *****\n" );
#endif
}

#if COMPILE_C
```

5

```
void  gen X row (
      COMPLEX BF16   *mpath1 bf,
      COMPLEX BF16   *mpath2_bf,
      COMPLEX BF16   *X_bf,
      int   phys index,
      int   tot_phys_users
    )

{
  COMPLEX BF16   *in mpath1p, *in mpath2p;
  COMPLEX_BF16   *out_mpath1p, *out_mpath2p;
  int   i, j, q, q1;
  BF32   s1r, s1i, s2r, s2i;
  BF32   a1r, a1i, a2r, a2i;
  BF32   cr, ci;

  out mpath1p = mpath1 bf + (phys index * NUM FINGERS);
  out_mpath2p = mpath2_bf + (phys_index * NUM_FINGERS);

  for ( i = 0; i < tot_phys_users; i++ ) {

    in mpath1p = mpath1 bf + (i * NUM FINGERS);   /* 4 complex values */
    in_mpath2p = mpath2_bf + (i * NUM_FINGERS);   /* 4 complex values */

    j = 0;
    for ( q1 = 0; q1 < NUM_FINGERS; q1++ ) {

      s1r = (BF32)out mpath1p[q1].real;
      s1i = (BF32)out mpath1p[q1].imag;
      s2r = (BF32)out mpath2p[q1].real;
      s2i = (BF32)out_mpath2p[q1].imag;

      for ( q = 0; q < NUM_FINGERS; q++ ) {

        a1r = (BF32)in mpath1p[q].real;
        a1i = (BF32)in mpath1p[q].imag;
        a2r = (BF32)in mpath2p[q].real;
        a2i = (BF32)in_mpath2p[q].imag;

        cr = (a1r * s1r) + (a1i * s1i);
        ci = (a1r * s1i) - (a1i * s1r);
        cr += (a2r * s2r) + (a2i * s2i);
        ci += (a2r * s2i) - (a2i * s2r);

        X bf[i * NUM FINGERS SQUARED + j].real = (BF16)(cr >> 16);
        X bf[i * NUM FINGERS_SQUARED + j].imag = (BF16)(ci >> 16);
        ++j;
      }
    }
  }
}

void  gen R sums (
      COMPLEX BF16   *X bf,
      COMPLEX BF8    *corr_bf,
      uchar   *ptov map,
      BF32   *R sums,
      int   num_phys_users
    )

{
  int   i, j, k;
  BF32   sum;

  for ( i = 0; i < num phys users; i++ ) {
    for ( j = 0; j < (int)ptov_map[i]; j++ ) {
      sum = 0;
```

6

```
        for ( k = 0; k < 16; k++ ) {
           sum += (BF32)X_bf[k].real * (BF32)corr_bf->real;
           sum += (BF32)X_bf[k].imag * (BF32)corr_bf->imag;
           ++corr_bf;
        }
        *R_sums++ = sum;
     }
     X_bf += NUM_FINGERS_SQUARED;
  }
}

void  gen_R_sums2 (
        COMPLEX BF16   *X_bf,
        COMPLEX BF8    *corra_bf,
        COMPLEX BF8    *corrb_bf,
        uchar   *ptov_map,
        BF32    *R_sumsa,
        BF32    *R_sumsb,
        int   num_phys_users
     )

{
  int   i, j, k;
  BF32   suma, sumb;

  for ( i = 0; i < num_phys_users; i++ ) {
     for ( j = 0; j < (int)ptov_map[i]; j++ ) {
        suma = 0;
        sumb = 0;
        for ( k = 0; k < 16; k++ ) {
           suma += (BF32)X_bf[k].real * (BF32)corra_bf->real;
           suma += (BF32)X_bf[k].imag * (BF32)corra_bf->imag;
           sumb += (BF32)X_bf[k].real * (BF32)corrb_bf->real;
           sumb += (BF32)X_bf[k].imag * (BF32)corrb_bf->imag;
           ++corra_bf;
           ++corrb_bf;
        }
        *R_sumsa++ = suma;
        *R_sumsb++ = sumb;
     }
     X_bf += NUM_FINGERS_SQUARED;
  }
}

void  gen_R_matrices (
        BF32   *R_sums,
        float  *bf_scalep,
        float  *inv_scalep,
        float  *scalep,
        BF8   *no_scale_row_bf,
        BF8   *scale_row_bf,
        int   num_virt_users
     )

{
  int   i;
  float  bf_scale, fsum, fsum_scale, inv_scale, scale;

  bf_scale = *bf_scalep;
  inv_scale = *inv_scalep;

  for ( i = 0; i < num_virt_users; i++ ) {
     scale = scalep[i];
     fsum = (float)(R_sums[i]);
     fsum *= bf_scale;

     fsum_scale = fsum * inv_scale;
```

7

rmats.c   2/23/2001

```
        fsum_scale *= scale;

#if DO_CALC_STATS
        UPDATE_MAX( fsum_scale, max_R_value )
        UPDATE_MAX( fsum, max_R_value )
#endif

#if DO_SQUELCH
        if ( FABS( fsum_scale ) <= SQUELCH_THRESH ) fsum_scale = 0.0;
        if ( FABS( fsum ) <= SQUELCH_THRESH ) fsum = 0.0;
#endif

#if DO_SATURATE
        SATURATE( fsum_scale )
        SATURATE( fsum )
#endif

        no_scale_row_bf[i] = BF8_FIX( fsum );
        scale_row_bf[i] = BF8_FIX( fsum_scale );
    }
}

#endif                                  /* COMPILE_C */
```

8

```
/*-----------------------------------------------------------+
|--- MC Standard Algorithms -- PPC Macro language Version   ---|
|-------------------------------------------------------------|
|                                                             |
|  File Name:    dotpr3_8bit.mac                              |
|  Description:  Source code for routine which computes three |
|                dot products, combining the three sums prior |
|                to exit.                                      |
|                                                             |
|                Mercury Computer Systems, Inc.               |
|                Copyright (c) 2000  All rights reserved      |
|                                                             |
|  Revision      Date     Engineer  Reason                    |
|  --------      ----     --------  --------                   |
|     0.0        000510     fpl     Created                    |
|     0.1        000521     fpl     Added num cached_rows       |
|     0.2        000521     fpl     Changed to fixed_point      |
|     0.3        000605     fpl     Changed to .k file          |
|     0.4        000926      jg     Back to .mac and no dsts   |
+-------------------------------------------------------------*/

#include "salppc.inc"

#define LVX_BT( vT, rA, rB )            LVX( vT, rA, rB )

#define FUNC_ENTRY                      dotpr3_8bit
#define VMSUM( vT, vA, vB, vC )         VMSUMMBM( vT, vA, vB, vC )
#define LOOP_COUNT_SHIFT 6
#define HALF_BLOCK_BIT 0x20
#define QUARTER_BLOCK_BIT 0x10

#define LOOP_BLOCK_SIZE 64

/**
 Input parameters
**/
#define bt1mptr r3
#define r1ptr    r4
#define r0ptr    r5
#define r1mptr   r6
#define C         r7
#define N         r8
#define hat_tc    r9
/**
 Local loop registers
**/
#define bt0ptr r10
#define bt1ptr r11
#define index1 r12
#define index2 r13

#define index3 r0
#define icount hat_tc

/**
 G4 registers
**/
#define rq10 v0
#define rq11 v1
#define rq12 v2
#define rq13 v3
#define zero v3

#define rq00 v4
#define rq01 v5
#define rq02 v6
```

1

dotpr3_8bit.mac   2/23/2001

```
#define rq03 v7

#define rq1m0 v8
#define rq1m1 v9
#define rq1m2 v10
#define rq1m3 v11

#define bt1m0 v12
#define bt1m1 v13
#define bt1m2 v14
#define bt1m3 v15

#define bt10 v16
#define bt11 v17
#define bt12 v18
#define bt13 v19

#define bt00 v20
#define bt01 v21
#define bt02 v22
#define bt03 v23

#define sum0 v24
#define sum1 v25
#define sum2 v26
#define sum3 v27

/**
 Begin code text
 Setup loop registers, test for zero N
**/
FUNC PROLOG
ENTRY 7( FUNC_ENTRY, bt1mptr, r1ptr, r0ptr, r1mptr, C, N, hat_tc )
  SAVE r13
  USE_THRU_v27( VRSAVE_COND )
/**
 Load up local loop registers
**/
   ADD(bt0ptr, bt1mptr, hat_tc)
   VXOR(sum0, sum0, sum0)
   ADD(bt1ptr, bt0ptr, hat_tc)

   LI(index1, 16)
   VXOR(sum1, sum1, sum1)
   LI(index2, 32)
   VXOR(sum2, sum2, sum2)
   LI(index3, 48)
   VXOR(sum3, sum3, sum3)
   SRWI C(icount, N, LOOP_COUNT_SHIFT) /* 32 sum updates per loop trip */
   BEQ(do_half_block)
/**
 Loop entry code
**/
   LVX( rq10, 0, r1ptr )
   LVX( rq11, r1ptr, index1 )
   LVX( rq12, r1ptr, index2 )
   LVX( rq13, r1ptr, index3 )
   DECR_C(icount)

   LVX BT( bt1m0, 0, bt1mptr )
   LVX BT( bt1m1, bt1mptr, index1 )
   ADDI(r1ptr, r1ptr, LOOP_BLOCK_SIZE)
   LVX BT( bt1m2, bt1mptr, index2 )
   LVX BT( bt1m3, bt1mptr, index3 )
   ADDI(bt1mptr, bt1mptr, LOOP_BLOCK_SIZE)
   BR( mid_loop )
/**
```

2

```
 Loop computes three dot products held in 16 parts
**/
LABEL( loop )
/* { */
    LVX( rq10, 0, r1ptr )
    VMSUM( sum0, rq1m0, bt10, sum0 )
    LVX( rq11, r1ptr, index1 )
    VMSUM( sum1, rq1m1, bt11, sum1 )
    LVX( rq12, r1ptr, index2 )
    VMSUM( sum2, rq1m2, bt12, sum2 )
    LVX( rq13, r1ptr, index3 )
    DECR_C(icount)

    LVX BT( bt1m0, 0, bt1mptr )
    VMSUM( sum3, rq1m3, bt13, sum3 )
    LVX BT( bt1m1, bt1mptr, index1 )
    ADDI(r1ptr, r1ptr, LOOP_BLOCK SIZE)
    LVX BT( bt1m2, bt1mptr, index2 )
    LVX BT( bt1m3, bt1mptr, index3 )
    ADDI(bt1mptr, bt1mptr, LOOP_BLOCK_SIZE)

LABEL( mid_loop )

    LVX( rq00, 0, r0ptr )
    VMSUM( sum0, rq10, bt1m0, sum0 )
    LVX( rq01, r0ptr, index1 )
    VMSUM( sum1, rq11, bt1m1, sum1 )
    LVX( rq02, r0ptr, index2 )
    VMSUM( sum2, rq12, bt1m2, sum2 )
    LVX( rq03, r0ptr, index3 )

    LVX BT( bt00, 0, bt0ptr )
    VMSUM( sum3, rq13, bt1m3, sum3 )
    LVX BT( bt01, bt0ptr, index1 )
    ADDI(r0ptr, r0ptr, LOOP BLOCK SIZE)
    LVX BT( bt02, bt0ptr, index2 )
    LVX BT( bt03, bt0ptr, index3 )
    ADDI(bt0ptr, bt0ptr, LOOP_BLOCK_SIZE)

    LVX( rq1m0, 0, r1mptr )
    VMSUM( sum0, rq00, bt00, sum0 )
    LVX( rq1m1, r1mptr, index1 )
    VMSUM( sum1, rq01, bt01, sum1 )
    LVX( rq1m2, r1mptr, index2 )
    VMSUM( sum2, rq02, bt02, sum2 )
    LVX( rq1m3, r1mptr, index3 )

    LVX BT( bt10, 0, bt1ptr )
    VMSUM( sum3, rq03, bt03, sum3 )
    LVX BT( bt11, bt1ptr, index1 )
    ADDI(r1mptr, r1mptr, LOOP BLOCK_SIZE)
    LVX BT( bt12, bt1ptr, index2 )
    LVX BT( bt13, bt1ptr, index3 )
    ADDI(bt1ptr, bt1ptr, LOOP_BLOCK_SIZE)
/* } */
  BNE( loop )
/**
 Loop exit code
**/
    VMSUM( sum0, rq1m0, bt10, sum0 )
    VMSUM( sum1, rq1m1, bt11, sum1 )
    VMSUM( sum2, rq1m2, bt12, sum2 )
    VMSUM( sum3, rq1m3, bt13, sum3 )
/**
 Remainders
**/
LABEL(do_half_block)
```

3

```
     dotpr3_8bit.mac

     ANDI C( icount, N, HALF_BLOCK_BIT )
     BEQ(do quarter block)
     LVX( rq10, 0, r1ptr )
     LVX( rq11, r1ptr, index1 )
     LVX BT( bt1m0, 0, bt1mptr )
     LVX BT( bt1m1, bt1mptr, index1 )
     ADDI(r1ptr, r1ptr, (LOOP BLOCK SIZE >> 1) )
     ADDI(bt1mptr, bt1mptr, (LOOP_BLOCK_SIZE >> 1) )

     VMSUM( sum0, rq10, bt1m0, sum0 )
     VMSUM( sum1, rq11, bt1m1, sum1 )

     LVX( rq00, 0, r0ptr )
     LVX( rq01, r0ptr, index1 )
     LVX BT( bt00, 0, bt0ptr )
     LVX BT( bt01, bt0ptr, index1 )
     ADDI(r0ptr, r0ptr, (LOOP BLOCK SIZE >> 1) )
     ADDI(bt0ptr, bt0ptr, (LOOP_BLOCK_SIZE >> 1) )

     VMSUM( sum0, rq00, bt00, sum0 )
     VMSUM( sum1, rq01, bt01, sum1 )

     LVX( rq1m0, 0, r1mptr )
     LVX( rq1m1, r1mptr, index1 )
     LVX BT( bt10, 0, bt1ptr )
     LVX BT( bt11, bt1ptr, index1 )
     ADDI(r1mptr, r1mptr, (LOOP BLOCK SIZE >> 1) )
     ADDI(bt1ptr, bt1ptr, (LOOP_BLOCK_SIZE >> 1) )

     VMSUM( sum0, rq1m0, bt10, sum0 )
     VMSUM( sum1, rq1m1, bt11, sum1 )

LABEL(do quarter block)
     ANDI C( icount, N, QUARTER_BLOCK_BIT )
     BEQ(combine)
     LVX( rq10, 0, r1ptr )
     LVX BT( bt1m0, 0, bt1mptr )
     VMSUM( sum0, rq10, bt1m0, sum0 )

     LVX( rq00, 0, r0ptr )
     LVX BT( bt00, 0, bt0ptr )
     VMSUM( sum0, rq00, bt00, sum0 )

     LVX( rq1m0, 0, r1mptr )
     LVX BT( bt10, 0, bt1ptr )
     VMSUM( sum0, rq1m0, bt10, sum0 )
/**
 Combine sums and return
**/
LABEL(combine)
     VXOR( zero, zero, zero )
     VADDSWS( sum0, sum0, sum1 )    /* s00 s01 s02 s03 */
     VADDSWS( sum2, sum2, sum3 )    /* s22 s21 s22 s23 */
     VADDSWS( sum0, sum0, sum2 )    /* s00 s01 s02 s03 */
     VSUMSWS( sum0, sum0, zero )    /* xxx xxx xxx s00 */
     VSPLTW( sum0, sum0, 3 )        /* s00 s00 s00 s00 */
     STVEWX( sum0, 0, C )
/**
 Return
**/
LABEL( ret )
   FREE THRU_v27( VRSAVE_COND )
   REST r13
   RETURN
FUNC_EPILOG
```

4

```
/*-----------------------------------------------------------------+
|--- MC Standard Algorithms -- PPC Macro language Version   ---|
|-----------------------------------------------------------------|
|                                                                 |
|  File Name:    dotpr6_8bit.mac                                  |
|  Description:  Source code for routine which computes six       |
|                dot products, combining the six sums prior       |
|                into two outputs prior to exit.                  |
|                                                                 |
|              Mercury Computer Systems, Inc.                     |
|              Copyright (c) 2000  All rights reserved            |
|                                                                 |
|  Revision      Date     Engineer  Reason                        |
|  --------      ----     --------  --------                      |
|    0.0        000510      fpl     Created                       |
|    0.1        000521      fpl     Changed to fixed point        |
|    0.2        000521      fpl     Added num cached rows          |
|    0.3        000605      fpl     Changed to .k file            |
|    0.4        000926      jg      Back to .mac and no dsts       |
+-----------------------------------------------------------------*/

#include "salppc.inc"

#define LVX_BT( vT, rA, rB )           LVX( vT, rA, rB )

#define FUNC ENTRY                     dotpr6 8bit
#define VMSUM( vT, vA, vB, vC )        VMSUMMBM( vT, vA, vB, vC )
#define LOOP COUNT SHIFT 6
#define HALF BLOCK BIT 0x20
#define QUARTER_BLOCK_BIT 0x10

#define LOOP_BLOCK_SIZE 64

/**
 Input parameters
**/
#define bt1mptr r3
#define r1ptr   r4
#define r0ptr   r5
#define r1mptr  r6
#define C       r7
#define N       r8
#define hat_tc  r9
/**
 Local loop registers
**/
#define bt0ptr r10
#define bt1ptr r11
#define bt2ptr r12
#define index1 r13
#define index2 r14

#define index3 r0
#define icount hat_tc

/**
 G4 registers
**/
#define rq10 v0
#define rq11 v1
#define rq12 v2.
#define rq13 v3
#define zero v3

#define rq00 v4
#define rq01 v5
```

1

dotpr6_8bit.mac   3/9/2001

```
#define rq02 v6
#define rq03 v7

#define rq1m0 v8
#define rq1m1 v9
#define rq1m2 v10
#define rq1m3 v11

#define bt1m0 v12
#define bt1m1 v13
#define bt1m2 v14
#define bt1m3 v15

#define bt10 v12
#define bt11 v13
#define bt12 v14
#define bt13 v15

#define bt00 v16
#define bt01 v17
#define bt02 v18
#define bt03 v19

#define bt20 v16
#define bt21 v17
#define bt22 v18
#define bt23 v19

#define sum00 v20
#define sum01 v21
#define sum02 v22
#define sum03 v23

#define sum10 v24
#define sum11 v25
#define sum12 v26
#define sum13 v27
/**
 Begin code text
**/
FUNC PROLOG
ENTRY 7( FUNC ENTRY, bt1mptr, r1ptr, r0ptr, r1mptr, C, N, hat_tc )
   SAVE r13 r14
   USE_THRU_v27( VRSAVE_COND )
/**
 Load up local loop registers
**/
   ADD(bt0ptr, bt1mptr, hat tc)
   VXOR(sum00, sum00, sum00)
   ADD(bt1ptr, bt0ptr, hat_tc)
   LI(index1, 16)
   ADD(bt2ptr, bt1ptr, hat_tc)

   VXOR(sum01, sum01, sum01)
   LI(index2, 32)
   VXOR(sum02, sum02, sum02)
   LI(index3, 48)
   VXOR(sum03, sum03, sum03)

   VXOR(sum10, sum10, sum10)
   VXOR(sum11, sum11, sum11)
   VXOR(sum12, sum12, sum12)
   VXOR(sum13, sum13, sum13)
   SRWI C(icount, N, LOOP_COUNT_SHIFT)
   BEQ(do_half_block)
/**
 Loop entry code
```

2

```
              dotpr6_8bit.mac                                     3/9/2001
**/
    LVX BT( bt1m0, 0, bt1mptr )
    DECR C(icount)
    LVX BT( bt1m1, bt1mptr, index1 )
    LVX BT( bt1m2, bt1mptr, index2 )
    LVX_BT( bt1m3, bt1mptr, index3 )

    LVX( rq10, 0, r1ptr )
    LVX( rq11, r1ptr, index1 )
    ADDI(bt1mptr, bt1mptr,  LOOP_BLOCK_SIZE)
    LVX( rq12, r1ptr, index2 )
    LVX( rq13, r1ptr, index3 )
    BR( mid_loop )
/**
 Loop computes three dot products held in 16 parts
**/
LABEL( loop )
/* { */
    LVX BT( bt1m0, 0, bt1mptr )
    VMSUM( sum10, rq1m0, bt20, sum10 )
    LVX BT( bt1m1, bt1mptr, index1 )
    VMSUM( sum11, rq1m1, bt21, sum11 )
    LVX BT( bt1m2, bt1mptr, index2 )
    DECR C(icount)
    VMSUM( sum12, rq1m2, bt22, sum12 )
    LVX_BT( bt1m3, bt1mptr, index3 )

    LVX( rq10, 0, r1ptr )
    VMSUM( sum13, rq1m3, bt23, sum13 )
    LVX( rq11, r1ptr, index1 )
    LVX( rq12, r1ptr, index2 )
    ADDI(bt2ptr, bt2ptr,  LOOP_BLOCK_SIZE)
    LVX( rq13, r1ptr, index3 )
    ADDI(bt1mptr, bt1mptr,  LOOP_BLOCK_SIZE)

LABEL( mid_loop )

    LVX BT( bt00, 0, bt0ptr )
    VMSUM( sum00, rq10, bt1m0, sum00 )
    LVX BT( bt01, bt0ptr, index1 )
    VMSUM( sum01, rq11, bt1m1, sum01 )
    LVX BT( bt02, bt0ptr, index2 )
    VMSUM( sum02, rq12, bt1m2, sum02 )
    LVX BT( bt03, bt0ptr, index3 )
    ADDI(r1ptr, r1ptr,  LOOP_BLOCK_SIZE)

    LVX( rq00, 0, r0ptr )
    VMSUM( sum03, rq13, bt1m3, sum03 )
    LVX( rq01, r0ptr, index1 )
    VMSUM( sum10, rq10, bt00, sum10 )
    LVX( rq02, r0ptr, index2 )
    VMSUM( sum11, rq11, bt01, sum11 )
    ADDI(bt0ptr, bt0ptr,  LOOP BLOCK SIZE)
    VMSUM( sum12, rq12, bt02, sum12 )
    LVX( rq03, r0ptr, index3 )
    VMSUM( sum13, rq13, bt03, sum13 )

    LVX BT( bt10, 0, bt1ptr )
    VMSUM( sum00, rq00, bt00, sum00 )
    LVX BT( bt11, bt1ptr, index1 )
    ADDI(r0ptr, r0ptr,  LOOP BLOCK_SIZE)
    LVX BT( bt12, bt1ptr, index2 )
    VMSUM( sum01, rq01, bt01, sum01 )
    LVX BT( bt13, bt1ptr, index3 )
    VMSUM( sum02, rq02, bt02, sum02 )

    LVX( rq1m0, 0, r1mptr )
```

3

```
          dotpr6_8bit.mac
          VMSUM( sum03, rq03, bt03, sum03 )
          ADDI(bt1ptr, bt1ptr,  LOOP BLOCK SIZE)
          VMSUM( sum10, rq00, bt10, sum10 )
          LVX( rq1m1, r1mptr, index1 )
          VMSUM( sum11, rq01, bt11, sum11 )
          LVX( rq1m2, r1mptr, index2 )
          VMSUM( sum12, rq02, bt12, sum12 )
          LVX( rq1m3, r1mptr, index3 )
          ADDI(r1mptr, r1mptr,  LOOP_BLOCK_SIZE)

          LVX BT( bt20, 0, bt2ptr )
          VMSUM( sum13, rq03, bt13, sum13 )
          LVX BT( bt21, bt2ptr, index1 )
          VMSUM( sum00, rq1m0, bt10, sum00 )
          LVX BT( bt22, bt2ptr, index2 )
          VMSUM( sum01, rq1m1, bt11, sum01 )
          LVX BT( bt23, bt2ptr, index3 )
          VMSUM( sum02, rq1m2, bt12, sum02 )
          VMSUM( sum03, rq1m3, bt13, sum03 )
/* } */
   BNE( loop )
/**
 Loop exit code
**/
       VMSUM( sum10, rq1m0, bt20, sum10 )
       VMSUM( sum11, rq1m1, bt21, sum11 )
       ADDI(bt2ptr, bt2ptr,  LOOP_BLOCK_SIZE)
       VMSUM( sum12, rq1m2, bt22, sum12 )
       VMSUM( sum13, rq1m3, bt23, sum13 )
/**
 Remainders
**/
LABEL(do half block)
       ANDI C( icount, N, HALF_BLOCK_BIT )
       BEQ(do_quarter_block)

       LVX BT( bt1m0, 0, bt1mptr )
       LVX BT( bt1m1, bt1mptr, index1 )
       ADDI(bt1mptr, bt1mptr, (LOOP_BLOCK_SIZE >> 1) )

       LVX( rq10, 0, r1ptr )
       LVX( rq11, r1ptr, index1 )
       ADDI(r1ptr, r1ptr, (LOOP_BLOCK_SIZE >> 1) )

       VMSUM( sum00, rq10, bt1m0, sum00 )
       VMSUM( sum01, rq11, bt1m1, sum01 )

       LVX BT( bt00, 0, bt0ptr )
       LVX BT( bt01, bt0ptr, index1 )
       ADDI(bt0ptr, bt0ptr, (LOOP_BLOCK_SIZE >> 1) )

       VMSUM( sum10, rq10, bt00, sum10 )
       VMSUM( sum11, rq11, bt01, sum11 )

       LVX( rq00, 0, r0ptr )
       LVX( rq01, r0ptr, index1 )
       ADDI(r0ptr, r0ptr, (LOOP_BLOCK_SIZE >> 1) )

       VMSUM( sum00, rq00, bt00, sum00 )
       VMSUM( sum01, rq01, bt01, sum01 )

       LVX BT( bt10, 0, bt1ptr )
       LVX BT( bt11, bt1ptr, index1 )
       ADDI(bt1ptr, bt1ptr, (LOOP_BLOCK_SIZE >> 1) )

       VMSUM( sum10, rq00, bt10, sum10 )
       VMSUM( sum11, rq01, bt11, sum11 )
```

4

        dotpr6_8bit.mac

```
    LVX( rq1m0, 0, r1mptr )
    LVX( rq1m1, r1mptr, index1 )
    ADDI(r1mptr, r1mptr, (LOOP_BLOCK_SIZE >> 1) )

    VMSUM( sum00, rq1m0, bt10, sum00 )
    VMSUM( sum01, rq1m1, bt11, sum01 )

    LVX BT( bt20, 0, bt2ptr )
    LVX BT( bt21, bt2ptr, index1 )
    ADDI(bt2ptr, bt2ptr, (LOOP_BLOCK_SIZE >> 1) )

    VMSUM( sum10, rq1m0, bt20, sum10 )
    VMSUM( sum11, rq1m1, bt21, sum11 )

LABEL(do quarter block)
    ANDI C( icount, N, QUARTER_BLOCK_BIT )
    BEQ(combine)

    LVX BT( bt1m0, 0, bt1mptr )
    LVX( rq10, 0, r1ptr )
    VMSUM( sum00, rq10, bt1m0, sum00 )

    LVX BT( bt00, 0, bt0ptr )
    VMSUM( sum10, rq10, bt00, sum10 )
    LVX( rq00, 0, r0ptr )
    VMSUM( sum00, rq00, bt00, sum00 )

    LVX BT( bt10, 0, bt1ptr )
    VMSUM( sum10, rq00, bt10, sum10 )
    LVX( rq1m0, 0, r1mptr )
    VMSUM( sum00, rq1m0, bt10, sum00 )
    LVX BT( bt20, 0, bt2ptr )
    VMSUM( sum10, rq1m0, bt20, sum10 )
/**
 Combine sums and return
**/
LABEL(combine)
    VXOR( zero, zero, zero )
    VADDSWS( sum00, sum00, sum01 )    /* s00 s01 s02 s03 */
    VADDSWS( sum10, sum10, sum11 )
    VADDSWS( sum02, sum02, sum03 )    /* s22 s21 s22 s23 */
    VADDSWS( sum12, sum12, sum13 )
    VADDSWS( sum00, sum00, sum02 )    /* s00 s01 s02 s03 */
    VADDSWS( sum10, sum10, sum12 )

    VSUMSWS( sum00, sum00, zero )     /* xxx xxx xxx s00 */
    VSUMSWS( sum10, sum10, zero )
    VSPLTW( sum00, sum00, 3 )         /* s00 s00 s00 s00 */
    STVEWX( sum00, 0, C )
    ADDI( C, C, 4 )
    VSPLTW( sum10, sum10, 3 )
    STVEWX( sum10, 0, C )
/**
 Return
**/
LABEL( ret )
    FREE THRU v27( VRSAVE_COND )
    REST r13_r14
    RETURN
FUNC_EPILOG
```

                                5

```
/*-------------------------------------------------------------+
|--- MC Standard Algorithms -- PPC Macro language Version  ---|
|-------------------------------------------------------------|
|                                                             |
|   File Name:    dotpr9_8bit.mac                             |
|   Description:  Source code for routine which computes nine |
|                 dot products, combining the nine sums prior |
|                 into three outputs prior to exit.           |
|                                                             |
|            Mercury Computer Systems, Inc.                   |
|            Copyright (c) 2000  All rights reserved          |
|                                                             |
|   Revision      Date      Engineer  Reason                  |
|   --------      ----      --------  --------                |
|      0.0        000510      fpl     Created                 |
|      0.1        000512      fpl     Added num cached_rows    |
|      0.2        000521      fpl     Changed to fixed point   |
|      0.3        000605      fpl     Changed to .k file       |
|      0.4        000926       jg     Back to .mac and no dsts |
+-------------------------------------------------------------*/

#include "salppc.inc"

#define LVX_BT( vT, rA, rB )          LVX( vT, rA, rB )

#define FUNC ENTRY                    dotpr9 8bit
#define VMSUM( vT, vA, vB, vC )       VMSUMMBM( vT, vA, vB, vC )
#define LOOP COUNT SHIFT 6
#define HALF BLOCK BIT 0x20
#define QUARTER_BLOCK_BIT 0x10

#define LOOP_BLOCK_SIZE 64

/**
 Input parameters
**/
#define bt1mptr r3
#define r1ptr   r4
#define r0ptr   r5
#define r1mptr  r6
#define C        r7
#define N        r8
#define hat_tc  r9
/**
 Local loop registers
**/
#define bt0ptr r10
#define bt1ptr r11
#define bt2ptr r12
#define bt3ptr r13
#define index1 r14
#define index2 r15

#define index3 r0
#define icount hat_tc

/**
 G4 registers
**/
#define rq10 v0
#define rq11 v1
#define rq12 v2
#define rq13 v3
#define zero v3

#define bt30 v0
```

1

```
dotpr9_8bit.mac

#define bt31 v1
#define bt32 v2
#define bt33 v3

#define rq00 v4
#define rq01 v5
#define rq02 v6
#define rq03 v7

#define rq1m0 v8
#define rq1m1 v9
#define rq1m2 v10
#define rq1m3 v11

#define bt1m0 v12
#define bt1m1 v13
#define bt1m2 v14
#define bt1m3 v15

#define bt10 v12
#define bt11 v13
#define bt12 v14
#define bt13 v15

#define bt00 v16
#define bt01 v17
#define bt02 v18
#define bt03 v19

#define bt20 v16
#define bt21 v17
#define bt22 v18
#define bt23 v19

#define sum00 v20
#define sum01 v21
#define sum02 v22
#define sum03 v23

#define sum10 v24
#define sum11 v25
#define sum12 v26
#define sum13 v27

#define sum20 v28
#define sum21 v29
#define sum22 v30
#define sum23 v31

/**
 Begin code text
**/
FUNC PROLOG
ENTRY 7( FUNC ENTRY, bt1mptr, r1ptr, r0ptr, r1mptr, C, N, hat_tc )
   SAVE r13 r15
   USE_THRU_v31( VRSAVE_COND )
/**
 Load up local loop registers
**/
   ADD(bt0ptr, bt1mptr, hat_tc)
   VXOR(sum00, sum00, sum00)
   ADD(bt1ptr, bt0ptr, hat_tc)
   LI(index1, 16)
   ADD(bt2ptr, bt1ptr, hat_tc)
   VXOR(sum01, sum01, sum01)
   ADD(bt3ptr, bt2ptr, hat_tc)
```

2

```
        LI(index2, 32)
        VXOR(sum02, sum02, sum02)
        LI(index3, 48)
        VXOR(sum03, sum03, sum03)

        VXOR(sum10, sum10, sum10)
        VXOR(sum11, sum11, sum11)
        VXOR(sum12, sum12, sum12)
        VXOR(sum13, sum13, sum13)

        VXOR(sum20, sum20, sum20)
        VXOR(sum21, sum21, sum21)
        VXOR(sum22, sum22, sum22)
        VXOR(sum23, sum23, sum23)
        SRWI C(icount, N, LOOP_COUNT_SHIFT)
        BEQ(do_half_block)
/**
 Loop entry code
**/
        LVX BT( bt1m0, 0, bt1mptr )
        LVX BT( bt1m1, bt1mptr, index1 )
        DECR C(icount)
        LVX BT( bt1m2, bt1mptr, index2 )
        LVX_BT( bt1m3, bt1mptr, index3 )

        LVX( rq10, 0, r1ptr )
        ADDI(bt1mptr, bt1mptr, LOOP_BLOCK_SIZE)
        LVX( rq11, r1ptr, index1 )
        LVX( rq12, r1ptr, index2 )
        LVX( rq13, r1ptr, index3 )
        LVX_BT( bt00, 0, bt0ptr )
        BR( mid_loop )
/**
 Nine dot products producing 3 sums:
   sum0 = (R1 * Bt1m) (R0 * Bt0) (R1m * Bt1)
   sum1 = (R1 * Bt0) (R0 * Bt1) (R1m * Bt2)
   sum2 = (R1 * Bt1) (R0 * Bt2) (R1m * Bt3)
**/
LABEL( loop )
/* { */
        LVX BT( bt1m0, 0, bt1mptr )
        VMSUM( sum20, rq1m0, bt30, sum20 ) /* R1m * Bt3 */
        LVX BT( bt1m1, bt1mptr, index1 )
        VMSUM( sum21, rq1m1, bt31, sum21 )
        LVX BT( bt1m2, bt1mptr, index2 )
        VMSUM( sum22, rq1m2, bt32, sum22 )
        LVX_BT( bt1m3, bt1mptr, index3 )

        LVX( rq10, 0, r1ptr )
        VMSUM( sum23, rq1m3, bt33, sum23 )
        ADDI(bt1mptr, bt1mptr, LOOP_BLOCK_SIZE)
        LVX( rq11, r1ptr, index1 )
        VMSUM( sum20, rq00, bt20, sum20 ) /* R0 * Bt2 */
        LVX( rq12, r1ptr, index2 )
        VMSUM( sum21, rq01, bt21, sum21 )
        DECR C(icount)
        VMSUM( sum22, rq02, bt22, sum22 )
        LVX( rq13, r1ptr, index3 )

        VMSUM( sum23, rq03, bt23, sum23 )
        LVX_BT( bt00, 0, bt0ptr )
/**
 Loop entry
**/
LABEL( mid_loop )
        VMSUM( sum00, rq10, bt1m0, sum00 ) /* R1 * Bt1m */
        LVX_BT( bt01, bt0ptr, index1 )
```

3

dotpr9_8bit.mac

```
        ADDI(r1ptr, r1ptr, LOOP BLOCK SIZE)
        LVX_BT( bt02, bt0ptr, index2 )
        VMSUM( sum01, rq11, bt1m1, sum01 )
        LVX_BT( bt03, bt0ptr, index3 )

        VMSUM( sum02, rq12, bt1m2, sum02 )
        LVX( rq00, 0, r0ptr )
        VMSUM( sum03, rq13, bt1m3, sum03 )
        ADDI(bt0ptr, bt0ptr, LOOP_BLOCK_SIZE)
        VMSUM( sum10, rq10, bt00, sum10 )  /* R1 * Bt0 */
        LVX( rq01, r0ptr, index1 )
        VMSUM( sum11, rq11, bt01, sum11 )
        LVX( rq02, r0ptr, index2 )
        VMSUM( sum12, rq12, bt02, sum12 )
        LVX( rq03, r0ptr, index3 )

        ADDI(r0ptr, r0ptr, LOOP BLOCK SIZE)
        VMSUM( sum13, rq13, bt03, sum13 )
        LVX_BT( bt10, 0, bt1ptr )
        LVX_BT( bt11, bt1ptr, index1 )
        VMSUM( sum00, rq00, bt00, sum00 )  /* R0 * Bt0 */
        LVX_BT( bt12, bt1ptr, index2 )
        VMSUM( sum01, rq01, bt01, sum01 )
        LVX_BT( bt13, bt1ptr, index3 )

        VMSUM( sum02, rq02, bt02, sum02 )
        VMSUM( sum03, rq03, bt03, sum03 )
        LVX( rq1m0, 0, r1mptr )
        VMSUM( sum20, rq10, bt10, sum20 )  /* R1 * Bt1 */
        LVX( rq1m1, r1mptr, index1 )
        VMSUM( sum21, rq11, bt11, sum21 )
        LVX( rq1m2, r1mptr, index2 )
        ADDI(bt1ptr, bt1ptr, LOOP BLOCK_SIZE)
        LVX( rq1m3, r1mptr, index3 )

        VMSUM( sum22, rq12, bt12, sum22 )
        LVX_BT( bt20, 0, bt2ptr )
        VMSUM( sum23, rq13, bt13, sum23 )
        LVX_BT( bt21, bt2ptr, index1 )
        VMSUM( sum10, rq00, bt10, sum10 )  /* R0 * Bt1 */
        ADDI(r1mptr, r1mptr, LOOP_BLOCK_SIZE)
        VMSUM( sum11, rq01, bt11, sum11 )
        LVX_BT( bt22, bt2ptr, index2 )
        VMSUM( sum12, rq02, bt12, sum12 )
        LVX_BT( bt23, bt2ptr, index3 )

        VMSUM( sum13, rq03, bt13, sum13 )
        LVX_BT( bt30, 0, bt3ptr )
        LVX_BT( bt31, bt3ptr, index1 )
        VMSUM( sum00, rq1m0, bt10, sum00 )  /* R1m * Bt1 */
        LVX_BT( bt32, bt3ptr, index2 )
        VMSUM( sum01, rq1m1, bt11, sum01 )
        LVX_BT( bt33, bt3ptr, index3 )

        VMSUM( sum02, rq1m2, bt12, sum02 )
        VMSUM( sum03, rq1m3, bt13, sum03 )
        ADDI(bt2ptr, bt2ptr, LOOP BLOCK SIZE)
        VMSUM( sum10, rq1m0, bt20, sum10 )  /* R1m * Bt2 */
        VMSUM( sum11, rq1m1, bt21, sum11 )
        ADDI(bt3ptr, bt3ptr, LOOP BLOCK SIZE)
        VMSUM( sum12, rq1m2, bt22, sum12 )
        VMSUM( sum13, rq1m3, bt23, sum13 )
/* } */
    BNE( loop )
/**
 Loop exit code
**/
```

4

dotpr9_8bit.mac

```
        VMSUM( sum20, rq1m0, bt30, sum20 ) /* R1m * Bt3 */
        VMSUM( sum21, rq1m1, bt31, sum21 )
        VMSUM( sum22, rq1m2, bt32, sum22 )
        VMSUM( sum23, rq1m3, bt33, sum23 )
        VMSUM( sum20, rq00, bt20, sum20 ) /* R0 * Bt2 */
        VMSUM( sum21, rq01, bt21, sum21 )
        VMSUM( sum22, rq02, bt22, sum22 )
        VMSUM( sum23, rq03, bt23, sum23 )
/**
 Remainders
**/
LABEL(do half block)
    ANDI C( icount, N, HALF_BLOCK_BIT )
    BEQ(do_quarter_block)

    LVX BT( bt1m0, 0, bt1mptr )
    LVX BT( bt1m1, bt1mptr, index1 )
    ADDI(bt1mptr, bt1mptr, (LOOP_BLOCK_SIZE >> 1) )

    LVX( rq10, 0, r1ptr )
    LVX( rq11, r1ptr, index1 )
    ADDI(r1ptr, r1ptr, (LOOP_BLOCK_SIZE >> 1) )

    VMSUM( sum00, rq10, bt1m0, sum00 ) /* R1 * Bt1m */
    VMSUM( sum01, rq11, bt1m1, sum01 )

    LVX BT( bt00, 0, bt0ptr )
    LVX BT( bt01, bt0ptr, index1 )
    ADDI(bt0ptr, bt0ptr, (LOOP_BLOCK_SIZE >> 1) )

    VMSUM( sum10, rq10, bt00, sum10 ) /* R1 * Bt0 */
    VMSUM( sum11, rq11, bt01, sum11 )

    LVX( rq00, 0, r0ptr )
    LVX( rq01, r0ptr, index1 )
    ADDI(r0ptr, r0ptr, (LOOP_BLOCK_SIZE >> 1) )

    VMSUM( sum00, rq00, bt00, sum00 ) /* R0 * Bt0 */
    VMSUM( sum01, rq01, bt01, sum01 )

    LVX BT( bt10, 0, bt1ptr )
    LVX BT( bt11, bt1ptr, index1 )
    ADDI(bt1ptr, bt1ptr, (LOOP_BLOCK_SIZE >> 1) )

    VMSUM( sum20, rq10, bt10, sum20 ) /* R1 * Bt1 */
    VMSUM( sum21, rq11, bt11, sum21 )

    VMSUM( sum10, rq00, bt10, sum10 ) /* R0 * Bt1 */
    VMSUM( sum11, rq01, bt11, sum11 )

    LVX( rq1m0, 0, r1mptr )
    LVX( rq1m1, r1mptr, index1 )
    ADDI(r1mptr, r1mptr, (LOOP_BLOCK_SIZE >> 1) )

    VMSUM( sum00, rq1m0, bt10, sum00 ) /* R1m * Bt1 */
    VMSUM( sum01, rq1m1, bt11, sum01 )

    LVX BT( bt20, 0, bt2ptr )
    LVX BT( bt21, bt2ptr, index1 )
    ADDI(bt2ptr, bt2ptr, (LOOP_BLOCK_SIZE >> 1) )

    VMSUM( sum20, rq00, bt20, sum20 ) /* R0 * Bt2 */
    VMSUM( sum21, rq01, bt21, sum21 )

    VMSUM( sum10, rq1m0, bt20, sum10 ) /* R1m * Bt2 */
    VMSUM( sum11, rq1m1, bt21, sum11 )
```

5

```
        dotpr9_8bit.mac
            LVX BT( bt30, 0, bt3ptr )
            LVX BT( bt31, bt3ptr, index1 )
            ADDI(bt3ptr, bt3ptr, (LOOP_BLOCK_SIZE >> 1) )

            VMSUM( sum20, rq1m0, bt30, sum20 ) /* R1m * Bt3 */
            VMSUM( sum21, rq1m1, bt31, sum21 )
/**
 four more sums
**/
LABEL(do quarter block)
            ANDI C( icount, N, QUARTER_BLOCK_BIT )
            BEQ(combine)

            LVX BT( bt1m0, 0, bt1mptr )
            LVX( rq10, 0, r1ptr )
            VMSUM( sum00, rq10, bt1m0, sum00 ) /* R1 * Bt1m */
            ADDI(bt1mptr, bt1mptr, 16)

            LVX BT( bt00, 0, bt0ptr )
            VMSUM( sum10, rq10, bt00, sum10 ) /* R1 * Bt0 */

            LVX( rq00, 0, r0ptr )
            VMSUM( sum00, rq00, bt00, sum00 ) /* R0 * Bt0 */

            LVX_BT( bt10, 0, bt1ptr )

            VMSUM( sum20, rq10, bt10, sum20 ) /* R1 * Bt1 */
            VMSUM( sum10, rq00, bt10, sum10 ) /* R0 * Bt1 */

            LVX( rq1m0, 0, r1mptr )
            VMSUM( sum00, rq1m0, bt10, sum00 ) /* R1m * Bt1 */

            LVX BT( bt20, 0, bt2ptr )
            VMSUM( sum20, rq00, bt20, sum20 ) /* R0 * Bt2 */
            VMSUM( sum10, rq1m0, bt20, sum10 ) /* R1m * Bt2 */

            LVX BT( bt30, 0, bt3ptr )
            VMSUM( sum20, rq1m0, bt30, sum20 ) /* R1m * Bt3 */
/**
 Combine sums and return
**/
LABEL(combine)
            VXOR( zero, zero, zero )
            VADDSWS( sum00, sum00, sum01 )
            VADDSWS( sum10, sum10, sum11 )
            VADDSWS( sum20, sum20, sum21 )

            VADDSWS( sum02, sum02, sum03 )
            VADDSWS( sum12, sum12, sum13 )
            VADDSWS( sum22, sum22, sum23 )

            VADDSWS( sum00, sum00, sum02 )
            VADDSWS( sum10, sum10, sum12 )
            VADDSWS( sum20, sum20, sum22 )

            VSUMSWS( sum00, sum00, zero )    /* xxx xxx xxx s00 */
            VSUMSWS( sum10, sum10, zero )
            VSUMSWS( sum20, sum20, zero )

            VSPLTW( sum00, sum00, 3 )        /* s00 s00 s00 s00 */
            STVEWX( sum00, 0, C )
            ADDI( C, C, 4 )
            VSPLTW( sum10, sum10, 3 )
            STVEWX( sum10, 0, C )
            ADDI( C, C, 4 )
            VSPLTW( sum20, sum20, 3 )
            STVEWX( sum20, 0, C )
```

6

dotpr9_8bit.mac

```
/**
 Return
**/
LABEL( ret )
  FREE THRU v31( VRSAVE_COND )
  REST r13_r15
  RETURN
FUNC_EPILOG
```

7

fixed_cdotpr.mac

```
#ifndef MCOS 55
#define MCOS_55 0
#endif
/*------------------------------------------------------------+
/*------------------------------------------------------------+
|--- MC Standard Algorithms -- 603e Macro language Version ---|
|------------------------------------------------------------|
|                                                            |
|  File Name:    CDOTPR.MAC                                   |
|  Description:  Vector Single Precision Complex Dot Product  |
|  Entry/params: CDOTPR (A, I, B, J, C, N)                    |
|  Formula: C[0] = sum (A[mI]*B[mJ] - A[mI+1]*B[mJ+1])        |
|           C[1] = sum (A[mI]*B[mJ+1] + A[mI+1]*B[mJ])        |
|                 for m=0 to N-1                              |
|                                                            |
|            Mercury Computer Systems, Inc.                  |
|            Copyright (c) 1995  All rights reserved         |
|                                                            |
|   Revision     Date      Engineer Reason                   |
|   --------     ----      ----------------                  |
|     0.0       960502     fpl  Created                       |
|     0.1       960618     fpl  Added Esal entry              |
|     0.2       970128     fpl  Added dcbt logic              |
|     0.3       970203     fpl  Corrected ABIT define         |
|     0.4       970522     jfk  Added new dcbx test macros    |
|     0.5       980325     fpl  Added 740 code segment        |
|     0.6       980404     fpl  Removed loop stall            |
|     0.7       980708     fpl  Added build macros            |
|     0.8       980820     jfk  Added new DCBT macro          |
|     0.9       981019     fpl  Added z function              |
|     0.10      981025     fpl  Modified z entry              |
|     0.11      990310     fpl  750/G4 integration            |
|     0.12      990730     fpl  Added conjugate entry         |
|     1.0       000223     fpl  Increased minimum VMX count   |
|     1.1       000305     jfkremoved branches to entrypoints|
|     1.2       000607     jfk Fixed floating point save bug  |
|     1.3       000610     fpl  Added new API macro           |
|                                                          -*/
+-----------------------------------------------------------

#include "salppc.inc"

#undef BR IF VMX Z2
#define BR_IF_VMX_Z2( root_name, uroot name, min n imm, unit_s_imm, \
                      pr1, pi1, s1, pr2, pi2, s2, n, eflag ) \
    cmplwi n, min n_imm; \
    blt z_skip vmx; \
    cmpwi s1, unit s imm; \
    bne z_skip vmx; \
    cmpwi s2, unit s imm; \
    xor r0, pr1, pi1; \
    bne z_skip vmx; \
    andi. r0, r0, 0xf; \
    xor r0, pr2, pi2; \
    bne z_skip vmx; \
    andi. r0, r0, 0xf; \
    xor r0, pr1, pr2; \
    bne z_skip vmx; \
    andi. r0, r0, 0xf; \
    bne z unaligned vmx; \
    BR VMX Z2( root_name, eflag, s1 ) \
z_unaligned vmx: \
    BR VMX Z2( uroot_name, eflag, s1 ) \
z_skip_vmx:

#define ACOND 5
#define ABIT  2
#define BCOND 6
```

1

```
fixed_cdotpr.mac

#define BBIT  1

/**
 API registers
**/
#define A     r3
#define I     r4
#define B     r5
#define J     r6
#define C     r7
#define N     r8
#define EFLAG r9

/**
 z input args
**/
#define Ar   A
#define Ai   r10
#define Br   B
#define Bi   r11
#define Cr   C
#define Ci   r12

/**
 Local registers
**/
#define count r13
#define rtmp r13
#define nextline r14

/**
 Fpu registers
**/
#define rsumr0 f0
#define rsumi0 f1
#define isumr0 f2
#define isumi0 f3

#define ar0 f4
#define ai0 f5
#define ar1 f6
#define ai1 f7
#define ar2 f8
#define ai2 f9
#define ar3 f10
#define ai3 f11

#define br0 f12
#define bi0 f13
#define br1 f14
#define bi1 f15
#define br2 f16
#define bi2 f17
#define br3 f18
#define bi3 f19

#if defined( BUILD_MAX )
#if MCOS 55
DECLARE_VMX_Z2( _zdotpr_vmx_cc )
#else
DECLARE_VMX_Z2( _zdotpr_vmx )
#endif
DECLARE_VMX_Z2( _zdotpr4_vmx )
#endif

/**
  Code text: Conjugate
```

2

fixed_cdotpr.mac

```
**/
FUNC PROLOG
#ifndef COMPILE C
U_ENTRY( fixed cidotpr  )                    /* Fortran SAL */
    FORTRAN DREF 3( I, J, N )
                                                 /* C SAL */
U_ENTRY( fixed cidotpr )
    LI( EFLAG, SAL NNN )                 /* NNN EFLAG (default) */
    BR( cidotprx common )                  /* common path */
U_ENTRY( fixed cidotprx   )                      /* Fortran ESAL */
    FORTRAN DREF 4( I, J, N, EFLAG )
U ENTRY( fixed cidotprx )              /* C ESAL */
LABEL( cidotprx common )                /* common path */
    ADDI( Ai, Ar, 4 )
    MR( Bi, Br )
    ADDI( Br, Br, 4 )
    MR( Ci, Cr )
    ADDI( Cr, Cr, 4 )
    BR( common )                   /* common path */
/**
 Normal
**/
FUNC PROLOG
#ifndef COMPILE C
U_ENTRY( fixed cdotpr_ )                      /* Fortran SAL */
    FORTRAN DREF 3( I, J, N )
                                                 /* C SAL */
U_ENTRY( fixed cdotpr )
    LI( EFLAG, SAL NNN )                 /* NNN EFLAG (default) */
    BR( cdotprx common )                   /* common path */
U_ENTRY( fixed cdotprx   )                       /* Fortran ESAL */
    FORTRAN DREF 4( I, J, N, EFLAG )
U ENTRY( fixed cdotprx )               /* C ESAL */
LABEL( cdotprx common )                 /* common path */
    ADDI( Ai, Ar, 4 )
    ADDI( Bi, Br, 4 )
    ADDI( Ci, Cr, 4 )
    BR( common )                   /* common path */
/**
 Split complex entries: Conjugate
**/
U_ENTRY( fixed zidotpr  )              /* Fortran SAL */
    FORTRAN DREF 3( I, J, N )
                                         /* C SAL */
U_ENTRY( fixed zidotpr )
    LI( EFLAG, SAL NNN )        /* NNN EFLAG (default) */
    BR( zidotprx common )
U_ENTRY( fixed zidotprx  )             /* Fortran ESAL */
    FORTRAN_DREF_4( I, J, N, EFLAG )
#endif
ENTRY 7( fixed zidotprx, A, I, B, J, C, N, EFLAG)
LABEL( zidotprx_common )
/**
 Assign split complex pointers, do the conjugate trick
**/
    LWZ( Ai, A, 4 )
    LWZ( Ar, A, 0 )
    LWZ( Bi, B, 0 )
    LWZ( Br, B, 4 )
    LWZ( Ci, C, 0 )
    LWZ( Cr, C, 4 )
    BR( z_common )
/**
 Normal
**/
U_ENTRY( fixed zdotpr_ )                   /* Fortran SAL */
    FORTRAN DREF 3( I, J, N )
                                          /* C SAL */
U_ENTRY( fixed zdotpr )
    LI( EFLAG, SAL NNN )           /* NNN EFLAG (default) */
    BR( zdotprx_common )
```

3

```
        fixed_cdotpr.mac
    U_ENTRY( fixed zdotprx  )                    /* Fortran ESAL */
      FORTRAN_DREF_4( I, J, N, EFLAG )
    #endif
    /**
     C ESAL
    **/
    ENTRY 7( fixed zdotprx, A, I, B, J, C, N, EFLAG)
       DECLARE r10 r14
       DECLARE_f0_f19

    LABEL( zdotprx_common )

    /**
     Assign split complex pointers
    **/
       LWZ( Ai, A, 4 ) /* must load imag first since Ar reg = A reg */
       LWZ( Ar, A, 0 )
       LWZ( Bi, B, 4 )
       LWZ( Br, B, 0 )
       LWZ( Ci, C, 4 )
       LWZ( Cr, C, 0 )
    /**
     VMX API filter
     Test if okay to enter VMX code and branch to VMX code
     VMX loop - process all N points
    **/

    LABEL( z_common )

    #if defined( BUILD_MAX )

    #define  MIN_VMX_N  20
    #define  UNIT_STRIDE  1

    #if MCOS 55
       BR_IF_VMX_Z2( zdotpr_vmx cc,  zdotpr4_vmx, MIN_VMX_N, UNIT_STRIDE, \
                     Ar, Ai, I, Br, Bi, J, N, EFLAG )

    #else
       BR_IF_VMX_Z2( zdotpr_vmx,  zdotpr4_vmx, MIN_VMX_N, UNIT_STRIDE, \
                     Ar, Ai, I, Br, Bi, J, N, EFLAG )

    #endif

    #endif  /* BUILD_MAX */

    /**
     Point of common path where all entries join
     Test for small counts
    **/
    LABEL( common )
       SAVE r13 r14
       SAVE f14 f19
       CMPLWI(N, 0)
       BEQ(ret)
       CMPLWI(N, 1)
       BEQ(do1)
       CMPLWI(N, 2)
       BEQ(do2)
       CMPLWI(N, 3)
       BEQ(do3)
    /**
     check for uncached (and local) vectors
    **/
       SET_2_DCBT_COND( ACOND, ABIT, BCOND, BBIT, EFLAG, rtmp )

       LI(nextline, 32)
    /**
     740 code segment, start up loop code
```

4

```
fixed_cdotpr.mac
**/
#if defined( BUILD_750 ) || defined( BUILD_MAX )
     LFS( ar0, Ar, 0 )
     SRWI( count, N, 2 )  /* count = N >> 2 */
     LFS( br0, Br, 0 )
     SLWI( I, I, 2 )       /* byte strides */
     LFS( ai0, Ai, 0 )
     SLWI( J, J, 2 )
     LFS( bi0, Bi, 0 )

     LFSUX( ar1, Ar, I )
     LFSUX( br1, Br, J )
     LFSUX( ai1, Ai, I )
     LFSUX( bi1, Bi, J )

     LFSUX( ar2, Ar, I )
     LFSUX( br2, Br, J )
     LFSUX( ai2, Ai, I )
     LFSUX( bi2, Bi, J )

     FMULS( rsumr0, ar0, br0 )
     LFSUX( ar3, Ar, I )
     LFSUX( br3, Br, J )
     FMULS( rsumi0, ai0, bi0 )
     LFSUX( ai3, Ai, I )
     LFSUX( bi3, Bi, J )
     FMULS( isumi0, ar0, bi0 )
     DECR C( count )
     FMULS( isumr0, ai0, br0 )
     BEQ(flush_loop_740)
     BR(mloop_740)
/**
 Top of 740 loop
**/
LABEL(loop_740)
     LFSUX( ar3, Ar, I )
     FMADDS( rsumr0, ar0, br0, rsumr0 )
     LFSUX( br3, Br, J )
     FMADDS( rsumi0, ai0, bi0, rsumi0 )
     LFSUX( ai3, Ai, I )
     FMADDS( isumi0, ar0, bi0, isumi0 )
     FMADDS( isumr0, ai0, br0, isumr0 )
     LFSUX( bi3, Bi, J )

LABEL(mloop_740)
     FMADDS( rsumr0, ar1, br1, rsumr0 )
     LFSUX( ar0, Ar, I )

     DCBT IF( ACOND, Ar, nextline )
     FMADDS( rsumi0, ai1, bi1, rsumi0 )
     LFSUX( br0, Br, J )

     DECR C( count )
     FMADDS( isumi0, ar1, bi1, isumi0 )
     LFSUX( ai0, Ai, I )
     FMADDS( isumr0, ai1, br1, isumr0 )
     LFSUX( bi0, Bi, J )

     DCBT IF( BCOND, Br, nextline )
     FMADDS( rsumr0, ar2, br2, rsumr0 )
     LFSUX( ar1, Ar, I )
     LFSUX( br1, Br, J )
     FMADDS( rsumi0, ai2, bi2, rsumi0 )
     LFSUX( ai1, Ai, I )
     FMADDS( isumi0, ar2, bi2, isumi0 )
     LFSUX( bi1, Bi, J )
     FMADDS( isumr0, ai2, br2, isumr0 )
```

5

```
        FMADDS( rsumr0, ar3, br3, rsumr0 )
        LFSUX( ar2, Ar, I )
        FMADDS( rsumi0, ai3, bi3, rsumi0 )
        LFSUX( br2, Br, J )
        FMADDS( isumi0, ar3, bi3, isumi0 )
        LFSUX( ai2, Ai, I )
        LFSUX( bi2, Bi, J )
        FMADDS( isumr0, ai3, br3, isumr0 )
        BNE( loop_740 )
/**
 Finish last pass
**/
        FMADDS( rsumr0, ar0, br0, rsumr0 )
        LFSUX( ar3, Ar, I )
        LFSUX( br3, Br, J )
        FMADDS( rsumi0, ai0, bi0, rsumi0 )
        LFSUX( ai3, Ai, I )
        LFSUX( bi3, Bi, J )
        FMADDS( isumi0, ar0, bi0, isumi0 )
        FMADDS( isumr0, ai0, br0, isumr0 )

LABEL( flush loop 740 )
        FMADDS( rsumr0, ar1, br1, rsumr0 )
        FMADDS( rsumi0, ai1, bi1, rsumi0 )

        FMADDS( isumi0, ar1, bi1, isumi0 )
        FMADDS( isumr0, ai1, br1, isumr0 )

        FMADDS( rsumr0, ar2, br2, rsumr0 )
        FMADDS( rsumi0, ai2, bi2, rsumi0 )
        FMADDS( isumi0, ar2, bi2, isumi0 )
        FMADDS( isumr0, ai2, br2, isumr0 )

        FMADDS( rsumr0, ar3, br3, rsumr0 )
        FMADDS( rsumi0, ai3, bi3, rsumi0 )
        FMADDS( isumi0, ar3, bi3, isumi0 )
        FMADDS( isumr0, ai3, br3, isumr0 )
        BR(remain)
#endif   /** 750 specific code section **/
/**
 set up for loop entry, here if N >= 2
**/
#if defined( BUILD_603 )
LABEL(start 603)
        LFS( ar0, Ar, 0 )
        SLWI( I, I, 2 )       /* byte strides */
        LFS( ai0, Ai, 0 )
        SRWI( count, N, 2 ) /* count = N >> 2 */
        LFSUX( ar1, Ar, I )
        SLWI( J, J, 2 )
        LFSUX( ai1, Ai, I )
        LFSUX( ar2, Ar, I )
        LFSUX( ai2, Ai, I )
        LFSUX( ar3, Ar, I )
        LFSUX( ai3, Ai, I )
        DCBT_IF( ACOND, Ar, nextline )

        LFS( br0, Br, 0 )
        DECR_C( count )
        LFS( bi0, Bi, 0 )
        LFSUX( br1, Br, J )
        LFSUX( bi1, Bi, J )
        LFSUX( br2, Br, J )
        LFSUX( bi2, Bi, J )
        LFSUX( br3, Br, J )
        LFSUX( bi3, Bi, J )
```

6

fixed_cdotpr.mac

```
        DCBT_IF( BCOND, Br, nextline )

        FMULS( rsumr0, ar0, br0 )
        FMULS( rsumi0, ai0, bi0 )
        FMULS( isumi0, ar0, bi0 )
        FMULS( isumr0, ai0, br0 )

        FMADDS( rsumr0, ar1, br1, rsumr0 )
        FMADDS( rsumi0, ai1, bi1, rsumi0 )
        FMADDS( isumi0, ar1, bi1, isumi0 )
        FMADDS( isumr0, ai1, br1, isumr0 )

        FMADDS( rsumr0, ar2, br2, rsumr0 )
        FMADDS( rsumi0, ai2, bi2, rsumi0 )
        FMADDS( isumi0, ar2, bi2, isumi0 )
        FMADDS( isumr0, ai2, br2, isumr0 )

        FMADDS( rsumr0, ar3, br3, rsumr0 )
        FMADDS( rsumi0, ai3, bi3, rsumi0 )
        FMADDS( isumi0, ar3, bi3, isumi0 )
        FMADDS( isumr0, ai3, br3, isumr0 )
    BEQ( remain )
/**
 main loop maintains four partial sums
 representing two complex sum updates per pass
**/
LABEL(loop)
        LFSUX( ar0, Ar, I )
        LFSUX( ai0, Ai, I )
        LFSUX( ar1, Ar, I )
        LFSUX( ai1, Ai, I )
        LFSUX( ar2, Ar, I )
        LFSUX( ai2, Ai, I )
        LFSUX( ar3, Ar, I )
        LFSUX( ai3, Ai, I )
        DCBT_IF( ACOND, Ar, nextline )

        DECR C( count )
        LFSUX( br0, Br, J )
        LFSUX( bi0, Bi, J )
        LFSUX( br1, Br, J )
        LFSUX( bi1, Bi, J )
        LFSUX( br2, Br, J )
        LFSUX( bi2, Bi, J )
        LFSUX( br3, Br, J )
        LFSUX( bi3, Bi, J )
        DCBT_IF( BCOND, Br, nextline )

        FMADDS( rsumr0, ar0, br0, rsumr0 )
        FMADDS( rsumi0, ai0, bi0, rsumi0 )
        FMADDS( isumi0, ar0, bi0, isumi0 )
        FMADDS( isumr0, ai0, br0, isumr0 )

        FMADDS( rsumr0, ar1, br1, rsumr0 )
        FMADDS( rsumi0, ai1, bi1, rsumi0 )
        FMADDS( isumi0, ar1, bi1, isumi0 )
        FMADDS( isumr0, ai1, br1, isumr0 )

        FMADDS( rsumr0, ar2, br2, rsumr0 )
        FMADDS( rsumi0, ai2, bi2, rsumi0 )
        FMADDS( isumi0, ar2, bi2, isumi0 )
        FMADDS( isumr0, ai2, br2, isumr0 )

        FMADDS( rsumr0, ar3, br3, rsumr0 )
        FMADDS( rsumi0, ai3, bi3, rsumi0 )
        FMADDS( isumi0, ar3, bi3, isumi0 )
        FMADDS( isumr0, ai3, br3, isumr0 )
```

7

fixed_cdotpr.mac

```
    BNE( loop )
#endif   /** 603 specific code section **/
/**
 remainder loop
**/
LABEL(remain)
    ANDI_C( count, N, 2 )   /* bit 2 */
    BEQ( sum1 )

  .LFSUX( ar0, Ar, I )
    LFSUX( ai0, Ai, I )
    LFSUX( ar1, Ar, I )
    LFSUX( ai1, Ai, I )

    LFSUX( br0, Br, J )
    LFSUX( bi0, Bi, J )
    LFSUX( br1, Br, J )
    LFSUX( bi1, Bi, J )

    FMADDS( rsumr0, ar0, br0, rsumr0 )
    FMADDS( rsumi0, ai0, bi0, rsumi0 )
    FMADDS( isumi0, ar0, bi0, isumi0 )
    FMADDS( isumr0, ai0, br0, isumr0 )

    FMADDS( rsumr0, ar1, br1, rsumr0 )
    FMADDS( rsumi0, ai1, bi1, rsumi0 )
    FMADDS( isumi0, ar1, bi1, isumi0 )
    FMADDS( isumr0, ai1, br1, isumr0 )

 LABEL(sum1)
    ANDI_C( count, N, 1 )   /* bit 0 */
    BEQ( combine )          /* if no sums left */

    LFSUX( ar0, Ar, I )
    LFSUX( br0, Br, J )
    LFSUX( ai0, Ai, I )
    LFSUX( bi0, Bi, J )

    FMADDS( rsumr0, ar0, br0, rsumr0 )
    FMADDS( rsumi0, ai0, bi0, rsumi0 )
    FMADDS( isumi0, ar0, bi0, isumi0 )
    FMADDS( isumr0, ai0, br0, isumr0 )
/**
 combine partial sums, write out results and return
**/
LABEL(combine)
    FSUBS( rsumr0, rsumr0, rsumi0 ) /** rsumr0 = rsumr0 - rsumi0 **/
    STFS( rsumr0, Cr, 0 )               /** *(S + 0) = rsumr0 **/
    FADDS( isumi0, isumi0, isumr0 )
    STFS( isumi0, Ci, 0 )
    BR(ret)
/**
 here for N = 1,2,3
**/
LABEL(do3)
    LFS( ar0, Ar, 0 )
    SLWI( I, I, 2 )         /* byte strides */
    LFS( ai0, Ai, 0 )
    LFSUX( ar1, Ar, I )
    SLWI( J, J, 2 )
    LFSUX( ai1, Ai, I )
    LFSUX( ar2, Ar, I )
    LFSUX( ai2, Ai, I )

    LFS( br0, Br, 0 )
    DECR_C( count )
    LFS( bi0, Bi, 0 )
```

8

```
                    fixed_cdotpr.mac
        LFSUX( br1, Br, J )
        LFSUX( bi1, Bi, J )
        LFSUX( br2, Br, J )
        LFSUX( bi2, Bi, J )

        FMULS( rsumr0, ar0, br0 )
        FMULS( rsumi0, ai0, bi0 )
        FMULS( isumi0, ar0, bi0 )
        FMULS( isumr0, ai0, br0 )

        FMADDS( rsumr0, ar1, br1, rsumr0 )
        FMADDS( rsumi0, ai1, bi1, rsumi0 )
        FMADDS( isumi0, ar1, bi1, isumi0 )
        FMADDS( isumr0, ai1, br1, isumr0 )

        FMADDS( rsumr0, ar2, br2, rsumr0 )
        FMADDS( rsumi0, ai2, bi2, rsumi0 )
        FMADDS( isumi0, ar2, bi2, isumi0 )
        FMADDS( isumr0, ai2, br2, isumr0 )
        BR(combine)

LABEL(do2)
        LFS( ar0, Ar, 0 )
        SLWI( I, I, 2 )        /* byte strides */
        LFS( ai0, Ai, 0 )
        LFSUX( ar1, Ar, I )
        SLWI( J, J, 2 )
        LFSUX( ai1, Ai, I )

        LFS( br0, Br, 0 )
        LFS( bi0, Bi, 0 )
        LFSUX( br1, Br, J )
        LFSUX( bi1, Bi, J )

        FMULS( rsumr0, ar0, br0 )
        FMULS( rsumi0, ai0, bi0 )
        FMULS( isumi0, ar0, bi0 )
        FMULS( isumr0, ai0, br0 )

        FMADDS( rsumr0, ar1, br1, rsumr0 )
        FMADDS( rsumi0, ai1, bi1, rsumi0 )
        FMADDS( isumi0, ar1, bi1, isumi0 )
        FMADDS( isumr0, ai1, br1, isumr0 )
        BR(combine)

LABEL(do1)
        LFS( ai0, Ai, 0 )
        LFS( bi0, Bi, 0 )
        LFS( br0, Br, 0 )
        LFS( ar0, Ar, 0 )

        FMULS( rsumi0, ai0, bi0)
        FMULS( isumr0, ai0, br0)
        FMSUBS( rsumr0, ar0, br0, rsumi0)
        STFS( rsumr0, Cr, 0 )
        FMADDS( isumi0, ar0, bi0, isumr0)
        STFS( isumi0, Ci, 0 )
/**
 return
**/
LABEL(ret)
        REST f14 f19
        REST r13_r14
        RETURN
FUNC_EPILOG
```

9

```
/*------------------------------------------------------------+
|--- MC Standard Algorithms -- PPC Macro language Version  ---|
|------------------------------------------------------------|
|                                                            |
|  File Name:    GEN R SUMS.MAC                              |
|  Description:  Multiple small dot product routine for wireless|
|                group application.                          |
|  Entry/params:                                             |
|  GEN_R_SUMS (X_bf, Coor_bf, Ptov_map, R_sums, Num_phys_users)|
|                                                            |
|  Formula:                                                  |
|     num_sums = 0;                                          |
|     for ( i = 0; i < Num phys users; i++ ) {              |
|        for ( j = 0; j < (int)Ptov_map[i]; j++ ) {         |
|           sum = 0;                                         |
|           for ( k = 0; k < 16; k++ ) {                    |
|              sum += (BF32)X bf[k].real * (BF32)Corr bf->real;|
|              sum += (BF32)X_bf[k].imag * (BF32)Corr_bf->imag;|
|           ++Corr_bf;                                       |
|           }                                                |
|           *R sums++ = sum;                                 |
|           ++num_sums;                                      |
|        }                                                   |
|        X_bf += N_FINGERS_MAX_SQUARED;                      |
|     }                                                      |
|              Mercury Computer Systems, Inc.               |
|              Copyright (c) 2000  All rights reserved      |
|                                                            |
|   Revision      Date     Engineer  Reason                 |
|   --------      ----     --------  --------                |
|     0.0        000906      fpl     Created                 |
|                                    ----------------------------*/
+------------------------------------------------------------
```

```
#include "salppc.inc"

#define DO IO  1
#define DO_PREFETCH  1

#if DO IO
#define   PTOV BUMP 1   1
#define   CORR BUMP 32  32
#define   CORR BUMP_64  64
#define   X BUMP 64   64
#define   RSUM BUMP 8   8
#define   RSUM_BUMP_4   4
#else
#define   PTOV BUMP 1   0
#define   CORR BUMP 32  0
#define   CORR BUMP_64  0
#define   X BUMP 64   0
#define   RSUM BUMP 8   0
#define   RSUM_BUMP_4   0
#endif

#define LOAD_CORR( vT, rA, rB )    LVX( vT, rA, rB )

#define  DST_BUMP  CORR_BUMP_64

#if DO PREFETCH
#define   PREFETCH( rA, rB, STRM ) \
   DST( rA, rB, STRM ) \
   ADDI( rA, rA, DST_BUMP )
#else
#define   PREFETCH( rA, rB, STRM )
#endif
```

1

gen_r_sums.mac

```
#define OLOOP_BIT 6

/**
 Input parameters
**/
#define X_bf            r3
#define Corr_bf         r4
#define Ptov_map        r5
#define R_sump          r6
#define Num_phys_users  r7
/**
 Local GPRs
**/
#define icount r8
#define ptov_count r9
#define indx1 r10
#define indx2 r11
#define indx3 r12
#define sindex1 r13
#define dstp r14
#define dst_code r15
/**
 G4 registers
**/
#define corr00 v0
#define corr01 v1
#define corr10 v2
#define corr11 v3

#define C0_0 v4
#define C1_0 v5
#define C0_8 v6
#define C1_8 v7

#define C0_16 v8
#define C1_16 v9
#define C0_24 v10
#define C1_24 v11

#define X0    v12
#define X8    v13
#define X16   v14
#define X24   v15

#define sum0 v16
#define sum1 v17
#define zero v18

/**
 Begin code text
**/
FUNC_PROLOG
ENTRY_5( gen_R_sums, X_bf, Corr_bf, Ptov_map, R_sump, Num_phys_users )

   CMPWI( Num_phys_users, 0 )
   BGT( start )
   RETURN

LABEL( start )

   SAVE r13 r15
   USE_THRU_v18( VRSAVE_COND )

/**
 DST setup
**/
   MAKE_STREAM_CODE_IIR( dst_code, DST_BUMP, 1, 0 )
```

2

gen_r_sums.mac

```
      ADDI( dstp, Corr bf, 80 )                        /* start prefetch advanced */
      PREFETCH( dstp, dst_code, 0 )

   /**
    Setup for outer loop entry
    Read and expand two coor vectors
    Set outer loop counter condition
   **/
      LI( indx1, 16 )
      LI( indx2, 32 )
      LI( indx3, 48 )
      LI( sindex1, 4 )
      CMPWI CR( OLOOP_BIT, Num phys_users, 0 )
      LVX( corr00, 0, Corr bf )
      VXOR( zero, zero, zero )
      LVX( corr01, Corr bf, indx1 )
      LVX( corr10, Corr bf, indx2 )
      LVX( corr11, Corr_bf, indx3 )

      VUPKHSB( C0 0, corr00 )
      ADDI( Corr bf, Corr bf, CORR_BUMP_64 )
      VUPKLSB( C0 8, corr00 )
      ADDI( Ptov map, Ptov map, -PTOV_BUMP_1 )
      VUPKHSB( C1 0, corr10 )
      ADDI( R sump, R sump, -RSUM_BUMP_8 )
      VUPKLSB( C1 8, corr10 )
      VUPKHSB( C0 16, corr01 )
      VUPKLSB( C0 24, corr01 )
      VUPKHSB( C1 16, corr11 )
      VUPKLSB( C1_24, corr11 )
   /**
    Outer loop for each physical user
   **/
   LABEL( oloop )
   /* { */
      DECR( Num phys users )
      LBZU( ptov count, Ptov_map, 1 )
      BEQ CR( OLOOP BIT, ret )
      LVX( X0, 0, X bf )
      LVX( X8, X bf, indx1 )
      SRWI_C( icount, ptov count, 1 )
      LVX( X16, X bf, indx2 )
      LVX( X24, X_bf, indx3 )
      ADDI( X bf, X bf, X BUMP 64 )
      CMPWI CR( OLOOP BIT, Num_phys_users, 0 )
      BEQ_MINUS( one_sum )
   /**
    Top of sum loop
    Produces two sums each pass
   **/
   LABEL( iloop )
   /* { */
      PREFETCH( dstp, dst code, 0 )
      VMSUMSHS( sum0, C0 0, X0, zero )
      VMSUMSHS( sum1, C1 0, X0, zero )
      LVX( corr00, 0, Corr bf )
      LVX( corr01, Corr bf, indx1 )
      LVX( corr10, Corr bf, indx2 )
      VMSUMSHS( sum0, C0_8, X8, sum0 )
      DECR C( icount )
      VMSUMSHS( sum1, C1 8, X8, sum1 )
      LVX( corr11, Corr bf, indx3 )
      VUPKHSB( C0 0, corr00 )
      VUPKLSB( C0 8, corr00 )
      VMSUMSHS( sum0, C0 16, X16, sum0 )
      VMSUMSHS( sum1, C1 16, X16, sum1 )
      VUPKHSB( C1_0, corr10 )
```

3

gen_r_sums.mac

```
    ADDI( R sump, R sump, RSUM_BUMP_8 )
    VUPKLSB( C1 8, corr10 )
    VMSUMSHS( sum0, C0 24, X24, sum0 )
    VUPKHSB( C0 16, corr01 )
    VMSUMSHS( sum1, C1 24, X24, sum1 )
    VUPKLSB( C0 24, corr01 )
    VUPKHSB( C1 16, corr11 )
    VSUMSWS( sum0, sum0, zero )
    VUPKLSB( C1 24, corr11 )
    VSUMSWS( sum1, sum1, zero )
    ADDI( Corr bf, Corr_bf, CORR_BUMP_64 )
    VSPLTW( sum0, sum0, 3 )
    STVEWX( sum0, 0, R sump )
    VSPLTW( sum1, sum1, 3 )
    STVEWX( sum1, R_sump, sindex1 )
/* } */
  BNE( iloop )
/**
 Drop out, check for remainders
**/
    ANDI_C(icount, ptov_count, 0x1)
    BEQ( oloop )
/**
 One more sum:
 Enters and exits with two coor vectors are loaded and expanded to 16 bit
**/
LABEL( one sum )
    VMSUMSHS( sum0, C0 0, X0, zero )
    VMSUMSHS( sum0, C0 8, X8, sum0 )
    ADDI( R sump, R_sump, RSUM BUMP 8 )
    VMSUMSHS( sum0, C0 16, X16, sum0 )
    VMSUMSHS( sum0, C0 24, X24, sum0 )
    VSUMSWS( sum0, sum0, zero )

    VSPLTW( sum0, sum0, 3 )
    STVEWX( sum0, 0, R sump )
    ADDI( R_sump, R_sump, -RSUM_BUMP_4 )   /* pre-dec pointer for loop reentry
     */
/**
 Seup for loop re-entry: corr00 consumed in one_sum section
    loop exit ptr v
 corr00  corr10  corr00  corr10
         corr00  corr10  corr00  corr10
        loop re-entry ptr ^
**/
    VMR( corr00, corr10 )
    LVX( corr10, 0, Corr bf )
    VMR( corr01, corr11 )
    LVX( corr11, Corr bf, indx1 )
    ADDI( Corr_bf, Corr_bf, CORR_BUMP_32 )

    VUPKHSB( C0 0, corr00 )
    VUPKLSB( C0 8, corr00 )
    VUPKHSB( C1 0, corr10 )
    VUPKLSB( C1 8, corr10 )
    VUPKHSB( C0 16, corr01 )
    VUPKLSB( C0 24, corr01 )
    VUPKHSB( C1 16, corr11 )
    VUPKLSB( C1_24, corr11 )
/* } */
  BR( oloop )
/**
 Exit routine
**/
LABEL( ret )
    FREE THRU v18( VRSAVE_COND )
    REST_r13_r15
```

4

```
RETURN
FUNC_EPILOG
```

```
/*-----------------------------------------------------------------+
|--- MC Standard Algorithms -- PPC Macro language Version    ---|
|-----------------------------------------------------------------|
|                                                                 |
|  File Name:    GEN R SUMS2.MAC                                   |
|  Description:  Multiple small dot product routine for wireless   |
|               group application.                                |
|  Entry/params:  GEN R SUMS2 (X bf, Corr0 bf, Corr1 bf,          |
|               Ptov_map, R_sums0, R_sums1, Num_phys_users)       |
|                                                                 |
|  Formula:                                                       |
|    num_sums = 0;                                                |
|    for ( i = 0; i < Num phys users; i++ ) {                     |
|       for ( j = 0; j < (int)Ptov_map[i]; j++ ) {                |
|          sum = 0;                                               |
|          for ( k = 0; k < 16; k++ ) {                           |
|             sum0 += (BF32)X bf[k].real * (BF32)Corr0 bf->real;   |
|             sum0 += (BF32)X_bf[k].imag * (BF32)Corr0_bf->imag;   |
|                                                                 |
|             sum1 += (BF32)X bf[k].real * (BF32)Corr1 bf->real;   |
|             sum1 += (BF32)X_bf[k].imag * (BF32)Corr1_bf->imag;   |
|             ++Corr0 bf;                                         |
|             ++Corr1_bf;                                         |
|          }                                                      |
|                                                                 |
|          *R sums0++ = sum0;                                     |
|          *R sums1++ = sum1;                                     |
|          ++num_sums;                                            |
|       }                                                         |
|       X_bf += N_FINGERS_MAX_SQUARED;                            |
|    }                                                            |
|            Mercury Computer Systems, Inc.                       |
|            Copyright (c) 2000  All rights reserved              |
|                                                                 |
|  Revision       Date     Engineer  Reason                       |
|  --------       ----     --------  --------                     |
|     0.0        000906       fpl    Created                      |
|     0.1        000908       fpl    Fixed zero bug --------------*|
+-----------------------------------------------------------------+

#include "salppc.inc"

#define DO IO  1
#define DO_PREFETCH  1

#if DO IO
#define   PTOV BUMP 1   1
#define   CORR BUMP 32  32
#define   CORR BUMP_64  64
#define   X BUMP 64   64
#define   RSUM BUMP 8   8
#define   RSUM_BUMP_4   4
#else
#define   PTOV BUMP 1   0
#define   CORR BUMP 32  0
#define   CORR BUMP_64  0
#define   X BUMP 64   0
#define   RSUM BUMP 8   0
#define   RSUM_BUMP_4   0
#endif

#define LOAD_CORR( vT, rA, rB )   LVX( vT, rA, rB )

#define  DST_BUMP  CORR_BUMP_64

#if DO PREFETCH
#define   PREFETCH( rA, rB, STRM ) \
```

1

```
gen_r_sums2.mac

        DST( rA, rB, STRM ) \
        ADDI( rA, rA, DST_BUMP )
#else
#define   PREFETCH( rA, rB, STRM )
#endif

#define OLOOP_BIT 6

/**
 Input parameters
**/
#define X bf            r3
#define Corr0 bf        r4
#define Corr1 bf        r5
#define Ptov map        r6
#define R sump0         r7
#define R sump1         r8
#define Num_phys_users r9
/**
 Local GPRs
**/
#define icount r10
#define ptov count r11
#define indx1 r12
#define indx2 r13
#define indx3 r14
#define sindex1 r15
#define dstp r16
#define dst code r17
#define dst_stride  indx3
/**
 G4 registers
**/
#define corr00 v0
#define corr01 v1
#define corr10 v2
#define corr11 v3
#define corr20 v4
#define corr21 v5
#define corr30 v6
#define corr31 corr00
#define zero    v7

#define C0_0 v8
#define C1_0 v9
#define C2_0 v10
#define C3_0 v11

#define C0_8 v12
#define C1_8 v13
#define C2_8 v14
#define C3_8 v15

#define C0_16 v16
#define C1_16 v17
#define C2_16 v18
#define C3_16 v19

#define C0_24 v20
#define C1_24 v21
#define C2_24 v22
#define C3_24 v23

#define X0  v24
#define X8  v25
#define X16 v26
#define X24 v27
```

2

```
#define sum0 v28
#define sum1 v29
#define sum2 v30
#define sum3 v31
/**
 Begin code text
**/
FUNC_PROLOG

#if 1                          /****** alignment may be important ******/
NOP
#endif

ENTRY_7( gen R sums2, X_bf, Corr0_bf, Corr1_bf, Ptov_map, R_sump0, R_sump1,
         Num_phys_users )

  CMPWI( Num_phys_users, 0 )
  BGT( start )
  RETURN

LABEL( start )
  SAVE r13 r17
  USE_THRU_v31( VRSAVE_COND )
/**
 DST setup
**/
  SUB( dst stride, Corr1 bf, Corr0 bf )
  MAKE STREAM_CODE IIR( dst code, DST_BUMP, 2, dst_stride )
  ADDI( dstp, Corr0 bf, 80 )                /* start prefetch advanced */
      /* 48: 1087, 64: 1094, 80: 1043, 96: 1058, 112: 1049, 128: 1061 */
  PREFETCH( dstp, dst_code, 0 )

/**
 Setup for outer loop entry
 Read and expand two coor vectors
 Set outer loop counter condition
**/
  LI( indx1, 16 )
  LI( indx2, 32 )
  LI( indx3, 48 )
  LI( sindex1, 4 )
  CMPWI_CR( OLOOP_BIT, Num_phys_users, 0 )

  LOAD CORR( corr00, 0, Corr0 bf )
  LOAD CORR( corr10, Corr0 bf, indx2 )
  ADDI( Ptov_map, Ptov map, -PTOV BUMP_1 )
  LOAD CORR( corr20, 0, Corr1 bf )
  ADDI( R sump0, R sump0, -RSUM BUMP_8 )
  LOAD_CORR( corr30, Corr1_bf, indx2 )

  LOAD CORR( corr01, Corr0 bf, indx1 )
  ADDI( R sump1, R sump1, -RSUM BUMP_8 )
  LOAD CORR( corr11, Corr0_bf, indx3 )
  VXOR( zero, zero, zero )
  LOAD_CORR( corr21, Corr1_bf, indx1 )

  VUPKHSB( C0 0, corr00 )
  ADDI( Corr0 bf, Corr0_bf, CORR_BUMP_64 )
  VUPKHSB( C1 0, corr10 )
  VUPKHSB( C2 0, corr20 )
  VUPKHSB( C3_0, corr30 )

  VUPKLSB( C0 8, corr00 )
  LOAD CORR( corr31, Corr1_bf, indx3 ) /* corr00, corr31 same register */
  VUPKLSB( C1 8, corr10 )
  ADDI( Corr1_bf, Corr1_bf, CORR_BUMP_64 )
```

3

```
            gen_r_sums2.mac
        VUPKLSB( C2_8, corr20 )
        VUPKLSB( C3_8, corr30 )

        VUPKHSB( C0_16, corr01 )
        VUPKHSB( C1_16, corr11 )
        VUPKHSB( C2_16, corr21 )
        VUPKHSB( C3_16, corr31 )

        VUPKLSB( C0_24, corr01 )
        VUPKLSB( C1_24, corr11 )
        VUPKLSB( C2_24, corr21 )
        VUPKLSB( C3_24, corr31 )
/**
 Outer loop for each physical user
**/
LABEL( oloop )
/* { */
        DECR( Num_phys_users )
        LBZU( ptov_count, Ptov_map, PTOV_BUMP_1 )
        BEQ_CR( OLOOP_BIT, ret )
        LVX( X0, 0, X_bf )
        LVX( X8, X_bf, indx1 )
        SRWI_C( icount, ptov_count, 1 )
        LVX( X16, X_bf, indx2 )
        LVX( X24, X_bf, indx3 )
        ADDI( X_bf, X_bf, X_BUMP_64 )
        CMPWI_CR( OLOOP_BIT, Num_phys_users, 0 )
        BEQ_MINUS( one_sum )
/**
 Top of sum loop
 Produces four sums each pass
**/
LABEL( iloop )
/* { */
        PREFETCH( dstp, dst_code, 0 )
        LOAD_CORR( corr00, 0, Corr0_bf )
        DECR_C( icount )
        LOAD_CORR( corr10, Corr0_bf, indx2 )
        VMSUMSHS( sum0, C0_0, X0, zero )
        LOAD_CORR( corr20, 0, Corr1_bf )
        VMSUMSHS( sum1, C1_0, X0, zero )
        LOAD_CORR( corr30, Corr1_bf, indx2 )
        LOAD_CORR( corr01, Corr0_bf, indx1 )
        VMSUMSHS( sum2, C2_0, X0, zero )
        LOAD_CORR( corr11, Corr0_bf, indx3 )
        LOAD_CORR( corr21, Corr1_bf, indx1 )
        VMSUMSHS( sum3, C3_0, X0, zero )
        VUPKHSB( C0_0, corr00 )
        VMSUMSHS( sum0, C0_8, X8, sum0 )
        VUPKHSB( C1_0, corr10 )
        ADDI( R_sump0, R_sump0, RSUM_BUMP_8 )
        VUPKHSB( C2_0, corr20 )
        VMSUMSHS( sum1, C1_8, X8, sum1 )
        VUPKHSB( C3_0, corr30 )
        VMSUMSHS( sum2, C2_8, X8, sum2 )
        VUPKLSB( C0_8, corr00 )
        VMSUMSHS( sum3, C3_8, X8, sum3 )
        ADDI( Corr0_bf, Corr0_bf, CORR_BUMP_64 )
        LOAD_CORR( corr31, Corr1_bf, indx3 ) /* corr00, corr31 same register */
        VUPKLSB( C1_8, corr10 )
        VMSUMSHS( sum0, C0_16, X16, sum0 )
        VUPKLSB( C2_8, corr20 )
        VMSUMSHS( sum1, C1_16, X16, sum1 )
        VUPKLSB( C3_8, corr30 )
        ADDI( R_sump1, R_sump1, RSUM_BUMP_8 )
        VUPKHSB( C0_16, corr01 )
        VMSUMSHS( sum2, C2_16, X16, sum2 )
```

4

gen_r_sums2.mac

```
        VUPKHSB( C1 16, corr11 )
        VMSUMSHS( sum3, C3 16, X16, sum3 )
        VUPKHSB( C2 16, corr21 )
        VMSUMSHS( sum0, C0 24, X24, sum0 )
        ADDI( Corr1 bf, Corr1 bf, CORR BUMP_64 )
        VMSUMSHS( sum1, C1 24, X24, sum1 )
        VUPKHSB( C3 16, corr31 )
        VMSUMSHS( sum2, C2 24, X24, sum2 )
        VUPKLSB( C0 24, corr01 )
        VMSUMSHS( sum3, C3 24, X24, sum3 )
        VSUMSWS( sum0, sum0, zero )
        VUPKLSB( C1 24, corr11 )
        VSUMSWS( sum1, sum1, zero )
        VUPKLSB( C2 24, corr21 )
        VSUMSWS( sum2, sum2, zero )
        VUPKLSB( C3 24, corr31 )
        VSPLTW( sum0, sum0, 3 )
        VSUMSWS( sum3, sum3, zero )
        VSPLTW( sum1, sum1, 3 )
        STVEWX( sum0, 0, R sump0 )
        VSPLTW( sum2, sum2, 3 )
        STVEWX( sum1, R sump0, sindex1 )
        VSPLTW( sum3, sum3, 3 )
        STVEWX( sum2, 0, R sump1 )
        STVEWX( sum3, R_sump1, sindex1 )
/* } */
    BNE( iloop )

/**
 Drop out, check for remainders
**/
    ANDI_C(icount, ptov_count, 0x1)
    BEQ( oloop )
/**
 One more sum:
 Enters and exits with two coor vectors are loaded and expanded to 16 bit
**/
LABEL( one sum )
    VMSUMSHS( sum0, C0 0, X0, zero )
    ADDI( R sump0, R sump0, RSUM BUMP_8 )
    VMSUMSHS( sum2, C2 0, X0, zero )
    ADDI( R sump1, R sump1, RSUM BUMP_8 )
    VMSUMSHS( sum0, C0 8, X8, sum0 )
    VMSUMSHS( sum2, C2 8, X8, sum2 )
    VMSUMSHS( sum0, C0 16, X16, sum0 )
    VMSUMSHS( sum2, C2 16, X16, sum2 )
    VMSUMSHS( sum0, C0 24, X24, sum0 )
    VMSUMSHS( sum2, C2 24, X24, sum2 )
    VSUMSWS( sum0, sum0, zero )
    VSUMSWS( sum2, sum2, zero )

    VSPLTW( sum0, sum0, 3 )
    STVEWX( sum0, 0, R sump0 )
    VSPLTW( sum2, sum2, 3 )
    STVEWX( sum2, 0, R sump1 )
    ADDI( R_sump0, R_sump0, -RSUM_BUMP_4 )   /* pre-dec pointers for loop
    reentry */
    ADDI( R_sump1, R_sump1, -RSUM_BUMP_4 )
/**
 Setup for loop re-entry: corr00 consumed in one_sum section
        exit ptr v
 corr00  corr10  corr00  corr10
        corr00  corr10  corr00  corr10
            re-entry ptr ^
**/
    VMR( corr21, corr31 )   /* corr00, corr31 same register */
    VMR( corr00, corr10 )
```

5

```
            LOAD_CORR( corr10, 0, Corr0_bf )
            VMR( corr01, corr11 )
            LOAD_CORR( corr11, Corr0_bf, indx1 )
            VMR( corr20, corr30 )
            LOAD_CORR( corr30, 0, Corr1_bf )

            VUPKHSB( C0 0, corr00 )
            VUPKLSB( C0 8, corr00 )
            LOAD CORR( corr31, Corr1_bf, indx1 ) /* corr00, corr31 same register */
            VUPKHSB( C1 0, corr10 )
            VUPKLSB( C1 8, corr10 )
            VUPKHSB( C2 0, corr20 )
            VUPKLSB( C2 8, corr20 )
            VUPKHSB( C3 0, corr30 )
            VUPKLSB( C3_8, corr30 )

            VUPKHSB( C0 16, corr01 )
            ADDI( Corr0 bf, Corr0 bf, CORR_BUMP_32 )
            VUPKLSB( C0 24, corr01 )
            ADDI( Corr1 bf, Corr1 bf, CORR_BUMP_32 )
            VUPKHSB( C1 16, corr11 )
            VUPKLSB( C1 24, corr11 )
            VUPKHSB( C2 16, corr21 )
            VUPKLSB( C2 24, corr21 )
            VUPKHSB( C3 16, corr31 )
            VUPKLSB( C3_24, corr31 )
    /* } */
        BR( oloop )
    /**
     Exit routine
    **/
    LABEL( ret )
        FREE THRU v31( VRSAVE_COND )
        REST r13_r17
        RETURN
    FUNC_EPILOG
```

6

```
/*-------------------------------------------------------------------+
|--- MC Standard Algorithms -- PPC Macro language Version    ---|
|-------------------------------------------------------------------|
|                                                                   |
| File Name:    GEN X ROW.MAC                                       |
| Description:  2 Complex scalers (4x1) 2 complex vectors (4xN)     |
|               16 bit complex multiplication producing a 16        |
|               bit complex vector of length 16*N.                  |
|                                                                   |
| Entry/params: GEN_X_ROW (A1, A2, C, Phys_index, N)                |
|                                                                   |
| Formula:                                                          |
|                                                                   |
| for ( i = 0; i < tot_phys_users; i++ ) {                          |
|                                                                   |
|   in mpath1p = mpath1 bf + (i * N FINGERS MAX);                   |
|   in_mpath2p = mpath2_bf + (i * N_FINGERS_MAX);                   |
|                                                                   |
|   j = 0;                                                          |
|   for ( q1 = 0; q1 < N_FINGERS_MAX; q1++ ) {                      |
|                                                                   |
|     s1r = (BF32)out mpath1p[q1].real;                             |
|     s1i = (BF32)out mpath1p[q1].imag;                             |
|     s2r = (BF32)out mpath2p[q1].real;                             |
|     s2i = (BF32)out_mpath2p[q1].imag;                             |
|                                                                   |
|     for ( q = 0; q < N_FINGERS_MAX; q++ ) {                       |
|                                                                   |
|       a1r = (BF32)in mpath1p[q].real;                             |
|       a1i = (BF32)in mpath1p[q].imag;                             |
|       a2r = (BF32)in mpath2p[q].real;                             |
|       a2i = (BF32)in_mpath2p[q].imag;                             |
|                                                                   |
|       cr = (a1r * s1r) + (a1i * s1i);                             |
|       ci = (a1r * s1i) - (a1i * s1r);                             |
|       cr += (a2r * s2r) + (a2i * s2i);                            |
|       ci += (a2r * s2i) - (a2i * s2r);                            |
|                                                                   |
|       X_bf[i * N_FINGERS_MAX_SQUARED + j].real                    |
|                                = (BF16)(cr >> 16);                |
|       X_bf[i * N_FINGERS_MAX_SQUARED + j].imag                    |
|                                = (BF16)(ci >> 16);                |
|                                                                   |
|       ++j;                                                        |
|     }                                                             |
|   }                                                               |
| }                                                                 |
|              Mercury Computer Systems, Inc.                       |
|              Copyright (c) 2000  All rights reserved              |
|                                                                   |
|   Revision      Date     Engineer  Reason                         |
|   --------      ----     --------  --------                       |
|     0.0        000907      fpl     Created                        |
+-------------------------------------------------------------------*/

#include "salppc.inc"

#define LOG N FINGERS MAX   2
#define LOG ELEMENT_SIZE   2
#define INDEX_SHIFT  (LOG_N_FINGERS_MAX + LOG_ELEMENT_SIZE)

/**
 Local read-only Permute vector table
**/

RODATA_SECTION( 6 )
```

1

gen_x_row.mac

```
START_L_ARRAY( local_table )

L_PERMUTE_MASK( 0x02031011, 0x06071415, 0x0a0b1819, 0x0e0f1c1d )

/**
 32 -> 16 bit: select the 16 MSBs of each 32 bit field
**/
L_PERMUTE_MASK( 0x00011011, 0x04051415, 0x08091819, 0x0c0d1c1d )

END_ARRAY

/**
 API registers
**/
#define A1        r3
#define A2        r4
#define C         r5
#define Phys_index r6
#define N         r7
/**
 Integer loop registers
**/
#define Cp0    C
#define Cp1    r8
#define sptr1  r8
#define Cp2    r9
#define sptr2  r9
#define Cp3    r10
#define tptr   r10
#define cindex r11
#define aindex r12
#define index  r12


/**
 G4 registers
**/
#define cr00 v0
#define cr01 v1
#define cr02 v2
#define cr03 v3

#define vtmp0 v0
#define vtmp2 v2

#define ci00 v4
#define ci01 v5
#define ci02 v6
#define ci03 v7

#define sr00 v8
#define sr01 v9
#define sr02 v10
#define sr03 v11

#define si00 v12
#define si01 v13
#define si02 v14
#define si03 v15

#define sr10 v16
#define sr11 v17
#define sr12 v18
#define sr13 v19

#define si10 v20
#define si11 v21
#define si12 v22
```

2

gen_x_row.mac   2/23/2001

```
#define si13 v23

#define c0 v24
#define c1 v24
#define c2 v25
#define c3 v26

#define a00 v27
#define a10 v27
#define a01 v28
#define a11 v29

#define sval v28
#define neg_sval v29

#define vc v30
#define zero v31

/**
 Begin code text
**/
FUNC PROLOG
ENTRY 5( gen X row, A1, A2, C, Phys_index, N )
  USE_THRU_v31( VRSAVE_COND )
/**
 Load up complex scaler
 sval = sr0 si0  sr1 si1  sr2 si2  sr3 si3
**/
   LA( tptr, local table, 0 )
   VXOR( zero, zero, zero )
   LI(index, 0)
/**
 Byte offset into 16 bit complex vector
**/
   SLWI( Phys index, Phys index, INDEX_SHIFT )
   ADD( sptr1, A1, Phys index )
   ADD( sptr2, A2, Phys_index )
/**
 Load up first scaler:
 if sval = sr0,si0 sr1,si1 sr2,si2 sr3,si3
         = s0 s1 s2 s3
**/
   LVX( sval, sptr1, index ) /* read 4 16 bit complex values */
   VSUBSHS( neg sval, zero, sval ) /* negate complex scaler values */
   VMRGHW(vtmp0, sval, sval)       /* vtmp0 = s0 s0 s1 s1 */
   VMRGLW(vtmp2, sval, sval)       /* vtmp2 = s2 s2 s3 s3 */
   VMRGHW(sr00, vtmp0, vtmp0) /* sr0 = s0 s0 s0 s0 */
   VMRGLW(sr01, vtmp0, vtmp0) /* sr1 = s1 s1 s1 s1 */
   VMRGHW(sr02, vtmp2, vtmp2) /* sr2 = s2 s2 s2 s2 */
   VMRGLW(sr03, vtmp2, vtmp2) /* sr3 = s3 s3 s3 s3 */
/**
  if neg sval = sr0,si0 sr1,si1 sr2,si2 sr3,si3
  after perm:
          = si0,-sr0 si1,-sr1 si2,-sr2 si3,-sr3
          = ns0 ns1 ns2 ns3
**/
   LVX( vc, tptr, index )
   VPERM( neg sval, sval, neg sval, vc ) /* si -sr */
   VMRGHW(vtmp0, neg sval, neg sval) /* vtmp0 = ns0 ns0 ns1 ns1 */
   VMRGLW(vtmp2, neg sval, neg sval) /* vtmp2 = ns2 ns2 ns3 ns3 */
   VMRGHW(si00, vtmp0, vtmp0) /* si0 = ns0 ns0 ns0 ns0 */
   VMRGLW(si01, vtmp0, vtmp0) /* si1 = ns1 ns1 ns1 ns1 */
   VMRGHW(si02, vtmp2, vtmp2) /* si2 = ns2 ns2 ns2 ns2 */
   VMRGLW(si03, vtmp2, vtmp2) /* si3 = ns3 ns3 ns3 ns3 */

/**
 Load up second scaler:
```

3

gen_x_row.mac

```
**/
   LVX( sval, sptr2, index ) /* read 4 16 bit complex values */
   ADDI(index, index, 16)
   VSUBSHS( neg sval, zero, sval ) /* negate complex scaler values */
   VMRGHW(vtmp0, sval, sval)      /* vtmp0 = s0 s0 s1 s1 */
   VMRGLW(vtmp2, sval, sval)      /* vtmp2 = s2 s2 s3 s3 */
   VMRGHW(sr10, vtmp0, vtmp0) /* sr0 = s0 s0 s0 s0 */
   VMRGLW(sr11, vtmp0, vtmp0) /* sr1 = s1 s1 s1 s1 */
   VMRGHW(sr12, vtmp2, vtmp2) /* sr2 = s2 s2 s2 s2 */
   VMRGLW(sr13, vtmp2, vtmp2) /* sr3 = s3 s3 s3 s3 */

   VPERM( neg sval, sval, neg sval, vc ) /* si -sr */
   VMRGHW(vtmp0, neg sval, neg sval) /* vtmp0 = ns0 ns0 ns1 ns1 */
   VMRGLW(vtmp2, neg sval, neg sval) /* vtmp2 = ns2 ns2 ns3 ns3 */
   VMRGHW(si10, vtmp0, vtmp0) /* si0 = ns0 ns0 ns0 ns0 */
   VMRGLW(si11, vtmp0, vtmp0) /* si1 = ns1 ns1 ns1 ns1 */
   VMRGHW(si12, vtmp2, vtmp2) /* si2 = ns2 ns2 ns2 ns2 */
   VMRGLW(si13, vtmp2, vtmp2) /* si3 = ns3 ns3 ns3 ns3 */
/**
 Assign loop pointers and index registers:
 Loop permute control vector assumes 16 bit input vectors
 C[] -> 16 x N complex elements
 A[] -> 4 x N complex elements
 N -> 4 byte (i.e. interleaved complex) elements
**/
   LVX( vc, tptr, index ) /* interleaves 16 MSBs of real, imaginary */
   LI(aindex, 0)
   LI(cindex, 0)
   ADDI( Cp1, C, 16 )
   ADDI( Cp2, C, 32 )
   ADDI( Cp3, C, 48 )
/**
 Start up loop code:
 Each read on A[] brings in 4 complex input values
**/
   LVX( a00, A1, aindex )
   DECR_C(N)
   LVX( a01, A2, aindex )
   ADDI(aindex, aindex, 16)

   VMSUMSHS( cr00, sr00, a00, zero )
   VMSUMSHS( ci00, si00, a00, zero )
   VMSUMSHS( cr01, sr01, a00, zero )
   VMSUMSHS( ci01, si01, a00, zero )
   VMSUMSHS( cr02, sr02, a00, zero )
   VMSUMSHS( ci02, si02, a00, zero )
   VMSUMSHS( cr03, sr03, a00, zero )
   VMSUMSHS( ci03, si03, a00, zero )
   BEQ( do1 )

   DECR_C(N)
   LVX( a10, A1, aindex )  /* read input for next pass */
   VMSUMSHS( cr00, sr10, a01, cr00 )
   VMSUMSHS( ci00, si10, a01, ci00 )
   LVX( a11, A2, aindex )
   VMSUMSHS( cr01, sr11, a01, cr01 )
   BR( mid_loop0 )
/**
 Top of double loop
**/
LABEL( loop0 )
/* { */
   VMSUMSHS( cr00, sr00, a00, zero )
   VMSUMSHS( ci00, si00, a00, zero )
   VPERM( c2, cr02, ci02, vc )
   STVX( c1, Cp1, cindex )
   VMSUMSHS( cr01, sr01, a00, zero )
```

4

```
                gen_x_row.mac
            DECR C(N)
            VMSUMSHS( ci01, si01, a00, zero )
            VMSUMSHS( cr02, sr02, a00, zero )
            VMSUMSHS( ci02, si02, a00, zero )
            VPERM( c3, cr03, ci03, vc )
            STVX( c2, Cp2, cindex )
            VMSUMSHS( cr03, sr03, a00, zero )
            VMSUMSHS( ci03, si03, a00, zero )
            LVX( a10, A1, aindex )  /* read input for next pass */
            VMSUMSHS( cr00, sr10, a01, cr00 )
            VMSUMSHS( ci00, si10, a01, ci00 )
            LVX( a11, A2, aindex )
            STVX( c3, Cp3, cindex )
            VMSUMSHS( cr01, sr11, a01, cr01 )
            ADDI(cindex, cindex, 64)
        LABEL( mid loop0 )
            VMSUMSHS( ci01, si11, a01, ci01 )
            VMSUMSHS( cr02, sr12, a01, cr02 )
            VPERM( c0, cr00, ci00, vc ) /* begin permute cycle for this pass */
            STVX( c0, Cp0, cindex ) /* begin write cycle from last pass */
            VMSUMSHS( ci02, si12, a01, ci02 )
            ADDI(aindex, aindex, 16)
            VMSUMSHS( cr03, sr13, a01, cr03 )
            VMSUMSHS( ci03, si13, a01, ci03 )
            VPERM( c1, cr01, ci01, vc )
        /* } */
          BNE( loop1 )
        /**
         Drop out to flush
        **/
            VMSUMSHS( cr00, sr00, a10, zero )
            VMSUMSHS( ci00, si00, a10, zero )
            VPERM( c2, cr02, ci02, vc )
            STVX( c1, Cp1, cindex )
            VMSUMSHS( cr01, sr01, a10, zero )
            VMSUMSHS( ci01, si01, a10, zero )
            VMSUMSHS( cr02, sr02, a10, zero )
            VMSUMSHS( ci02, si02, a10, zero )
            VPERM( c3, cr03, ci03, vc )
            STVX( c2, Cp2, cindex )
            VMSUMSHS( cr03, sr03, a10, zero )
            VMSUMSHS( ci03, si03, a10, zero )
            VMSUMSHS( cr00, sr10, a11, cr00 )
            VMSUMSHS( ci00, si10, a11, ci00 )
            STVX( c3, Cp3, cindex )
            VMSUMSHS( cr01, sr11, a11, cr01 )
            ADDI(cindex, cindex, 64)
            VMSUMSHS( ci01, si11, a11, ci01 )
            VMSUMSHS( cr02, sr12, a11, cr02 )
            VPERM( c0, cr00, ci00, vc ) /* begin permute cycle for this pass */
            STVX( c0, Cp0, cindex ) /* begin write cycle from last pass */
            VMSUMSHS( ci02, si12, a11, ci02 )
            VMSUMSHS( cr03, sr13, a11, cr03 )
            VMSUMSHS( ci03, si13, a11, ci03 )
            VPERM( c1, cr01, ci01, vc )

            VPERM( c2, cr02, ci02, vc )
            STVX( c1, Cp1, cindex )
            VPERM( c3, cr03, ci03, vc )
            STVX( c2, Cp2, cindex )
            STVX( c3, Cp3, cindex )
            BR( ret )
        /**
         Top of second loop
        **/
        LABEL( loop1 )
        /* { */
```

5

gen_x_row.mac

```
        VMSUMSHS( cr00, sr00, a10, zero )
        VMSUMSHS( ci00, si00, a10, zero )
        VPERM( c2, cr02, ci02, vc )
        STVX( c1, Cp1, cindex )
        VMSUMSHS( cr01, sr01, a10, zero )
        DECR C(N)
        VMSUMSHS( ci01, si01, a10, zero )
        VMSUMSHS( cr02, sr02, a10, zero )
        VMSUMSHS( ci02, si02, a10, zero )
        VPERM( c3, cr03, ci03, vc )
        STVX( c2, Cp2, cindex )
        VMSUMSHS( cr03, sr03, a10, zero )
        VMSUMSHS( ci03, si03, a10, zero )
        LVX( a00, A1, aindex )    /* read input for next pass */
        VMSUMSHS( cr00, sr10, a11, cr00 )
        VMSUMSHS( ci00, si10, a11, ci00 )
        LVX( a01, A2, aindex )
        STVX( c3, Cp3, cindex )
        VMSUMSHS( cr01, sr11, a11, cr01 )
        ADDI(cindex, cindex, 64)
        VMSUMSHS( ci01, si11, a11, ci01 )
        VMSUMSHS( cr02, sr12, a11, cr02 )
        VPERM( c0, cr00, ci00, vc ) /* begin permute cycle for this pass */
        STVX( c0, Cp0, cindex ) /* begin write cycle from last pass */
        VMSUMSHS( ci02, si12, a11, ci02 )
        ADDI(aindex, aindex, 16)
        VMSUMSHS( cr03, sr13, a11, cr03 )
        VMSUMSHS( ci03, si13, a11, ci03 )
        VPERM( c1, cr01, ci01, vc )
    /* } */
      BNE( loop0 )
    /**
     Flush loop
    **/
        VMSUMSHS( cr00, sr00, a00, zero )
        VMSUMSHS( ci00, si00, a00, zero )
        VPERM( c2, cr02, ci02, vc )
        STVX( c1, Cp1, cindex )
        VMSUMSHS( cr01, sr01, a00, zero )
        VMSUMSHS( ci01, si01, a00, zero )
        VMSUMSHS( cr02, sr02, a00, zero )
        VMSUMSHS( ci02, si02, a00, zero )
        VPERM( c3, cr03, ci03, vc )
        STVX( c2, Cp2, cindex )
        VMSUMSHS( cr03, sr03, a00, zero )
        VMSUMSHS( ci03, si03, a00, zero )
        VMSUMSHS( cr00, sr10, a01, cr00 )
        VMSUMSHS( ci00, si10, a01, ci00 )
        STVX( c3, Cp3, cindex )
        VMSUMSHS( cr01, sr11, a01, cr01 )
        ADDI(cindex, cindex, 64)
        VMSUMSHS( ci01, si11, a01, ci01 )
        VMSUMSHS( cr02, sr12, a01, cr02 )
        VPERM( c0, cr00, ci00, vc ) /* begin permute cycle for this pass */
        STVX( c0, Cp0, cindex ) /* begin write cycle from last pass */
        VMSUMSHS( ci02, si12, a01, ci02 )
        VMSUMSHS( cr03, sr13, a01, cr03 )
        VMSUMSHS( ci03, si13, a01, ci03 )
        VPERM( c1, cr01, ci01, vc )

        VPERM( c2, cr02, ci02, vc )
        STVX( c1, Cp1, cindex )
        VPERM( c3, cr03, ci03, vc )
        STVX( c2, Cp2, cindex )
        STVX( c3, Cp3, cindex )
        BR( ret )
```

6

```
LABEL( do1 )
    VMSUMSHS( cr00, sr10, a01, cr00 )
    VMSUMSHS( ci00, si10, a01, ci00 )
    VMSUMSHS( cr01, sr11, a01, cr01 )
    VMSUMSHS( ci01, si11, a01, ci01 )
    VMSUMSHS( cr02, sr12, a01, cr02 )
    VPERM( c0, cr00, ci00, vc )  /* begin permute cycle for this pass */
    STVX( c0, Cp0, cindex )  /* begin write cycle from last pass */
    VMSUMSHS( ci02, si12, a01, ci02 )
    VMSUMSHS( cr03, sr13, a01, cr03 )
    VMSUMSHS( ci03, si13, a01, ci03 )
    VPERM( c1, cr01, ci01, vc )
    VPERM( c2, cr02, ci02, vc )
    STVX( c1, Cp1, cindex )
    VPERM( c3, cr03, ci03, vc )
    STVX( c2, Cp2, cindex )
    STVX( c3, Cp3, cindex )

/**
 Return
**/
LABEL( ret )
    FREE THRU_v31( VRSAVE_COND )
    RETURN
FUNC_EPILOG
```

7

```
#include "mudlib.h"

/*
 *  Return the offset in units of complex elements into the Corr0 matrix
 *  corresponding to a specified starting physical user and starting virtual
 *  user (within the starting physical user) pair.
 */
int  mudlib_get_Corr0_offset (
            unsigned char  *ptov_map,  /* no more than 256 virts. per phys */
            int   num_fingers,         /* typically, 4 */
            int   tot_virt_users,      /* sum of ptov_map over all phys users
            */
            int   start_phys_user,     /* zero-based index into ptov map */
            int   start_virt_user      /* must be < ptov_map[start_phys_user]
            */
          )
{
   int  num_Corrs, num_virt_users;

   num_virt_users = mudlib_get_num_virt_users( ptov_map, 0, 0, start_phys_user,
                                               start_virt_user ) - 1;
   num_Corrs = (num_virt_users * tot_virt_users) -
               ((num_virt_users * (num_virt_users + 1)) / 2);

   return ( num_Corrs * (num_fingers * num_fingers) );
}

/*
 *  Return the size (in bytes) of the portion of the Corr0 matrix
 *  corresponding to a specified starting physical user, virtual
 *  user (within the starting physical user) pair and an ending physical
 *  user, virtual user pair, inclusive. Elements of Corr0 are assumed
 *  to be of type COMPLEX_BF8.
 */
int  mudlib_get_Corr0_size (
            unsigned char  *ptov_map,  /* no more than 256 virts. per phys */
            int   num_fingers,         /* typically, 4 */
            int   tot_virt_users,      /* sum of ptov_map over all phys users
            */
            int   start_phys_user,     /* zero-based index into ptov map */
            int   start_virt_user,     /* must be < ptov_map[start_phys_user]
            */
            int   end_phys_user,       /* zero-based index into ptov map */
            int   end_virt_user        /* must be < ptov_map[end_phys_user] */
          )
{
   int  start_offset, end_offset;

   start_offset = mudlib_get_Corr0_offset ( ptov_map,
                                            num_fingers,
                                            tot_virt_users,
                                            start_phys_user,
                                            start_virt_user );

   MUDLIB_INCR_VIRT_USER( ptov_map, end_phys_user, end_virt_user )

   end_offset = mudlib_get_Corr0_offset ( ptov_map,
                                          num_fingers,
                                          tot_virt_users,
                                          end_phys_user,
                                          end_virt_user );

   return ( (end_offset - start_offset) * sizeof(COMPLEX_BF8) );
}
```

1

get_sizes.c   2/23/2001

```c
/*
 *  Return the offset in units of complex elements into the Corrl matrix
 *  corresponding to a specified starting physical user and starting virtual
 *  user (within the starting physical user) pair.
 */
int   mudlib get Corrl offset (
            unsigned char  *ptov_map,  /* no more than 256 virts. per phys */
            int   num fingers,         /* typically, 4 */
            int   tot_virt_users,      /* sum of ptov_map over all phys users
            */
            int   start phys user,     /* zero-based index into ptov map */
            int   start_virt_user      /* must be < ptov_map[start_phys_user]
            */
            )
{
  int   num_Corrs, num_virt_users;

   num virt users = mudlib_get_num_virt_users( ptov_map, 0, 0,
   start_phys_user,
                                        start_virt_user ) - 1;

   num_Corrs = (num_virt_users * tot_virt_users);

   return ( num_Corrs * (num_fingers * num_fingers) );
}


/*
 *  Return the size (in bytes) of the portion of the Corrl matrix
 *  corresponding to a specified starting physical user, virtual
 *  user (within the starting physical user) pair and an ending physical
 *  user, virtual user pair, inclusive. Elements of Corrl are assumed
 *  to be of type COMPLEX_BF8.
 */
int   mudlib get Corrl size (
            unsigned char  *ptov_map,  /* no more than 256 virts. per phys */
            int   num fingers,         /* typically, 4 */
            int   tot_virt_users,      /* sum of ptov_map over all phys users
            */
            int   start phys user,     /* zero-based index into ptov map */
            int   start_virt_user,     /* must be < ptov_map[start_phys_user]
            */
            int   end phys user,       /* zero-based index into ptov map */
            int   end_virt_user        /* must be < ptov_map[end_phys_user] */
            )
{
  int   start_offset, end_offset;

   start_offset = mudlib_get_Corrl_offset ( ptov map,
                                            num fingers,
                                            tot virt users,
                                            start phys user,
                                            start_virt_user );

     MUDLIB_INCR_VIRT_USER( ptov_map, end_phys_user, end_virt_user )

   end_offset = mudlib_get_Corrl_offset ( ptov map,
                                          num fingers,
                                          tot virt users,
                                          end phys user,
                                          end_virt_user );

   return ( (end_offset - start_offset) * sizeof(COMPLEX_BF8) );
}


/*
 *  Return the offset into the R0 matrix corresponding to a specified
 *  starting physical user and starting virtual user (within the
 *  starting physical user) pair.
```

2

```
                     */
           int   mudlib get R0 offset (
                   unsigned char  *ptov_map,  /* no more than 256 virts. per phys */
                   int  tot_virt_users,       /* sum of ptov_map over all phys users
                   */
                   int  start phys user,      /* zero-based index into ptov map */
                   int  start_virt_user       /* must be < ptov_map[start_phys_user]
                   */
                   )
           {
             int  i, num_virt_users, offset, tcols;

             tcols = (tot virt users + R MATRIX ALIGN MASK) & ~R MATRIX ALIGN_MASK;
             num virt users = mudlib_get_num_virt_users( ptov_map, 0, 0,
             start_phys_user,
                                                    start_virt_user ) - 1;

             offset = 0;
             for ( i = 0; i < num_virt_users; i++ )
               offset += (tcols - (i & ~R_MATRIX_ALIGN_MASK));
             return offset;
           }


           /*
            *  Return the size (in bytes) of the portion of the R0 matrix
            *  corresponding to a specified starting physical user, virtual
            *  user (within the starting physical user) pair and an ending physical
            *  user, virtual user pair, inclusive. Elements of R0 are assumed
            *  to be of type BF8.
            */
           int   mudlib get R0 size (
                   unsigned char  *ptov_map,  /* no more than 256 virts. per phys */
                   int  tot_virt_users,       /* sum of ptov_map over all phys users
                   */
                   int  start phys user,      /* zero-based index into ptov map */
                   int  start_virt_user,      /* must be < ptov_map[start_phys_user]
                   */
                   int  end phys user,        /* zero-based index into ptov map */
                   int  end_virt_user         /* must be < ptov_map[end_phys_user] */
                   )
           {
             int  start_offset, end_offset;

             start_offset = mudlib_get_R0_offset ( ptov map,
                                                 tot virt users,
                                                 start phys user,
                                                 start_virt_user );

             MUDLIB_INCR_VIRT_USER( ptov_map, end_phys_user, end_virt_user )

             end_offset = mudlib_get_R0_offset ( ptov map,
                                                 tot virt users,
                                                 end phys user,
                                                 end_virt_user );

             return ( (end_offset - start_offset) * sizeof(BF8) );
           }

           /*
            *  Return the offset into the R1 matrix corresponding to a specified
            *  starting physical user and starting virtual user (within the
            *  starting physical user) pair.
            */
           int   mudlib get R1 offset (
                   unsigned char  *ptov_map,  /* no more than 256 virts. per phys */
                   int  tot_virt_users,       /* sum of ptov_map over all phys users
                   */
                   int  start_phys_user,      /* zero-based index into ptov_map */
```

3

```
                    int   start_virt_user        /* must be < ptov_map[start_phys_user]
                    */
                )
{
  int   num_virt_users, tcols;

  tcols = (tot virt users + R MATRIX ALIGN MASK) & ~R MATRIX ALIGN_MASK;
  num virt users = mudlib_get_num_virt_users( ptov_map, 0, 0,
  start_phys_user,
                                              start_virt_user ) - 1;

  return ( num_virt_users * tcols );
}

/*
 *  Return the size (in bytes) of the portion of the R1 matrix
 *  corresponding to a specified starting physical user, virtual
 *  user (within the starting physical user) pair and an ending physical
 *  user, virtual user pair, inclusive. Elements of R1 are assumed
 *  to be of type BF8.
 */
int   mudlib get R1 size (
                unsigned char  *ptov_map, /* no more than 256 virts. per phys */
                int   tot_virt_users,     /* sum of ptov_map over all phys users
                */
                int   start phys user,    /* zero-based index into ptov map */
                int   start_virt_user,    /* must be < ptov_map[start_phys_user]
                */
                int   end phys user,      /* zero-based index into ptov map */
                int   end_virt_user       /* must be < ptov_map[end_phys_user] */
            )
{
  int   start_offset, end_offset;

  start_offset = mudlib_get_R1_offset ( ptov map,
                                        tot virt users,
                                        start phys user,
                                        start_virt_user );

  MUDLIB_INCR_VIRT_USER( ptov_map, end_phys_user, end_virt_user )

  end_offset = mudlib_get_R1_offset ( ptov map,
                                      tot virt users,
                                      end phys user,
                                      end_virt_user );

  return ( (end_offset - start_offset) * sizeof(BF8) );
}

/*
 *  Return the number of virtual users
 *  corresponding to a specified starting physical user, virtual
 *  user (within the starting physical user) pair and an ending physical
 *  user, virtual user pair, inclusive.
 */
int   mudlib get num_virt_users (
                unsigned char  *ptov map, /* no more than 256 virts. per phys */
                int   start phys user,    /* zero-based index into ptov map */
                int   start_virt_user,    /* must be < ptov_map[start_phys_user]
                */
                int   end phys user,      /* zero-based index into ptov map */
                int   end_virt_user       /* must be < ptov_map[end_phys_user] */
            )
{
  int   i, num_virt_users;

  if ( start_phys user == end phys user )
    return ( end_virt_user - start_virt_user + 1 );
```

4

```c
      else {
        num_virt users = ptov map[start phys_user] - start virt_user;
        for ( i = (start_phys user + 1); i < end_phys_user; i++ )
          num virt users += ptov map[i];
        num virt_users += (end virt_user + 1);
        return ( num_virt_users );
      }
    }

/*
 *  For a specified starting physical user, virtual user
 *  (within the starting physical user) pair and a specified
 *  number of virtual users inclusive of the starting pair,
 *  return (in separate arguments), the corresponding ending
 *  physical user, virtual user pair (inclusive).
 */
void  mudlib get end user_pair (
            unsigned char  *ptov map,  /* no more than 256 virts. per phys */
            int   start phys user,     /* zero-based index into ptov map */
            int   start_virt_user,     /* must be < ptov_map[start_phys_user]
            */
            int   num virt users,      /* number from start (must be > 0) */
            int   *end phys user,      /* zero-based index into ptov map */
            int   *end_virt_user       /* will be < ptov_map[*end_phys_user] */
          )
{
  int  i, j;

  for ( i = start phys user; ; i++ ) {
    for ( j = start virt user; j < ptov map[i]; j++ )
      if ( --num virt users == 0 ) break;
    if ( num virt users == 0 ) break;
    start_virt_user = 0;
  }

  *end phys user = i;
  *end_virt_user = j;
}
```

5

```c
#include "mudlib.h"


/**************************************************************************
 * Virtual users version
 **************************************************************************/

int  mudlib get Corr0 offset v (
            unsigned char  *ptov_map, /* no more than 256 virts. per phys */
            int   num fingers,        /* typically, 4 */
            int   tot_virt_users,     /* sum of ptov_map over all phys users
            */
            int   start phys user,    /* zero-based index into ptov map */
            int   start_virt_user     /* must be < ptov_map[start_phys_user]
            */
            )
{
  int  i, num_fingers_squared, remaining_size, skipped_virt_users,
  total_size;

  num fingers squared = num_fingers * num_fingers;
  skipped_virt_users = 0;

  for ( i = 0; i < start phys user; i++ )
    skipped_virt_users += (int)ptov_map[i];

  skipped_virt_users += start_virt_user;

  // Always even
  total size = tot_virt users * ( tot_virt users - 1 );
  remaining_size = ( tot virt users - skipped virt users )
                  * ( tot_virt_users - skipped_virt_users - 1 );

  // zero based units of complex elements
  return ( num_fingers_squared * ( ( total_size - remaining_size ) >> 1 ) );
}


int   mudlib get Corr1 offset v (
            unsigned char  *ptov_map, /* no more than 256 virts. per phys */
            int   num fingers,        /* typically, 4 */
            int   tot_virt_users,     /* sum of ptov_map over all phys users
            */
            int   start phys user,    /* zero-based index into ptov map */
            int   start_virt_user     /* must be < ptov_map[start_phys_user]
            */
            )
{
  int  i, num_fingers_squared, skipped_virt_users;

  num fingers squared = num_fingers * num_fingers;
  skipped_virt_users = 0;

  for ( i = 0; i < start phys user; i++ )
    skipped_virt_users += (int)ptov_map[i];

  skipped_virt_users += start_virt_user;

  return ( num_fingers_squared * ( skipped_virt_users * tot_virt_users ) );
}


int   mudlib get R0 offset_v (
            unsigned char  *ptov_map, /* no more than 256 virts. per phys */
            int   tot_virt_users,     /* sum of ptov_map over all phys users
            */
```

1

```
            get_sizes_v.c                                        2/23/2001
                       int   start phys user,      /* zero-based index into ptov map */
                       int   start_virt_user       /* must be < ptov_map[start_phys_user]
                       */
                    )
        {
          int   i, iv;
          int   R0_skipped_virt_users, R0_tcols, tcols, size;

          tcols = (tot_virt_users + R_MATRIX_ALIGN_MASK) & ~R_MATRIX_ALIGN_MASK;

          R0_skipped_virt_users = 0;

          size = 0;

          for ( i = 0; i < start phys user; i++ ) {
            for ( iv = 0; iv < (int)ptov_map[i]; iv++ ) {

              R0_tcols = tcols - (R0_skipped_virt_users & ~R_MATRIX_ALIGN_MASK);

              size += R0 tcols;
              ++R0_skipped_virt_users;
            }
          }

          /* Handle last physical user, potentially split on virt users */

          for ( iv = 0; iv < (int) start_virt_user; iv++ ) {

            R0_tcols = tcols - (R0_skipped_virt_users & ~R_MATRIX_ALIGN_MASK);

            size += R0 tcols;
            ++R0_skipped_virt_users;
          }

          return size;
        }


        int   mudlib get R0 size v (
                   unsigned char   *ptov_map, /* no more than 256 virts. per phys */
                   int   tot_virt_users,      /* sum of ptov_map over all phys users
                   */
                   int   start phys user,      /* zero-based index into ptov map */
                   int   start_virt_user,      /* must be < ptov_map[start_phys_user]
                   */
                   int   end phys user,        /* zero-based index into ptov map */
                   int   end_virt_user        /* must be < ptov_map[end_phys_user] */
                 )
        {
          int   i, iv;
          int   R0_skipped_virt_users, R0_tcols, tcols, size;

          tcols = (tot_virt_users + R_MATRIX_ALIGN_MASK) & ~R_MATRIX_ALIGN_MASK;

          R0 skipped virt users = 0;
          for ( i = 0; i < start phys user; i++ )
            R0_skipped_virt_users += (int)ptov_map[i];

          R0_skipped_virt_users += start_virt_user;

          // printf("skipped:  %d\n", R0_skipped_virt_users);

          size = 0;

          if ( start_phys_user == end_phys_user )
          {
            //    printf("start == end phys\n");
```

2

```c
     // <= for Inclusive
     for ( iv = start_virt_user; iv <= (int) end_virt_user; iv++ ) {

        R0_tcols = tcols - (R0_skipped_virt_users & ~R_MATRIX_ALIGN_MASK);

        size += R0 tcols;
        //  printf("size:  %d, R0tc:  %d\n", size, R0_tcols);
        ++R0_skipped_virt_users;
     }
  }
  else
  {
     for ( i = start_phys_user; i < end phys user; i++ ) {
        for ( iv = 0; iv < (int)ptov_map[i]; iv++ ) {

           R0_tcols = tcols - (R0_skipped_virt_users & ~R_MATRIX_ALIGN_MASK);

           size += R0 tcols;
           //  printf("size:  %d, R0tc:  %d\n", size, R0_tcols);
           ++R0_skipped_virt_users;
        }
     }

     /* Handle last physical user, potentially split on virt users */
     //     printf("last phys user \n");
     // <= for Inclusive
     for ( iv = start_virt_user; iv <= (int) end_virt_user; iv++ ) {

        R0_tcols = tcols - (R0_skipped_virt_users & ~R_MATRIX_ALIGN_MASK);

        size += R0 tcols;
        //        printf("size:  %d, R0tc:  %d\n", size, R0_tcols);
        ++R0_skipped_virt_users;
     }
  }

  return size;
}


int  mudlib get R1 offset_v (
            unsigned char  *ptov_map, /* no more than 256 virts. per phys */
            int  tot_virt_users,      /* sum of ptov_map over all phys users
            */
            int  start phys user,     /* zero-based index into ptov map */
            int  start_virt_user      /* must be < ptov_map[start_phys_user]
            */
         )
{
  int  i, tcols, virt_users;

  tcols = (tot_virt_users + R_MATRIX_ALIGN_MASK) & ~R_MATRIX_ALIGN_MASK;

  virt_users = 0;

  // Main loop
  for ( i = 0;  i < start phys user; i++ ) {
     virt_users += (int)ptov_map[i];
  }

  // Trailing virtual users
  virt_users += start_virt_user;

  return ( virt_users * tcols );
}
```

3

get_sizes_v.c   2/23/2001

```c
int   mudlib get R1 size v (
              unsigned char  *ptov_map,  /* no more than 256 virts. per phys */
              int   tot_virt_users,      /* sum of ptov_map over all phys users
              */
              int   start phys user,     /* zero-based index into ptov map */
              int   start_virt_user,     /* must be < ptov_map[start_phys_user]
              */
              int   end phys user,       /* zero-based index into ptov map */
              int   end_virt_user        /* must be < ptov_map[end_phys_user] */
          )
{
  int  i, tcols, virt_users;

  tcols = (tot_virt_users + R_MATRIX_ALIGN_MASK) & ~R_MATRIX_ALIGN_MASK;

  virt_users = 0;

  if ( start_phys_user == end_phys_user )
  {
    virt_users = end_virt_user - start_virt_user + 1;
  }
  else if (start_phys_user < end_phys_user)
  {
    // Leading virtual users
    virt_users = (int) ptov_map[start_phys_user] - start_virt_user;

    // Main loop
    for ( i = (start phys user + 1); i < end_phys_user; i++ )
      virt_users += (int)ptov_map[i];

    // Trailing virtual users
    virt_users += (end_virt_user + 1);
  }

  return ( virt_users * tcols );
}
```

4

```
#define IO 1
#define TIME 0

//
//  Asynchronous MPIC
//
#if TIME
#include <tmr.h>
#endif

#include "mudlib.h"

void sve3_8bit( BF8 *A, BF8 *B, BF8 *C, BF32 *sum, int n );

void dotpr3_8bit( BF8 *A, BF8 *B0, BF8 *B1, BF8 *B2,
                  BF32 *sums, int N, int tcols );

void dotpr6_8bit( BF8 *A, BF8 *B0, BF8 *B1, BF8 *B2,
                  BF32 *sums, int N, int tcols );

void dotpr9_8bit( BF8 *A, BF8 *B0, BF8 *B1, BF8 *B2,
                  BF32 *sums, int N, int tcols );

#if TIME
static int time_count = 0;
static int z;
static float  time;
static TMR ts  time0, time1;
static TMR_timespec  elapsed;
#endif

/*
 *   void async multirate mpic ( BF8 *Bt hat, BF8 *R0 hat,
 *                               BF8 *R1 hat, BF8 *R1m hat,
 *                               BF32 *Y, BF32 Ythresh,
 *                               int N_users, int N_bits, int N_stages )
 *
 *   N users must be > 0 and divisible by 4
 *   N_bits must be >= 5
 */

void  mudlib_mpic ( BF8 *Bt hat,
                    BF8 *R0 hat,
                    BF8 *R1 hat,
                    BF8 *R1m_hat,
                    BF32 *Y,
                    BF32 Ythresh,
                    int N users,
                    int N bits,
                    int N_stages )

{
  BF8   *Bt hatp;
  BF8   *R0 hatp, *R1_hatp, *R1m_hatp;
  BF32   *Yp;
  BF32   R bias, sums[3];
  int   hat_tc, i, m, N_users_pad, stage;

  hat tc = (N_users + R MATRIX ALIGN MASK) & ~R MATRIX ALIGN MASK;
  N_users_pad = (N_users + ALTIVEC_ALIGN_MASK) & ~ALTIVEC_ALIGN_MASK;

#if 0
  if ( ( (long)Bt hat | (long)R0 upper bf | (long)R0 lower bf |
         (long)R1 trans bf | (long)R1m bf) & ALTIVEC ALIGN_MASK ) {
    printf ( "***** inputs are NON-ALIGNED ****\n" );
    exit( -1 );
```

1

```
        }
    #endif

        //
        //   Subtract interference in N_stages
        //
        for ( stage = 0; stage < N_stages; stage++ ) {

            R0 hatp = R0 hat;
            R1 hatp = R1 hat;
            R1m hatp = R1m_hat;
            Yp = Y;

            for ( i = 0; i < N_users; i++ ) {

                sve3_8bit( R0_hatp, R1_hatp, R1m_hatp, &R_bias, N_users_pad );

    #if 0
                R0_hatp[i] = BF8_ZERO;              /* zero diagonal element */
    #endif

                Bt hatp = Bt_hat + hat_tc;          /* points to leading row */
                m = 2;

                while ( m < (N bits-4) ) {
                    if ( BFABS( Yp[m] ) < Ythresh ) {
                        if ( BFABS( Yp[m+1] ) < Ythresh ) {
                            if ( BFABS( Yp[m+2] ) < Ythresh ) {
                                dotpr9_8bit( Bt hatp, R1 hatp, R0 hatp, R1m_hatp,
                                             sums, N_users_pad, hat_tc );
                                sums[0] -= R bias;
                                sums[1] -= ((BF32)Bt hatp[hat tc + i] * (BF32)R1_hatp[i]);
                                if ( (Yp[m] - sums[0]) > BF32 ZERO )
                                    Bt_hatp[hat_tc + i] = 1 + BIAS_8BIT;
                                else
                                    Bt hatp[hat tc + i] = -1 + BIAS 8BIT;
                                sums[1] += ((BF32)Bt_hatp[hat_tc + i] * (BF32)R1_hatp[i]);

                                sums[1] -= R bias;
                                sums[2] -= ((BF32)Bt hatp[2*hat tc + i] * (BF32)R1_hatp[i]);
                                if ( (Yp[m+1] - sums[1]) > BF32 ZERO )
                                    Bt_hatp[2*hat_tc + i] = 1 + BIAS_8BIT;
                                else
                                    Bt hatp[2*hat tc + i] = -1 + BIAS 8BIT;
                                sums[2] += ((BF32)Bt_hatp[2*hat_tc + i] * (BF32)R1_hatp[i]);

                                sums[2] -= R bias;
                                if ( (Yp[m+2] - sums[2]) > BF32 ZERO )
                                    Bt_hatp[3*hat_tc + i] = 1 + BIAS_8BIT;
                                else
                                    Bt_hatp[3*hat_tc + i] = -1 + BIAS_8BIT;
                            }
                            else {                          /* skip third sum */
                                dotpr6_8bit( Bt hatp, R1 hatp, R0 hatp, R1m_hatp,
                                             sums, N_users_pad, hat_tc );
                                sums[0] -= R bias;
                                sums[1] -= ((BF32)Bt hatp[hat tc + i] * (BF32)R1_hatp[i]);
                                if ( (Yp[m] - sums[0]) > BF32 ZERO )
                                    Bt_hatp[hat_tc + i] = 1 + BIAS_8BIT;
                                else
                                    Bt hatp[hat tc + i] = -1 + BIAS 8BIT;
                                sums[1] += ((BF32)Bt_hatp[hat_tc + i] * (BF32)R1_hatp[i]);

                                sums[1] -= R bias;
                                if ( (Yp[m+1] - sums[1]) > BF32 ZERO )
                                    Bt_hatp[2*hat_tc + i] = 1 + BIAS_8BIT;
                                else
```

2

```
                            Bt_hatp[2*hat_tc + i] = -1 + BIAS_8BIT;
                    }
#if IO
                    Bt_hatp += hat_tc;              /* bump leading row pointer */
#endif
                    ++m;                            /* bump row */
                }
                else {                              /* skip second sum */
                    dotpr3_8bit( Bt hatp, R1 hatp, R0 hatp, R1m_hatp,
                                 sums, N_users_pad, hat_tc );
                    sums[0] -= R bias;
                    if ( (Yp[m] - sums[0]) > BF32 ZERO )
                        Bt_hatp[hat_tc + i] = 1 + BIAS_8BIT;
                    else
                        Bt_hatp[hat_tc + i] = -1 + BIAS_8BIT;
                }
#if IO
                Bt_hatp += hat_tc;                  /* bump leading row pointer */
#endif
                ++m;                                /* bump row */
            }

#if IO
            Bt_hatp += hat_tc;                      /* bump leading row pointer */
#endif
            ++m;                                    /* bump row */
        }

        /*
         *  do last 0, 1 or 2 dot product calculations
         */
        while ( m < (N bits-2) ) {
            if ( BFABS( Yp[m] ) < Ythresh ) {
                dotpr3_8bit( Bt hatp, R1 hatp, R0 hatp, R1m_hatp,
                             sums, N_users_pad, hat_tc );
                sums[0] -= R bias;
                if ( (Yp[m] - sums[0]) > BF32 ZERO )
                    Bt_hatp[hat_tc + i] = 1 + BIAS_8BIT;
                else
                    Bt_hatp[hat_tc + i] = -1 + BIAS_8BIT;
            }
#if IO
            Bt_hatp += hat_tc;                      /* bump leading row pointer */
#endif
            ++m;
        }

#if IO
        R0 hatp += hat tc;                          /* bump pointer */
        R1 hatp += hat tc;                          /* bump pointer */
        R1m hatp += hat_tc;                         /* bump pointer */
        Yp += N_bits;                               /* bump pointer */
#endif
                                                    /* end of loop over N users */
        }                                           /* end of loop over N_stages */
    }
}

#if defined( COMPILE_C )

void dotpr3_8bit( BF8 *A, BF8 *B0, BF8 *B1, BF8 *B2,
                  BF32 *sums, int N, int tcols )
{
    int  j;

    sums[0] = BF32_ZERO;
    for ( j = 0; j < N; j++ ) {
```

3

Page No. 249

mpic.c   2/23/2001

```
        sums[0] += (BF32)A[j] * (BF32)B0[j];
        sums[0] += (BF32)A[tcols+j] * (BF32)B1[j];
        sums[0] += (BF32)A[(tcols<<1)+j] * (BF32)B2[j];
    }
}

void dotpr6_8bit( BF8 *A, BF8 *B0, BF8 *B1, BF8 *B2,
                  BF32 *sums, int N, int tcols )
{
    int  i, j;

    for ( i = 0; i < 2; i++ ) {
        sums[i] = BF32_ZERO;
        for ( j = 0; j < N; j++ ) {
            sums[i] += (BF32)A[i*tcols + j] * (BF32)B0[j];
            sums[i] += (BF32)A[(i+1)*tcols + j] * (BF32)B1[j];
            sums[i] += (BF32)A[(i+2)*tcols + j] * (BF32)B2[j];
        }
    }
}

void dotpr9_8bit( BF8 *A, BF8 *B0, BF8 *B1, BF8 *B2,
                  BF32 *sums, int N, int tcols )
{
    int  i, j;

    for ( i = 0; i < 3; i++ ) {
        sums[i] = BF32_ZERO;
        for ( j = 0; j < N; j++ ) {
            sums[i] += (BF32)A[i*tcols + j] * (BF32)B0[j];
            sums[i] += (BF32)A[(i+1)*tcols + j] * (BF32)B1[j];
            sums[i] += (BF32)A[(i+2)*tcols + j] * (BF32)B2[j];
        }
    }
}

void sve3_8bit( BF8 *A, BF8 *B, BF8 *C, BF32 *sum, int n )
{
    int  i;
    BF32  wsum;

    wsum = 0;
    for ( i = 0; i < n; i++ ) {
        wsum += (BF32)A[i];
        wsum += (BF32)B[i];
        wsum += (BF32)C[i];
    }
    *sum = wsum;
}

#endif
```

4

```
/*-------------------------------------------------------------+
|--- MC Standard Algorithms -- PPC Macro language Version  ---|
|-------------------------------------------------------------|
|                                                             |
|  File Name:    GEN R_MATRICES.MAC                           |
|  Description:  Float and scale R matrix values, convert to byte.|
|                                                             |
|  Entry/params: GEN_R_MATRICES( Rsump, Bf scalep, Inv scalep,|
|                                Scalep, No scale row bfp,     |
|                                Scale_row_bfp, Num_virt_users )|
|                                                             |
|  Formula:                                                   |
|                                                             |
|   bf scale = *bf scalep;                                    |
|   inv_scale = *inv_scalep;                                  |
|                                                             |
|   for ( i = 0; i < num_virt_users; i++ ) {                  |
|      scale = scalep[i];                                     |
|      fsum = (float)(R sums[i]);                             |
|      fsum *= bf_scale;                                      |
|                                                             |
|      fsum scale = fsum * inv_scale;                         |
|      fsum_scale *= scale;                                   |
|                                                             |
|      SATURATE( fsum_scale )                                 |
|      SATURATE( fsum )                                       |
|                                                             |
|      no scale row bfp[i] = BF8 FIX( fsum );                 |
|      scale_row_bfp[i] = BF8_FIX( fsum_scale );              |
|   }                                                         |
|                                                             |
|            Mercury Computer Systems, Inc.                   |
|            Copyright (c) 2000  All rights reserved          |
|                                                             |
|  Revision      Date      Engineer  Reason                   |
|  --------      ----      --------  --------                  |
|     0.0        000910       fpl    Created                  |
|     0.1        000914       fpl    Removed VMAXFP and added |
|                                    windin code              |
|     0.3        000920       fpl    Removed all windin and windout|
+-------------------------------------------------------------*/

#include "salppc.inc"

#define DO_IO  1

#if DO IO
#define   SCALE_BUMP_16   16
#else
#define   SCALE_BUMP_16   0
#endif

#define STORE_SCALE( vS, rA, rB )    STVX( vS, rA, rB )

#define ZERO_COND  6

RODATA_SECTION( 6 )

START_L_ARRAY( local_table )

/**
 First stage for byte pack
**/
L_PERMUTE_MASK( 0x0004080c, 0x1014181c, 0x0004080c, 0x1014181c )

 /**
```

gen_r_matrices.mac

```
   Second stage for byte pack
**/
L_PERMUTE_MASK( 0x00010203, 0x04050607, 0x10111213, 0x14151617 )

END_ARRAY

/**
 Input parameters
**/
#define Rsump              r3
#define Bf_scalep          r4
#define Inv_scalep         r5
#define Scalep             r6
#define No_scale_row_bfp   r7
#define Scale_row_bfp      r8
#define Num_virt_users     r9


/**
 Local GPRs
**/
#define indx1              r10
#define indx2              r11
#define indx3              r12

#define low4                r0

#define tptr               indx2
#define low4x4             low4

/**
 G4 registers
**/
#define zero               v0
#define inv_scale          v1
#define bf_scale           v2

#define byte_pack          v3
#define byte_merge         v4

#define scale0             v5
#define scale1             v6
#define vtmp               scale1
#define scale2             v7
#define vtmp2              scale2
#define scale3             v8

#define fsum0              v9
#define fsum1              v10
#define fsum2              v11
#define fsum3              v12

#define fsum_scale0        v13
#define fsum_scale1        v14
#define fsum_scale2        v15
#define fsum_scale3        v16

#define bsum0              v17
#define bsum1              v18
#define bsum2              v19
#define bsum3              v20

#define bsum_scale0        v21
#define bsum_scale1        v22
#define bsum_scale2        v23
#define bsum_scale3        v24

#define bvector            v25
```

2

gen_r_matrices.mac

```
#define bscale_vector   v26

#define rsum0           v27
#define rsum1           v28
#define rsum2           v29
#define rsum3           v30
#define seven           v31


/**
 Begin code text
**/
FUNC_PROLOG

ENTRY_7( gen R matrices, Rsump, Bf scalep, Inv scalep, Scalep, \
         No_scale_row_bfp, Scale_row_bfp, Num_virt_users )

  CMPWI( Num_virt_users, 0 )
  BGT( start )
  RETURN

LABEL( start )
  USE_THRU_v31( VRSAVE_COND )
/**
 Load up permute vectors and loop scalers
**/
  LA( tptr, local_table, 0 )
  LI( indx1, 16 )
  LVX( byte_pack, 0, tptr )
  VSPLTISB( seven, 7 )
  LVX( byte merge, tptr, indx1 )
  SCALAR SPLAT( bf scale, vtmp, Bf scalep )
  SCALAR_SPLAT( inv_scale, vtmp, Inv_scalep )


/**
 Back up to nearest 16-byte boundary. It's okay to write before and after to
 nearest 16-byte boundary in both directions.
**/
  RLWINM( low4, No scale_row_bfp, 0, 28, 31 )      /* lower 4 bits */
  VXOR( zero, zero, zero )
  ADD( Num virt users, Num virt users, low4 )
  SUB( No scale row bfp, No scale row bfp, low4 )
  SUB( Scale row bfp, Scale_row_bfp, low4 )
  SLWI( low4x4, low4, 2 )
  LI( indx2, 32 )
  SUB( Rsump, Rsump, low4x4 )


/**
 Start up loop
**/
  LVX( rsum0, 0, Rsump )
  LI( indx3, 48 )
  LVX( rsum1, Rsump, indx1 )
  SUB( Scalep, Scalep, low4x4 )
  LVX( rsum2, Rsump, indx2 )
  VCFSX( fsum0, rsum0, 0 )
  LVX( rsum3, Rsump, indx3 )
  VCFSX( fsum1, rsum1, 0 )
  LVX( scale0, 0, Scalep )
  VCFSX( fsum2, rsum2, 0 )
  LVX( scale1, Scalep, indx1 )
  VCFSX( fsum3, rsum3, 0 )
  LVX( scale2, Scalep, indx2 )
  VMADDFP( fsum0, fsum0, bf scale, zero )
  LVX( scale3, Scalep, indx3 )
  VMADDFP( fsum1, fsum1, bf scale, zero )
  ADDIC C( Num virt users, Num virt users, -16 )
  VMADDFP( fsum2, fsum2, bf_scale, zero )
```

3

```
gen_r_matrices.mac
        VMADDFP( fsum3, fsum3, bf scale, zero )
        VMADDFP( fsum scale0, fsum0, inv scale, zero )
        VMADDFP( fsum scale1, fsum1, inv scale, zero )
        VMADDFP( fsum scale2, fsum2, inv_scale, zero )
        ADDI( Rsump, Rsump, 64 )
        VMADDFP( fsum_scale3, fsum3, inv_scale, zero )
        ADDI( Scalep, Scalep, 64 )
        VMADDFP( fsum scale0, fsum scale0, scale0, zero )
        VMADDFP( fsum scale1, fsum scale1, scale1, zero )
        VMADDFP( fsum scale2, fsum scale2, scale2, zero )
        VMADDFP( fsum scale3, fsum_scale3, scale3, zero )
        BLE( sixteen_sums )

        LVX( rsum0, 0, Rsump )
        LVX( rsum1, Rsump, indx1 )
        VCTSXS( bsum0, fsum0, 24 )
        LVX( rsum2, Rsump, indx2 )
        VCTSXS( bsum1, fsum1, 24 )
        VCTSXS( bsum2, fsum2, 24 )
        LVX( rsum3, Rsump, indx3 )
        ADDI( Rsump, Rsump, 64 )
        VCTSXS( bsum3, fsum3, 24 )
        LVX( scale0, 0, Scalep )
        VCTSXS( bsum scale0, fsum scale0, 24 )
        VCTSXS( bsum_scale1, fsum scale1, 24 )
        LVX( scale1, Scalep, indx1 )
        VCTSXS( bsum_scale2, fsum scale2, 24 )
        LVX( scale2, Scalep, indx2 )
        ADDI( No scale row bfp, No scale row_bfp, -SCALE_BUMP_16 )
        VCTSXS( bsum scale3, fsum scale3, 24 )
        ADDI( Scale_row_bfp, Scale_row_bfp, -SCALE_BUMP_16 )

    BR( mloop )
/**
 Top of loop outputs 32 bytes per trip
**/
LABEL( loop )
/* { */
        STORE SCALE( bvector, 0, No scale_row bfp )
        VCTSXS( bsum_scale3, fsum scale3, 24 )
        STORE_SCALE( bscale_vector, 0, Scale_row_bfp )

LABEL( mloop )
        LVX( scale3, Scalep, indx3 )
        VCFSX( fsum0, rsum0, 0 )
        VPERM( bsum0, bsum0, bsum1, byte_pack )
        VCFSX( fsum1, rsum1, 0 )
        VCFSX( fsum2, rsum2, 0 )
        ADDI( No scale row bfp, No_scale_row_bfp, SCALE_BUMP_16 )
        VCFSX( fsum3, rsum3, 0 )
        ADDI( Scale row_bfp, Scale row bfp, SCALE_BUMP_16 )
        VMADDFP( fsum0, fsum0, bf scale, zero )
        VPERM( bsum2, bsum2, bsum3, byte_pack )
        VMADDFP( fsum1, fsum1, bf scale, zero )
        VMADDFP( fsum2, fsum2, bf_scale, zero )

        VMADDFP( fsum3, fsum3, bf scale, zero )
        VMADDFP( fsum scale0, fsum0, inv scale, zero )
        VPERM( bvector, bsum0, bsum2, byte merge )
        VMADDFP( fsum scale1, fsum1, inv scale, zero )
        ADDIC C( Num virt users, Num_virt users, -16 )
        VMADDFP( fsum scale2, fsum2, inv scale, zero )
        VMADDFP( fsum_scale3, fsum3, inv_scale, zero )
        ADDI( Scalep, Scalep, 64 )
        VMADDFP( fsum scale0, fsum scale0, scale0, zero )
        VPERM( bsum scale0, bsum scale0, bsum scale1, byte_pack )
        VMADDFP( fsum_scale1, fsum_scale1, scale1, zero )
```

4

```
     gen_r_matrices.mac
          VMADDFP( fsum scale2, fsum scale2, scale2, zero )
          VMADDFP( fsum scale3, fsum scale3, scale3, zero )
          VPERM( bsum scale2, bsum scale2, bsum_scale3, byte_pack )
            VSRB( vtmp, bvector, seven )
          VPERM( bscale vector, bsum scale0, bsum_scale2, byte_merge )
            VSRB( vtmp2, bscale_vector, seven )
          BLE( loop_flush )

          LVX( rsum0, 0, Rsump )
            VADDSBS( bvector, bvector, vtmp )
          LVX( rsum1, Rsump, indx1 )
            VADDSBS( bscale vector, bscale_vector, vtmp2 )
          LVX( rsum2, Rsump, indx2 )
          VCTSXS( bsum0, fsum0, 24 )
          LVX( rsum3, Rsump, indx3 )
          VCTSXS( bsum1, fsum1, 24 )
          ADDI( Rsump, Rsump, 64 )
          VCTSXS( bsum2, fsum2, 24 )
          LVX( scale0, 0, Scalep )
          VCTSXS( bsum3, fsum3, 24 )
          LVX( scale1, Scalep, indx1 )
          VCTSXS( bsum scale0, fsum scale0, 24 )
          VCTSXS( bsum_scale1, fsum scale1, 24 )
          LVX( scale2, Scalep, indx2 )
          VCTSXS( bsum_scale2, fsum_scale2, 24 )
/* } */
   BR( loop )

/**
 Flush loop
**/
LABEL( loop flush )
          VADDSBS( bvector, bvector, vtmp )
        STORE SCALE( bvector, 0, No scale row bfp )
          VADDSBS( bscale vector, bscale vector, vtmp2 )
        STORE_SCALE( bscale vector, 0, Scale row bfp )
        ADDI( No scale row bfp, No scale row bfp, SCALE BUMP_16 )
        ADDI( Scale_row_bfp, Scale_row_bfp, SCALE_BUMP_16 )

LABEL( sixteen_sums )

        VCTSXS( bsum0, fsum0, 24 )
        VCTSXS( bsum1, fsum1, 24 )
        VCTSXS( bsum2, fsum2, 24 )
        VCTSXS( bsum3, fsum3, 24 )
        VCTSXS( bsum scale0, fsum scale0, 24 )
        VPERM( bsum0, bsum0, bsum1, byte pack )
        VCTSXS( bsum scale1, fsum scale1, 24 )
        VPERM( bsum2, bsum2, bsum3, byte pack )
        VCTSXS( bsum scale2, fsum scale2, 24 )
        VPERM( bvector, bsum0, bsum2, byte merge )
        VCTSXS( bsum_scale3, fsum_scale3, 24 )

        VPERM( bsum scale0, bsum scale0, bsum scale1, byte pack )
        VPERM( bsum scale2, bsum scale2, bsum_scale3, byte_pack )
          VSRB( vtmp, bvector, seven )
        VPERM( bscale vector, bsum scale0, bsum_scale2, byte_merge )
          VADDSBS( bvector, bvector, vtmp )
          VSRB( vtmp, bscale vector, seven )
        STORE SCALE( bvector, 0, No scale row bfp )
          VADDSBS( bscale vector, bscale vector, vtmp )
        STORE_SCALE( bscale_vector, 0, Scale_row_bfp )
/**
 Return
**/
LABEL( ret )
   FREE_THRU_v31( VRSAVE_COND )
```

5

```
gen_r_matrices.mac                                    2/23/2001

        RETURN
        FUNC_EPILOG
```

6

m_voter.vhd

```vhdl
--*****************************************************
--*****************************************************
--**
--**   Majority Voter Control Logic
--**
--**   Description: This Module serves as a generic majority voter
--**
--**
--**   Author     : Steven Imperiali/Mirza Cifric
--**   Date       : 5-15-2000
--**
--**
--*****************************************************
LIBRARY IEEE;
USE IEEE.STD LOGIC 1164.ALL;
use ieee.std logic arith.all;
use ieee.std logic unsigned.all;
USE STD.TEXTIO.ALL;


ENTITY m_voter IS
   PORT(
           clk 66 pal6      :IN       std logic;
           reset 0          :IN       std logic;
           request0 0       :IN       std logic;
           request1 0       :IN       std logic;
           request2 0       :IN       std logic;
           request3 0       :IN       std logic;
           request4 0       :IN       std logic;
           healthy0 1       :IN       std logic;
           healthy1 1       :IN       std logic;
           healthy2 1       :IN       std logic;
           healthy3 1       :IN       std logic;
           healthy4 1       :IN       std logic;
           voteout_0        :OUT      std_logic);


END m_voter;

ARCHITECTURE voter OF m voter IS
signal pro: STD_LOGIC VECTOR(3 downto 0);
signal against: STD_LOGIC_VECTOR(3 downto 0);

signal result: STD_LOGIC;

BEGIN




check result:process(request0_0,request1_0,request2_0,request3_0,request4_0,healthy0 1,
healthy1_1,healthy2 1,healthy3 1,healthy4 1)
variable pro: STD_LOGIC VECTOR(3 downto 0);
variable against: STD LOGIC VECTOR(3 downto 0);
variable solution: STD_LOGIC;
begin
    pro:= "0000";                        -- set number of pro voters
    against:="0000";
-- set number of against voters-- Get the number of pros
        if (healthy0_1 = '1' and request0_0='1') then
        pro := pro + "0001";
            end if;
    if (healthy1 1='1' and request1_0='1') then
        pro := pro + "0001";
            end if;
        if (healthy2_1='1' and request2_0='1') then
```

1

```vhdl
        pro := pro + "0001";
            end if;
    if (healthy3_1='1' and request3_0='1') then
        pro := pro + "0001";
            end if;
    if (healthy4_1='1' and request4_0='1') then
        pro := pro + "0001";
            end if;
-- Get the number of cons
        if (healthy0_1 = '1' and request0_0='0') then
        against := against + "0001";
            end if;
    if (healthy1_1 = '1' and request1_0 ='0') then
        against := against + "0001";
            end if;
    if (healthy2_1 = '1' and request2_0 ='0') then
        against := against + "0001";
            end if;
    if (healthy3_1 ='1' and request3_0 ='0') then
        against := against + "0001";
            end if;
    if (healthy4_1 ='1' and request4_0 ='0') then
        against := against + "0001";
            end if;
-- final score
            if(pro = "0001" and against < "0001") then
        solution := '1';
            elsif(pro = "0010" and against < "0010") then
        solution := '1';
    elsif(pro = "0011" and against <  "0011") then
        solution := '1';
    elsif(pro = "0100" and against <  "0011") then
        solution := '1';
    elsif(pro = "0101" and against <  "0011") then
        solution := '1';

    else    solution := '0';
    end if;
            result <= solution;          -- put variable val into
            signal val
--          voteout_0 <= solution;       -- put variable val into
signal val


end process check_result;




result_latch:process(reset_0, clk_66_pal6)
begin
        IF (reset_0 = '0') THEN
                voteout_0 <= '1';
        ELSIF rising_edge(clk_66_pal6) THEN
                IF result = '0' THEN
                        voteout_0 <= '0';

                END IF;
        END IF;
END PROCESS;

END voter;
```

2

```
/*****************************************************************************
 *
 * FILENAME: mudlib.h
 *
 * CC NUMBER:
 *
 * ABSTRACT:
 *
 * USAGE:
 *
 * COMMENTS:
 *
 * AUTHOR: M. Vinskus
 *
 * DATE: 18-JUL-2000
 *
 *****************************************************************************
 **/

/* @MERCURY.COPYRIGHT.H@ */
```

1

```
#ifndef  MUDLIB H
#define _MUDLIB_H

/**************************************************************************
***
 *   INCLUDE FILES
 **************************************************************************
 **/

#include <sal.h>

/**************************************************************************
***
 *   DEFINED CONSTANTS
 **************************************************************************
 **/

#define NUM FINGERS LOG  2
#define NUM FINGERS_SQUARED LOG  (2 * NUM FINGERS_LOG)
#define NUM FINGERS  (1 << NUM FINGERS LOG)
#define NUM_FINGERS_SQUARED  (1 << NUM_FINGERS_SQUARED_LOG)

#define L1 CACHE SIZE  32768
#define L1_CACHE_LINE_SIZE  32

#define L1 CACHE ALIGN_LOG  5
#define L1 CACHE ALIGN  (1 << L1 CACHE ALIGN_LOG)
#define L1_CACHE_ALIGN_MASK  (L1_CACHE_ALIGN - 1)

#define R MATRIX ALIGN_LOG  5
#define R MATRIX ALIGN  (1 << R MATRIX ALIGN_LOG)
#define R_MATRIX_ALIGN_MASK  (R_MATRIX_ALIGN - 1)

#define ALTIVEC ALIGN_LOG  4
#define ALTIVEC ALIGN  (1 << ALTIVEC ALIGN_LOG)
#define ALTIVEC_ALIGN_MASK  (ALTIVEC_ALIGN - 1)

#define BF CORR FRAC BITS 8
#define BF_CORR_FACTOR ((float)(1 << BF_CORR_FRAC_BITS))

#define BF MPATH FRAC BITS 15              /* this should be dynamic */
#define BF_MPATH_FACTOR ((float)(1 << BF_MPATH_FRAC_BITS))

#define BF RSUMS FRAC_BITS ((2 * BF_MPATH_FRAC_BITS) - 16 +
BF CORR_FRAC BITS)
#define BF RSUMS FACTOR ((float)(1 << BF RSUMS FRAC_BITS))
#define BF_RSUMS_RFACTOR (1.0 / BF_RSUMS_FACTOR)

#define BF RY FRAC BITS 9              /* 0 <= BF RY_FRAC_BITS <= 14 */
#define BF RY FACTOR ((float)(1 << BF RY FRAC_BITS))
#define BF_RY_RFACTOR (1.0 / BF_RY_FACTOR)

#define BF COMBINED FACTOR ((float)( 1 <<
(BF RSUMS FRAC BITS-BF RY FRAC BITS)))
#define BF_COMBINED_RFACTOR (1.0 / BF_COMBINED_FACTOR)

#define BF8 ZERO 0
#define BF8 MAX 0x7f
#define BF8 RY ONE ((BF8)(1 << BF RY FRAC BITS))
#define BF16 RY ONE ((BF16)(1 << BF_RY_FRAC_BITS))
#define BF16 RY MONE (-BF16_RY_ONE)
#define BF16 ZERO 0
#define BF16 MAX 0x7fff
#define BF32 ZERO 0
#define BF32 RY ONE ((BF32)(1 << BF_RY_FRAC_BITS))
#define BF32_MAX 0x7fffffff
```

2

```
        #define BIAS_8BIT  1

#define  BFABS( x )   (((x) >= 0) ? (x) : (-(x)))
#define  FABS( f )    (((f) >= 0.0) ? (f) : (-(f)))

/************************************************************************
***
 *  TYPE DEFINITIONS
 ************************************************************************
 **/
typedef long   BF32;
typedef short  BF16;
typedef char   BF8;

typedef struct {
  BF8   real;
  BF8   imag;
} COMPLEX_BF8;

typedef struct {
  BF16   real;
  BF16   imag;
} COMPLEX_BF16;

typedef struct {
  BF32   real;
  BF32   imag;
} COMPLEX_BF32;

/************************************************************************
***
 *  MACRO DEFINITIONS
 ************************************************************************
 **/
/* assumes (-(2.0 ^ 7) - 0.5) < (bf_factor * s) < ((2.0 ^ 7) - 0.5) */

#define SFtoBF8( bf_factor, s ) \
  ((BF8)((bf_factor) * (s) + (((s) > 0.0) ? 0.5 : -0.5)))

#define VFtoBF8( bf_factor, v, bfv, n ) \
  { \
    int i; \
    float factor = bf_factor; \
    vsmulx ( v, 1, &factor, v, 1, n, 0 ); \
    for ( i = 0; i < n; i++ ) \
      bfv[i] = (v[i] > 0.0) ? (BF8)(v[i] + 0.5) : (BF8)(v[i] - 0.5); \
  }

#define SBF8toF( bf_rfactor, bfs ) \
  ((bf_rfactor) * (float)(bfs))

#define VBF8toF( bf_rfactor, bfv, v, n ) \
  { \
    int i; \
    float rfactor = bf_rfactor; \
    for ( i = 0; i < n; i++ ) \
      v[i] = (float)bfv[i]; \
    vsmulx ( v, 1, &rfactor, v, 1, n, 0 ); \
  }

/* assumes (-(2.0 ^ 15) - 0.5) < (bf_factor * s) < ((2.0 ^ 15) - 0.5) */

#define SFtoBF16( bf_factor, s ) \
  ((BF16)((bf_factor) * (s) + (((s) > 0.0) ? 0.5 : -0.5)))

#define VFtoBF16( bf_factor, v, bfv, n ) \
  { \
```

3

```
            float factor = bf factor; \
            vsmulx ( (float *)v, 1, &factor, (float *)v, 1, n, 0 ); \
            vfixrx ( (float *)v, 1, (BF16 *)bfv, 1, n, 0 ); \
        }

#define SBF16toF( bf rfactor, bfs ) \
    ((bf_rfactor) * (float)(bfs))

#define VBF16toF( bf_rfactor, bfv, v, n ) \
    { \
        float rfactor = bf rfactor; \
        vfltx ( (short *)bfv, 1, v, 1, n, 0 ); \
        vsmulx ( v, 1, &rfactor, v, 1, n, 0 ); \
    }

/* assumes (-(2.0 ^ 31) - 0.5) < (bf_factor * x) < ((2.0 ^ 31) - 0.5) */

#define SFtoBF32( bf factor, s ) \
    ((BF32)((bf_factor) * (s) + (((s) > 0.0) ? 0.5 : -0.5)))

#define VFtoBF32( bf_factor, v, bfv, n ) \
    { \
        float factor = bf factor; \
        vsmulx ( v, 1, &factor, (float *)bfv, 1, n, 0 ); \
        vfixr32x ( (float *)bfv, 1, (int *)bfv, 1, n, 0 ); \
    }

#define SBF32toF( bf rfactor, bfs ) \
    ((bf_rfactor) * (float)(bfs))

#define VBF32toF( bf_rfactor, bfv, v, n ) \
    { \
        float rfactor = bf rfactor; \
        vflt32x ( (int *)bfv, 1, v, 1, n, 0 ); \
        vsmulx ( v, 1, &rfactor, v, 1, n, 0 ); \
    }

#define CORR SFtoBF( s )              SFtoBF8( BF CORR FACTOR, s )
#define MPATH_VFtoBF( v, bfv, n ) VFtoBF16( BF_MPATH_FACTOR, v, bfv, ((n)<<1)
)

#define BHAT SFtoBF( s )             ((BF8)((s) + (float)BIAS 8BIT))
#define BHAT SBFtoF( bfs )           ((float)(bfs) - (float)BIAS_8BIT)
#define BHAT_VFtoBF( v, bfv, n ) \
    { \
        float bias = (float)BIAS 8BIT; \
        vsaddx( v, 1, &bias, v, 1, n, 0 ); \
        fixpixax( v, 1, bfv, n, 0 ); \
    }

#define BHAT_VBFtoF( bfv, v, n ) \
    { \
        float bias = (float)(-BIAS 8BIT); \
        fltpixax( bfv, v, 1, n, 0 ); \
        vsaddx( v, 1, &bias, v, 1, n, 0 ); \
    }

#define RHAT SFtoBF( s )             SFtoBF8( BF RY FACTOR, s )
#define RHAT SBFtoF( bfs )           SBF8toF( BF RY RFACTOR, bfs )
#define RHAT VFtoBF( v, bfv, n )     VFtoBF8( BF RY FACTOR, v, bfv, n )
#define RHAT_VBFtoF( bfv, v, n )     VBF8toF( BF_RY_RFACTOR, bfv, v, n )

#define Y SFtoBF( s )                SFtoBF32( BF RY FACTOR, s )
#define Y SBFtoF( bfs )              SBF32toF( BF RY RFACTOR, bfs )
#define Y VFtoBF( v, bfv, n )        VFtoBF32( BF RY FACTOR, v, bfv, n )
#define Y_VBFtoF( bfv, v, n )        VBF32toF( BF_RY_RFACTOR, bfv, v, n )
```

4

```
#define MUDLIB_DECR_VIRT_USER( ptov_map, phys_user, virt_user ) \
  { \
    --virt user; \
    if ( virt user < 0 ) { \
      --phys user; \
      virt_user = ptov_map[phys_user] - 1; \
    } \
  }


#define MUDLIB_INCR_VIRT_USER( ptov_map, phys_user, virt_user ) \
  { \
    ++virt user; \
    if ( virt user == ptov_map[phys_user] ) { \
      ++phys user; \
      virt_user = 0; \
    } \
  }
```

```
/*******************************************************************
***
*   PUBLIC FUNCTION PROTOTYPES
*******************************************************************
**/

int   mudlib get Corr0 offset (
          unsigned char  *ptov_map,   /* no more than 256 virts. per phys */
          int   num fingers,          /* typically, 4 */
          int   tot_virt_users,       /* sum of ptov_map over all phys users
          */
          int   start phys user,      /* zero-based index into ptov map */
          int   start_virt_user       /* must be < ptov_map[start_phys_user]
          */
        );

int   mudlib get Corr0 size (
          unsigned char  *ptov_map,   /* no more than 256 virts. per phys */
          int   num fingers,          /* typically, 4 */
          int   tot_virt_users,       /* sum of ptov_map over all phys users
          */
          int   start phys user,      /* zero-based index into ptov map */
          int   start_virt_user,      /* must be < ptov_map[start_phys_user]
          */
          int   end phys user,        /* zero-based index into ptov map */
          int   end_virt_user         /* must be < ptov_map[end_phys_user] */
        );

int   mudlib get Corr1 offset (
          unsigned char  *ptov_map,   /* no more than 256 virts. per phys */
          int   num fingers,          /* typically, 4 */
          int   tot_virt_users,       /* sum of ptov_map over all phys users
          */
          int   start phys user,      /* zero-based index into ptov map */
          int   start_virt_user       /* must be < ptov_map[start_phys_user]
          */
        );

int   mudlib get Corr1 size (
          unsigned char  *ptov_map,   /* no more than 256 virts. per phys */
          int   num fingers,          /* typically, 4 */
          int   tot_virt_users,       /* sum of ptov_map over all phys users
          */
          int   start phys user,      /* zero-based index into ptov map */
          int   start_virt_user,      /* must be < ptov_map[start_phys_user]
          */
          int   end phys user,        /* zero-based index into ptov map */
          int   end_virt_user         /* must be < ptov_map[end_phys_user] */
        );
```

5

```
int   mudlib get R0 offset (
              unsigned char  *ptov_map,   /* no more than 256 virts. per phys */
              int  tot_virt_users,        /* sum of ptov_map over all phys users
              */
              int  start phys user,       /* zero-based index into ptov map */
              int  start_virt_user        /* must be < ptov_map[start_phys_user]
              */
         );

int   mudlib get R0 size (
              unsigned char  *ptov_map,   /* no more than 256 virts. per phys */
              int  tot_virt_users,        /* sum of ptov_map over all phys users
              */
              int  start phys user,       /* zero-based index into ptov map */
              int  start_virt_user,       /* must be < ptov_map[start_phys_user]
              */
              int  end phys user,         /* zero-based index into ptov map */
              int  end_virt_user          /* must be < ptov_map[end_phys_user] */
         );

int   mudlib get R1 offset (
              unsigned char  *ptov_map,   /* no more than 256 virts. per phys */
              int  tot_virt_users,        /* sum of ptov_map over all phys users
              */
              int  start phys user,       /* zero-based index into ptov map */
              int  start_virt_user        /* must be < ptov_map[start_phys_user]
              */
         );

int   mudlib get R1 size (
              unsigned char  *ptov_map,   /* no more than 256 virts. per phys */
              int  tot_virt_users,        /* sum of ptov_map over all phys users
              */
              int  start phys user,       /* zero-based index into ptov map */
              int  start_virt_user,       /* must be < ptov_map[start_phys_user]
              */
              int  end phys user,         /* zero-based index into ptov map */
              int  end_virt_user          /* must be < ptov_map[end_phys_user] */
         );

int   mudlib get num_virt_users (
              unsigned char  *ptov map,   /* no more than 256 virts. per phys */
              int  start phys user,       /* zero-based index into ptov map */
              int  start_virt_user,       /* must be < ptov_map[start_phys_user]
              */
              int  end phys user,         /* zero-based index into ptov map */
              int  end_virt_user          /* must be < ptov_map[end_phys_user] */
         );

void  mudlib get end user_pair (
              unsigned char  *ptov map,   /* no more than 256 virts. per phys */
              int  start phys user,       /* zero-based index into ptov map */
              int  start_virt_user,       /* must be < ptov_map[start_phys_user]
              */
              int  num virt users,        /* number from start (must be > 0) */
              int  *end phys user,        /* zero-based index into ptov map */
              int  *end_virt_user         /* will be < ptov_map[*end_phys_user] */
         );

void  mudlib gen R (
              COMPLEX BF16  *mpath1 bf,
              COMPLEX BF16  *mpath2 bf,
              COMPLEX_BF8  *corr_0_bf,    /* adjusted for starting physical user
              */
              COMPLEX_BF8  *corr_1_bf,    /* adjusted for starting physical user
              */
```

6

```
                  unsigned char  *ptov_map,     /* no more than 256 virts. per phys */
                  float  *bf scalep,            /* scalar: always a power of 2 */
                  float  *inv_scalep,           /* adjusted for starting physical user
                  */
                  float  *scalep,               /* start at 0'th physical user */
                  char  *L1 cachep,
                  BF8  *R0 upper bf,            /* must be 32-byte aligned */
                  BF8  *R0 lower bf,
                  BF8  *R1 trans_bf,
                  BF8  *R1m bf,
                  int  tot phys users,
                  int  tot virt users,
                  int  start phys user,        /* zero-based ("starting row") */
                  int  start virt user,        /* relative to start phys user */
                  int  end_phys_user,          /* actual number of "rows" to process
                  */
                  int  end_virt_user           /* relative to end_phys_user */
              );

void  mudlib 4R_to 3R (
              BF8  *R0 upper bf,               /* input matrix */
              BF8  *R0 lower bf,               /* input matrix */
              BF8  *R1 trans bf,               /* input matrix */
              char  *L1 cachep,                /* 32K-byte temp, 32-byte aligned */
              BF8  *R0 bf,                     /* output matrix */
              BF8  *R1 bf,                     /* output matrix */
              int  tot_virt_users
          );

void  mudlib_mpic ( BF8 *Bt hat,
                    BF8 *R0 hat,
                    BF8 *R1 hat,
                    BF8 *R1m_hat,
                    BF32 *Y,
                    BF32 Ythresh,
                    int N users,
                    int N bits,
                    int N_stages );

void  mudlib_reformat_corr ( COMPLEX  *in_corr,
                             COMPLEX BF8  *corr 0 bf,
                             COMPLEX BF8  *corr 1_bf,
                             int  num virt users,
                             int  num_multipath );

void  fixed_zidotprx ( COMPLEX SPLIT *A, int I, COMPLEX SPLIT *B, int J,
                    COMPLEX_SPLIT *C, int N, int X );

/*
 *  temp names (_v)
 */
int  mudlib get Corr0 offset v (
            unsigned char  *ptov_map, /* no more than 256 virts. per phys */
            int  num fingers,         /* typically, 4 */
            int  tot_virt_users,      /* sum of ptov_map over all phys users
            */
            int  start phys user,     /* zero-based index into ptov map */
            int  start_virt_user      /* must be < ptov_map[start_phys_user]
            */
          );

int  mudlib get Corr1 offset v (
            unsigned char  *ptov_map, /* no more than 256 virts. per phys */
            int  num fingers,         /* typically, 4 */
            int  tot_virt_users,      /* sum of ptov_map over all phys users
            */
            int  start_phys_user,     /* zero-based index into ptov_map */
```

7

mudlib.h   2/23/2001

```
            int   start_virt_user      /* must be < ptov_map[start_phys_user]
                                           */
            );

   int   mudlib get R0 offset_v (
            unsigned char  *ptov_map,  /* no more than 256 virts. per phys */
            int   tot_virt_users,      /* sum of ptov_map over all phys users
                                           */
            int   start phys user,     /* zero-based index into ptov map */
            int   start_virt_user      /* must be < ptov_map[start_phys_user]
                                           */
            );

   int   mudlib get R0 size v (
            unsigned char  *ptov_map,  /* no more than 256 virts. per phys */
            int   tot_virt_users,      /* sum of ptov_map over all phys users
                                           */
            int   start phys user,     /* zero-based index into ptov map */
            int   start_virt_user,     /* must be < ptov_map[start_phys_user]
                                           */
            int   end phys user,       /* zero-based index into ptov map */
            int   end_virt_user        /* must be < ptov_map[end_phys_user] */
            );

   int   mudlib get R1 offset_v (
            unsigned char  *ptov_map,  /* no more than 256 virts. per phys */
            int   tot_virt_users,      /* sum of ptov_map over all phys users
                                           */
            int   start phys user,     /* zero-based index into ptov map */
            int   start_virt_user      /* must be < ptov_map[start_phys_user]
                                           */
            );

   int   mudlib get R1 size v (
            unsigned char  *ptov_map,  /* no more than 256 virts. per phys */
            int   tot_virt_users,      /* sum of ptov_map over all phys users
                                           */
            int   start phys user,     /* zero-based index into ptov map */
            int   start_virt_user,     /* must be < ptov_map[start_phys_user]
                                           */
            int   end phys user,       /* zero-based index into ptov map */
            int   end_virt_user        /* must be < ptov_map[end_phys_user] */
            );

#endif  /* _MUDLIB_H */
```

8

reformat_corr.c

```
#include "mudlib.h"

#define INDEX_5D_TO_LIN(a0, a1, a2, a3, a4, max_a1, max_a2, max_a3, max_a4) \
            ((a4) + (max_a4) * ((a3) + (max_a3) * ((a2) + (max_a2) * ((a1)
            \
              + (max_a1) * (a0)))))

void  mudlib reformat corr (
            COMPLEX  *in_corr,
            COMPLEX BF8  *corr_0_bf,
            COMPLEX BF8  *corr_1_bf,
            int  num virt users,
            int  num_fingers )
{
  int  i, j, q, q1;

  for ( i = 0; i < num_virt users; i++ ) {
    for ( j = (i+1); j < num virt users; j++ ) {
      for ( q = 0; q < num_fingers; q++ ) {
        for ( q1 = 0; q1 < num fingers; q1++ ) {
          corr_0_bf->real = CORR_SFtoBF( in_corr[INDEX 5D_TO_LIN(
                                         0, i, j, q1, q,
                                         num virt users,
                                         num virt users,
                                         num fingers,
                                         num fingers)].real );

          corr_0_bf->imag = CORR_SFtoBF( in_corr[INDEX 5D_TO_LIN(
                                         0, i, j, q1, q,
                                         num virt users,
                                         num virt users,
                                         num fingers,
                                         num_fingers)].imag );

          ++corr_0_bf;
        }
      }
    }
  }

  for ( i = 0; i < num virt users; i++ ) {
    for ( j = 0; j < num virt users; j++ ) {
      for ( q = 0; q < num_fingers; q++ ) {
        for ( q1 = 0; q1 < num fingers; q1++ ) {
          corr_1_bf->real = CORR_SFtoBF( in_corr[INDEX 5D_TO_LIN(
                                         1, i, j, q1, q,
                                         num virt users,
                                         num virt users,
                                         num fingers,
                                         num fingers)].real );

          corr_1_bf->imag = CORR_SFtoBF( in_corr[INDEX 5D_TO_LIN(
                                         1, i, j, q1, q,
                                         num virt users,
                                         num virt users,
                                         num fingers,
                                         num_fingers)].imag );

          ++corr_1_bf;
        }
      }
    }
  }
}
```

1

reformat_r.c

```
#include "mudlib.h"

void mtrans32 8bit (
        BF8   *A,           /* logically contiguous input 32 x 32 blocks */
        BF8   *C,           /* output blocks separated by 32 * out_tc elements
        */
        char  *L1 cachep,
        int   A ncols,
        int   A nrows,
        int   C_tcols
     );

void mtriangle 8bit (
        BF8   *A,
        BF8   *C,
        int   N
     );

void  mudlib_4R to 3R (
        BF8   *R0 upper bf,               /* input matrix */
        BF8   *R0 lower bf,               /* input matrix */
        BF8   *R1 trans bf,               /* input matrix */
        char  *L1_cachep,                 /* temp: 32K bytes, 32-byte aligned
        */
        BF8   *R0 bf,                     /* output matrix */
        BF8   *R1 bf,                     /* output matrix */
        int   tot_virt_users
     )
{
  BF8   *R0 work;
  int   i, nrows, R0_tcols, tcols;

  tcols = (tot_virt_users + R_MATRIX_ALIGN_MASK) & ~R_MATRIX_ALIGN_MASK;

  nrows = R_MATRIX ALIGN;
  for ( i = tot virt_users; i > 0; i -= R_MATRIX_ALIGN ) {
    if ( nrows > i ) nrows = i;
     mtrans32_8bit ( R1 trans bf, R1_bf, L1_cachep, tot_virt_users,
                     nrows, tcols );
    R1 trans_bf += (tcols << R_MATRIX_ALIGN_LOG);
    R1_bf += R_MATRIX_ALIGN;
  }

  R0 work = R0 bf;
  R0 tcols = tcols;
  nrows = R_MATRIX ALIGN;
  for ( i = tot virt_users; i > 0; i -= R_MATRIX_ALIGN ) {
    if ( nrows > i ) nrows = i;
    mtrans32 8bit ( R0 lower_bf, R0 work, L1 cachep, i, nrows, tcols );
    R0 lower bf += (R0_tcols << R MATRIX ALIGN LOG);
    R0 work += ((tcols << R MATRIX_ALIGN_LOG) + R_MATRIX_ALIGN);
    R0_tcols -= R_MATRIX_ALIGN;
  }

  mtriangle_8bit( R0_upper_bf, R0_bf, tot_virt_users );
}

#if COMPILE_C

void mtrans32 8bit (
        BF8   *A,           /* logically contiguous input A_nrows x A_ncols
        blocks */
        BF8   *C,           /* output blocks separated by 32 * C_tcols elements
        */
        char  *L1 cachep,
        int   A_ncols,
```

1

reformat_r.c

```
            int  A nrows,
            int  C_tcols
         )
  {
    BF8  *Ap, *Cp;
    int  A tcols, C_nrows;
    int  i, j;

    (void)L1_cachep;

    A tcols = (A ncols + R MATRIX_ALIGN_MASK) & ~R_MATRIX_ALIGN_MASK;
    C_nrows = R_MATRIX_ALIGN;

    while ( A ncols ) {
      if ( A ncols < C_nrows ) C_nrows = A_ncols;
      Ap = A;
      Cp = C;
      for ( i = 0; i < A_nrows; i++ ) {
        for ( j = 0; j < C nrows; j++ )
          Cp[j * C tcols] = Ap[j];
        Ap += A tcols;
        Cp += 1;
      }
      A += R MATRIX_ALIGN;                    /* input travels horizontally */
      C += (C_tcols << R MATRIX_ALIGN_LOG);   /* output travels vertically */
      A_ncols -= C_nrows;
    }
  }

  void mtriangle 8bit (
          BF8  *A,
          BF8  *C,
          int  N
        )
  {
    int  A counter, A_tcols, altivec_N, C_tcols;
    int  i, j;

    A counter = (N + R MATRIX_ALIGN_MASK) & ~R_MATRIX_ALIGN_MASK;
    C_tcols = A_counter + 1;

    altivec_N = (N + ALTIVEC_ALIGN_MASK) & ~ALTIVEC_ALIGN_MASK;

    for ( i = 0; i < N; i++ ) {
      for ( j = 0; j < altivec_N; j++ )
        C[j] = A[j];

      --altivec N;
      --A counter;
      A_tcols = (A counter + R_MATRIX_ALIGN_MASK) & ~R_MATRIX_ALIGN_MASK;
      A += (A tcols + 1);
      C += C_tcols;
    }
  }

  #endif                         /* COMPILE_C */
```

2

```
/*-----------------------------------------------------------------------+
|                                                                        |
|      MC Standard Algorithms -- PPC Macro Language Version              |
|------------------------------------------------------------------------|
|                                                                        |
|   File Name:    mtrans32 8bit.mac                                      |
|   Description:  Perform N_tiles 32 x 32 byte transposes                |
|                                                                        |
|   void mtrans32 8bit (                                                 |
|           BF8   *A,           contiguous input 32 x 32 blocks          |
|           BF8   *C,           output blocks separated by               |
|                               32 * out_tc elements                     |
|           char  *L1 cache,                                             |
|           int   A ncols,                                               |
|           int   A nrows,                                               |
|           int   C_tcols                                                |
|        )                                                               |
|                                                                        |
| {                                                                      |
|   BF8   *Ap, *Cp;                                                      |
|   int   A_tcols, C_nrows;                                              |
|   int   i, j;                                                          |
|                                                                        |
|   A_tcols = (A ncols + R MATRIX ALIGN_MASK) &                          |
|             ~R MATRIX ALIGN_MASK;                                      |
|   C_nrows = R_MATRIX_ALIGN;                                            |
|                                                                        |
|   while ( A ncols ) {                                                  |
|     if ( A ncols < C_nrows ) C_nrows = A_ncols;                        |
|     Ap = A;                                                            |
|     Cp = C;                                                            |
|     for ( i = 0; i < A_nrows; i++ ) {                                  |
|       for ( j = 0; j < C nrows; j++ )                                  |
|         Cp[j * C tcols] = Ap[j];                                       |
|       Ap += A tcols;                                                   |
|       Cp += 1;                                                         |
|     }                                                                  |
|     A += R MATRIX_ALIGN;                                               |
|     C += (C_tcols << R MATRIX_ALIGN_LOG);                              |
|     A_ncols -= C_nrows;                                                |
|   }                                                                    |
| }                                                                      |
|                                                                        |
|  Restrictions:  A, C and L1 cache must all be 16-byte aligned.         |
|                 C_tcols must be a multiple of 16.                      |
|                                                                        |
|         Mercury Computer Systems, Inc.                                 |
|         Copyright (c) 2000  All rights reserved                        |
|                                                                        |
|   Revision   Date   Engineer  Reason                                   |
|   --------   ----   --------  ------                                   |
|     0.0     000913   fpl      Created                                  |
+------------------------------------------------------------------------*/

#include "salppc.inc"

#define DO_PREFETCH   1

#define LOAD INPUT( vT, rA, rB )       LVXL( vT, rA, rB )
#define LOAD_CACHE( vT, rA, rB )       LVX( vT, rA, rB )

#define STORE CACHE( vS, rA, rB )      STVX( vS, rA, rB )
#define STORE_OUTPUT( vS, rA, rB )     STVX( vS, rA, rB )

#define R MATRIX ALIGN_LOG    5
#define R MATRIX ALIGN        (1 << R MATRIX ALIGN_LOG)
#define R_MATRIX_ALIGN_MASK   (R_MATRIX_ALIGN - 1)
```

1

```
#define ALTIVEC ALIGN_LOG      4
#define ALTIVEC ALIGN          (1 << ALTIVEC_ALIGN_LOG)
#define ALTIVEC_ALIGN_MASK     (ALTIVEC_ALIGN - 1)

#if DO PREFETCH
#define  PREFETCH( rA, rB, STRM, DST_BUMP ) \
   DSTT( rA, rB, STRM ) \
   ADD( rA, rA, DST_BUMP )
#else
#define  PREFETCH( rA, rB, STRM, DST_BUMP )
#endif

/**
 Four permute vectors for output stage
**/
RODATA_SECTION( 5 )

START_L_ARRAY( local_table )

L PERMUTE MASK( 0x00010405, 0x08090c0d, 0x10111415, 0x18191c1d )
L PERMUTE MASK( 0x02030607, 0x0a0b0e0f, 0x12131617, 0x1a1b1e1f )
L PERMUTE MASK( 0x00020406, 0x080a0c0e, 0x10121416, 0x181a1c1e )
L_PERMUTE_MASK( 0x01030507, 0x090b0d0f, 0x11131517, 0x191b1d1f )

END_ARRAY

/**
 Input parameters
**/
#define A          r3
#define C          r4
#define L1_cache   r5
#define NC         r6
#define NR         r7
#define TCC        r8

#define NC left    NC
#define TCA        r9
#define TCA4       r10
#define icount     r11

#define aptr0      r12
#define aptr1      r13
#define aptr2      r14
#define aptr3      r15

#define aindx0     r16
#define aindx1     r17
#define aindx2     r18
#define aindx3     r19

#define cptr0      r20
#define cptr1      r21
#define cptr2      r22
#define cptr3      r23

#define cindx0     r24
#define cindx1     r25
#define cindx2     r26
#define cindx3     r27

#define cindx4     aindx0
#define cindx5     aindx1
#define cindx6     aindx2
#define cindx7     aindx3
```

2

mtrans32_8bit.mac

2/23/2001

```
#define out indx0    aptr0
#define out indx1    aptr1
#define out indx2    aptr2
#define out_indx3    aptr3

#define cptr         cptr0
#define outptr0      cptr1
#define outptr1      cptr2
#define TCC4         cptr3

#define tptr         icount
#define temp         aptr3

#define Cbump        r0
#define dstp         r0
#define dst_code     r28

/**
 G4 registers
 **/
#define a00          v0
#define a01          v1
#define a02          v2
#define a03          v3

#define a10          v4
#define a11          v5
#define a12          v6
#define a13          v7

#define a20          v8
#define a21          v9
#define a22          v10
#define a23          v11

#define a30          v12
#define a31          v13
#define a32          v14
#define a33          v15

#define c00          v16
#define c01          v17
#define c02          v18
#define c03          v19

#define c10          v20
#define c11          v21
#define c12          v22
#define c13          v23

#define c20          c00
#define c21          c01
#define c22          c02
#define c23          c03

#define c30          c10
#define c31          c11
#define c32          c12
#define c33          c13

#define vt0          v24
#define vt1          v25
#define vt2          v26
#define vt3          v27

#define vt4          c00
#define vt5          c01
```

3

mtrans32_8bit.mac   2/23/2001

```
#define vt6        c02
#define vt7        c03

#define vp0          v28
#define vp1          v29
#define vp2          v30
#define vp3          v31

#define c0         a00
#define c1         a01
#define c2         a02
#define c3         a03
#define c4         a10
#define c5         a11
#define c6         a12
#define c7         a13

#define out0       a20
#define out1       a21
#define out2       a22
#define out3       a23
#define out4       a30
#define out5       a31
#define out6       a32
#define out7       a33

/**
 Text begins
**/
FUNC PROLOG
ENTRY_5( mtrans32_8bit, A, C, L1_cache, N, TCC )

  SAVE r13 r28
  USE_THRU_v31( VRSAVE_COND )

  ADDI( TCA, NC, R MATRIX_ALIGN_MASK )
  CMPWI( NC left, 32 )
  RLWINM( TCA, TCA, 0, 0, (31 - R_MATRIX_ALIGN_LOG) )

  LA( tptr, local table, 0 )
  MAKE_STREAM_CODE_IIR( dst_code, 64, 4, TCA )

    LVX( vp0, 0, tptr )
  ADDI( tptr, tptr, 16 )
    LVX( vp1, 0, tptr )
  ADDI( tptr, tptr, 16 )
  XORI( temp, A, 32 )
    LVX( vp2, 0, tptr )
  ADDI( tptr, tptr, 16 )
  SLWI( TCA4, TCA, 2 )
    LVX( vp3, 0, tptr )

  BLE( cont )

  ANDI C( temp, temp, 32 )
  BR( cont )

/**
 Outer loop transposes 2 (or 1 at end) 32 x 32 tiles per trip
**/
LABEL( outer_loop )
/* { */
    CMPWI( NC_left, 32 )

LABEL( cont )
    ADD( dstp, A, TCA4 )                    /* start prefetch advanced */
    MR( aptr0, A )
```

4

```
            ADD( dstp, dstp, TCA )                    /* advanced further */
            LI( aindx0, 0 )
            ADD( aptr1, aptr0, TCA )
            LI( aindx1, 16 )
            ADD( aptr2, aptr1, TCA )
            MR( cptr0, L1 cache )
            ADD( aptr3, aptr2, TCA )

            ADDI( cptr1, cptr0, 512 )
            LI( cindx0, 0 )
             LOAD INPUT( a00, aptr0, aindx0 )   /*** begins next sequence ***/
            LI( cindx1, 128 )
             LOAD INPUT( a10, aptr1, aindx0 )
            LI( cindx2, 256 )
             LOAD INPUT( a20, aptr2, aindx0 )
            LI( cindx3, 384 )
             LOAD INPUT( a30, aptr3, aindx0 )
            MR( icount, NR )

            BLE( input_loop_do1 )

            LI( aindx2, 32 )                 /* these are used only in two tile loop */
             LOAD INPUT( a02, aptr0, aindx2 )
            LI( aindx3, 48 )
             LOAD INPUT( a12, aptr1, aindx2 )
            ADDI( cptr2, cptr1, 512 )
             LOAD INPUT( a22, aptr2, aindx2 )
            ADDI( cptr3, cptr2, 512 )
             LOAD_INPUT( a32, aptr3, aindx2 )

/**
 Top of input loop processes a 4 x 64 byte tile each trip
**/
LABEL( input_loop_do2 )
/* { */
  PREFETCH( dstp, dst code, 0, TCA4 )
      ADDIC C( icount, icount, -4 )
          VMRGHW(vt0, a00, a20)      /* vt0 = a00[0-3] a20[0-3] a00[4-7] a20[4-7] */
      LOAD INPUT( a01, aptr0, aindx1 )
          VMRGLW(vt2, a00, a20)      /* vt2 = a00[8-b] a20[8-b] a00[c-f] a20[c-f] */
      LOAD INPUT( a11, aptr1, aindx1 )
          VMRGHW(vt1, a10, a30)      /* vt1 = a10[0-3] a30[0-3] a10[4-7] a30[4-7] */
      LOAD INPUT( a21, aptr2, aindx1 )
          VMRGLW(vt3, a10, a30)      /* vt3 = a10[8-b] a10[8-b] a30[c-f] a30[c-f] */
      LOAD_INPUT( a31, aptr3, aindx1 )

          VMRGHW(c00, vt0, vt1)      /* c00 = a00[0-3] a10[0-3] a20[0-3] a30[0-3] */
      STORE CACHE( c00, cptr0, cindx0 )
          VMRGLW(c01, vt0, vt1)      /* c01 = a00[4-7] a10[4-7] a20[4-7] a30[4-7] */
      STORE CACHE( c01, cptr0, cindx1 )
          VMRGHW(c02, vt2, vt3)      /* c02 = a00[8-b] a10[8-b] a20[8-b] a30[8-b] */
      STORE CACHE( c02, cptr0, cindx2 )
          VMRGLW(c03, vt2, vt3)      /* c03 = a00[c-f] a10[c-f] a20[c-f] a30[c-f] */
      STORE_CACHE( c03, cptr0, cindx3 )

          VMRGHW(vt0, a01, a21)      /* vt0 = a01[0-3] a21[0-3] a01[4-7] a21[4-7] */
      LOAD INPUT( a03, aptr0, aindx3 )
          VMRGLW(vt2, a01, a21)      /* vt2 = a01[8-b] a21[8-b] a01[c-f] a21[c-f] */
      LOAD INPUT( a13, aptr1, aindx3 )
          VMRGHW(vt1, a11, a31)      /* vt1 = a11[0-3] a31[0-3] a11[4-7] a31[4-7] */
      LOAD INPUT( a23, aptr2, aindx3 )
          VMRGLW(vt3, a11, a31)      /* vt3 = a11[8-b] a11[8-b] a31[c-f] a31[c-f] */
      LOAD_INPUT( a33, aptr3, aindx3 )

          VMRGHW(c10, vt0, vt1)      /* c10 = a01[0-3] a11[0-3] a21[0-3] a31[0-3] */
      STORE CACHE( c10, cptr1, cindx0 )
          VMRGLW(c11, vt0, vt1)      /* c11 = a01[4-7] a11[4-7] a21[4-7] a31[4-7] */
```

5

```
        STORE CACHE( c11, cptr1, cindx1 )
          VMRGHW(c12, vt2, vt3)     /* c12 = a01[8-b] a11[8-b] a21[8-b] a31[8-b] */
        STORE CACHE( c12, cptr1, cindx2 )
          VMRGLW(c13, vt2, vt3)     /* c13 = a01[c-f] a11[c-f] a21[c-f] a31[c-f] */
        STORE_CACHE( c13, cptr1, cindx3 )

    BLE( flush_input_loop_do2 )

    ADD( aindx0, aindx0, TCA4 )      /* bump for next load sequence */
    ADD( aindx1, aindx1, TCA4 )
    ADD( aindx2, aindx2, TCA4 )
    ADD( aindx3, aindx3, TCA4 )

        VMRGHW(vt0, a02, a22)     /* vt0 = a02[0-3] a22[0-3] a02[4-7] a22[4-7] */
        LOAD INPUT( a00, aptr0, aindx0 )   /*** begins next sequence ***/
          VMRGLW(vt2, a02, a22)     /* vt2 = a02[8-b] a22[8-b] a02[c-f] a22[c-f] */
        LOAD INPUT( a02, aptr0, aindx2 )
          VMRGHW(vt1, a12, a32)     /* vt1 = a12[0-3] a32[0-3] a12[4-7] a32[4-7] */
        LOAD INPUT( a10, aptr1, aindx0 )
          VMRGLW(vt3, a12, a32)     /* vt3 = a12[8-b] a12[8-b] a32[c-f] a32[c-f] */
        LOAD_INPUT( a12, aptr1, aindx2 )

          VMRGHW(c20, vt0, vt1)     /* c20 = a02[0-3] a12[0-3] a22[0-3] a32[0-3] */
        STORE CACHE( c20, cptr2, cindx0 )
          VMRGLW(c21, vt0, vt1)     /* c21 = a02[4-7] a12[4-7] a22[4-7] a32[4-7] */
        STORE CACHE( c21, cptr2, cindx1 )
          VMRGHW(c22, vt2, vt3)     /* c22 = a02[8-b] a12[8-b] a22[8-b] a32[8-b] */
        STORE CACHE( c22, cptr2, cindx2 )
          VMRGLW(c23, vt2, vt3)     /* c23 = a02[c-f] a12[c-f] a22[c-f] a32[c-f] */
        STORE CACHE( c23, cptr2, cindx3 )

        VMRGHW(vt0, a03, a23)     /* vt0 = a03[0-3] a23[0-3] a03[4-7] a23[4-7] */
        LOAD INPUT( a20, aptr2, aindx0 )
          VMRGLW(vt2, a03, a23)     /* vt2 = a03[8-b] a23[8-b] a03[c-f] a23[c-f] */
        LOAD INPUT( a22, aptr2, aindx2 )
          VMRGHW(vt1, a13, a33)     /* vt1 = a13[0-3] a33[0-3] a13[4-7] a33[4-7] */
        LOAD INPUT( a30, aptr3, aindx0 )
          VMRGLW(vt3, a13, a33)     /* vt3 = a13[8-b] a13[8-b] a33[c-f] a33[c-f] */
        LOAD_INPUT( a32, aptr3, aindx2 )

          VMRGHW(c30, vt0, vt1)     /* c30 = a03[0-3] a13[0-3] a23[0-3] a33[0-3] */
        STORE CACHE( c30, cptr3, cindx0 )
          VMRGLW(c31, vt0, vt1)     /* c31 = a03[4-7] a13[4-7] a23[4-7] a33[4-7] */
        STORE CACHE( c31, cptr3, cindx1 )
          VMRGHW(c32, vt2, vt3)     /* c32 = a03[8-b] a13[8-b] a23[8-b] a33[8-b] */
        STORE CACHE( c32, cptr3, cindx2 )
          VMRGLW(c33, vt2, vt3)     /* c33 = a03[c-f] a13[c-f] a23[c-f] a33[c-f] */
        STORE_CACHE( c33, cptr3, cindx3 )

    ADDI( cindx0, cindx0, 16 )       /* bump for next store sequence */
    ADDI( cindx1, cindx1, 16 )
    ADDI( cindx2, cindx2, 16 )
    ADDI( cindx3, cindx3, 16 )

    BR( input_loop_do2 )

LABEL( flush_input_loop_do2 )

        VMRGHW(vt0, a02, a22)     /* vt0 = a02[0-3] a22[0-3] a02[4-7] a22[4-7] */
        VMRGLW(vt2, a02, a22)     /* vt2 = a02[8-b] a22[8-b] a02[c-f] a22[c-f] */
        VMRGHW(vt1, a12, a32)     /* vt1 = a12[0-3] a32[0-3] a12[4-7] a32[4-7] */
        VMRGLW(vt3, a12, a32)     /* vt3 = a12[8-b] a12[8-b] a32[c-f] a32[c-f] */

        VMRGHW(c20, vt0, vt1)     /* c20 = a02[0-3] a12[0-3] a22[0-3] a32[0-3] */
        STORE CACHE( c20, cptr2, cindx0 )
          VMRGLW(c21, vt0, vt1)     /* c21 = a02[4-7] a12[4-7] a22[4-7] a32[4-7] */
        STORE_CACHE( c21, cptr2, cindx1 )
```

6

```
        VMRGHW(c22, vt2, vt3)     /* c22 = a02[8-b] a12[8-b] a22[8-b] a32[8-b] */
    STORE_CACHE( c22, cptr2, cindx2 )
        VMRGLW(c23, vt2, vt3)     /* c23 = a02[c-f] a12[c-f] a22[c-f] a32[c-f] */
    STORE_CACHE( c23, cptr2, cindx3 )

        VMRGHW(vt0, a03, a23)     /* vt0 = a03[0-3] a23[0-3] a03[4-7] a23[4-7] */
        VMRGLW(vt2, a03, a23)     /* vt2 = a03[8-b] a23[8-b] a03[c-f] a23[c-f] */
        VMRGHW(vt1, a13, a33)     /* vt1 = a13[0-3] a33[0-3] a13[4-7] a33[4-7] */
        VMRGLW(vt3, a13, a33)     /* vt3 = a13[8-b] a13[8-b] a33[c-f] a33[c-f] */

        VMRGHW(c30, vt0, vt1)     /* c30 = a03[0-3] a13[0-3] a23[0-3] a33[0-3] */
    STORE_CACHE( c30, cptr3, cindx0 )
        VMRGLW(c31, vt0, vt1)     /* c31 = a03[4-7] a13[4-7] a23[4-7] a33[4-7] */
    STORE_CACHE( c31, cptr3, cindx1 )
        VMRGHW(c32, vt2, vt3)     /* c32 = a03[8-b] a13[8-b] a23[8-b] a33[8-b] */
    STORE_CACHE( c32, cptr3, cindx2 )
        VMRGLW(c33, vt2, vt3)     /* c33 = a03[c-f] a13[c-f] a23[c-f] a33[c-f] */
    STORE_CACHE( c33, cptr3, cindx3 )

    MR( outptr0, C )                     /* set for output loop in current pass */
    SLWI( Cbump, TCC, 6 )
    ADDI( A, A, 64 )
    ADD( C, C, Cbump )               /* bump C for next pass */
    LI( icount, 64 )                 /* set icount for 2 tiles */
    BR( output_start )               /* join to common output loop */

/**
 Top of input loop processes a 4 x 32 byte tile each trip
**/
LABEL( input_loop_do1 )
/* { */
    PREFETCH( dstp, dst_code, 0, TCA4 )
        ADDIC_C( icount, icount, -4 )
        VMRGHW(vt0, a00, a20)     /* vt0 = a00[0-3] a20[0-3] a00[4-7] a20[4-7] */
    LOAD_INPUT( a01, aptr0, aindx1 )
        VMRGLW(vt2, a00, a20)     /* vt2 = a00[8-b] a20[8-b] a00[c-f] a20[c-f] */
    LOAD_INPUT( a11, aptr1, aindx1 )
        VMRGHW(vt1, a10, a30)     /* vt1 = a10[0-3] a30[0-3] a10[4-7] a30[4-7] */
    LOAD_INPUT( a21, aptr2, aindx1 )
        VMRGLW(vt3, a10, a30)     /* vt3 = a10[8-b] a10[8-b] a30[c-f] a30[c-f] */
    LOAD_INPUT( a31, aptr3, aindx1 )

        VMRGHW(c00, vt0, vt1)     /* c00 = a00[0-3] a10[0-3] a20[0-3] a30[0-3] */
    STORE_CACHE( c00, cptr0, cindx0 )
        VMRGLW(c01, vt0, vt1)     /* c01 = a00[4-7] a10[4-7] a20[4-7] a30[4-7] */
    STORE_CACHE( c01, cptr0, cindx1 )
        VMRGHW(c02, vt2, vt3)     /* c02 = a00[8-b] a10[8-b] a20[8-b] a30[8-b] */
    STORE_CACHE( c02, cptr0, cindx2 )
        VMRGLW(c03, vt2, vt3)     /* c03 = a00[c-f] a10[c-f] a20[c-f] a30[c-f] */
    STORE_CACHE( c03, cptr0, cindx3 )

    BLE( flush_input_loop_do1 )

    ADD( aindx0, aindx0, TCA4 )     /* bump for next load sequence */
    ADD( aindx1, aindx1, TCA4 )

        VMRGHW(vt0, a01, a21)     /* vt0 = a01[0-3] a21[0-3] a01[4-7] a21[4-7] */
    LOAD_INPUT( a00, aptr0, aindx0 )   /*** begins next sequence ***/
        VMRGLW(vt2, a01, a21)     /* vt2 = a01[8-b] a21[8-b] a01[c-f] a21[c-f] */
    LOAD_INPUT( a10, aptr1, aindx0 )
        VMRGHW(vt1, a11, a31)     /* vt1 = a11[0-3] a31[0-3] a11[4-7] a31[4-7] */
    LOAD_INPUT( a20, aptr2, aindx0 )
        VMRGLW(vt3, a11, a31)     /* vt3 = a11[8-b] a11[8-b] a31[c-f] a31[c-f] */
    LOAD_INPUT( a30, aptr3, aindx0 )

        VMRGHW(c10, vt0, vt1)     /* c10 = a01[0-3] a11[0-3] a21[0-3] a31[0-3] */
    STORE_CACHE( c10, cptr1, cindx0 )
```

7

```
        VMRGLW(c11, vt0, vt1)    /* c11 = a01[4-7] a11[4-7] a21[4-7] a31[4-7] */
     STORE_CACHE( c11, cptr1, cindx1 )
        VMRGHW(c12, vt2, vt3)    /* c12 = a01[8-b] a11[8-b] a21[8-b] a31[8-b] */
     STORE_CACHE( c12, cptr1, cindx2 )
        VMRGLW(c13, vt2, vt3)    /* c13 = a01[c-f] a11[c-f] a21[c-f] a31[c-f] */
     STORE_CACHE( c13, cptr1, cindx3 )

    ADDI( cindx0, cindx0, 16 )      /* bump for next store sequence */
    ADDI( cindx1, cindx1, 16 )
    ADDI( cindx2, cindx2, 16 )
    ADDI( cindx3, cindx3, 16 )

    BR( input_loop_do1 )

LABEL( flush_input_loop_do1 )

        VMRGHW(vt0, a01, a21)    /* vt0 = a01[0-3] a21[0-3] a01[4-7] a21[4-7] */
        VMRGLW(vt2, a01, a21)    /* vt2 = a01[8-b] a21[8-b] a01[c-f] a21[c-f] */
        VMRGHW(vt1, a11, a31)    /* vt1 = a11[0-3] a31[0-3] a11[4-7] a31[4-7] */
        VMRGLW(vt3, a11, a31)    /* vt3 = a11[8-b] a11[8-b] a31[c-f] a31[c-f] */

        VMRGHW(c10, vt0, vt1)    /* c10 = a01[0-3] a11[0-3] a21[0-3] a31[0-3] */
     STORE_CACHE( c10, cptr1, cindx0 )
        VMRGLW(c11, vt0, vt1)    /* c11 = a01[4-7] a11[4-7] a21[4-7] a31[4-7] */
     STORE_CACHE( c11, cptr1, cindx1 )
        VMRGHW(c12, vt2, vt3)    /* c12 = a01[8-b] a11[8-b] a21[8-b] a31[8-b] */
     STORE_CACHE( c12, cptr1, cindx2 )
        VMRGLW(c13, vt2, vt3)    /* c13 = a01[c-f] a11[c-f] a21[c-f] a31[c-f] */
     STORE_CACHE( c13, cptr1, cindx3 )

    MR( outptr0, C )               /* set for output loop in current pass */
    SLWI( Cbump, TCC, 5 )
    ADDI( A, A, 32 )
    ADD( C, C, Cbump )             /* bump C for next pass */
    LI( icount, 32 )               /* set icount for 1 tile */

/**
 Second stage of transposition, write output
**/
LABEL( output_start )

    CMPW_CR( 6, icount, NC_left )

    MR( cptr, L1 cache )
    SLWI( TCC4, TCC, 2 )
    LI( cindx0, 0 )
    LI( cindx1, 16 )
    LI( cindx2, 2*16 )
    LI( cindx3, 3*16 )
    LI( cindx4, 4*16 )
    LI( cindx5, 5*16 )
    LI( cindx6, 6*16 )

    BLE_CR( 6, PC OFFSET( 8 ) )
    MR( icount, NC_left )

    LI( cindx7, 7*16 )
    SUB( NC_left, NC_left, icount )

    ADDIC C( icount, icount, -4 )
    LI( out indx0, 0 )
      LOAD CACHE( c0, cptr, cindx0 )
    ADD( out indx1, out indx0, TCC )
      LOAD CACHE( c1, cptr, cindx1 )
    ADD( out indx2, out indx1, TCC )
      LOAD CACHE( c2, cptr, cindx2 )
    ADD( out_indx3, out_indx2, TCC )
```

8

```
      mtrans32_8bit.mac

          LOAD CACHE( c3, cptr, cindx3 )
       ADDI( outptr1, outptr0, 16 )
          LOAD CACHE( c4, cptr, cindx4 )
            VPERM( vt0, c0, c1, vp0 )
          LOAD CACHE( c5, cptr, cindx5 )
            VPERM( vt1, c0, c1, vp1 )
          LOAD CACHE( c6, cptr, cindx6 )
            VPERM( vt2, c2, c3, vp0 )
          LOAD CACHE( c7, cptr, cindx7 )
            VPERM( vt3, c2, c3, vp1 )
       ADDI( cptr, cptr, 128 )
       BR( output_mloop )


/**
 Loop outputs four 32 byte rows
**/
LABEL( output loop )
    ADDIC_C( icount, icount, -4 )
    ADDI( cptr, cptr, 128 )

      STORE OUTPUT( out0, outptr0, out_indx0 )
        VPERM( out4, vt4, vt6, vp2 )
      STORE OUTPUT( out4, outptr1, out_indx0 )
        VPERM( out5, vt4, vt6, vp3 )
      STORE OUTPUT( out1, outptr0, out_indx1 )
        VPERM( out6, vt5, vt7, vp2 )
      STORE OUTPUT( out5, outptr1, out_indx1 )
        VPERM( out7, vt5, vt7, vp3 )

      STORE OUTPUT( out2, outptr0, out_indx2 )
        VPERM( vt0, c0, c1, vp0 )
      STORE OUTPUT( out6, outptr1, out_indx2 )
        VPERM( vt1, c0, c1, vp1 )
      STORE OUTPUT( out3, outptr0, out_indx3 )
        VPERM( vt2, c2, c3, vp0 )
      STORE OUTPUT( out7, outptr1, out_indx3 )
        VPERM( vt3, c2, c3, vp1 )

      ADD( outptr0, outptr0, TCC4 )
      ADD( outptr1, outptr1, TCC4 )

  LABEL( output mloop )
    BLE( flush output_loop )
      LOAD CACHE( c0, cptr, cindx0 )
        VPERM( vt4, c4, c5, vp0 )
      LOAD CACHE( c1, cptr, cindx1 )
        VPERM( vt5, c4, c5, vp1 )
      LOAD CACHE( c2, cptr, cindx2 )
        VPERM( vt6, c6, c7, vp0 )
      LOAD CACHE( c3, cptr, cindx3 )
        VPERM( vt7, c6, c7, vp1 )

      LOAD CACHE( c4, cptr, cindx4 )
        VPERM( out0, vt0, vt2, vp2 )
      LOAD CACHE( c5, cptr, cindx5 )
        VPERM( out1, vt0, vt2, vp3 )
      LOAD CACHE( c6, cptr, cindx6 )
        VPERM( out2, vt1, vt3, vp2 )
      LOAD CACHE( c7, cptr, cindx7 )
        VPERM( out3, vt1, vt3, vp3 )

      BR( output_loop )

  LABEL( flush_output_loop )

        VPERM( vt4, c4, c5, vp0 )
        VPERM( vt5, c4, c5, vp1 )
```

9

mtrans32_8bit.mac   2/23/2001

```
            VPERM( vt6, c6, c7, vp0 )
            VPERM( vt7, c6, c7, vp1 )

        CMPWI( icount, -3 )
            VPERM( out0, vt0, vt2, vp2 )
          STORE OUTPUT( out0, outptr0, out_indx0 )
            VPERM( out4, vt4, vt6, vp2 )
          STORE OUTPUT( out4, outptr1, out_indx0 )
        BEQ( oloop_next )

        CMPWI( icount, -2 )
            VPERM( out1, vt0, vt2, vp3 )
          STORE OUTPUT( out1, outptr0, out_indx1 )
            VPERM( out5, vt4, vt6, vp3 )
          STORE OUTPUT( out5, outptr1, out_indx1 )
        BEQ( oloop_next )

        CMPWI( icount, -1 )
            VPERM( out2, vt1, vt3, vp2 )
          STORE OUTPUT( out2, outptr0, out_indx2 )
            VPERM( out6, vt5, vt7, vp2 )
          STORE OUTPUT( out6, outptr1, out_indx2 )
        BEQ( oloop_next )

            VPERM( out3, vt1, vt3, vp3 )
          STORE OUTPUT( out3, outptr0, out_indx3 )
            VPERM( out7, vt5, vt7, vp3 )
          STORE_OUTPUT( out7, outptr1, out_indx3 )

/**
 Next four rows of C?
**/
LABEL( oloop next )
    BLT_CR( 6, outer_loop )                    /* branch if icount < NC_left */

/**
 Exit routine
**/
 LABEL( ret )
 FREE THRU v31( VRSAVE_COND )
 REST r13_r28
 RETURN

FUNC_EPILOG
```

10

mtriangle_8bit.mac   2/23/2001

```
/*-----------------------------------------------------------------+
|--- MC Standard Algorithms -- PPC Macro language Version    ---|
|-----------------------------------------------------------------|
|                                                                 |
|   File Name:    mtriangle_8bit.mac.                             |
|   Description:  Move from an upper triangular matrix stored     |
|                 as a series of 32-line rectangles, each of      |
|                 width 32 elements less than its immediate       |
|                 predecessor to the upper triangle of an         |
|                 full N x N matrix.                              |
|                                                                 |
|   mtriangle_8bit ( char *A, char *C, int N )                   |
|                                                                 |
|   Restrictions:  A, B and C must all be 16-byte aligned.       |
|                  N must be a multiple of 16 and >= 16.         |
|                                                                 |
|           Mercury Computer Systems, Inc.                        |
|           Copyright (c) 2000  All rights reserved               |
|                                                                 |
|   Revision      Date      Engineer  Reason                      |
|   --------      ----      -------- --------                     |
|     0.0         000605      jg   Created                        |
+-----------------------------------------------------------------*/

#include "salppc.inc"

#define LOAD_A( vT, rA, rB )       LVXL( vT, rA, rB )
#define LOAD_C( vT, rA, rB )       LVX( vT, rA, rB )
#define STORE_C( vS, rA, rB )      STVX( vS, rA, rB )

#define R_MATRIX_ALIGN_LOG    5
#define R_MATRIX_ALIGN         (1 << R_MATRIX_ALIGN_LOG)
#define R_MATRIX_ALIGN_MASK   (R_MATRIX_ALIGN - 1)

#define ALTIVEC_ALIGN_LOG     4
#define ALTIVEC_ALIGN          (1 << ALTIVEC_ALIGN_LOG)
#define ALTIVEC_ALIGN_MASK    (ALTIVEC_ALIGN - 1)

/**
 Input parameters
**/
#define A              r3
#define C              r4
#define N              r5

#define A_tcols        r6
#define C_tcols        r7
#define altivec_N      r8
#define A_counter      r9
#define index0         r10
#define index1         r11
#define index2         r12
#define index3         r13

#define count          r0

#define a0             v0
#define a1             v1
#define a2             v2
#define a3             v3
#define c0             v4
#define shift          v5
#define shift_incr     v6
#define mask           v7
#define left           v8
#define right          v9
```

1

```
FUNC_PROLOG

ENTRY_3( mtriangle_8bit, A, C, N )

  SAVE r13
  USE_THRU_v9( VRSAVE_COND )

  ADDI( A_counter, N, R_MATRIX_ALIGN_MASK )
      VSPLTISW( shift_incr, 8 )
  ADDI( altivec_N, N, ALTIVEC_ALIGN_MASK )
        VXOR( shift, shift, shift )
  RLWINM( A_counter, A_counter, 0, 0, (31 - R_MATRIX_ALIGN_LOG) )
  RLWINM( altivec_N, altivec_N, 0, 0, (31 - ALTIVEC_ALIGN_LOG ) )
  ADDI( C_tcols, A_counter, 1 )

LABEL( oloop )

  ADDIC_C( count, altivec_N, -64 )
    LOAD_C( c0, 0, C )
      VSPLTISW( mask, -1 )
    LOAD_A( a0, 0, A )
      VSRO( mask, mask, shift )
  LI( index0, 16 )
      VANDC( left, c0, mask )
  LI( index1, 32 )
      VAND( right, a0, mask )
  LI( index2, 48 )
      VOR( c0, left, right )
    STORE_C( c0, 0, C )
  BLE( dosmall )
  LI( index3, 64 )

LABEL( iloop )
    LOAD_A( a0, A, index0 )
  ADDIC_C( count, count, -64 )
    LOAD_A( a1, A, index1 )
    LOAD_A( a2, A, index2 )
    LOAD_A( a3, A, index3 )
    STORE_C( a0, C, index0 )
  ADDI( index0, index0, 64 )
    STORE_C( a1, C, index1 )
  ADDI( index1, index1, 64 )
    STORE_C( a2, C, index2 )
  ADDI( index2, index2, 64 )
    STORE_C( a3, C, index3 )
  ADDI( index3, index3, 64 )
  BGT( iloop )

LABEL( dosmall )
  ADDIC_C( count, count, 48 )
  BLE( windout )

LABEL( sloop )
  ADDIC_C( count, count, -16 )
    LOAD_A( a0, A, index0 )
    STORE_C( a0, C, index0 )
  ADDI( index0, index0, 16 )
  BGT( sloop )

LABEL( windout )
  DECR_C( N )
      VADDUWM( shift, shift, shift_incr )
  ADDI( A_counter, A_counter, -1 )
  ADDI( A, A, 1 )
  ADDI( A_tcols, A_counter, R_MATRIX_ALIGN_MASK )
  DECR( altivec_N )
```

2

```
         mtriangle_8bit.mac

    RLWINM( A tcols, A_tcols, 0, 0, (31 - R_MATRIX_ALIGN_LOG) )
    ADD( C, C, C tcols )
    ADD( A, A, A_tcols )
    BNE( oloop )

    FREE THRU_v9( VRSAVE_COND )
    REST r13
    RETURN

FUNC_EPILOG
```

3

```
#if !defined( SALPPC_H )
#define SALPPC_H

#if 0
+*******************************************************************+
|***    MC Standard Algorithms -- PPC Version                   ***|
|*****************************************************************  *|
|*                                                                 *|
|*          File Name:      salppc.h                               *|
|*          Description:    SAL macro include file                 *|
|*                                                                 *|
|*          Source files should have extension .mac. For example, vadd.mac  *|
|*          and must include this file (salppc.h).                 *|
|*                                                                 *|
|*          To assemble for PPC ucode, use the following basic     *|
|*          makefile build rule:                                   *|
|*                                                                 *|
|*              .SUFFIXES: .mac .c .s .o                           *|
|*                                                                 *|
|*              .mac.o:                                            *|
|*                  cp $*.mac $*.c                                 *|
|*                  ccmc -o $*.s -E $*.c                           *|
|*                  ccmc -c -o $*.o $*.s                           *|
|*                  rm -f $*.s                                     *|
|*                  rm -f $*.c                                     *|
|*                                                                 *|
|*          To compile for C, use the following basic makefile build rule:  *|
|*                                                                 *|
|*              .SUFFIXES: .mac .c .o                              *|
|*                                                                 *|
|*              .mac.o:                                            *|
|*                  cp $*.mac $*.c                                 *|
|*                  ccmc -DCOMPILE_C -c -o $*.o $*.c               *|
|*                  rm -f $*.c                                     *|
|*                                                                 *|
|*          The first 8 function arguments are passed in GPR registers  *|
|*          r3 - r10. Arguments beyond 8 are passed on the stack and may  *|
|*          be obtained with the GET_ARG8, GET_ARG9, ... GET ARG15 macros.  *|
|*          Additional GPR registers should be assigned in ascending order  *|
|*          starting from the last function argument. These may be declared *|
|*          with the DECLARE_rx[ ry] macros. For example, a function with  *|
|*          5 arguments that requires 3 additional GPR registers would  *|
|*          issue: DECLARE r8 r10. r0, if required, should be declared  *|
|*          separately with the DECLARE r0 macro. GPR registers above r12  *|
|*          must be saved and restored using the SAVE_r13[_ry] and  *|
|*          REST_r13[_ry] macros, respectively.                    *|
|*                                                                 *|
|*          FPR registers should be assigned in ascending order starting  *|
|*          with f0[d0]. These may be declared with the DECLARE_f0[_fy]  *|
|*          or DECLARE d0[ dy] macros.                             *|
|*          For example, DECLARE f0 f11. FPR registers above f13[d13] must  *|
|*          be saved and restored using the SAVE f14[ fy] and REST f14[_fy]  *|
|*          or SAVE_d14[_dy] and REST_d14[_dy] macros, respectively.  *|
|*                                                                 *|
|*          All variables must be assigned a register using the    *|
|*          pre-processor #define directive. GPR registers are named  *|
|*          r0 - r31; Single precision FPR registers are named f0 - f31.  *|
|*          Double precision FPR registers are named d0 - d31. Different  *|
|*          variables may be assigned to the same register as in:  *|
|*                                                                 *|
|*              #define vara   f12                                 *|
|*              #define varb   f12                                 *|
|*                                                                 *|
|*          Functions must begin with the FUNC_PROLOG macro and end  *|
|*          with the FUNC_EPILOG macro.                            *|
|*                                                                 *|
```

1

```
*        Macros are provided for both Fortran and C entry points.     *|
*                                                                     *|
*        The GET SALCACHE macro should be used to get the address of  *|
*        the "current" salcache buffer into a GPR register.           *|
*                                                                     *|
*        Avoid terminating macro lines with a semicolon.              *|
*                                                                     *|
*        The following example demonstrates typical usage:            *|
*                                                                     *|
*            #include "salppc.h"                                      *|
*                                                                     *|
*            /*                                                       *|
*             *   assign variables to registers                      *|
*             */                                                      *|
*            #define A   r3                                           *|
*            #define I   r4                                           *|
*            #define B   r5                                           *|
*            #define J   r6                                           *|
*            #define C   r7                                           *|
*            #define K   r8                                           *|
*            #define D   r9                                           *|
*            #define L   r10                                          *|
*            #define N   r12                                          *|
*            #define EFLAG   r11                                      *|
*            #define count   r11                                      *|
*                                                                     *|
*            #define t0   r13                                         *|
*            #define t1   r13                                         *|
*            #define t2   r14                                         *|
*            #define t3   r14                                         *|
*            #define t4   r15                                         *|
*            #define t5   r15                                         *|
*            #define t6   r16                                         *|
*                                                                     *|
*            #define a0   f0                                          *|
*            #define a1   f1                                          *|
*            #define a2   f2                                          *|
*            #define a3   f3                                          *|
*            #define b0   f4                                          *|
*            #define b1   f5                                          *|
*            #define b2   f6                                          *|
*            #define b3   f7                                          *|
*            #define c0   f8                                          *|
*            #define c1   f9                                          *|
*            #define c2   f10                                         *|
*            #define c3   f11                                         *|
*            #define d0   f12                                         *|
*            #define d1   f13                                         *|
*            #define d2   f14                                         *|
*            #define d3   f15                                         *|
*                                                                     *|
*        FUNC_PROLOG                     /* must precede function */   *|
*                                                                     *|
*        #if !defined( COMPILE_C )                                    *|
*            U ENTRY(foo )                                            *|
*            FORTRAN DREF 4(I, J, K, L)                               *|
*            FORTRAN_DREF_ARG8                                        *|
*                                                                     *|
*            U ENTRY(foo)                                             *|
*            LI(EFLAG, 0)                                             *|
*            BR(common)                                               *|
*                                                                     *|
*            U ENTRY(foo x )                                          *|
*            FORTRAN DREF 4(I, J, K, L)                               *|
*            FORTRAN DREF ARG8                                        *|
*            FORTRAN_DREF_ARG9                                        *|
*        #endif                                                       *|
```

2

salppc.h   2/23/2001

```
|*                                                                      *|
|*          ENTRY 10(foo x, A, I, B, J, C, K, D, L, N, EFLAG)           *|
|*              DECLARE r13 r16                                         *|
|*              DECLARE f0 f15                                          *|
|*              GET_ARG9( EFLAG )   /* get the 9'th arg (EFLAG) off stack */ *|
|*                                                                      *|
|*          LABEL(common)                                               *|
|*                                                                      *|
|*              SAVE CR                /* needed if using fields 2,3 or 4 */  *|
|*              SAVE r13 r16                                            *|
|*              SAVE f14_f15                                            *|
|*              SAVE_LR                /* needed if making a function call */ *|
|*                                                                      *|
|*              GET_ARG8( N )          /* get the 8'th arg (N) off stack */   *|
|*                                                                      *|
|*                  /* ... body of function ... */                      *|
|*                                                                      *|
|*              REST CR                                                 *|
|*              REST r13 r16                                            *|
|*              REST f14_f15                                            *|
|*              REST LR                                                 *|
|*              RETURN                                                  *|
|*                                                                      *|
|*          FUNC_EPILOG                           /* must conclude function */ *|
|*                                                                      *|
|*              Mercury Computer Systems, Inc.                          *|
|*              Copyright (c) 1996  All rights reserved                 *|
|*                                                                      *|
|* Revision      Date         Engineer; Reason                         *|
|* --------      ----         ----------------                         *|
|*   0.0         960223       jg; Created                              *|
|*   0.1         970109       jfk; Added POSTING BUFFER COUNT and made  *|
|*                                 TEST IF DCBZ macro time "stw" instead *|
|*                                 of doing the TEST IF DCBT macro(lwz) *|
|*   0.2         970124       jfk; Added SALCACHE ALLOC SIZE ,          *|
|*                                 ALIGN SALCACHE, CREATE_SALCACHE_FRAME *|
|*                                 DESTROY SALCACHE FRAME               *|
|*   0.3         970521       jfk; Added SET DCB[TZ] COND macros.       *|
|*                                 Made old macros not assemble         *|
|*   0.4         980813       jfk; Changes SALCACHE ALLOC SIZE for 750  *|
+************************************************************************+
#endif                                      /* header */

#include <math.h>

#define uchar    unsigned char
#define ulong    unsigned long
#define ushort   unsigned short

#define CR   _cr
#define CTR  _ctr
#define VSCR _vscr

/*
 *   define a structure to represent a VMX register
 */
typedef union {
    char   c[16];
    uchar  uc[16];
    short  s[8];
    ushort us[8];
    long   l[4];
    ulong  ul[4];
    float  f[4];
} VMX_reg;

#define FUNC_PROLOG
```

3

salppc.h   2/23/2001

```
#define FUNC_EPILOG \
    }

#define TEXT_SECTION( logb2_align )

#define DATA_SECTION( logb2_align )

#define RODATA_SECTION( logb2_align )

/*
 *   macro for C extern declarations
 */
#define EXTERN_DATA( symbol ) \
    extern long  symbol;

#define EXTERN_FUNC( func ) \
    extern void  func( void );

/*
 *   macro for a global declaration
 */
#define GLOBAL( symbol )

/*
 *   macro for a local declaration
 */
#define LOCAL( symbol )

/*
 *   macros for creating static arrays
 */
#define START_ARRAY( type, name ) \
type name##[] = {

#define START_C_ARRAY( name ) START_ARRAY( char, name )
#define START_UC_ARRAY( name ) START_ARRAY( uchar, name )
#define START_S_ARRAY( name ) START_ARRAY( short, name )
#define START_US_ARRAY( name ) START_ARRAY( ushort, name )
#define START_L_ARRAY( name ) START_ARRAY( long, name )
#define START_UL_ARRAY( name ) START_ARRAY( ulong, name )
#define START_F_ARRAY( name ) START_ARRAY( float, name )

#define END_ARRAY \
};

#define DATA( d1 ) \
d1,

#define DATA2( d1, d2 ) \
d1, d2,

#define DATA4( d1, d2, d3, d4 ) \
d1, d2, d3, d4,

#define DATA8( d1, d2, d3, d4, d5, d6, d7, d8 ) \
d1, d2, d3, d4, d5, d6, d7, d8,

#define C_DATA( d1 )    DATA( d1 )
#define UC_DATA( d1 )   DATA( d1 )
#define S_DATA( d1 )    DATA( d1 )
#define US_DATA( d1 )   DATA( d1 )
#define L_DATA( d1 )    DATA( d1 )
#define UL_DATA( d1 )   DATA( d1 )
#define F_DATA( d1 )    DATA( d1 )

#if defined( LITTLE_ENDIAN )
```

4

salppc.h

```
#define D_DATA( d1, d2 )    DATA2( d2, d1 )
#else
#define D_DATA( d1, d2 )    DATA2( d1, d2 )
#endif

#define C DATA2( d1, d2 )    DATA2( d1, d2 )
#define UC DATA2( d1, d2 )   DATA2( d1, d2 )
#define S DATA2( d1, d2 )    DATA2( d1, d2 )
#define US DATA2( d1, d2 )   DATA2( d1, d2 )
#define L DATA2( d1, d2 )    DATA2( d1, d2 )
#define UL DATA2( d1, d2 )   DATA2( d1, d2 )
#define F_DATA2( d1, d2 )    DATA2( d1, d2 )

#define C DATA4( d1, d2, d3, d4 )    DATA4( d1, d2, d3, d4 )
#define UC DATA4( d1, d2, d3, d4 )   DATA4( d1, d2, d3, d4 )
#define S DATA4( d1, d2, d3, d4 )    DATA4( d1, d2, d3, d4 )
#define US DATA4( d1, d2, d3, d4 )   DATA4( d1, d2, d3, d4 )
#define L DATA4( d1, d2, d3, d4 )    DATA4( d1, d2, d3, d4 )
#define UL DATA4( d1, d2, d3, d4 )   DATA4( d1, d2, d3, d4 )
#define F_DATA4( d1, d2, d3, d4 )    DATA4( d1, d2, d3, d4 )

#define C DATA8( d1, d2, d3, d4, d5, d6, d7, d8 ) \
        DATA8( d1, d2, d3, d4, d5, d6, d7, d8 )
#define UC DATA8( d1, d2, d3, d4, d5, d6, d7, d8 ) \
        DATA8( d1, d2, d3, d4, d5, d6, d7, d8 )
#define S DATA8( d1, d2, d3, d4, d5, d6, d7, d8 ) \
        DATA8( d1, d2, d3, d4, d5, d6, d7, d8 )
#define US DATA8( d1, d2, d3, d4, d5, d6, d7, d8 ) \
        DATA8( d1, d2, d3, d4, d5, d6, d7, d8 )
#define L DATA8( d1, d2, d3, d4, d5, d6, d7, d8 ) \
        DATA8( d1, d2, d3, d4, d5, d6, d7, d8 )
#define UL DATA8( d1, d2, d3, d4, d5, d6, d7, d8 ) \
        DATA8( d1, d2, d3, d4, d5, d6, d7, d8 )
#define F DATA8( d1, d2, d3, d4, d5, d6, d7, d8 ) \
        DATA8( d1, d2, d3, d4, d5, d6, d7, d8 )

/*
 *  macros for creating vmx permute masks (128-bits)
 */
#if defined( LITTLE_ENDIAN )

#define L PERMUTE MUNGE( l )  ( (l) ^ 0x1c1c1c1c )
#define S PERMUTE MUNGE( s )  ( (s) ^ 0x1e1e )
#define C_PERMUTE_MUNGE( c )  ( (c) ^ 0x1f )

#define L INDEX MUNGE( x )  ( (x) ^ 0x3 )
#define S INDEX MUNGE( x )  ( (x) ^ 0x7 )
#define C_INDEX_MUNGE( x )  ( (x) ^ 0xf )

#else

#define L PERMUTE MUNGE( l )  ( l )
#define S PERMUTE MUNGE( s )  ( s )
#define C_PERMUTE_MUNGE( c )  ( c )

#define L INDEX MUNGE( x )  ( x )
#define S INDEX MUNGE( x )  ( x )
#define C_INDEX_MUNGE( x )  ( x )

#endif

#define L PERMUTE MASK( l1, l2, l3, l4 ) \
L PERMUTE MUNGE( l1 ), L PERMUTE MUNGE( l2 ), \
L_PERMUTE_MUNGE( l3 ), L_PERMUTE_MUNGE( l4 ),

#define S PERMUTE MASK( s1, s2, s3, s4, s5, s6, s7, s8 ) \
S_PERMUTE_MUNGE( s1 ), S_PERMUTE_MUNGE( s2 ), \
```

5

salppc.h

```
S PERMUTE MUNGE( s3 ), S PERMUTE MUNGE( s4 ), \
S PERMUTE MUNGE( s5 ), S PERMUTE MUNGE( s6 ), \
S_PERMUTE_MUNGE( s7 ), S_PERMUTE_MUNGE( s8 ),

#define C_PERMUTE_MASK( c1, c2, c3, c4, c5, c6, c7, c8, \
                        c9, c10, c11, c12, c13, c14, c15, c16 ) \
C PERMUTE MUNGE( c1 ), C PERMUTE MUNGE( c2 ), \
C PERMUTE MUNGE( c3 ), C PERMUTE MUNGE( c4 ), \
C PERMUTE MUNGE( c5 ), C PERMUTE MUNGE( c6 ), \
C PERMUTE MUNGE( c7 ), C PERMUTE MUNGE( c8 ), \
C PERMUTE MUNGE( c9 ), C PERMUTE MUNGE( c10 ), \
C PERMUTE MUNGE( c11 ), C PERMUTE MUNGE( c12 ), \
C PERMUTE MUNGE( c13 ), C PERMUTE MUNGE( c14 ), \
C_PERMUTE_MUNGE( c15 ), C_PERMUTE_MUNGE( c16 ),

/*
 *  macro for a microcode entry point (e.g. vaddx, vaddx_)
 *  U_ENTRY is a "nop" for C code
 */
#define U_ENTRY( func_name )

/*
 *  macros for C function prototypes
 */
#define C PROTOTYPE_0( func_name ) \
   void func_name ( void );

#define C PROTOTYPE_1( func_name ) \
   void func_name ( long );

#define C PROTOTYPE_2( func name ) \
   void func_name ( long, long );

#define C PROTOTYPE_3( func name ) \
   void func_name ( long, long, long );

#define C PROTOTYPE_4( func name ) \
   void func_name ( long, long, long, long );

#define C PROTOTYPE_5( func name ) \
   void func_name ( long, long, long, long, long );

#define C PROTOTYPE_6( func name ) \
   void func_name ( long, long, long, long, long, long );

#define C PROTOTYPE_7( func name ) \
   void func_name ( long, long, long, long, long, long, long );

#define C PROTOTYPE_8( func name ) \
   void func_name ( long, long, long, long, long, long, long, long );

#define C PROTOTYPE_9( func name ) \
   void func_name ( long, long, long, long, long, long, long, long, \
                    long );

#define C PROTOTYPE_10( func name ) \
   void func_name ( long, long, long, long, long, long, long, long, \
                    long, long );

#define C PROTOTYPE_11( func name ) \
   void func_name ( long, long, long, long, long, long, long, long, \
                    long, long, long );

#define C PROTOTYPE_12( func name ) \
   void func_name ( long, long, long, long, long, long, long, long, \
                    long, long, long, long );
```

6

```
#define C_PROTOTYPE_13( func_name ) \
   void func_name ( long, long, long, long, long, long, long, long, \
                    long, long, long, long, long );

#define C_PROTOTYPE_14( func_name ) \
   void func_name ( long, long, long, long, long, long, long, long, \
                    long, long, long, long, long, long );

#define C_PROTOTYPE_15( func_name ) \
   void func_name ( long, long, long, long, long, long, long, long, \
                    long, long, long, long, long, long, long );

#define C_PROTOTYPE_16( func_name ) \
   void func_name ( long, long, long, long, long, long, long, long, \
                    long, long, long, long, long, long, long, long );

#define AUTO_r3 r31 \
   long r3, r4, r5, r6, r7, r8, r9, r10, r11, r12, r13, r14, r15, r16, r17, \
        r18, r19, r20, r21, r22, r23, r24, r25, r26, r27, r28, r29, r30, \
        r31;
#define AUTO_r4 r31 \
   long r4, r5, r6, r7, r8, r9, r10, r11, r12, r13, r14, r15, r16, r17, \
        r18, r19, r20, r21, r22, r23, r24, r25, r26, r27, r28, r29, r30, \
        r31;
#define AUTO_r5 r31 \
   long r5, r6, r7, r8, r9, r10, r11, r12, r13, r14, r15, r16, r17, \
        r18, r19, r20, r21, r22, r23, r24, r25, r26, r27, r28, r29, r30, \
        r31;
#define AUTO_r6 r31 \
   long r6, r7, r8, r9, r10, r11, r12, r13, r14, r15, r16, r17, \
        r18, r19, r20, r21, r22, r23, r24, r25, r26, r27, r28, r29, r30, \
        r31;
#define AUTO_r7 r31 \
   long r7, r8, r9, r10, r11, r12, r13, r14, r15, r16, r17, \
        r18, r19, r20, r21, r22, r23, r24, r25, r26, r27, r28, r29, r30, \
        r31;
#define AUTO_r8 r31 \
   long r8, r9, r10, r11, r12, r13, r14, r15, r16, r17, \
        r18, r19, r20, r21, r22, r23, r24, r25, r26, r27, r28, r29, r30, \
        r31;
#define AUTO_r9 r31 \
   long r9, r10, r11, r12, r13, r14, r15, r16, r17, \
        r18, r19, r20, r21, r22, r23, r24, r25, r26, r27, r28, r29, r30, \
        r31;
#define AUTO_r10 r31 \
   long r10, r11, r12, r13, r14, r15, r16, r17, \
        r18, r19, r20, r21, r22, r23, r24, r25, r26, r27, r28, r29, r30, \
        r31;
#define AUTO_r11 r31 \
   long r11, r12, r13, r14, r15, r16, r17, \
        r18, r19, r20, r21, r22, r23, r24, r25, r26, r27, r28, r29, r30, \
        r31;
#define AUTO_r12 r31 \
   long r12, r13, r14, r15, r16, r17, \
        r18, r19, r20, r21, r22, r23, r24, r25, r26, r27, r28, r29, r30, \
        r31;
#define AUTO_r13 r31 \
   long r13, r14, r15, r16, r17, r18, r19, r20, r21, r22, r23, r24, r25, \
        r26, r27, r28, r29, r30, r31;
#define AUTO_r14 r31 \
   long r14, r15, r16, r17, r18, r19, r20, r21, r22, r23, r24, r25, \
        r26, r27, r28, r29, r30, r31;
#define AUTO_r15 r31 \
   long r15, r16, r17, r18, r19, r20, r21, r22, r23, r24, r25, \
        r26, r27, r28, r29, r30, r31;
#define AUTO_r16_r31 \
```

7

```
    long  r16, r17, r18, r19, r20, r21, r22, r23, r24, r25, \
          r26, r27, r28, r29, r30, r31;
#define AUTO r17 r31 \
    long  r17, r18, r19, r20, r21, r22, r23, r24, r25, \
          r26, r27, r28, r29, r30, r31;
#define AUTO r18 r31 \
    long  r18, r19, r20, r21, r22, r23, r24, r25, \
          r26, r27, r28, r29, r30, r31;
#define AUTO r19 r31 \
    long  r19, r20, r21, r22, r23, r24, r25, \
          r26, r27, r28, r29, r30, r31;

#define AUTO f0 f31 \
    float  f0, f1, f2, f3, f4, f5, f6, f7, f8, f9, f10, f11, f12, f13, f14, \
           f15, f16, f17, f18, f19, f20, f21, f22, f23, f24, f25, f26, f27, \
           f28, f29, f30, f31;

#define AUTO d0 d31 \
    double  d0, d1, d2, d3, d4, d5, d6, d7, d8, d9, d10, d11, d12, d13, d14, \
            d15, d16, d17, d18, d19, d20, d21, d22, d23, d24, d25, d26, d27, \
            d28, d29, d30, d31;

#if defined( BUILD MAX )
#define AUTO v0_v31 \
    VMX_reg  v0, v1, v2, v3, v4, v5, v6, v7, v8, v9, v10, v11, v12, v13, v14,
    \
             v15, v16, v17, v18, v19, v20, v21, v22, v23, v24, v25, v26, v27, \
             v28, v29, v30, v31;
#endif

/*
 *  For C implementation, create a dummy stack on function entry of size
 4096.
 */
#define STACK_SIZE  4096

/*
 *  macros for C and Fortran callable entry points
 */
#define ENTRY 0( func name ) \
    C PROTOTYPE 0( func name ) \
    void func_name ( void ) \
    { \
        long CR[8]; ulong CTR; ulong VSCR; long r0; \
        AUTO r3 r31 \
        AUTO f0 f31 \
        AUTO d0 d31 \
        AUTO_v0 v31 \
        long gpr save area[ 19 + 4 ]; \
        long fpr save area[ 2*18 + 4 ]; \
        long vr save area[ 4*12 + 4 ]; \
        long stack[STACK_SIZE + 4], sp;

#define ENTRY 1( func name, arg0 ) \
    C PROTOTYPE 1( func name ) \
    void func_name ( long arg0 ) \
    { \
        long CR[8]; ulong CTR; ulong VSCR; long r0; \
        AUTO r4 r31 \
        AUTO f0 f31 \
        AUTO d0 d31 \
        AUTO_v0 v31 \
        long gpr save area[ 19 + 4 ]; \
        long fpr save area[ 2*18 + 4 ]; \
        long vr save area[ 4*12 + 4 ]; \
        long stack[STACK_SIZE + 4], sp;
```

8

```
#define ENTRY 2( func name, arg0, arg1 ) \
    C PROTOTYPE 2( func name ) \
    void func_name ( long arg0, long arg1 ) \
    { \
        long CR[8]; ulong CTR; ulong VSCR; long r0; \
        AUTO r5 r31 \
        AUTO f0 f31 \
        AUTO d0 d31 \
        AUTO_v0 v31 \
        long gpr save area[ 19 + 4 ]; \
        long fpr save area[ 2*18 + 4 ]; \
        long vr save area[ 4*12 + 4 ]; \
        long stack[STACK_SIZE + 4], sp;

#define ENTRY 3( func name, arg0, arg1, arg2 ) \
    C PROTOTYPE 3( func name ) \
    void func_name ( long arg0, long arg1, long arg2 ) \
    { \
        long CR[8]; ulong CTR; ulong VSCR; long r0; \
        AUTO r6 r31 \
        AUTO f0 f31 \
        AUTO d0 d31 \
        AUTO_v0 v31 \
        long gpr save area[ 19 + 4 ]; \
        long fpr save area[ 2*18 + 4 ]; \
        long vr save area[ 4*12 + 4 ]; \
        long stack[STACK_SIZE + 4], sp;

#define ENTRY 4( func name, arg0, arg1, arg2, arg3 ) \
    C PROTOTYPE 4( func name ) \
    void func_name ( long arg0, long arg1, long arg2, long arg3 ) \
    { \
        long CR[8]; ulong CTR; ulong VSCR; long r0; \
        AUTO r7 r31 \
        AUTO f0 f31 \
        AUTO d0 d31 \
        AUTO_v0 v31 \
        long gpr save area[ 19 + 4 ]; \
        long fpr save area[ 2*18 + 4 ]; \
        long vr save area[ 4*12 + 4 ]; \
        long stack[STACK_SIZE + 4], sp;

#define ENTRY 5( func name, arg0, arg1, arg2, arg3, arg4 ) \
    C PROTOTYPE 5( func name ) \
    void func_name ( long arg0, long arg1, long arg2, long arg3, long arg4 ) \
    { \
        long CR[8]; ulong CTR; ulong VSCR; long r0; \
        AUTO r8 r31 \
        AUTO f0 f31 \
        AUTO d0 d31 \
        AUTO_v0 v31 \
        long gpr save area[ 19 + 4 ]; \
        long fpr save area[ 2*18 + 4 ]; \
        long vr save area[ 4*12 + 4 ]; \
        long stack[STACK_SIZE + 4], sp;

#define ENTRY 6( func name, arg0, arg1, arg2, arg3, arg4, arg5 ) \
    C PROTOTYPE 6( func name ) \
    void func_name ( long arg0, long arg1, long arg2, long arg3, long arg4, \
                     long arg5 ) \
    { \
        long CR[8]; ulong CTR; ulong VSCR; long r0; \
        AUTO r9 r31 \
        AUTO f0 f31 \
        AUTO d0 d31 \
        AUTO_v0 v31 \
        long gpr_save_area[ 19 + 4 ]; \
```

9

```
          long fpr save area[ 2*18 + 4 ]; \
          long vr save area[ 4*12 + 4 ]; \
          long stack[STACK_SIZE + 4], sp;

#define ENTRY_7( func_name, arg0, arg1, arg2, arg3, arg4, arg5, \
                            arg6 ) \
   C PROTOTYPE 7( func name ) \
   void func_name ( long arg0, long arg1, long arg2, long arg3, long arg4, \
                    long arg5, long arg6 ) \
   { \
       long CR[8]; ulong CTR; ulong VSCR; long r0; \
       AUTO r10 r31 \
       AUTO f0 f31 \
       AUTO d0 d31 \
       AUTO_v0 v31 \
       long gpr save area[ 19 + 4 ]; \
       long fpr save area[ 2*18 + 4 ]; \
       long vr save area[ 4*12 + 4 ]; \
       long stack[STACK_SIZE + 4], sp;

#define ENTRY_8( func_name, arg0, arg1, arg2, arg3, arg4, arg5, \
                            arg6, arg7 ) \
   C PROTOTYPE 8( func name ) \
   void func_name ( long arg0, long arg1, long arg2, long arg3, long arg4, \
                    long arg5, long arg6, long arg7 ) \
   { \
       long CR[8]; ulong CTR; ulong VSCR; long r0; \
       AUTO r11 r31 \
       AUTO f0 f31 \
       AUTO d0 d31 \
       AUTO_v0 v31 \
       long gpr save area[ 19 + 4 ]; \
       long fpr save area[ 2*18 + 4 ]; \
       long vr save area[ 4*12 + 4 ]; \
       long stack[STACK_SIZE + 4], sp;

#define ENTRY_9( func_name, arg0, arg1, arg2, arg3, arg4, arg5, \
                            arg6, arg7, arg8 ) \
   C PROTOTYPE 9( func name ) \
   void func_name ( long arg0, long arg1, long arg2, long arg3, long arg4, \
                    long arg5, long arg6, long arg7, long arg8 ) \
   { \
       long CR[8]; ulong CTR; ulong VSCR; long r0; \
       AUTO r12 r31 \
       AUTO f0 f31 \
       AUTO d0 d31 \
       AUTO_v0 v31 \
       long gpr save area[ 19 + 4 ]; \
       long fpr save area[ 2*18 + 4 ]; \
       long vr save area[ 4*12 + 4 ]; \
       long stack[STACK_SIZE + 4], sp;

#define ENTRY_10( func_name, arg0, arg1, arg2, arg3, arg4, arg5, \
                             arg6, arg7, arg8, arg9 ) \
   C PROTOTYPE 10( func name ) \
   void func_name ( long arg0, long arg1, long arg2, long arg3, long arg4, \
                    long arg5, long arg6, long arg7, long arg8, long arg9 ) \
   { \
       long CR[8]; ulong CTR; ulong VSCR; long r0; \
       AUTO r13 r31 \
       AUTO f0 f31 \
       AUTO d0 d31 \
       AUTO_v0 v31 \
       long gpr save area[ 19 + 4 ]; \
       long fpr save area[ 2*18 + 4 ]; \
       long vr save area[ 4*12 + 4 ]; \
       long stack[STACK_SIZE + 4], sp;
```

10

```
#define ENTRY_11( func_name, arg0, arg1, arg2, arg3, arg4, arg5, \
                              arg6, arg7, arg8, arg9, arg10 ) \
    C PROTOTYPE 11( func name ) \
    void func_name ( long arg0, long arg1, long arg2, long arg3, long arg4, \
                     long arg5, long arg6, long arg7, long arg8, long arg9, \
                     long arg10 ) \
    { \
        long CR[8]; ulong CTR; ulong VSCR; long r0; \
        AUTO r14 r31 \
        AUTO f0 f31 \
        AUTO d0 d31 \
        AUTO_v0 v31 \
        long gpr save area[ 19 + 4 ]; \
        long fpr save area[ 2*18 + 4 ]; \
        long vr save area[ 4*12 + 4 ]; \
        long stack[STACK_SIZE + 4], sp;

#define ENTRY_12( func_name, arg0, arg1, arg2, arg3, arg4, arg5, \
                              arg6, arg7, arg8, arg9, arg10, arg11 ) \
    C PROTOTYPE 12( func name ) \
    void func_name ( long arg0, long arg1, long arg2, long arg3, long arg4, \
                     long arg5, long arg6, long arg7, long arg8, long arg9, \
                     long arg10, long arg11 ) \
    { \
        long CR[8]; ulong CTR; ulong VSCR; long r0; \
        AUTO r15 r31 \
        AUTO f0 f31 \
        AUTO d0 d31 \
        AUTO_v0 v31 \
        long gpr save area[ 19 + 4 ]; \
        long fpr save area[ 2*18 + 4 ]; \
        long vr save area[ 4*12 + 4 ]; \
        long stack[STACK_SIZE + 4], sp;

#define ENTRY_13( func_name, arg0, arg1, arg2, arg3, arg4, arg5, \
                              arg6, arg7, arg8, arg9, arg10, arg11, \
                              arg12 ) \
    C PROTOTYPE 13( func name ) \
    void func_name ( long arg0, long arg1, long arg2, long arg3, long arg4, \
                     long arg5, long arg6, long arg7, long arg8, long arg9, \
                     long arg10, long arg11, long arg12 ) \
    { \
        long CR[8]; ulong CTR; ulong VSCR; long r0; \
        AUTO r16 r31 \
        AUTO f0 f31 \
        AUTO d0 d31 \
        AUTO_v0 v31 \
        long gpr save area[ 19 + 4 ]; \
        long fpr save area[ 2*18 + 4 ]; \
        long vr save area[ 4*12 + 4 ]; \
        long stack[STACK_SIZE + 4], sp;

#define ENTRY_14( func_name, arg0, arg1, arg2, arg3, arg4, arg5, \
                              arg6, arg7, arg8, arg9, arg10, arg11, \
                              arg12, arg13 ) \
    C PROTOTYPE 14( func name ) \
    void func_name ( long arg0, long arg1, long arg2, long arg3, long arg4, \
                     long arg5, long arg6, long arg7, long arg8, long arg9, \
                     long arg10, long arg11, long arg12, long arg13 ) \
    { \
        long CR[8]; ulong CTR; ulong VSCR; long r0; \
        AUTO r17 r31 \
        AUTO f0 f31 \
        AUTO d0 d31 \
        AUTO_v0 v31 \
        long gpr_save_area[ 19 + 4 ]; \
```

11

```
                    long fpr save area[ 2*18 + 4 ]; \
                    long vr save area[ 4*12 + 4 ]; \
                    long stack[STACK_SIZE + 4], sp;

        #define ENTRY_15( func_name, arg0, arg1, arg2, arg3, arg4, arg5, \
                              arg6, arg7, arg8, arg9, arg10, arg11, \
                              arg12, arg13, arg14 ) \
            C PROTOTYPE 15( func_name ) \
            void func_name ( long arg0, long arg1, long arg2, long arg3, long arg4, \
                              long arg5, long arg6, long arg7, long arg8, long arg9, \
                              long arg10, long arg11, long arg12, long arg13, \
                              long arg14 ) \
            { \
                    long CR[8]; ulong CTR; ulong VSCR; long r0; \
                    AUTO r18 r31 \
                    AUTO f0 f31 \
                    AUTO d0 d31 \
                    AUTO_v0 v31 \
                    long gpr save area[ 19 + 4 ]; \
                    long fpr save area[ 2*18 + 4 ]; \
                    long vr save area[ 4*12 + 4 ]; \
                    long stack[STACK_SIZE + 4], sp;

        #define ENTRY_16( func_name, arg0, arg1, arg2, arg3, arg4, arg5, \
                              arg6, arg7, arg8, arg9, arg10, arg11, \
                              arg12, arg13, arg14, arg15 ) \
            C PROTOTYPE 16( func_name ) \
            void func_name ( long arg0, long arg1, long arg2, long arg3, long arg4, \
                              long arg5, long arg6, long arg7, long arg8, long arg9, \
                              long arg10, long arg11, long arg12, long arg13, \
                              long arg14, long arg15 ) \
            { \
                    long CR[8]; ulong CTR; ulong VSCR; long r0; \
                    AUTO r19 r31 \
                    AUTO f0 f31 \
                    AUTO d0 d31 \
                    AUTO_v0 v31 \
                    long gpr save area[ 19 + 4 ]; \
                    long fpr save area[ 2*18 + 4 ]; \
                    long vr save area[ 4*12 + 4 ]; \
                    long stack[STACK_SIZE + 4], sp;

        /*
         *   macros to get GPR arguments beyond 8
         */
        #define GET ARG8( rD )
        #define GET ARG9( rD )
        #define GET ARG10( rD )
        #define GET ARG11( rD )
        #define GET ARG12( rD )
        #define GET ARG13( rD )
        #define GET ARG14( rD )
        #define GET ARG15( rD )
        #define GET ARG16( rD )
        #define GET_ARG17( rD )

        /*
         *   macros to set GPR arguments beyond 8
         */
        #define SET ARG8( rD )
        #define SET ARG9( rD )
        #define SET ARG10( rD )
        #define SET ARG11( rD )
        #define SET ARG12( rD )
        #define SET ARG13( rD )
        #define SET ARG14( rD )
        #define SET_ARG15( rD )
```

salppc.h

```
#define SET ARG16( rD )
#define SET_ARG17( rD )

/*
 *   macro to branch from one entry point to another
 */
#define BR FUNC( func_name ) \
   func_name (); \

/*
 *   macros to call functions
 */
#define CALL_FUNC( func_name ) \
   func_name ( );

/*
 *   macros to call functions
 */
#define CALL_0( func_name ) \
   func_name ( );

#define CALL_1( func name, arg0 ) \
   func_name ( arg0 );

#define CALL_2( func_name, arg0, arg1 ) \
   func_name ( arg0, arg1 );

#define CALL_3( func_name, arg0, arg1, arg2 ) \
   func_name ( arg0, arg1, arg2 );

#define CALL_4( func_name, arg0, arg1, arg2, arg3 ) \
   func_name ( arg0, arg1, arg2, arg3 );

#define CALL_5( func_name, arg0, arg1, arg2, arg3, arg4 ) \
   func_name ( arg0, arg1, arg2, arg3, arg4 );

#define CALL_6( func_name, arg0, arg1, arg2, arg3, arg4, arg5 ) \
   func_name ( arg0, arg1, arg2, arg3, arg4, arg5 );

#define CALL_7( func_name, arg0, arg1, arg2, arg3, arg4, arg5, arg6 ) \
   func_name ( arg0, arg1, arg2, arg3, arg4, arg5, arg6 );

#define CALL_8( func_name, arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7 ) \
   func_name ( arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7 );

#define CALL_9( func_name, arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
                arg8 ) \
   func_name ( arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
                arg8 );

#define CALL_10( func name, arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
                arg8, arg9 ) \
   func_name ( arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
                arg8, arg9 );

#define CALL_11( func name, arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
                arg8, arg9, arg10 ) \
   func_name ( arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
                arg8, arg9, arg10 );

#define CALL_12( func name, arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
                arg8, arg9, arg10, arg11 ) \
   func_name ( arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
                arg8, arg9, arg10, arg11 );

#define CALL_13( func name, arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
                arg8, arg9, arg10, arg11, arg12 ) \
```

13

```
        func_name ( arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
                    arg8, arg9, arg10, arg11, arg12 );

#define CALL_14( func name, arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
                 arg8, arg9, arg10, arg11, arg12, arg13 ) \
    func_name ( arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
                    arg8, arg9, arg10, arg11, arg12, arg13 );

#define CALL_15( func name, arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
                 arg8, arg9, arg10, arg11, arg12, arg13, arg14 ) \
    func_name ( arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
                    arg8, arg9, arg10, arg11, arg12, arg13, arg14 );

#define CALL_16( func name, arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
                 arg8, arg9, arg10, arg11, arg12, arg13, arg14, arg15 ) \
    func_name ( arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
                    arg8, arg9, arg10, arg11, arg12, arg13, arg14, arg15 );

#if defined( BUILD_MAX )

/*
 *  G4 macros to create a dummy jump table.
 *      (not supported in C)
 */
#define DECLARE VMX V1( root name )
#define DECLARE VMX V2( root name )
#define DECLARE VMX V3( root name )
#define DECLARE VMX V4( root name )
#define DECLARE_VMX_V5( root_name )

#define DECLARE VMX Z1( root name )
#define DECLARE VMX Z2( root name )
#define DECLARE VMX Z3( root name )
#define DECLARE VMX Z4( root name )
#define DECLARE_VMX_Z5( root_name )

/*
 *  G4 macros to decide whether to enter a VMX loop
 *  VMX loop is entered if at least minimum count,
 *  all vectors have the same relative alignment
 *  (i.e., same lower 4 bits) and all strides are unit.
 *  Note, a unit s imm argument is provided because some
 *  packed interleaved complex functions (stride 2) such
 *  as cvaddx() can be implemented with a VMX loop.
 *  Only one macro should be invoked per source file.
 *      (not supported in C)
 */
#define BR IF VMX V1( root name, min n imm, unit s imm, p1, s1, n, eflag )
#define BR_IF_VMX_V1_ALIGNED( root name, min n_imm, unit_s_imm, \
                            p1, s1, n, eflag )
#define BR_IF_VMX_V2( root name, min n imm, unit_s_imm, \
                      p1, s1, p2, s2, n, eflag )
#define BR_IF_VMX_V2_LS( root name, min n imm, unit_s_imm, \
                    p1, s1, ps, s2, n, eflag )
#define BR_IF_VMX_V2_LC( root name, min_n imm, unit_s_imm, \
                    p1, s1, pc, n, eflag )
#define BR_IF_VMX_V2_ALIGNED( root name, min n imm, unit_s_imm, \
                            p1, s1, p2, s2, n, eflag )
#define BR_IF_VMX_V3( root name, min n imm, unit_s imm, \
                    p1, s1, p2, s2, p3, s3, n, eflag )
#define BR_IF_VMX_V3_ALIGNED( root name, min n imm, unit_s imm, \
                            p1, s1, p2, s2, p3, s3, n, eflag )
#define BR_IF_VMX_V4( root name, min n imm, unit s imm, \
                    p1, s1, p2, s2, p3, s3, p4, s4, n, eflag )
#define BR_IF_VMX_V4_ALIGNED( root name, min n imm, unit s imm, \
                            p1, s1, p2, s2, p3, s3, p4, s4, n, eflag )
#define BR_IF_VMX_V5( root_name, min_n_imm, unit_s_imm, \
```

14

salppc.h   2/23/2001

```
                         p1, s1, p2, s2, p3, s3, p4, s4, p5, s5, n, eflag )
#define BR_IF_VMX_V5_ALIGNED( root_name, min_n_imm, unit_s_imm, \
                         p1, s1, p2, s2, p3, s3, p4, s4, p5, s5, n, \
                         eflag )
#define BR_IF_VMX_Z1( root_name, min_n_imm, unit_s_imm, \
                     pr1, pi1, s1, n, eflag )
#define BR_IF_VMX_Z2( root_name, min_n_imm, unit_s_imm, \
                     pr1, pi1, s1, pr2, pi2, s2, n, eflag )
#define BR_IF_VMX_Z3( root_name, min_n_imm, unit_s_imm, \
                     pr1, pi1, s1, pr2, pi2, s2, pr3, pi3, s3, n, eflag )
#define BR_IF_VMX_Z4( root_name, min_n_imm, unit_s_imm, \
                     pr1, pi1, s1, pr2, pi2, s2, pr3, pi3, s3, \
                     pr4, pi4, s4, n, eflag )
#define BR_IF_VMX_Z5( root_name, min_n_imm, unit_s_imm, \
                     pr1, pi1, s1, pr2, pi2, s2, pr3, pi3, s3, \
                     pr4, pi4, s4, pr5, pi5, s5, n, eflag )
#define BR_IF_VMX_CONV( root_name, min_n_imm, \
                     p1, s1, s2, p3, s3, n, eflag )
#define BR_IF_VMX_ZCONV( root_name, min_n_imm, \
                     pr1, pi1, s1, s2, pr3, pi3, s3, n, eflag )


/*
 * G4 macro to get VMX unaligned (FP) count
 * assumes all vectors have the same relative alignment
 * and that the last 2 bits of ptr are 0
 * sets condition code CR0
 */
#define GET_VMX_UNALIGNED_COUNT( count, ptr ) \
    { \
        (count) = -(ptr); \
        (count) = ( (count) >> 2) & 3; \
        CR[0] = (long)(count); \
    }


/*
 * G4 macro to get VMX unaligned short count
 * assumes that the last bit of ptr is 0
 * sets condition code CR0
 */
#define GET_VMX_UNALIGNED_COUNT_S( count, ptr ) \
    { \
        (count) = -(ptr); \
        (count) = ( (count) >> 1) & 7; \
        CR[0] = (long)(count); \
    }


/*
 * G4 macro to get VMX unaligned char count
 * sets condition code CR0
 */
#define GET_VMX_UNALIGNED_COUNT_C( count, ptr ) \
    { \
        (count) = -(ptr); \
        (count) = (count) & 15; \
        CR[0] = (long)(count); \
    }


/*
 * G4 macro to load and splat an FP scalar independent of alignment
 */
#define SCALAR_SPLAT( vt, vtmp, scalarp ) \
    (vt).f[0] = (vt).f[1] = (vt).f[2] = (vt).f[3] = *scalarp;


#endif                                          /* end BUILD_MAX */


/*
 *  cache (DCBT and DCBZ) macros.
```

15

salppc.h

```
*/
#define DCBT_TRUE( cond_bit, scratch ) \
    CR[(cond_bit)] = -1;                        /* true (<= 0) */

#define DCBZ_TRUE( cond_bit, scratch ) \
    DCBT_TRUE( cond_bit, scratch )

#define DCBT_FALSE( cond_bit, scratch ) \
    CR[(cond_bit)] = 1;                         /* false (> 0) */

#define DCBZ_FALSE( cond_bit, scratch ) \
    DCBT_FALSE( cond_bit, scratch )

#define SET_DCBT_COND( cond_bit, cache_bit, eflag, scratch1 ) \
    CR[(cond_bit)] = (eflag & (cache_bit));

#define SET_DCBZ_COND( cond_bit, cache_bit, eflag, buffer, stride, \
                       unit_stride, count, tmp1, tmp2, tmp3) \
    CR[(cond_bit)] = (eflag & (cache_bit));

#define DCBT_IF( cond_bit, rA, rB ) \
    if ( CR[(cond_bit)] <= 0 ) \
        { DCBT( rA, rB ) }

#define DCBZ_IF( cond_bit, rA, rB ) \
    if ( CR[(cond_bit)] <= 0 ) \
        { DCBZ( rA, rB ) }

#define DCBT_IF_CACHABLE( cond_bit, rA, rB ) \
    DCBT_IF( cond_bit, rA, rB )

#define DCBZ_IF_CACHABLE( cond_bit, rA, rB ) \
    DCBZ_IF( cond_bit, rA, rB )

#define BR_IF_CACHABLE( cond_bit, label ) \
    if ( CR[(cond_bit)] <= 0 ) \
        goto label;

#define BR_IF_NOT_CACHABLE( cond_bit, label ) \
    if ( CR[(cond_bit)] > 0 ) \
        goto label;

/*
 *  ASIC macros
 */
#if defined( COMPILE_PREFETCH )

#define LOAD_PREFETCH_CONTROL( mode, scratch1, scratch2 ) \
    *(volatile long *)PREFETCH_CONTROL = (mode);

#define LOAD_MISCON_B( mode, scratch1, scratch2 ) \
    *(volatile long *)MISCON_B = (mode);

#define RESET_PREFETCH_CONTROL( scratch1, scratch2 ) \
    { \
        volatile long  i; \
        i = *(volatile long *)MISCON_B; \
        i &= PREFETCH_MASK; \
        i |= USE_PREFETCH_CONTROL; \
        *(volatile long *)PREFETCH_CONTROL = i; \
    }

#else

#define LOAD_PREFETCH_CONTROL( mode, scratch1, scratch2 )
#define LOAD_MISCON_B( mode, scratch1, scratch2 )
#define RESET_PREFETCH_CONTROL( scratch1, scratch2 )
```

16

```
#endif

/*
 *  instruction macros
 */
#define ADD( rD, rA, rB )                   (rD) = (rA) + (rB);
#define ADD_C( rD, rA, rB )                 (rD) = (rA) + (rB); CR[0] =
(long)(rD);
#define ADDI( rD, rA, SIMM )                (rD) = (rA) + (SIMM);
#define ADDIC_C( rD, rA, SIMM )             (rD) = (rA) + (SIMM); CR[0] = (long)(
rD);
#define ADDIS( rD, rA, SIMM )               (rD) = (rA) + ((SIMM) << 16);
#define AND( rA, rS, rB )                   (rA) = (rS) & (rB);
#define AND_C( rA, rS, rB )                 (rA) = (rS) & (rB); CR[0] =
(long)(rA);
#define ANDC( rA, rS, rB )                  (rA) = (rS) & ~(rB);
#define ANDC_C( rA, rS, rB )                (rA) = (rS) & ~(rB); CR[0] =
(long)(rA);
#define ANDI_C( rA, rS, UIMM )              (rA) = (rS) & (UIMM); CR[0] = (long)(
rA);
#define ANDIS_C( rA, rS, UIMM )             (rA) = (rS) & ((UIMM) << 16); \
                                                CR[0] = (long)(rA);

#define BA( addr )                          goto (addr);
#define BCTR                                (*(void (*)(void))CTR)();
#define BEQ( label )                        if ( CR[0] == 0 ) goto label;
#define BEQ_PLUS( label )                   BEQ( label )
#define BEQ_MINUS( label )                  BEQ( label )
#define BEQ_CR( bit, label )                if ( CR[(bit)] == 0 ) goto label;
#define BEQ_CR_PLUS( bit, label )           BEQ_CR( bit, label )
#define BEQ_CR_MINUS( bit, label )          BEQ_CR( bit, label )
#define BEQLR                               if ( CR[0] == 0 ) return;
#define BEQLR_PLUS                          BEQLR
#define BEQLR_MINUS                         BEQLR
#define BEQLR_CR( bit )                     if ( CR[(bit)] == 0 ) return;
#define BEQLR_CR_PLUS( bit )                BEQLR_CR( bit )
#define BEQLR_CR_MINUS( bit )               BEQLR_CR( bit )
#define BGE( label )                        if ( CR[0] >= 0 ) goto label;
#define BGE_PLUS( label )                   BGE( label )
#define BGE_MINUS( label )                  BGE( label )
#define BGE_CR( bit, label )                if ( CR[(bit)] >= 0 ) goto label;
#define BGE_CR_PLUS( bit, label )           BGE_CR( bit, label )
#define BGE_CR_MINUS( bit, label )          BGE_CR( bit, label )
#define BGELR                               if ( CR[0] >= 0 ) return;
#define BGELR_PLUS                          BGELR
#define BGELR_MINUS                         BGELR
#define BGELR_CR( bit )                     if ( CR[(bit)] >= 0 ) return;
#define BGELR_CR_PLUS( bit )                BGELR_CR( bit )
#define BGELR_CR_MINUS( bit )               BGELR_CR( bit )
#define BGT( label )                        if ( CR[0] > 0 ) goto label;
#define BGT_PLUS( label )                   BGT( label )
#define BGT_MINUS( label )                  BGT( label )
#define BGT_CR( bit, label )                if ( CR[(bit)] > 0 ) goto label;
#define BGT_CR_PLUS( bit, label )           BGT_CR( bit, label )
#define BGT_CR_MINUS( bit, label )          BGT_CR( bit, label )
#define BGTLR                               if ( CR[0] > 0 ) return;
#define BGTLR_PLUS                          BGTLR
#define BGTLR_MINUS                         BGTLR
#define BGTLR_CR( bit )                     if ( CR[(bit)] > 0 ) return;
#define BGTLR_CR_PLUS( bit )                BGTLR_CR( bit )
#define BGTLR_CR_MINUS( bit )               BGTLR_CR( bit )
#define BL( func_name )                     func_name ( );
#define BLE( label )                        if ( CR[0] <= 0 ) goto label;
#define BLE_PLUS( label )                   BLE( label )
#define BLE_MINUS( label )                  BLE( label )
#define BLE_CR( bit, label )                if ( CR[(bit)] <= 0 ) goto label;
#define BLE_CR_PLUS( bit, label )           BLE_CR( bit, label )
```

17

```
#define BLE CR_MINUS( bit, label )      BLE CR( bit, label )
#define BLELR                           if ( CR[0] <= 0 ) return;
#define BLELR PLUS                      BLELR
#define BLELR MINUS                     BLELR
#define BLELR CR( bit )                 if ( CR[(bit)] <= 0 ) return;
#define BLELR CR PLUS( bit )            BLELR CR( bit )
#define BLELR_CR_MINUS( bit )           BLELR CR( bit )
#define BLR                             return;
#define BLT( label )                    if ( CR[0] < 0 ) goto label;
#define BLT PLUS( label )               BLT( label )
#define BLT MINUS( label )              BLT( label )
#define BLT CR( bit, label )            if ( CR[(bit)] < 0 ) goto label;
#define BLT CR PLUS( bit, label )       BLT CR( bit, label )
#define BLT CR_MINUS( bit, label )      BLT CR( bit, label )
#define BLTLR                           if ( CR[0] < 0 ) return;
#define BLTLR PLUS                      BLTLR
#define BLTLR MINUS                     BLTLR
#define BLTLR CR( bit )                 if ( CR[(bit)] < 0 ) return;
#define BLTLR CR PLUS( bit )            BLTLR CR( bit )
#define BLTLR CR MINUS( bit )           BLTLR CR( bit )
#define BNE( label )                    if ( CR[0] != 0 ) goto label;
#define BNE PLUS( label )               BNE( label )
#define BNE MINUS( label )              BNE( label )
#define BNE CR( bit, label )            if ( CR[(bit)] != 0 ) goto label;
#define BNE CR PLUS( bit, label )       BNE CR( bit, label )
#define BNE CR_MINUS( bit, label )      BNE CR( bit, label )
#define BNELR                           if ( CR[0] != 0 ) return;
#define BNELR PLUS                      BNELR
#define BNELR MINUS                     BNELR
#define BNELR CR( bit )                 if ( CR[(bit)] != 0 ) return;
#define BNELR CR PLUS( bit )            BNELR CR( bit )
#define BNELR CR MINUS( bit )           BNELR CR( bit )
#define BR( label )                     goto label;
#define CLRLWI( rA, rS, nbits )         (rA) = (rS) & ((1 << (32-nbits)) - 1);
#define CLRLWI_C( rA, rS, nbits )       (rA) = (rS) & ((1 << (32-nbits)) - 1);
\
                                                CR[0] = (long)(rA);
#define CLRRWI( rA, rS, nbits )          (rA) = (rS) & ~((1 << nbits) - 1);
#define CLRRWI_C( rA, rS, nbits )       (rA) = (rS) & ~((1 << nbits) - 1); \
                                                CR[0] = (long)(rA);
#define CMPLW( rA, rB )                 CR[0] = (((rA)^(rB)) & (1 << 31)) ? \
                                           ((rB) - (rA)) : ((rA) - (rB));
#define CMPLW_CR( bit, rA, rB )         CR[(bit)] = (((rA)^(rB)) & (1 << 31))
? \
                                           ((rB) - (rA)) : ((rA) - (rB));
#define CMPLWI( rA, UIMM )              CR[0] = (((rA)^(UIMM)) & (1 << 31)) ?
\
                                           ((UIMM) - (rA)) : ((rA) -
                                           (UIMM));
#define CMPLWI_CR( bit, rA, UIMM )      CR[(bit)] = (((rA)^(UIMM)) & (1 <<
31)) ? \
                                           ((UIMM) - (rA)) : ((rA) -
                                           (UIMM));
#define CMPW( rA, rB )                  CR[0] = (rA) - (rB);
#define CMPW CR( bit, rA, rB )          CR[(bit)] = (rA) - (rB);
#define CMPWI( rA, SIMM )               CR[0] = (rA) - (SIMM);
#define CMPWI_CR( bit, rA, SIMM )       CR[(bit)] = (rA) - (SIMM);
#define DCBF( rA, rB )
#define DCBI( rA, rB )
#define DCBST( rA, rB )
#define DCBT( rA, rB )
#define DCBTST( rA, rB )
#define DCBZ( rA, rB )      *(long *)(((rA)+(rB)) & ~CACHE LINE MASK) = 0; \
                            *(long *)((((rA)+(rB)) & ~CACHE LINE MASK)+4) = 0; \
                            *(long *)((((rA)+(rB)) & ~CACHE LINE MASK)+8) = 0; \
                            *(long *)((((rA)+(rB)) & ~CACHE_LINE_MASK)+12) = 0;
                            \
```

18

```
                            *(long *)(((((rA)+(rB)) & ~CACHE_LINE_MASK)+16) = 0;
                            \
                            *(long *)(((((rA)+(rB)) & ~CACHE_LINE_MASK)+20) = 0;
                            \
                            *(long *)(((((rA)+(rB)) & ~CACHE_LINE_MASK)+24) = 0;
                            \
                            *(long *)(((((rA)+(rB)) & ~CACHE_LINE_MASK)+28) = 0;
#define DECR( rD )                      --(rD);
#define DECR C( rD )                    --(rD); CR[0] = (long)(rD);
#define DIVW( rD, rA, rB )              (rD) = (rA) / (rB);
#define DIVW_C( rD, rA, rB )            (rD) = (rA) / (rB); CR[0] =
(long)(rD);
#define DIVWU( rD, rA, rB )             (rD) = (ulong)(rA) / (ulong)(rB);
#define DIVWU_C( rD, rA, rB )           (rD) = (ulong)(rA) / (ulong)(rB); \
                                            CR[0] = (long)(rD);
#define EQV( rA, rS, rB )               (rA) = ~((rS) ^ (rB));
.#define EQV_C( rA, rS, rB )            (rA) = ~((rS) ^ (rB)); \
                                        CR[0] = (long)(rA);
#define FABS( frD, frB )                (frD) = ((frB) >= 0.0) ? (frB) :
-(frB);
#define FADD( frD, frA, frB )           (frD) = (frA) + (frB);
#define FADDS( frD, frA, frB )          (frD) = (frA) + (frB);
#define FCMPO( bit, frA, frB ) \
    { \
        if ( (frA) < (frB) ) CR[(bit)] = -1; \
        else if ( (frA) > (frB) ) CR[(bit)] = 1; \
        else CR[(bit)] = 0; \
    }
#define FCMPU( bit, frA, frB )          FCMPO( bit, frA, frB )
#define FCTIW( frD, frB )
#define FCTIWZ( frD, frB ) \
    { \
        union { \
            long i[2]; \
            double d; \
        } u; \
        u.i[0] = (long)(frB); \
        u.i[1] = 0; \
        (frD) = u.d; \
    }
#define FDIV( frD, frA, frB )           (frD) = (frA) / (frB);
#define FDIVS( frD, frA, frB )          (frD) = (frA) / (frB);
#define FMADD( frD, frA, frC, frB)      (frD) = (frA) * (frC) + (frB);
#define FMADDS( frD, frA, frC, frB)     (frD) = (frA) * (frC) + (frB);
#define FMOV( frD, frB )                (frD) = (frB);
#define FMR( frD, frB )                 (frD) = (frB);
#define FMUL( frD, frA, frB )           (frD) = (frA) * (frB);
#define FMULS( frD, frA, frB )          (frD) = (frA) * (frB);
#define FMSUB( frD, frA, frC, frB )     (frD) = (frA) * (frC) - (frB);
#define FMSUBS( frD, frA, frC, frB )    (frD) = (frA) * (frC) - (frB);
#define FNABS( frD, frB )               (frD) = ((frB) >= 0.0) ? -(frB) :
(frB);
#define FNEG( frD, frB )                (frD) = -(frB);
#define FNMADD( frD, frA, frC, frB )    (frD) = -((frA) * (frC) + (frB));
#define FNMADDS( frD, frA, frC, frB )   (frD) = -((frA) * (frC) + (frB));
#define FNMSUB( frD, frA, frC, frB )    (frD) = -((frA) * (frC) - (frB));
#define FNMSUBS( frD, frA, frC, frB )   (frD) = -((frA) * (frC) - (frB));
#define FRES( frD, frB )
#define FRSP( frD, frB )                (frD) = (float)(frB);
#define FRSQRTE( frD, frB )
#define FSEL( frD, frA, frC, frB )      (frD) = ((frA) >= 0.0) ? (frC) :
(frB);
#define FSUB( frD, frA, frB )           (frD) = (frA) - (frB);
#define FSUBS( frD, frA, frB )          (frD) = (frA) - (frB);
#define GOTO( label )                   BR( label )
#define INCR( rD )                      ++(rD);
#define INCR_C( rD )                    ++(rD); CR[0] = (long)(rD);
```

19

```
#define LA( rD, symbol, SIMM )            (rD) = (long)&(symbol);
#define LABEL( label )                    label:
#define LBZ( rD, rA, d )                  (rD) = *(uchar *)((rA) + (d));
#define LBZA( rD, symbol )                (rD) = *(uchar *)&(symbol);
#define LBZU( rD, rA, d )                 (rD) = *(uchar *)((rA) += (d));
#define LBZUX( rD, rA, rB )               (rD) = *(uchar *)((rA) += (rB));
#define LBZX( rD, rA, rB )                (rD) = *(uchar *)((rA) + (rB));
#define LFD( frD, rA, d )                 (frD) = *(double *)((rA) + (d));
#define LFDU( frD, rA, d )                (frD) = *(double *)((rA) += (d));
#define LFDUX( frD, rA, rB )              (frD) = *(double *)((rA) += (rB));
#define LFDX( frD, rA, rB )               (frD) = *(double *)((rA) + (rB));
#define LFS( frD, rA, d )                 (frD) = *(float *)((rA) + (d));
#define LFSA( frD, symbol, rT )           (frD) = *(float *)&(symbol);
#define LFSU( frD, rA, d )                (frD) = *(float *)((rA) += (d));
#define LFSUX( frD, rA, rB )              (frD) = *(float *)((rA) += (rB));
#define LFSX( frD, rA, rB )               (frD) = *(float *)((rA) + (rB));
#define LHA( rD, rA, d )                  (rD) = *(short *)((rA) + (d));
#define LHAA( rD, symbol )                (rD) = *(short *)&(symbol);
#define LHAU( rD, rA, d )                 (rD) = *(short *)((rA) += (d));
#define LHAUX( rD, rA, rB )               (rD) = *(short *)((rA) += (rB));
#define LHAX( rD, rA, rB )                (rD) = *(short *)((rA) + (rB));
#define LHZ( rD, rA, d )                  (rD) = *(ushort *)((rA) + (d));
#define LHZA( rD, symbol )                (rD) = *(ushort *)&(symbol);
#define LHZU( rD, rA, d )                 (rD) = *(ushort *)((rA) += (d));
#define LHZUX( rD, rA, rB )               (rD) = *(ushort *)((rA) += (rB));
#define LHZX( rD, rA, rB )                (rD) = *(ushort *)((rA) + (rB));
#define LI( rD, SIMM )                    (rD) = (SIMM);
#define LIS( rD, SIMM )                   (rD) = ((SIMM) << 16);
#define LOAD_COUNT( rD )                  CTR = (rD);
#define LWZ( rD, rA, d )                  (rD) = *(long *)((rA) + (d));
#define LWZA( rD, symbol )                (rD) = *(long *)&(symbol);
#define LWZU( rD, rA, d )                 (rD) = *(long *)((rA) += (d));
#define LWZUX( rD, rA, rB )               (rD) = *(long *)((rA) += (rB));
#define LWZX( rD, rA, rB )                (rD) = *(long *)((rA) + (rB));
#define MCRF( crfD, crfS )
#define MCRFS( crfD, crfS )
#define MFCR( rD )
#define MFCTR( rD )
#define MFLR( rD )
#define MFSPR( rD, SPR )
#define MOV( rA, rS )                     (rA) = (rS);
#define MOV_C( rA, rS )                   (rA) = (rS); CR[0] = (long)(rA);
#define MR( rA, rS )                      (rA) = (rS);
#define MR_C( rA, rS )                    (rA) = (rS); CR[0] = (long)(rA);
#define MTCR( rD )
#define MTCTR( rD )
#define MTFSFI( crfD, IMM )
#define MTLR( rD )
#define MTSPR( SPR, rS )
#define MULLI( rD, rA, SIMM )             (rD) = (rA) * (SIMM);
#define MULLW( rD, rA, rB )               (rD) = (rA) * (rB);
#define MULLW_C( rD, rA, rB )             (rD) = (rA) * (rB); CR[0] =
(long)(rD);
#define NAND( rA, rS, rB )                (rA) = ~((rS) & (rB));
#define NAND_C( rA, rS, rB )              (rA) = ~((rS) & (rB)); CR[0] = (long)(
rA);
#define NEG( rD, rA )                     (rD) = -(rA);
#define NEG_C( rD, rA )                   (rD) = -(rA); CR[0] = (long)(rA);
#define NOP
#define NOR( rA, rS, rB )                 (rA) = ~((rS) | (rB));
#define NOR_C( rA, rS, rB )               (rA) = ~((rS) | (rB)); CR[0] = (long)(
rA);
#define OR( rA, rS, rB )                  (rA) = (rS) | (rB);
#define OR_C( rA, rS, rB )                (rA) = (rS) | (rB); CR[0] =
(long)(rA);
#define ORC( rA, rS, rB )                 (rA) = (rS) | ~(rB);
#define ORC_C( rA, rS, rB )               (rA) = (rS) | ~(rB); CR[0] =
```

20

salppc.h   2/23/2001

```
(long) (rA);
#define ORI( rA, rS, UIMM )           (rA) = (rS) | (UIMM);
#define ORIS( rA, rS, UIMM )          (rA) = (rS) | ((UIMM) << 16);
#define RETURN                        BLR
#define RLWIMI( rA, rS, SH, MB, ME ) \
{ \
    ulong mask; \
    mask = ((1 << ((ME) - (MB) + 1)) - 1) << (31 - (ME)); \
    (rA) &= ~mask; \
    (rA) |= (((((rS) << (SH)) | ((ulong)(rS) >> (32 - (SH)))) & mask); \
}
#define RLWIMI_C( rA, rS, SH, MB, ME ) \
{ \
    ulong mask; \
    mask = ((1 << ((ME) - (MB) + 1)) - 1) << (31 - (ME)); \
    (rA) &= ~mask; \
    (rA) |= (((((rS) << (SH)) | ((ulong)(rS) >> (32 - (SH)))) & mask); \
    CR[0] = (long)(rA); \
}
#define RLWINM( rA, rS, SH, MB, ME ) \
{ \
    ulong mask; \
    mask = ((1 << ((ME) - (MB) + 1)) - 1) << (31 - (ME)); \
    (rA) = ((((rS) << (SH)) | ((ulong)(rS) >> (32 - (SH)))) & mask; \
}
#define RLWINM_C( rA, rS, SH, MB, ME ) \
{ \
    ulong mask; \
    mask = ((1 << ((ME) - (MB) + 1)) - 1) << (31 - (ME)); \
    (rA) = ((((rS) << (SH)) | ((ulong)(rS) >> (32 - (SH)))) & mask; \
    CR[0] = (long)(rA); \
}
#define RLWNM( rA, rS, rB, MB, ME )     RLWINM( rA, rS, (rB) & 0x1f, MB, ME )
#define RLWNM_C( rA, rS, rB, MB, ME )   RLWINM_C( rA, rS, (rB) & 0x1f, MB, ME
)
#define EXTLWI( rA, rS, n, b )          RLWINM( rA, rS, (b), 0, (n)-1 )
#define EXTLWI_C( rA, rS, n, b )        RLWINM_C( rA, rS, (b), 0, (n)-1 )
#define EXTRWI( rA, rS, n, b )          RLWINM( rA, rS, (b)+(n), 32-(n), 31 )
#define EXTRWI_C( rA, rS, n, b )        RLWINM( rA, rS, (b)+(n), 32-(n), 31 )
#define INSLWI( rA, rS, n, b )          RLWIMI( rA, rS, 32-(b), (b), (b)+(n)-1
)
#define INSLWI_C( rA, rS, n, b )        RLWIMI_C( rA, rS, 32-(b), (b),
(b)+(n)-1 )
#define INSRWI( rA, rS, n, b )          RLWIMI( rA, rS, 32-((b)+(n)), (b), (b)
+(n)-1 )
#define INSRWI_C( rA, rS, n, b )        RLWIMI_C( rA, rS, 32-((b)+(n)), (b), (
b)+(n)-1 )
#define ROTLW( rA, rS, rB )             RLWNM( rA, rS, rB, 0, 31 )
#define ROTLW_C( rA, rS, rB )           RLWNM_C( rA, rS, rB, 0, 31 )
#define ROTLWI( rA, rS, n )             RLWINM( rA, rS, (n), 0, 31 )
#define ROTLWI_C( rA, rS, n )           RLWINM_C( rA, rS, (n), 0, 31 )
#define ROTRWI( rA, rS, n )             RLWINM( rA, rS, 32-(n), 0, 31 )
#define ROTRWI_C( rA, rS, n )           RLWINM( rA, rS, 32-(n), 0, 31 )
#define SLW( rA, rS, rB )               (rA) = (rS) << (rB);
#define SLW_C( rA, rS, rB )             (rA) = (rS) << (rB); CR[0] =
(long)(rA);
#define SLWI( rA, rS, SH )              (rA) = (rS) << (SH);
#define SLWI_C( rA, rS, SH )            (rA) = (rS) << (SH); CR[0] =
(long)(rA);
#define SRAW( rA, rS, rB )              (rA) = (long)(rS) >> (rB);
#define SRAW_C( rA, rS, rB )            (rA) = (long)(rS) >> (rB); CR[0] = (
long)(rA);
#define SRAWI( rA, rS, SH )             (rA) = (long)(rS) >> (SH);
#define SRAWI_C( rA, rS, SH )           (rA) = (long)(rS) >> (SH); CR[0] = (
long)(rA);
#define SRW( rA, rS, rB )               (rA) = (ulong)(rS) >> (rB);
#define SRW_C( rA, rS, rB )             (rA) = (ulong)(rS) >> (rB); CR[0] = (
```

21

salppc.h   2/23/2001

```
long)(rA);
#define SRWI( rA, rS, SH )        (rA) = (ulong)(rS) >> (SH);
#define SRWI_C( rA, rS, SH )      (rA) = (ulong)(rS) >> (SH); CR[0] = (
long)(rA);
#define STB( rS, rA, d )          *(char *)((rA) + (d)) = (rS);
#define STBU( rS, rA, d )         *(char *)((rA) += (d)) = (rS);
#define STBUX( rS, rA, rB )       *(char *)((rA) += (rB)) = (rS);
#define STBX( rS, rA, rB )        *(char *)((rA) + (rB)) = (rS);
#define STFD( frD, rA, d )        *(double *)((rA) + (d)) = (frD);
#define STFDU( frD, rA, d )       *(double *)((rA) += (d)) = (frD);
#define STFDUX( frD, rA, rB )     *(double *)((rA) += (rB)) = (frD);
#define STFDX( frD, rA, rB )      *(double *)((rA) + (rB)) = (frD);
#define STFS( frD, rA, d )        *(float *)((rA) + (d)) = (frD);
#define STFSU( frD, rA, d )       *(float *)((rA) += (d)) = (frD);
#define STFSUX( frD, rA, rB )     *(float *)((rA) += (rB)) = (frD);
#define STFSX( frD, rA, rB )      *(float *)((rA) + (rB)) = (frD);
#define STH( rS, rA, d )          *(short *)((rA) + (d)) = (rS);
#define STHU( rS, rA, d )         *(short *)((rA) += (d)) = (rS);
#define STHUX( rS, rA, rB )       *(short *)((rA) += (rB)) = (rS);
#define STHX( rS, rA, rB )        *(short *)((rA) + (rB)) = (rS);
#define STW( rS, rA, d )          *(long *)((rA) + (d)) = (rS);
#define STWU( rS, rA, d )         *(long *)((rA) += (d)) = (rS);
#define STWUX( rS, rA, rB )       *(long *)((rA) += (rB)) = (rS);
#define STWX( rS, rA, rB )        *(long *)((rA) + (rB)) = (rS);
#define SUB( rD, rA, rB )         (rD) = (rA) - (rB);
#define SUB_C( rD, rA, rB )       (rD) = (rA) - (rB); CR[0] =
(long)(rD);
#define SUBFIC( rD, rA, SIMM )    (rD) = (SIMM) - (rA);
#define SUBI( rD, rA, SIMM )      (rD) = (rA) - (SIMM);
#define SUBIC_C( rD, rA, SIMM )   (rD) = (rA) - (SIMM); CR[0] = (long)(
rD);
#define SUBIS( rD, rA, SIMM )     (rD) = (rA) - ((SIMM) << 16);
#define TEST_COUNT( label )       if ( --CTR ) goto label;
#define XOR( rA, rS, rB )         (rA) = (rS) ^ (rB);
#define XOR_C( rA, rS, rB )       (rA) = (rS) ^ (rB); CR[0] =
(long)(rA);
#define XORI( rA, rS, UIMM )      (rA) = (rS) ^ (UIMM);
#define XORIS( rA, rS, UIMM )     (rA) = (rS) ^ ((UIMM) << 16);

#if defined( BUILD_MAX )

/*
 *   VMX instructions
 */
#define BR_VMX_ALL_TRUE( label )     if( CR[6] & 0x8 ) goto label;
#define BR_VMX_ALL_FALSE( label )    if( CR[6] & 0x2 ) goto label;
#define BR_VMX_NONE_TRUE( label )    if( CR[6] & 0x2 ) goto label;
#define BR_VMX_SOME_FALSE( label )   if( !(CR[6] & 0x8) ) goto label;
#define BR_VMX_SOME_TRUE( label )    if( !(CR[6] & 0x2) ) goto label;

#define DSS( STRM )
#define DSSALL
#define DST( rA, rB, STRM )
#define DSTT( rA, rB, STRM )
#define DSTST( rA, rB, STRM )
#define DSTSTT( rA, rB, STRM )

#if defined( COMPILE_NON_ALIGNED )
#define VMX_ADDR_MASK   0
#else
#define VMX_ADDR_MASK   15
#endif

#if defined( COMPILE_LVX_CHARS )

#define LVX( vT, rA, rB ) \
    { \
```

22

salppc.h

```
        char *addr; \
        ulong i; \
        addr = (char *)(((ulong)(rA) + (ulong)(rB)) & ~VMX_ADDR_MASK); \
        for ( i = 0; i < 16; i++ ) \
            (vT).c[C_INDEX_MUNGE( i )] = addr[i]; \
    }
#define LVEBX( vT, rA, rB ) \
    { \
        char *addr; \
        ulong i; \
        addr = (char *)((ulong)(rA) + (ulong)(rB)); \
        i = (ulong)addr & VMX_ADDR_MASK; \
        (vT).c[C_INDEX_MUNGE( i )] = addr[0]; \
    }
#define LVEHX( vT, rA, rB ) \
    { \
        char *addr; \
        ulong i; \
        addr = (char *)(((ulong)(rA) + (ulong)(rB)) & ~1); \
        i = (ulong)addr & VMX_ADDR_MASK; \
        (vT).c[C_INDEX_MUNGE( i )] = addr[0]; \
        (vT).c[C_INDEX_MUNGE( i + 1 )] = addr[1]; \
    }
#define LVEWX( vT, rA, rB ) \
    { \
        char *addr; \
        ulong i; \
        addr = (char *)(((ulong)(rA) + (ulong)(rB)) & ~3); \
        i = (ulong)addr & VMX_ADDR_MASK; \
        (vT).c[C_INDEX_MUNGE( i )] = addr[0]; \
        (vT).c[C_INDEX_MUNGE( i + 1 )] = addr[1]; \
        (vT).c[C_INDEX_MUNGE( i + 2 )] = addr[2]; \
        (vT).c[C_INDEX_MUNGE( i + 3 )] = addr[3]; \
    }

#elif defined( COMPILE_LVX_SHORTS )

#define LVX( vT, rA, rB ) \
    { \
        short *addr; \
        ulong i; \
        addr = (short *)(((ulong)(rA) + (ulong)(rB)) & ~VMX_ADDR_MASK); \
        for ( i = 0; i < 8; i++ ) \
            (vT).s[S_INDEX_MUNGE( i )] = addr[i]; \
    }
#define LVEBX( vT, rA, rB ) \
    { \
        char *addr; \
        ulong i; \
        addr = (char *)((ulong)(rA) + (ulong)(rB)); \
        i = (ulong)addr & VMX_ADDR_MASK; \
        (vT).c[C_INDEX_MUNGE( i )] = addr[0]; \
    }
#define LVEHX( vT, rA, rB ) \
    { \
        short *addr; \
        ulong i; \
        addr = (short *)(((ulong)(rA) + (ulong)(rB)) & ~1); \
        i = ((ulong)addr & VMX_ADDR_MASK) >> 1; \
        (vT).s[S_INDEX_MUNGE( i )] = addr[0]; \
    }
#define LVEWX( vT, rA, rB ) \
    { \
        short *addr; \
        ulong i; \
        addr = (short *)(((ulong)(rA) + (ulong)(rB)) & ~3); \
        i = ((ulong)addr & VMX_ADDR_MASK) >> 1; \
        (vT).s[S_INDEX_MUNGE( i )] = addr[0]; \
```

23

```
        (vT).s[S_INDEX_MUNGE( i + 1 )] = addr[1]; \
    }

#else

#define LVX( vT, rA, rB ) \
    { \
        long *addr; \
        ulong i; \
        addr = (long *)(((ulong)(rA) + (ulong)(rB)) & ~VMX_ADDR_MASK); \
        for ( i = 0; i < 4; i++ ) \
            (vT).l[L_INDEX_MUNGE( i )] = addr[i]; \
    }
#define LVEBX( vT, rA, rB ) \
    { \
        char *addr; \
        ulong i; \
        addr = (char *)((ulong)(rA) + (ulong)(rB)); \
        i = (ulong)addr & VMX_ADDR_MASK; \
        (vT).c[C_INDEX_MUNGE( i )] = addr[0]; \
    }
#define LVEHX( vT, rA, rB ) \
    { \
        short *addr; \
        ulong i; \
        addr = (short *)(((ulong)(rA) + (ulong)(rB)) & ~1); \
        i = ((ulong)addr & VMX_ADDR_MASK) >> 1; \
        (vT).s[S_INDEX_MUNGE( i )] = addr[0]; \
    }
#define LVEWX( vT, rA, rB ) \
    { \
        long *addr; \
        ulong i; \
        addr = (long *)(((ulong)(rA) + (ulong)(rB)) & ~3); \
        i = ((ulong)addr & VMX_ADDR_MASK) >> 2; \
        (vT).l[L_INDEX_MUNGE( i )] = addr[0]; \
    }

#endif

#if defined( COMPILE_STVX_CHARS )

#define STVX( vS, rA, rB ) \
    { \
        char *addr; \
        ulong i; \
        addr = (char *)(((ulong)(rA) + (ulong)(rB)) & ~VMX_ADDR_MASK); \
        for ( i = 0; i < 16; i++ ) \
            addr[i] = (vS).c[C_INDEX_MUNGE( i )]; \
    }
#define STVEBX( vS, rA, rB ) \
    { \
        char *addr; \
        ulong i; \
        addr = (char *)((ulong)(rA) + (ulong)(rB)); \
        i = (ulong)addr & VMX_ADDR_MASK; \
        addr[0] = (vS).c[C_INDEX_MUNGE( i )]; \
    }
#define STVEHX( vS, rA, rB ) \
    { \
        char *addr; \
        ulong i; \
        addr = (char *)(((ulong)(rA) + (ulong)(rB)) & ~1); \
        i = (ulong)addr & VMX_ADDR_MASK; \
        addr[0] = (vS).c[C_INDEX_MUNGE( i )]; \
        addr[1] = (vS).c[C_INDEX_MUNGE( i + 1 )]; \
    }
```

24

salppc.h   2/23/2001

```
#define STVEWX( vS, rA, rB ) \
    { \
        char *addr; \
        ulong i; \
        addr = (char *)(((ulong)(rA) + (ulong)(rB)) & ~3); \
        i = (ulong)addr & VMX ADDR MASK; \
        addr[0] = (vS).c[C INDEX MUNGE( i )]; \
        addr[1] = (vS).c[C INDEX MUNGE( i + 1 )]; \
        addr[2] = (vS).c[C INDEX MUNGE( i + 2 )]; \
        addr[3] = (vS).c[C_INDEX_MUNGE( i + 3 )]; \
    }

#elif defined( COMPILE_STVX_SHORTS )

#define STVX( vS, rA, rB ) \
    { \
        short *addr; \
        ulong i; \
        addr = (short *)(((ulong)(rA) + (ulong)(rB)) & ~VMX_ADDR_MASK); \
        for ( i = 0; i < 8; i++ ) \
            addr[i] = (vS).s[S_INDEX_MUNGE( i )]; \
    }
#define STVEBX( vS, rA, rB ) \
    { \
        char *addr; \
        ulong i; \
        addr = (char *)((ulong)(rA) + (ulong)(rB)); \
        i = (ulong)addr & VMX ADDR MASK; \
        addr[0] = (vS).c[C_INDEX_MUNGE( i )]; \
    }
#define STVEHX( vS, rA, rB ) \
    { \
        short *addr; \
        ulong i; \
        addr = (short *)(((ulong)(rA) + (ulong)(rB)) & ~1); \
        i = ((ulong)addr & VMX ADDR MASK) >> 1; \
        addr[0] = (vS).s[S_INDEX_MUNGE( i )]; \
    }
#define STVEWX( vS, rA, rB ) \
    { \
        short *addr; \
        ulong i; \
        addr = (short *)(((ulong)(rA) + (ulong)(rB)) & ~3); \
        i = ((ulong)addr & VMX ADDR MASK) >> 1; \
        addr[0] = (vS).s[S INDEX MUNGE( i )]; \
        addr[1] = (vS).s[S_INDEX_MUNGE( i + 1 )]; \
    }

#else

#define STVX( vS, rA, rB ) \
    { \
        long *addr; \
        ulong i; \
        addr = (long *)(((ulong)(rA) + (ulong)(rB)) & ~VMX_ADDR_MASK); \
        for ( i = 0; i < 4; i++ ) \
            addr[i] = (vS).l[L_INDEX_MUNGE( i )]; \
    }
#define STVEBX( vS, rA, rB ) \
    { \
        char *addr; \
        ulong i; \
        addr = (char *)((ulong)(rA) + (ulong)(rB)); \
        i = (ulong)addr & VMX ADDR MASK; \
        addr[0] = (vS).c[C_INDEX_MUNGE( i )]; \
    }
#define STVEHX( vS, rA, rB ) \
```

25

```
    { \
        short *addr; \
        ulong i; \
        addr = (short *)(((ulong)(rA) + (ulong)(rB)) & ~1); \
        i = ((ulong)addr & VMX_ADDR_MASK) >> 1; \
        addr[0] = (vS).s[S_INDEX_MUNGE( i )]; \
    }
#define STVEWX( vS, rA, rB ) \
    { \
        long *addr; \
        ulong i; \
        addr = (long *)(((ulong)(rA) + (ulong)(rB)) & ~3); \
        i = ((ulong)addr & VMX_ADDR_MASK) >> 2; \
        addr[0] = (vS).l[L_INDEX_MUNGE( i )]; \
    }

#endif

#define LVSL_BE( vT, rA, rB ) \
    { \
        ulong i, j; \
        j = ((ulong)(rA) + (ulong)(rB)) & VMX_ADDR_MASK; \
        for ( i = 0; i < 16; i++ ) \
            (vT).uc[i] = j + i; \
    }
#define LVSR_BE( vT, rA, rB ) \
    { \
        ulong i, j; \
        j = 16 - (((ulong)(rA) + (ulong)(rB)) & VMX_ADDR_MASK); \
        for ( i = 0; i < 16; i++ ) \
            (vT).uc[i] = j + i; \
    }

#if defined( LITTLE_ENDIAN )
#define LVSL( vT, rA, rB )              LVSR_BE( vT, rA, rB );
#define LVSR( vT, rA, rB )              LVSL_BE( vT, rA, rB );
#else
#define LVSL( vT, rA, rB )              LVSL_BE( vT, rA, rB );
#define LVSR( vT, rA, rB )              LVSR_BE( vT, rA, rB );
#endif

#define LVXL( vT, rA, rB )              LVX( vT, rA, rB )
#define STVXL( vS, rA, rB )             STVX( vS, rA, rB )
#define VADDFP( vT, vA, vB ) \
    { \
        ulong i; \
        float a, b, c; \
        for ( i = 0; i < 4; i++ ) { \
            a = (vA).f[i]; \
            b = (vB).f[i]; \
            c = a + b; \
            (vT).f[i] = c; \
        } \
    }
#define VADDSBS( vT, vA, vB ) \
    { \
        ulong i; \
        long itemp; \
        for ( i = 0; i < 16; i++ ) { \
            itemp = (long)(vA).c[i] + (long)(vB).c[i]; \
            if ( itemp < -128 ) (vT).c[i] = -128; \
            else if ( itemp > 127 ) (vT).c[i] = 127; \
            else (vT).c[i] = (char)itemp; \
        } \
    }
#define VADDSHS( vT, vA, vB ) \
    { \
```

26

```
        ulong i; \
        long itemp; \
        for ( i = 0; i < 8; i++ ) { \
            itemp = (long)(vA).s[i] + (long)(vB).s[i]; \
            if ( itemp < -32768 ) (vT).s[i] = -32768; \
            else if ( itemp > 32767 ) (vT).s[i] = 32767; \
            else (vT).s[i] = (short)itemp; \
        } \
    }
#define VADDSWS( vT, vA, vB ) \
    { \
        ulong i; \
        long itemp; \
        for ( i = 0; i < 4; i++ ) { \
            itemp = (vA).l[i] + (vB).l[i]; \
            if ( ( (vA).l[i] > 0) && ( (vB).l[i] > 0) && (itemp < 0) ) \
                (vT).l[i] = (long)0x7fffffff; \
            else if ( ( (vA).l[i] < 0) && ( (vB).l[i] < 0) && (itemp > 0) ) \
                (vT).l[i] = (long)0x80000000; \
            else (vT).l = itemp[i]; \
        } \
    }
#define VADDUBM( vT, vA, vB ) \
    { \
        ulong i; \
        for ( i = 0; i < 16; i++ ) \
            (vT).uc[i] = (vA).uc[i] + (vB).uc[i]; \
    }
#define VADDUBS( vT, vA, vB ) \
    { \
        ulong i, itemp; \
        for ( i = 0; i < 16; i++ ) { \
            itemp = (ulong)(vA).uc[i] + (ulong)(vB).uc[i]; \
            if ( itemp > 255 ) (vT).uc[i] = 255; \
            else (vT).uc[i] = (uchar)itemp; \
        } \
    }
#define VADDUHM( vT, vA, vB ) \
    { \
        ulong i; \
        for ( i = 0; i < 8; i++ ) \
            (vT).us[i] = (vA).us[i] + (vB).us[i]; \
    }
#define VADDUHS( vT, vA, vB ) \
    { \
        ulong i, itemp; \
        for ( i = 0; i < 8; i++ ) { \
            itemp = (ulong)(vA).us[i] + (ulong)(vB).us[i]; \
            if ( itemp > 65535 ) (vT).uc[i] = 65535; \
            else (vT).uc[i] = (ushort)itemp; \
        } \
    }
#define VADDUWM( vT, vA, vB ) \
    { \
        ulong i; \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = (vA).ul[i] + (vB).ul[i]; \
    }
#define VADDUWS( vT, vA, vB ) \
    { \
        ulong i, itemp; \
        for ( i = 0; i < 4; i++ ) { \
            itemp = (vA).ul[i] + (vB).ul[i]; \
            if ( itemp < (vA).ul[i] ) (vT).ul[i] = (ulong)0xffffffff; \
            else (vT).ul[i] = itemp; \
        } \
    }
```

27

```
#define VAND( vT, vA, vB ) \
    { \
        ulong i; \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = (vA).ul[i] & (vB).ul[i]; \
    }
#define VANDC( vT, vA, vB ) \
    { \
        ulong i; \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = (vA).ul[i] & ~(vB).ul[i]; \
    }
#define VCMPEQFP( vT, vA, vB ) \
    { \
        ulong i; \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = ( (vA).f[i] == (vB).f[i] ) ? 0xffffffff : 0; \
    }
#define VCMPEQFP_C( vT, vA, vB ) \
    { \
        ulong i; \
        ulong t, f; \
        t = 0xffffffff; \
        f = 0; \
        for ( i = 0; i < 4; i++ ) { \
            (vT).ul[i] = ( (vA).f[i] == (vB).f[i] ) ? 0xffffffff : 0; \
            t &= (vT).ul[i]; \
            f |= (vT).ul[i]; \
        } \
        if ( t ) CR[6] = 0x8; \
        else if ( !f ) CR[6] = 0x2; \
        else CR[6] = 0; \
    }
#define VCMPEQUB( vT, vA, vB ) \
    { \
        ulong i; \
        for ( i = 0; i < 16; i++ ) \
            (vT).uc[i] = ( (vA).uc[i] == (vB).uc[i] ) ? 0xff : 0; \
    }
#define VCMPEQUB_C( vT, vA, vB ) \
    { \
        ulong i; \
        uchar t, f; \
        t = 0xff; \
        f = 0; \
        for ( i = 0; i < 16; i++ ) { \
            (vT).uc[i] = ( (vA).uc[i] == (vB).uc[i] ) ? 0xff : 0; \
            t &= (vT).uc[i]; \
            f |= (vT).uc[i]; \
        } \
        if ( t ) CR[6] = 0x8; \
        else if ( !f ) CR[6] = 0x2; \
        else CR[6] = 0; \
    }
#define VCMPEQUH( vT, vA, vB ) \
    { \
        ulong i; \
        for ( i = 0; i < 8; i++ ) \
            (vT).us[i] = ( (vA).us[i] == (vB).us[i] ) ? 0xffff : 0; \
    }
#define VCMPEQUH_C( vT, vA, vB ) \
    { \
        ulong i; \
        ushort t, f; \
        t = 0xffff; \
        f = 0; \
        for ( i = 0; i < 8; i++ ) { \
```

28

```
            (vT).us[i] = ( (vA).us[i] == (vB).us[i] ) ? 0xffff : 0; \
            t &= (vT).us[i]; \
            f |= (vT).us[i]; \
        } \
        if ( t ) CR[6] = 0x8; \
        else if ( !f ) CR[6] = 0x2; \
        else CR[6] = 0; \
    }
#define VCMPEQUW( vT, vA, vB ) \
    { \
        ulong i; \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = ( (vA).ul[i] == (vB).ul[i] ) ? 0xffffffff : 0; \
    }
#define VCMPEQUW_C( vT, vA, vB ) \
    { \
        ulong i; \
        ulong t, f; \
        t = 0xffffffff; \
        f = 0; \
        for ( i = 0; i < 4; i++ ) { \
            (vT).ul[i] = ( (vA).ul[i] == (vB).ul[i] ) ? 0xffffffff : 0; \
            t &= (vT).ul[i]; \
            f |= (vT).ul[i]; \
        } \
        if ( t ) CR[6] = 0x8; \
        else if ( !f ) CR[6] = 0x2; \
        else CR[6] = 0; \
    }
#define VCMPGEFP( vT, vA, vB ) \
    { \
        ulong i; \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = ( (vA).f[i] >= (vB).f[i] ) ? 0xffffffff : 0; \
    }
#define VCMPGEFP_C( vT, vA, vB ) \
    { \
        ulong i; \
        ulong t, f; \
        t = 0xffffffff; \
        f = 0; \
        for ( i = 0; i < 4; i++ ) { \
            (vT).ul[i] = ( (vA).f[i] >= (vB).f[i] ) ? 0xffffffff : 0; \
            t &= (vT).ul[i]; \
            f |= (vT).ul[i]; \
        } \
        if ( t ) CR[6] = 0x8; \
        else if ( !f ) CR[6] = 0x2; \
        else CR[6] = 0; \
    }
#define VCMPGTFP( vT, vA, vB ) \
    { \
        ulong i; \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = ( (vA).f[i] > (vB).f[i] ) ? 0xffffffff : 0; \
    }
#define VCMPGTFP_C( vT, vA, vB ) \
    { \
        ulong i; \
        ulong t, f; \
        t = 0xffffffff; \
        f = 0; \
        for ( i = 0; i < 4; i++ ) { \
            (vT).ul[i] = ( (vA).f[i] > (vB).f[i] ) ? 0xffffffff : 0; \
            t &= (vT).ul[i]; \
            f |= (vT).ul[i]; \
        } \
```

29

```
                if ( t ) CR[6] = 0x8; \
                else if ( !f ) CR[6] = 0x2; \
                else CR[6] = 0; \
        }
#define VCMPGTSB( vT, vA, vB ) \
        { \
                ulong i; \
                for ( i = 0; i < 16; i++ ) \
                    (vT).uc[i] = ( (vA).c[i] > (vB).c[i] ) ? 0xff : 0; \
        }
#define VCMPGTSB_C( vT, vA, vB ) \
        { \
                ulong i; \
                uchar t, f; \
                t = 0xff; \
                f = 0; \
                for ( i = 0; i < 16; i++ ) { \
                    (vT).uc[i] = ( (vA).c[i] > (vB).c[i] ) ? 0xff : 0; \
                    t &= (vT).uc[i]; \
                    f |= (vT).uc[i]; \
                } \
                if ( t ) CR[6] = 0x8; \
                else if ( !f ) CR[6] = 0x2; \
                else CR[6] = 0; \
        }
#define VCMPGTSH( vT, vA, vB ) \
        { \
                ulong i; \
                for ( i = 0; i < 8; i++ ) \
                    (vT).us[i] = ( (vA).s[i] > (vB).s[i] ) ? 0xffff : 0; \
        }
#define VCMPGTSH_C( vT, vA, vB ) \
        { \
                ulong i; \
                ushort t, f; \
                t = 0xffff; \
                f = 0; \
                for ( i = 0; i < 8; i++ ) { \
                    (vT).us[i] = ( (vA).s[i] > (vB).s[i] ) ? 0xffff : 0; \
                    t &= (vT).us[i]; \
                    f |= (vT).us[i]; \
                } \
                if ( t ) CR[6] = 0x8; \
                else if ( !f ) CR[6] = 0x2; \
                else CR[6] = 0; \
        }
#define VCMPGTSW( vT, vA, vB ) \
        { \
                ulong i; \
                for ( i = 0; i < 4; i++ ) \
                    (vT).ul[i] = ( (vA).l[i] > (vB).l[i] ) ? 0xffffffff : 0; \
        }
#define VCMPGTSW_C( vT, vA, vB ) \
        { \
                ulong i; \
                ulong t, f; \
                t = 0xffffffff; \
                f = 0; \
                for ( i = 0; i < 4; i++ ) { \
                    (vT).ul[i] = ( (vA).l[i] > (vB).l[i] ) ? 0xffffffff : 0; \
                    t &= (vT).ul[i]; \
                    f |= (vT).ul[i]; \
                } \
                if ( t ) CR[6] = 0x8; \
                else if ( !f ) CR[6] = 0x2; \
                else CR[6] = 0; \
        }
```

salppc.h   2/23/2001

```
#define VCMPGTUB( vT, vA, vB ) \
    { \
        ulong i; \
        for ( i = 0; i < 16; i++ ) \
            (vT).uc[i] = ( (vA).uc[i] > (vB).uc[i] ) ? 0xff : 0; \
    }
#define VCMPGTUB_C( vT, vA, vB ) \
    { \
        ulong i; \
        uchar t, f; \
        t = 0xff; \
        f = 0; \
        for ( i = 0; i < 16; i++ ) { \
            (vT).uc[i] = ( (vA).uc[i] > (vB).uc[i] ) ? 0xff : 0; \
            t &= (vT).uc[i]; \
            f |= (vT).uc[i]; \
        } \
        if ( t ) CR[6] = 0x8; \
        else if ( !f ) CR[6] = 0x2; \
        else CR[6] = 0; \
    }
#define VCMPGTUH( vT, vA, vB ) \
    { \
        ulong i; \
        for ( i = 0; i < 8; i++ ) \
            (vT).us[i] = ( (vA).us[i] > (vB).us[i] ) ? 0xffff : 0; \
    }
#define VCMPGTUH_C( vT, vA, vB ) \
    { \
        ulong i; \
        ushort t, f; \
        t = 0xffff; \
        f = 0; \
        for ( i = 0; i < 8; i++ ) { \
            (vT).us[i] = ( (vA).us[i] > (vB).us[i] ) ? 0xffff : 0; \
            t &= (vT).us[i]; \
            f |= (vT).us[i]; \
        } \
        if ( t ) CR[6] = 0x8; \
        else if ( !f ) CR[6] = 0x2; \
        else CR[6] = 0; \
    }
#define VCMPGTUW( vT, vA, vB ) \
    { \
        ulong i; \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = ( (vA).ul[i] > (vB).ul[i] ) ? 0xffffffff : 0; \
    }
#define VCMPGTUW_C( vT, vA, vB ) \
    { \
        ulong i; \
        ulong t, f; \
        t = 0xffffffff; \
        f = 0; \
        for ( i = 0; i < 4; i++ ) { \
            (vT).ul[i] = ( (vA).ul[i] > (vB).ul[i] ) ? 0xffffffff : 0; \
            t &= (vT).ul[i]; \
            f |= (vT).ul[i]; \
        } \
        if ( t ) CR[6] = 0x8; \
        else if ( !f ) CR[6] = 0x2; \
        else CR[6] = 0; \
    }
#define VCFSX( vT, vB, UIMM ) \
    { \
        float fj; \
        ulong i, j; \
```

31

salppc.h

```
        j = (127 - ((UIMM) & 0x1f)) << 23; \
        fj = *(float *)&j; \
        for ( i = 0; i < 4; i++ ) \
            (vT).f[i] = (float)((vB).l[i]) / fj; \
    }
#define VCFUX( vT, vB, UIMM ) \
    { \
        float fj; \
        ulong i, j; \
        j = (127 - ((UIMM) & 0x1f)) << 23; \
        fj = *(float *)&j; \
        for ( i = 0; i < 4; i++ ) \
            (vT).f[i] = (float)((vB).ul[i]) / fj; \
    }
#define VCTSXS( vT, vB, UIMM ) \
    { \
        float f, g, max, scale; \
        ulong i; \
        long l; \
        i = (127 + 31) << 23; \
        max = *(float *)&i; \
        i = (127 + ((UIMM) & 0x1f)) << 23; \
        scale = *(float *)&i; \
        for ( i = 0; i < 4; i++ ) { \
            f = (vB).f[i]; \
            g = f * scale; \
            if ( g <= -max ) l = 0x80000000; \
            else if ( g >= max ) l = 0x7fffffff; \
            else l = (long)f << ((UIMM) & 0x1f); \
            (vT).l[i] = l; \
        } \
    }
#define VCTUXS( vT, vB, UIMM ) \
    { \
        float f, g, max, scale; \
        ulong i, ul; \
        i = (127 + 32) << 23; \
        max = *(float *)&i; \
        i = (127 + ((UIMM) & 0x1f)) << 23; \
        scale = *(float *)&i; \
        for ( i = 0; i < 4; i++ ) { \
            f = (vB).f[i]; \
            g = f * scale; \
            if ( g <= 0 ) ul = 0; \
            else if ( g >= max ) ul = 0xffffffff; \
            else ul = (ulong)f << ((UIMM) & 0x1f); \
            (vT).ul[i] = ul; \
        } \
    }
#define VEXPTEFP( vT, vB ) \
    { \
        for ( i = 0; i < 4; i++ ) \
            (vT).f[i] = exp(0.693147180559945 * (vB).f[i]); \
    }
#define VLOGEFP( vT, vB ) \
    { \
        for ( i = 0; i < 4; i++ ) \
            (vT).f[i] = 1.442695040888963 * log((vB).f[i]); \
    }
#define VMADDFP( vT, vA, vC, vB ) \
    { \
        ulong i; \
        float a, b, c, d; \
        for ( i = 0; i < 4; i++ ) { \
            a = (vA).f[i]; \
            b = (vB).f[i]; \
            c = (vC).f[i]; \
```

```
            d = a * c; \
            d = b + d; \
            (vT).f[i] = d; \
        } \
    }
#define VMAXFP( vT, vA, vB ) \
    { \
        ulong i; \
        for ( i = 0; i < 4; i++ ) \
            (vT).f[i] = ((vA).f[i] >= (vB).f[i]) ? (vA).f[i] : (vB).f[i]; \
    }
#define VMAXSB( vT, vA, vB ) \
    { \
        ulong i; \
        for ( i = 0; i < 16; i++ ) \
            (vT).c[i] = ((vA).c[i] >= (vB).c[i]) ? (vA).c[i] : (vB).c[i]; \
    }
#define VMAXSH( vT, vA, vB ) \
    { \
        ulong i; \
        for ( i = 0; i < 8; i++ ) \
            (vT).s[i] = ((vA).s[i] >= (vB).s[i]) ? (vA).s[i] : (vB).s[i]; \
    }
#define VMAXSW( vT, vA, vB ) \
    { \
        ulong i; \
        for ( i = 0; i < 4; i++ ) \
            (vT).l[i] = ((vA).l[i] >= (vB).l[i]) ? (vA).l[i] : (vB).l[i]; \
    }
#define VMAXUB( vT, vA, vB ) \
    { \
        ulong i; \
        for ( i = 0; i < 16; i++ ) \
            (vT).uc[i] = ((vA).uc[i] >= (vB).uc[i]) ? (vA).uc[i] : (vB).uc[i]; \
    }
#define VMAXUH( vT, vA, vB ) \
    { \
        ulong i; \
        for ( i = 0; i < 8; i++ ) \
            (vT).us[i] = ((vA).us[i] >= (vB).us[i]) ? (vA).us[i] : (vB).us[i]; \
    }
#define VMAXUW( vT, vA, vB ) \
    { \
        ulong i; \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = ((vA).ul[i] >= (vB).ul[i]) ? (vA).ul[i] : (vB).ul[i]; \
    }
#define VMHADDSHS( vD, vA, vB, vC ) \
    { \
        ulong i; \
        long a; \
        for ( i = 0; i < 8; i++ ) { \
            a = (long)(vA).s[i] * (long)(vB).s[i]; \
            a >>= 15; \
            a += (long)(vC).s[i]; \
            if ( a > 32767 ) a = 32767; \
            else if ( a < -32768 ) a = -32768; \
            (vD).s[i] = (short)a; \
        } \
    }
#define VMHRADDSHS( vD, vA, vB, vC ) \
    { \
        ulong i; \
        long a; \
        for ( i = 0; i < 8; i++ ) { \
            a = (long)(vA).s[i] * (long)(vB).s[i]; \
            a += 0x00004000; \
```

33

```
                a >>= 15; \
                a += (long)(vC).s[i]; \
                if ( a > 32767 ) a = 32767; \
                else if ( a < -32768 ) a = -32768; \
                (vD).s[i] = (short)a; \
            } \
        }
    #define VMINFP( vT, vA, vB ) \
        { \
            ulong i; \
            for ( i = 0; i < 4; i++ ) \
                (vT).f[i] = ((vA).f[i] <= (vB).f[i]) ? (vA).f[i] : (vB).f[i]; \
        }
    #define VMINSB( vT, vA, vB ) \
        { \
            ulong i; \
            for ( i = 0; i < 16; i++ ) \
                (vT).c[i] = ((vA).c[i] <= (vB).c[i]) ? (vA).c[i] : (vB).c[i]; \
        }
    #define VMINSH( vT, vA, vB ) \
        { \
            ulong i; \
            for ( i = 0; i < 16; i++ ) \
                (vT).s[i] = ((vA).s[i] <= (vB).s[i]) ? (vA).s[i] : (vB).s[i]; \
        }
    #define VMINSW( vT, vA, vB ) \
        { \
            ulong i; \
            for ( i = 0; i < 16; i++ ) \
                (vT).l[i] = ((vA).l[i] <= (vB).l[i]) ? (vA).l[i] : (vB).l[i]; \
        }
    #define VMINUB( vT, vA, vB ) \
        { \
            ulong i; \
            for ( i = 0; i < 16; i++ ) \
                (vT).uc[i] = ((vA).uc[i] <= (vB).uc[i]) ? (vA).uc[i] : (vB).uc[i]; \
        }
    #define VMINUH( vT, vA, vB ) \
        { \
            ulong i; \
            for ( i = 0; i < 16; i++ ) \
                (vT).us[i] = ((vA).us[i] <= (vB).us[i]) ? (vA).us[i] : (vB).us[i]; \
        }
    #define VMINUW( vT, vA, vB ) \
        { \
            ulong i; \
            for ( i = 0; i < 16; i++ ) \
                (vT).ul[i] = ((vA).ul[i] <= (vB).ul[i]) ? (vA).ul[i] : (vB).ul[i]; \
        }
    #define VMLADDUHM( vD, vA, vB, vC ) \
        { \
            ulong i; \
            ulong a, b, c; \
            for ( i = 0; i < 8; i++ ) { \
                a = (ulong)(vA).us[i]; \
                b = (ulong)(vB).us[i]; \
                c = (ulong)(vC).us[i]; \
                c += (a * b); \
                (vD).us[i] = (ushort)c; \
            } \
        }
    #define VMR( vD, vS ) \
        { \
            ulong i; \
            for ( i = 0; i < 4; i++ ) \
                (vD).ul[i] = (vS).ul[i]; \
        }
```

34

```
#define VMRGHB_BE( vT, vA, vB ) \
    { \
        VMX reg v; \
        ulong i, j; \
        for ( i = 0; i < 8; i++ ) { \
            j = i + i; \
            v.uc[j] = (vA).uc[i]; \
            v.uc[(j+1)] = (vB).uc[i]; \
        } \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = v.ul[i]; \
    }
#define VMRGHH_BE( vT, vA, vB ) \
    { \
        VMX reg v; \
        ulong i, j; \
        for ( i = 0; i < 4; i++ ) { \
            j = i + i; \
            v.us[j] = (vA).us[i]; \
            v.us[(j+1)] = (vB).us[i]; \
        } \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = v.ul[i]; \
    }
#define VMRGHW_BE( vT, vA, vB ) \
    { \
        VMX reg v; \
        ulong i, j; \
        for ( i = 0; i < 2; i++ ) { \
            j = i + i; \
            v.ul[j] = (vA).ul[i]; \
            v.ul[(j+1)] = (vB).ul[i]; \
        } \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = v.ul[i]; \
    }
#define VMRGLB_BE( vT, vA, vB ) \
    { \
        VMX reg v; \
        ulong i, j; \
        for ( i = 0; i < 8; i++ ) { \
            j = i + i; \
            v.uc[j] = (vA).uc[(8+i)]; \
            v.uc[(j+1)] = (vB).uc[(8+i)]; \
        } \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = v.ul[i]; \
    }
#define VMRGLH_BE( vT, vA, vB ) \
    { \
        VMX reg v; \
        ulong i, j; \
        for ( i = 0; i < 4; i++ ) { \
            j = i + i; \
            v.us[j] = (vA).us[(4+i)]; \
            v.us[(j+1)] = (vB).us[(4+i)]; \
        } \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = v.ul[i]; \
    }
#define VMRGLW_BE( vT, vA, vB ) \
    { \
        VMX reg v; \
        ulong i, j; \
        for ( i = 0; i < 2; i++ ) { \
            j = i + i; \
            v.ul[j] = (vA).ul[(2+i)]; \
```

35

```
            v.ul[(j+1)] = (vB).ul[(2+i)]; \
        } \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = v.ul[i]; \
    }

#if defined( LITTLE_ENDIAN )
#define VMRGHB( vT, vA, vB )        VMRGLB_BE( vT, vB, vA );
#define VMRGHH( vT, vA, vB )        VMRGLH_BE( vT, vB, vA );
#define VMRGHW( vT, vA, vB )        VMRGLW_BE( vT, vB, vA );
#define VMRGLB( vT, vA, vB )        VMRGHB_BE( vT, vB, vA );
#define VMRGLH( vT, vA, vB )        VMRGHH_BE( vT, vB, vA );
#define VMRGLW( vT, vA, vB )        VMRGHW_BE( vT, vB, vA );
#else
#define VMRGHB( vT, vA, vB )        VMRGHB_BE( vT, vA, vB );
#define VMRGHH( vT, vA, vB )        VMRGHH_BE( vT, vA, vB );
#define VMRGHW( vT, vA, vB )        VMRGHW_BE( vT, vA, vB );
#define VMRGLB( vT, vA, vB )        VMRGLB_BE( vT, vA, vB );
#define VMRGLH( vT, vA, vB )        VMRGLH_BE( vT, vA, vB );
#define VMRGLW( vT, vA, vB )        VMRGLW_BE( vT, vA, vB );
#endif

#define VMSUMMBM( vT, vA, vB, vC ) \
    { \
        ulong i, j; \
        long a, c; \
        ulong b; \
        for ( i = 0; i < 4; i++ ) { \
            c = (vC).l[i]; \
            for ( j = 0; j < 4; j++ ) { \
                a = (long)(vA).c[4*i+j]; \
                b = (ulong)(vB).uc[4*i+j]; \
                c += (a * b); \
            } \
            (vT).l[i] = c; \
        } \
    }
#define VMSUMSHM( vT, vA, vB, vC ) \
    { \
        ulong i, j; \
        long a, b, c; \
        for ( i = 0; i < 4; i++ ) { \
            c = (vC).l[i]; \
            for ( j = 0; j < 2; j++ ) { \
                a = (long)(vA).s[4*i+j]; \
                b = (long)(vB).s[4*i+j]; \
                c += (a * b); \
            } \
            (vT).l[i] = c; \
        } \
    }
#define VMSUMSHS( vT, vA, vB, vC ) \
    { \
        ulong i, j; \
        long a, b; \
        double c; \
        for ( i = 0; i < 4; i++ ) { \
            c = (double)(vC).l[i]; \
            for ( j = 0; j < 2; j++ ) { \
                a = (long)(vA).s[4*i+j]; \
                b = (long)(vB).s[4*i+j]; \
                c += (double)(a * b); \
            } \
            if ( c >= 2147483647.0 ) c = 2147483647.0; \
            else if ( c <= -2147483648.0 ) c = -2147483648.0; \
            (vT).l[i] = (long)c; \
        } \
```

36

```
    }
#define VMSUMUBM( vT, vA, vB, vC ) \
    { \
        ulong i, j; \
        ulong a, b, c; \
        for ( i = 0; i < 4; i++ ) { \
            c = (vC).ul[i]; \
            for ( j = 0; j < 4; j++ ) { \
                a = (ulong)(vA).uc[4*i+j]; \
                b = (ulong)(vB).uc[4*i+j]; \
                c += (a * b); \
            } \
            (vT).ul[i] = c; \
        } \
    }
#define VMSUMUHM( vT, vA, vB, vC ) \
    { \
        ulong i, j; \
        ulong a, b, c; \
        for ( i = 0; i < 4; i++ ) { \
            c = (vC).ul[i]; \
            for ( j = 0; j < 2; j++ ) { \
                a = (ulong)(vA).us[4*i+j]; \
                b = (ulong)(vB).us[4*i+j]; \
                c += (a * b); \
            } \
            (vT).ul[i] = c; \
        } \
    }
#define VMSUMUHS( vT, vA, vB, vC ) \
    { \
        ulong i, j; \
        ulong a, b; \
        double c; \
        for ( i = 0; i < 4; i++ ) { \
            c = (double)(vC).ul[i]; \
            for ( j = 0; j < 2; j++ ) { \
                a = (ulong)(vA).us[4*i+j]; \
                b = (ulong)(vB).us[4*i+j]; \
                c += (double)(a * b); \
            } \
            if ( c >= 4294967295.0 ) c = 4294967295.0; \
            (vT).ul[i] = (ulong)c; \
        } \
    }
#define VMULESB( vT, vA, vB ) \
    { \
        ulong i; \
        long a, b, c; \
        for ( i = 0; i < 8; i++ ) { \
            a = (long)(vA).c[2*i]; \
            b = (long)(vB).c[2*i]; \
            c = a * b; \
            (vT).s[i] = (short)c; \
        } \
    }
#define VMULESH( vT, vA, vB ) \
    { \
        ulong i; \
        long a, b, c; \
        for ( i = 0; i < 4; i++ ) { \
            a = (long)(vA).s[2*i]; \
            b = (long)(vB).s[2*i]; \
            c = a * b; \
            (vT).l[i] = (long)c; \
        } \
    }
```

37

salppc.h   2/23/2001

```
#define VMULEUB( vT, vA, vB ) \
    { \
        ulong i; \
        ulong a, b, c; \
        for ( i = 0; i < 8; i++ ) { \
            a = (ulong)(vA).uc[2*i]; \
            b = (ulong)(vB).uc[2*i]; \
            c = a * b; \
            (vT).us[i] = (ushort)c; \
        } \
    }
#define VMULEUH( vT, vA, vB ) \
    { \
        ulong i; \
        ulong a, b, c; \
        for ( i = 0; i < 4; i++ ) { \
            a = (ulong)(vA).us[2*i]; \
            b = (ulong)(vB).us[2*i]; \
            c = a * b; \
            (vT).ul[i] = (ulong)c; \
        } \
    }
#define VMULOSB( vT, vA, vB ) \
    { \
        ulong i; \
        long a, b, c; \
        for ( i = 0; i < 8; i++ ) { \
            a = (long)(vA).c[2*i+1]; \
            b = (long)(vB).c[2*i+1]; \
            c = a * b; \
            (vT).s[i] = (short)c; \
        } \
    }
#define VMULOSH( vT, vA, vB ) \
    { \
        ulong i; \
        long a, b, c; \
        for ( i = 0; i < 4; i++ ) { \
            a = (long)(vA).s[2*i+1]; \
            b = (long)(vB).s[2*i+1]; \
            c = a * b; \
            (vT).l[i] = (long)c; \
        } \
    }
#define VMULOUB( vT, vA, vB ) \
    { \
        ulong i; \
        ulong a, b, c; \
        for ( i = 0; i < 8; i++ ) { \
            a = (ulong)(vA).uc[2*i+1]; \
            b = (ulong)(vB).uc[2*i+1]; \
            c = a * b; \
            (vT).us[i] = (ushort)c; \
        } \
    }
#define VMULOUH( vT, vA, vB ) \
    { \
        ulong i; \
        ulong a, b, c; \
        for ( i = 0; i < 4; i++ ) { \
            a = (ulong)(vA).us[2*i+1]; \
            b = (ulong)(vB).us[2*i+1]; \
            c = a * b; \
            (vT).ul[i] = (ulong)c; \
        } \
    }
#define VNMSUBFP( vT, vA, vC, vB ) \
```

38

```
    { \
        ulong i; \
        float a, b, c, d; \
        for ( i = 0; i < 4; i++ ) { \
            a = (vA).f[i]; \
            b = (vB).f[i]; \
            c = (vC).f[i]; \
            d = a * c; \
            d = b - d; \
            (vT).f[i] = d; \
        } \
    }
#define VNOR( vT, vA, vB ) \
    { \
        ulong i; \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = ~((vA).ul[i] | (vB).ul[i]); \
    }
#define VNOT( vT, vA )                 VNOR( vT, vA, vA )
#define VOR( vT, vA, vB ) \
    { \
        ulong i; \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = (vA).ul[i] | (vB).ul[i]; \
    }
#define VPERM_BE( vT, vA, vB, vC ) \
    { \
        VMX reg v; \
        ulong field, i; \
        for ( i = 0; i < 16; i++ ) { \
            field = (vC).uc[i]; \
            v.uc[i] = ( field < 16 ) ? (vA).uc[field] : (vB).uc[field - 16]; \
        } \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = v.ul[i]; \
    }
#define VPKUHUM_BE( vT, vA, vB, base ) \
    { \
        VMX reg v; \
        ulong i, j; \
        j = base; \
        for ( i = 0; i < 8; i++ ) { \
            v.uc[i] = (vA).uc[(j)]; \
            v.uc[i+8] = (vB).uc[(j)]; \
            j += 2; \
        } \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = v.ul[i]; \
    }
#define VPKUHUS_BE( vT, vA, vB, base ) \
    { \
        VMX reg v; \
        ulong i, j; \
        j = base; \
        for ( i = 0; i < 8; i++ ) { \
            v.uc[i] = (vA).uc[(j^1)] ? (uchar)255 : (vA).uc[(j)]; \
            v.uc[i+8] = (vB).uc[(j^1)] ? (uchar)255 : (vB).uc[(j)]; \
            j += 2; \
        } \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = v.ul[i]; \
    }
#define VPKSHUS_BE( vT, vA, vB, base ) \
    { \
        VMX reg v; \
        ulong i, j; \
        j = base; \
```

39

```
            for ( i = 0; i < 8; i++ ) { \
                if ( (vA).s[i] <= 0 ) v.uc[i] = 0; \
                else if ( (vA).s[i] >= 255 ) v.uc[i] = 255; \
                else v.uc[i] = (vA).uc[j]; \
                if ( (vB).s[i] <= 0 ) v.uc[i+8] = 0; \
                else if ( (vB).s[i] >= 255 ) v.uc[i+8] = 255; \
                else v.uc[i+8] = (vB).uc[j]; \
                j += 2; \
            } \
            for ( i = 0; i < 4; i++ ) \
                (vT).ul[i] = v.ul[i]; \
        }
#define VPKSHSS_BE( vT, vA, vB, base ) \
        { \
            VMX reg v; \
            ulong i, j; \
            j = base; \
            for ( i = 0; i < 8; i++ ) { \
                if ( (vA).s[i] <= -128 ) v.c[i] = -128; \
                else if ( (vA).s[i] >= 127 ) v.c[i] = 127; \
                else v.c[i] = (vA).c[j]; \
                if ( (vB).s[i] <= -128 ) v.c[i+8] = -128; \
                else if ( (vB).s[i] >= 127 ) v.c[i+8] = 127; \
                else v.c[i+8] = (vB).c[j]; \
                j += 2; \
            } \
            for ( i = 0; i < 4; i++ ) \
                (vT).ul[i] = v.ul[i]; \
        }
#define VPKUWUM_BE( vT, vA, vB, base ) \
        { \
            VMX reg v; \
            ulong i, j; \
            j = base; \
            for ( i = 0; i < 4; i++ ) { \
                v.us[i] = (vA).us[(j)]; \
                v.us[i+4] = (vB).us[(j)]; \
                j += 2; \
            } \
            for ( i = 0; i < 4; i++ ) \
                (vT).ul[i] = v.ul[i]; \
        }
#define VPKUWUS_BE( vT, vA, vB, base ) \
        { \
            VMX reg v; \
            ulong i, j; \
            j = base; \
            for ( i = 0; i < 4; i++ ) { \
                v.us[i] = (vA).us[(j^1)] ? (ushort)65535 : (vA).us[(j)]; \
                v.us[i+4] = (vB).us[(j^1)] ? (ushort)65535 : (vB).us[(j)]; \
                j += 2; \
            } \
            for ( i = 0; i < 4; i++ ) \
                (vT).ul[i] = v.ul[i]; \
        }
#define VPKSWUS_BE( vT, vA, vB, base ) \
        { \
            VMX reg v; \
            ulong i, j; \
            j = base; \
            for ( i = 0; i < 4; i++ ) { \
                if ( (vA).l[i] <= 0 ) v.us[i] = 0; \
                else if ( (vA).l[i] >= 65535 ) v.us[i] = 65535; \
                else v.us[i] = (vA).us[j]; \
                if ( (vB).l[i] <= 0 ) v.us[i+4] = 0; \
                else if ( (vB).l[i] >= 65535 ) v.us[i+4] = 65535; \
                else v.us[i+4] = (vB).us[j]; \
```

```
            j += 2; \
        } \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = v.ul[i]; \
    }
#define VPKSWSS_BE( vT, vA, vB, base ) \
    { \
        VMX reg v; \
        ulong i, j; \
        j = base; \
        for ( i = 0; i < 8; i++ ) { \
            if ( (vA).l[i] <= -32768 ) v.s[i] = -32768; \
            else if ( (vA).l[i] >= 32767 ) v.s[i] = 32767; \
            else v.s[i] = (vA).s[j]; \
            if ( (vB).l[i] <= -32768 ) v.s[i+8] = -32768; \
            else if ( (vB).l[i] >= 32767 ) v.s[i+8] = 32767; \
            else v.s[i+8] = (vB).s[j]; \
            j += 2; \
        } \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = v.ul[i]; \
    }


#if defined( LITTLE ENDIAN )
#define VPERM( vT, vA, vB, vC )         VPERM BE( vT, vB, vA, vC );
#define VPKUHUM( vT, vA, vB )           VPKUHUM BE( vT, vB, vA, 0 );
#define VPKUHUS( vT, vA, vB )           VPKUHUS BE( vT, vB, vA, 0 );
#define VPKSHUS( vT, vA, vB )           VPKSHUS BE( vT, vB, vA, 0 );
#define VPKSHSS( vT, vA, vB )           VPKSHSS BE( vT, vB, vA, 0 );
#define VPKUWUM( vT, vA, vB )           VPKUWUM BE( vT, vB, vA, 0 );
#define VPKUWUS( vT, vA, vB )           VPKUWUS BE( vT, vB, vA, 0 );
#define VPKSWUS( vT, vA, vB )           VPKSWUS BE( vT, vB, vA, 0 );
#define VPKSWSS( vT, vA, vB )           VPKSWSS_BE( vT, vB, vA, 0 );
#else
#define VPERM( vT, vA, vB, vC )         VPERM BE( vT, vA, vB, vC );
#define VPKUHUM( vT, vA, vB )           VPKUHUM BE( vT, vA, vB, 1 );
#define VPKUHUS( vT, vA, vB )           VPKUHUS BE( vT, vA, vB, 1 );
#define VPKSHUS( vT, vA, vB )           VPKSHUS BE( vT, vA, vB, 1 );
#define VPKSHSS( vT, vA, vB )           VPKSHSS BE( vT, vA, vB, 1 );
#define VPKUWUM( vT, vA, vB )           VPKUWUM BE( vT, vA, vB, 1 );
#define VPKUWUS( vT, vA, vB )           VPKUWUS BE( vT, vA, vB, 1 );
#define VPKSWUS( vT, vA, vB )           VPKSWUS BE( vT, vA, vB, 1 );
#define VPKSWSS( vT, vA, vB )           VPKSWSS_BE( vT, vA, vB, 1 );
#endif

#define VREFP( vT, vB ) \
    { \
        for ( i = 0; i < 4; i++ ) \
            (vT).f[i] = 1.0 / (vB).f[i]; \
    }
#define VRFIM( vT, vB ) \
    { \
        float f, max, r; \
        ulong i; \
        i = (127 + 31) << 23; \
        max = *(float *)&i; \
        for ( i = 0; i < 4; i++ ) { \
            f = (vB).f[i]; \
            if ( (f >= -max) && (f < max) ) { \
                r = (float)((long)f); \
                if ( r > f ) --r; \
                f = r; \
            } \
            (vT).f[i] = f; \
        } \
    }
#define VRFIN( vT, vB ) \
```

41

```
    { \
        float  f, r, s; \
        ulong i; \
        long lr; \
        for ( i = 0; i < 4; i++ ) { \
            s = f = (vB).f[i]; \
            if ( f < 0.0 ) f = -f; \
            r = f + 0.5; \
            if ( r != f ) { \
                lr = (long)r; \
                f = (float)lr; \
                if ( f == r ) f = (float)(lr & ~1); \
            } \
            if ( s < 0.0 ) f = -f; \
            (vT).f[i] = f; \
        } \
    }
#define VRFIP( vT, vB ) \
    { \
        float f, max, r; \
        ulong i; \
        i = (127 + 31) << 23; \
        max = *(float *)&i; \
        for ( i = 0; i < 4; i++ ) { \
            f = (vB).f[i]; \
            if ( (f >= -max) && (f < max) ) { \
                r = (float)((long)f); \
                if ( r < f ) ++r; \
                f = r; \
            } \
            (vT).f[i] = f; \
        } \
    }
#define VRFIZ( vT, vB ) \
    { \
        float f, max; \
        ulong i; \
        i = (127 + 31) << 23; \
        max = *(float *)&i; \
        for ( i = 0; i < 4; i++ ) { \
            f = (vB).f[i]; \
            if ( (f >= -max) && (f < max) ) \
                f = (float)((long)f); \
            (vT).f[i] = f; \
        } \
    }
#define VRLB( vT, vA, vB ) \
    { \
        ulong i, sh; \
        for ( i = 0; i < 16; i++ ) { \
            sh = (vB).uc[i] & 0x7; \
            (vT).uc[i] = ((vA).uc[i] << sh) | ((vA).uc[i] >> (8-sh)); \
        } \
    }
#define VRLH( vT, vA, vB ) \
    { \
        ulong i, sh; \
        for ( i = 0; i < 8; i++ ) { \
            sh = (vB).us[i] & 0xf; \
            (vT).us[i] = ((vA).us[i] << sh) | ((vA).us[i] >> (16-sh)); \
        } \
    }
#define VRSQRTEFP( vT, vB ) \
    { \
        for ( i = 0; i < 4; i++ ) \
            (vT).f[i] = 1.0 / sqrt((vB).f[i]); \
    }
```

42

salppc.h

```
#define VRLW( vT, vA, vB ) \
    { \
        ulong i, sh; \
        for ( i = 0; i < 4; i++ ) { \
            sh = (vB).ul[i] & 0x1f; \
            (vT).ul[i] = ((vA).ul[i] << sh) | ((vA).ul[i] >> (32-sh)); \
        } \
    }
#define VSEL( vT, vA, vB, vC ) \
    { \
        ulong atemp, btemp, i; \
        for ( i = 0; i < 4; i++ ) { \
            atemp = (vA).ul[i] & ~(vC).ul[i]; \
            btemp = (vA).ul[i] & (vC).ul[i]; \
            (vT).ul[i] = atemp | btemp; \
        } \
    }
#define VSL( vT, vA, vB ) \
    { \
        ulong i, sh; \
        sh = (vB).ul[3] & 0x7; \
        (vT).ul[0] = ((vA).ul[0] << sh) | ((vA).ul[1] >> (32-sh)); \
        (vT).ul[1] = ((vA).ul[1] << sh) | ((vA).ul[2] >> (32-sh)); \
        (vT).ul[2] = ((vA).ul[2] << sh) | ((vA).ul[3] >> (32-sh)); \
        (vT).ul[3] = (vA).ul[3] << sh; \
    }
#define VSLDOI( vT, vA, vB, UIMM ) \
    { \
        VMX reg v; \
        ulong i, j, sh; \
        sh = (UIMM) & 0xf; \
        for ( i = 0; i < (16-sh); i++ ) \
            v.uc[i] = (vA).uc[i+sh]; \
        for ( j = i; j < 16; j++ ) \
            v.uc[j] = (vB).uc[j-i]; \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = v.ul[i]; \
    }
#define VSLB( vT, vA, vB ) \
    { \
        ulong i, sh; \
        for ( i = 0; i < 16; i++ ) { \
            sh = (vB).uc[i] & 0x7; \
            (vT).uc[i] = (vA).uc[i] << sh; \
        } \
    }
#define VSLH( vT, vA, vB ) \
    { \
        ulong i, sh; \
        for ( i = 0; i < 8; i++ ) { \
            sh = (vB).us[i] & 0xf; \
            (vT).us[i] = (vA).us[i] << sh; \
        } \
    }
#define VSLO( vT, vA, vB ) \
    { \
        ulong i, j, sh; \
        sh = ((vB).ul[3] >> 3) & 0xf; \
        for ( i = 0; i < (16-sh); i++ ) \
            (vT).uc[i] = (vA).uc[i+sh]; \
        for ( j = i; j < 16; j++ ) \
            (vT).uc[j] = 0; \
    }
#define VSLW( vT, vA, vB ) \
    { \
        ulong i, sh; \
        for ( i = 0; i < 4; i++ ) { \
```

43

```
            sh = (vB).ul[i] & 0x1f; \
            (vT).ul[i] = (vA).ul[i] << sh; \
        } \
    }
#define VSR( vT, vA, vB ) \
    { \
        ulong i, sh; \
        sh = (vB).ul[3] & 0x7; \
        (vT).ul[3] = ((vA).ul[3] >> sh) | ((vA).ul[2] << (32-sh)); \
        (vT).ul[2] = ((vA).ul[2] >> sh) | ((vA).ul[1] << (32-sh)); \
        (vT).ul[1] = ((vA).ul[1] >> sh) | ((vA).ul[0] << (32-sh)); \
        (vT).ul[0] = (vA).ul[0] >> sh; \
    }
#define VSRAB( vT, vA, vB ) \
    { \
        ulong i, sh; \
        for ( i = 0; i < 16; i++ ) { \
            sh = (vB).uc[i] & 0x7; \
            (vT).c[i] = (vA).c[i] >> sh; \
        } \
    }
#define VSRAH( vT, vA, vB ) \
    { \
        ulong i, sh; \
        for ( i = 0; i < 8; i++ ) { \
            sh = (vB).us[i] & 0xf; \
            (vT).s[i] = (vA).s[i] >> sh; \
        } \
    }
#define VSRAW( vT, vA, vB ) \
    { \
        ulong i, sh; \
        for ( i = 0; i < 4; i++ ) { \
            sh = (vB).ul[i] & 0x1f; \
            (vT).l[i] = (vA).l[i] >> sh; \
        } \
    }
#define VSRB( vT, vA, vB ) \
    { \
        ulong i, sh; \
        for ( i = 0; i < 16; i++ ) { \
            sh = (vB).uc[i] & 0x7; \
            (vT).uc[i] = (vA).uc[i] >> sh; \
        } \
    }
#define VSRH( vT, vA, vB ) \
    { \
        ulong i, sh; \
        for ( i = 0; i < 8; i++ ) { \
            sh = (vB).us[i] & 0xf; \
            (vT).us[i] = (vA).us[i] >> sh; \
        } \
    }
#define VSRO( vT, vA, vB ) \
    { \
        long i, j, sh; \
        sh = ((vB).ul[3] >> 3) & 0xf; \
        for ( i = 15; i >= sh; i-- ) \
            (vT).uc[i] = (vA).uc[i-sh]; \
        for ( j = i; j >= 0; j-- ) \
            (vT).uc[j] = 0; \
    }
#define VSRW( vT, vA, vB ) \
    { \
        ulong i, sh; \
        for ( i = 0; i < 4; i++ ) { \
            sh = (vB).ul[i] & 0x1f; \
```

44

```
            (vT).ul[i] = (vA).ul[i] >> sh; \
        } \
    }
#define VSPLTB( vT, vB, UIMM ) \
    { \
        uchar c; \
        ulong i; \
        c = (vB).uc[C INDEX MUNGE( UIMM ) & 0xf]; \
        for ( i = 0; i < 16; i++ ) \
            (vT).uc[i] = c; \
    }
#define VSPLTH( vT, vB, UIMM ) \
    { \
        ushort s; \
        ulong i; \
        s = (vB).us[S INDEX_MUNGE( UIMM ) & 0x7]; \
        for ( i = 0; i < 8; i++ ) \
            (vT).us[i] = s; \
    }
#define VSPLTW( vT, vB, UIMM ) \
    { \
        ulong i, l; \
        l = (vB).ul[L INDEX_MUNGE( UIMM ) & 0x3]; \
        for ( i = 0; i < 4; i++ ) \
            (vT).ul[i] = l; \
    }
#define VSPLTISB( vT, SIMM ) \
    { \
        ulong i; \
        for ( i = 0; i < 16; i++ ) \
            (vT).c[i] = (char)(SIMM); \
    }
#define VSPLTISH( vT, SIMM ) \
    { \
        ulong i; \
        for ( i = 0; i < 8; i++ ) \
            (vT).s[i] = (short)(SIMM); \
    }
#define VSPLTISW( vT, SIMM ) \
    { \
        ulong i; \
        for ( i = 0; i < 4; i++ ) \
            (vT).l[i] = (long)(SIMM); \
    }
#define VSUBFP( vT, vA, vB ) \
    { \
        ulong i; \
        float a, b, c; \
        for ( i = 0; i < 4; i++ ) { \
            a = (vA).f[i]; \
            b = (vB).f[i]; \
            c = a - b; \
            (vT).f[i] = c; \
        } \
    }
#define VSUBSBS( vT, vA, vB ) \
    { \
        ulong i; \
        long itemp; \
        for ( i = 0; i < 16; i++ ) { \
            itemp = (long)(vA).c[i] - (long)(vB).c[i]; \
            if ( itemp < -128 ) (vT).c[i] = -128; \
            else if ( itemp > 127 ) (vT).c[i] = 127; \
            else (vT).c[i] = (char)itemp; \
        } \
    }
#define VSUBSHS( vT, vA, vB ) \
```

45

```
{ \
    ulong i; \
    long itemp; \
    for ( i = 0; i < 8; i++ ) { \
        itemp = (long)(vA).s[i] - (long)(vB).s[i]; \
        if ( itemp < -32768 ) (vT).s[i] = -32768; \
        else if ( itemp > 32767 ) (vT).s[i] = 32767; \
        else (vT).s[i] = (short)itemp; \
    } \
}
#define VSUBSWS( vT, vA, vB ) \
    { \
    ulong i; \
    long itemp; \
    for ( i = 0; i < 4; i++ ) { \
        itemp = (vA).l[i] - (vB).l[i]; \
        if ( ( (vA).l[i] >= 0) && ( (vB).l[i] < 0) && (itemp < 0) ) \
            (vT).l[i] = (long)0x7fffffff; \
        else if ( ( (vA).l[i] < 0) && ( (vB).l[i] > 0) && (itemp > 0) ) \
            (vT).l[i] = (long)0x80000000; \
        else (vT).l = itemp[i]; \
    } \
}
#define VSUBUBM( vT, vA, vB ) \
    { \
    ulong i; \
    for ( i = 0; i < 16; i++ ) \
        (vT).uc[i] = (vA).uc[i] - (vB).uc[i]; \
    }
#define VSUBUBS( vT, vA, vB ) \
    { \
    ulong i; \
    for ( i = 0; i < 16; i++ ) { \
        if ( (vA).uc[i] <= (vB).uc[i] ) (vT).uc[i] = 0; \
        else (vT).uc[i] = (vA).uc[i] - (vB).uc[i]; \
    } \
    }
#define VSUBUHM( vT, vA, vB ) \
    { \
    ulong i; \
    for ( i = 0; i < 8; i++ ) \
        (vT).us[i] = (vA).us[i] - (vB).us[i]; \
    }

#define VSUBUHS( vT, vA, vB ) \
    { \
    ulong i; \
    for ( i = 0; i < 8; i++ ) { \
        if ( (vA).us[i] <= (vB).us[i] ) (vT).us[i] = 0; \
        else (vT).us[i] = (vA).us[i] - (vB).us[i]; \
    } \
    }
#define VSUBUWM( vT, vA, vB ) \
    { \
    ulong i; \
    for ( i = 0; i < 4; i++ ) \
        (vT).ul[i] = (vA).ul[i] - (vB).ul[i]; \
    }
#define VSUBUWS( vT, vA, vB ) \
    { \
    ulong i; \
    for ( i = 0; i < 4; i++ ) { \
        if ( (vA).ul[i] <= (vB).ul[i] ) (vT).ul[i] = 0; \
        else (vT).ul[i] = (vA).ul[i] - (vB).ul[i]; \
    } \
    }
#define VSUMSWS( vT, vA, vB ) \
```

46

```
        { \
            ulong i; \
            double sum; \
            sum = (double)(vB).l[L INDEX_MUNGE( 3 )]; \
            for ( i = 0; i < 4; i++ ) \
                sum += (double)(vA).l[i]; \
            if ( sum > (double)(0x7fffffff) ) \
                (vT).l[L INDEX MUNGE( 3 )] = 0x7fffffff; \
            else if ( sum < (double)(0x80000000) ) \
                (vT).l[L_INDEX_MUNGE( 3 )] = 0x80000000; \
            else \
                (vT).l[L_INDEX_MUNGE( 3 )] = (long)sum; \
        }
#define VSUM2SWS( vT, vA, vB ) \
        { \
            ulong i; \
            double sum1, sum2; \
            sum1 = (double)(vB).l[L INDEX MUNGE( 1 )]; \
            sum2 = (double)(vB).l[L_INDEX_MUNGE( 3 )]; \
            for ( i = 0; i < 2; i++ ) { \
                sum1 += (double)(vA).l[L INDEX MUNGE( i )]; \
                sum2 += (double)(vA).l[L_INDEX_MUNGE( i+2 )]; \
            } \
            if ( sum1 > (double)(0x7fffffff) ) \
                (vT).l[L INDEX MUNGE( 1 )] = 0x7fffffff; \
            else if ( sum1 < (double)(0x80000000) ) \
                (vT).l[L_INDEX_MUNGE( 1 )] = 0x80000000; \
            else \
                (vT).l[L_INDEX_MUNGE( 1 )] = (long)sum1; \
            if ( sum2 > (double)(0x7fffffff) ) \
                (vT).l[L INDEX MUNGE( 3 )] = 0x7fffffff; \
            else if ( sum2 < (double)(0x80000000) ) \
                (vT).l[L_INDEX_MUNGE( 3 )] = 0x80000000; \
            else \
                (vT).l[L_INDEX_MUNGE( 3 )] = (long)sum2; \
        }
#define VSUM4SBS( vT, vA, vB ) \
        { \
            ulong i, j; \
            double sum; \
            for ( i = 0; i < 4; i++ ) { \
                sum = (double)(vB).l[i]; \
                for ( j = 0; j < 4; j++ ) { \
                    sum += (double)(vA).c[4*i + j]; \
                    if ( sum > (double)(0x7fffffff) ) \
                        (vT).l[i] = 0x7fffffff; \
                    else if ( sum < (double)(0x80000000) ) \
                        (vT).l[i] = 0x80000000; \
                    else \
                        (vT).l[i] = (long)sum; \
                } \
            } \
        }
#define VSUM4SHS( vT, vA, vB ) \
        { \
            ulong i, j; \
            double sum; \
            for ( i = 0; i < 4; i++ ) { \
                sum = (double)(vB).l[i]; \
                for ( j = 0; j < 2; j++ ) { \
                    sum += (double)(vA).s[2*i + j]; \
                    if ( sum > (double)(0x7fffffff) ) \
                        (vT).l[i] = 0x7fffffff; \
                    else if ( sum < (double)(0x80000000) ) \
                        (vT).l[i] = 0x80000000; \
                    else \
                        (vT).l[i] = (long)sum; \
```

47

```
            } \
          } \
      }
  #define VSUM4UBS( vT, vA, vB ) \
      { \
          ulong i, j; \
          double sum; \
          for ( i = 0; i < 4; i++ ) { \
              sum = (double)(vB).ul[i]; \
              for ( j = 0; j < 4; j++ ) { \
                  sum += (double)(vA).uc[4*i + j]; \
                  if ( sum > (2.0 * (double)(0x7fffffff) + 1.0) ) \
                      (vT).ul[i] = 0xffffffff; \
                  else \
                      (vT).ul[i] = (ulong)sum; \
              } \
          } \
      }
  #define VUPKHSB_BE( vT, vB ) \
      { \
          long i; \
          for ( i = 7; i >= 0; i-- ) \
              (vT).s[i] = (short)(vB).c[i]; \
      }
  #define VUPKHSH_BE( vT, vB ) \
      { \
          long i; \
          for ( i = 3; i >= 0; i-- ) \
              (vT).l[i] = (long)(vB).s[i]; \
      }
  #define VUPKLSB_BE( vT, vB ) \
      { \
          ulong i; \
          for ( i = 0; i < 8; i++ ) \
              (vT).s[i] = (short)(vB).c[i+8]; \
      }
  #define VUPKLSH_BE( vT, vB ) \
      { \
          ulong i; \
          for ( i = 0; i < 4; i++ ) \
              (vT).l[i] = (long)(vB).s[i+4]; \
      }

  #if defined( LITTLE ENDIAN )               VUPKLSB BE( vT, vB );
  #define VUPKHSB( vT, vB )                  VUPKLSH BE( vT, vB );
  #define VUPKHSH( vT, vB )                  VUPKHSB BE( vT, vB );
  #define VUPKLSB( vT, vB )                  VUPKHSH_BE( vT, vB );
  #define VUPKLSH( vT, vB )
  #else
  #define VUPKHSB( vT, vB )                  VUPKHSB BE( vT, vB );
  #define VUPKHSH( vT, vB )                  VUPKHSH BE( vT, vB );
  #define VUPKLSB( vT, vB )                  VUPKLSB BE( vT, vB );
  #define VUPKLSH( vT, vB )                  VUPKLSH_BE( vT, vB );
  #endif

  #define VXOR( vT, vA, vB ) \
      { \
          ulong i; \
          for ( i = 0; i < 4; i++ ) \
              (vT).ul[i] = (vA).ul[i] ^ (vB).ul[i]; \
      }

  #endif                                    /* end BUILD_MAX */

  /*
   *  stack and register macros
   */
```

48

salppc.h

```
#define VRSAVE_COND 7                    /* recommended VR condition bit */

/*
 *   macros to save and restore the CR register
 */
#define SAVE CR
#define REST_CR

/*
 *   macros to save and restore the LR register
 */
#define SAVE LR
#define REST_LR

/*
 *   GET FPR SAVE AREA places the start of the FPR save area into a register
 *   GET_GPR_SAVE_AREA places the start of the GPR save area into a register
 *
 *   For MAX only:
 *
 *     GET_VR_SAVE_AREA places the start of the VR save area into a register
 */
#define GET GPR SAVE AREA( ptr ) \
   ptr = (long)(((ulong)gpr_save_area + 15) & ~15);

#define GET FPR SAVE AREA( ptr ) \
   ptr = (long)(((ulong)fpr_save_area + 15) & ~15);

#if defined( BUILD MAX )
#define GET VR SAVE AREA( ptr ) \
   ptr = (long)(((ulong)vr_save_area + 15) & ~15);
#endif

/*
 *   macros to allocate and free space on the user stack.
 *   For C implementation, the size is limited to 4096 bytes.
 */
#define PUSH STACK( nbytes ) \
   sp = (long)(((ulong)stack + 15) & ~15);

#define POP_STACK( nbytes ) \
   sp = 0;

#define ALLOCATE STACK SPACE( ptr, nbytes ) \
   PUSH STACK( nbytes ) \
   ptr = sp;

#define FREE_STACK_SPACE( nbytes ) POP_STACK( nbytes )

#define CREATE_STACK FRAME( nbytes ) \
   PUSH_STACK( nbytes )

#define CREATE STACK FRAME X( nbytes ) \
   CREATE_STACK_FRAME( nbytes )

#define DESTROY_STACK_FRAME \
   sp = 0;

#define CREATE STACK BUFFER( bufferp, byte_align, nbytes ) \
   ALLOCATE_STACK_SPACE( bufferp, nbytes )

#define CREATE STACK BUFFER X( bufferp, byte_align, nbytes ) \
   CREATE_STACK_BUFFER( bufferp, byte_align, nbytes )

#define DESTROY_STACK_BUFFER \
   sp = 0;
```

49

salppc.h

```
/*
 * macros to create salcache from the stack. used in ucode only
 */
#define CREATE_STACK_SALCACHE \
    char __localcachebuffer[SALCACHE_ALLOC_SIZE];

#define DESTROY_STACK_SALCACHE

/*
 *   macros for saving and restoring non-volatile
 *   floating point registers (FPRs)
 */
#define SAVE f14
#define SAVE f14 f15
#define SAVE f14 f16
#define SAVE f14 f17
#define SAVE f14 f18
#define SAVE f14 f19
#define SAVE f14 f20
#define SAVE f14 f21
#define SAVE f14 f22
#define SAVE f14 f23
#define SAVE f14 f24
#define SAVE f14 f25
#define SAVE f14 f26
#define SAVE f14 f27
#define SAVE f14 f28
#define SAVE f14 f29
#define SAVE f14 f30
#define SAVE_f14_f31

#define SAVE d14
#define SAVE d14 d15
#define SAVE d14 d16
#define SAVE d14 d17
#define SAVE d14 d18
#define SAVE d14 d19
#define SAVE d14 d20
#define SAVE d14 d21
#define SAVE d14 d22
#define SAVE d14 d23
#define SAVE d14 d24
#define SAVE d14 d25
#define SAVE d14 d26
#define SAVE d14 d27
#define SAVE d14 d28
#define SAVE d14 d29
#define SAVE d14 d30
#define SAVE_d14_d31

#define REST f14
#define REST f14 f15
#define REST f14 f16
#define REST f14 f17
#define REST f14 f18
#define REST f14 f19
#define REST f14 f20
#define REST f14 f21
#define REST f14 f22
#define REST f14 f23
#define REST f14 f24
#define REST f14 f25
#define REST f14 f26
#define REST f14 f27
#define REST f14 f28
#define REST f14 f29
#define REST_f14_f30
```

50

salppc.h   2/23/2001

```
#define REST_f14_f31

#define REST d14
#define REST d14 d15
#define REST d14 d16
#define REST d14 d17
#define REST d14 d18
#define REST d14 d19
#define REST d14 d20
#define REST d14 d21
#define REST d14 d22
#define REST d14 d23
#define REST d14 d24
#define REST d14 d25
#define REST d14 d26
#define REST d14 d27
#define REST d14 d28
#define REST d14 d29
#define REST d14 d30
#define REST_d14_d31

/*
 *   macros for saving and restoring non-volatile
 *   general purpose registers (GPRs)
 */
#define SAVE r13
#define SAVE r13 r14
#define SAVE r13 r15
#define SAVE r13 r16
#define SAVE r13 r17
#define SAVE r13 r18
#define SAVE r13 r19
#define SAVE r13 r20
#define SAVE r13 r21
#define SAVE r13 r22
#define SAVE r13 r23
#define SAVE r13 r24
#define SAVE r13 r25
#define SAVE. r13 r26
#define SAVE r13 r27
#define SAVE r13 r28
#define SAVE r13 r29
#define SAVE r13 r30
#define SAVE_r13_r31

#define REST r13
#define REST r13 r14
#define REST r13 r15
#define REST r13 r16
#define REST r13 r17
#define REST r13 r18
#define REST r13 r19
#define REST r13 r20
#define REST r13 r21
#define REST r13 r22
#define REST r13 r23
#define REST r13 r24
#define REST r13 r25
#define REST r13 r26
#define REST r13 r27
#define REST r13 r28
#define REST r13 r29
#define REST r13 r30
#define REST_r13_r31

#define SAVE r14
#define SAVE_r14_r15
```

51

salppc.h   2/23/2001

```
#define SAVE r14 r16
#define SAVE r14 r17
#define SAVE r14 r18
#define SAVE r14 r19
#define SAVE r14 r20
#define SAVE r14 r21
#define SAVE r14 r22
#define SAVE r14 r23
#define SAVE r14 r24
#define SAVE r14 r25
#define SAVE r14 r26
#define SAVE r14 r27
#define SAVE r14 r28
#define SAVE r14 r29
#define SAVE r14 r30
#define SAVE_r14_r31

#define REST r14
#define REST r14 r15
#define REST r14 r16
#define REST r14 r17
#define REST r14 r18
#define REST r14 r19
#define REST r14 r20
#define REST r14 r21
#define REST r14 r22
#define REST r14 r23
#define REST r14 r24
#define REST r14 r25
#define REST r14 r26
#define REST r14 r27
#define REST r14 r28
#define REST r14 r29
#define REST r14 r30
#define REST_r14_r31

#define SAVE r15
#define SAVE r15 r16
#define SAVE r15 r17
#define SAVE r15 r18
#define SAVE r15 r19
#define SAVE r15 r20
#define SAVE r15 r21
#define SAVE r15 r22
#define SAVE r15 r23
#define SAVE r15 r24
#define SAVE r15 r25
#define SAVE r15 r26
#define SAVE r15 r27
#define SAVE r15 r28
#define SAVE r15 r29
#define SAVE r15 r30
#define SAVE_r15_r31

#define REST r15
#define REST r15 r16
#define REST r15 r17
#define REST r15 r18
#define REST r15 r19
#define REST r15 r20
#define REST r15 r21
#define REST r15 r22
#define REST r15 r23
#define REST r15 r24
#define REST r15 r25
#define REST r15 r26
#define REST_r15_r27
```

52

salppc.h   2/23/2001

```
#define REST_r15_r28
#define REST_r15_r29
#define REST_r15_r30
#define REST_r15_r31

#define SAVE_r16
#define SAVE_r16_r17
#define SAVE_r16_r18
#define SAVE_r16_r19
#define SAVE_r16_r20
#define SAVE_r16_r21
#define SAVE_r16_r22
#define SAVE_r16_r23
#define SAVE_r16_r24
#define SAVE_r16_r25
#define SAVE_r16_r26
#define SAVE_r16_r27
#define SAVE_r16_r28
#define SAVE_r16_r29
#define SAVE_r16_r30
#define SAVE_r16_r31

#define REST_r16
#define REST_r16_r17
#define REST_r16_r18
#define REST_r16_r19
#define REST_r16_r20
#define REST_r16_r21
#define REST_r16_r22
#define REST_r16_r23
#define REST_r16_r24
#define REST_r16_r25
#define REST_r16_r26
#define REST_r16_r27
#define REST_r16_r28
#define REST_r16_r29
#define REST_r16_r30
#define REST_r16_r31

/*
 *  VMX registers
 */
#define USE_THRU_v0( cond )
#define USE_THRU_v1( cond )
#define USE_THRU_v2( cond )
#define USE_THRU_v3( cond )
#define USE_THRU_v4( cond )
#define USE_THRU_v5( cond )
#define USE_THRU_v6( cond )
#define USE_THRU_v7( cond )
#define USE_THRU_v8( cond )
#define USE_THRU_v9( cond )
#define USE_THRU_v10( cond )
#define USE_THRU_v11( cond )
#define USE_THRU_v12( cond )
#define USE_THRU_v13( cond )
#define USE_THRU_v14( cond )
#define USE_THRU_v15( cond )
#define USE_THRU_v16( cond )
#define USE_THRU_v17( cond )
#define USE_THRU_v18( cond )
#define USE_THRU_v19( cond )
#define USE_THRU_v20( cond )
#define USE_THRU_v21( cond )
#define USE_THRU_v22( cond )
#define USE_THRU_v23( cond )
#define USE_THRU_v24( cond )
```

53

salppc.h   2/23/2001

```
#define USE THRU v25( cond )
#define USE THRU v26( cond )
#define USE THRU v27( cond )
#define USE THRU v28( cond )
#define USE THRU v29( cond )
#define USE THRU v30( cond )
#define USE_THRU_v31( cond )

#define FREE THRU v0( cond )
#define FREE THRU v1( cond )
#define FREE THRU v2( cond )
#define FREE THRU v3( cond )
#define FREE THRU v4( cond )
#define FREE THRU v5( cond )
#define FREE THRU v6( cond )
#define FREE THRU v7( cond )
#define FREE THRU v8( cond )
#define FREE THRU v9( cond )
#define FREE THRU v10( cond )
#define FREE THRU v11( cond )
#define FREE THRU v12( cond )
#define FREE THRU v13( cond )
#define FREE THRU v14( cond )
#define FREE THRU v15( cond )
#define FREE THRU v16( cond )
#define FREE THRU v17( cond )
#define FREE THRU v18( cond )
#define FREE THRU v19( cond )
#define FREE THRU v20( cond )
#define FREE THRU v21( cond )
#define FREE THRU v22( cond )
#define FREE THRU v23( cond )
#define FREE THRU v24( cond )
#define FREE THRU v25( cond )
#define FREE THRU v26( cond )
#define FREE THRU v27( cond )
#define FREE THRU v28( cond )
#define FREE THRU v29( cond )
#define FREE THRU v30( cond )
#define FREE_THRU_v31( cond )

#endif                              /* end SALPPC_H */

/*
 *-------------------------------------------------------------
 *
 *                  END OF FILE salppc.h
 *
 *-------------------------------------------------------------
 */
```

54

```
#if !defined( SALPPC_INC )
#define SALPPC_INC

#if 0
+*****************************************************************************+
|***   MC Standard Algorithms -- PPC Version                            ***|
|*****************************************************************************|
|*                                                                         *|
|*        File Name:     salppc.inc                                        *|
|*        Description:   SAL macro include file                            *|
|*                                                                         *|
|*        Source files should have extension .mac. For example, vadd.mac   *|
|*        and must include this file (salppc.inc).                         *|
|*                                                                         *|
|*        To assemble for PPC ucode, use the following basic               *|
|*        makefile build rule:                                             *|
|*                                                                         *|
|*            .SUFFIXES: .mac .c .s .o                                     *|
|*                                                                         *|
|*            .mac.o:   .                                                  *|
|*                cp $*.mac $*.c                                           *|
|*                ccmc -o $*.s -E $*.c                                     *|
|*                ccmc -c -o $*.o $*.s                                     *|
|*                rm -f $*.s                                               *|
|*                rm -f $*.c                     .                         *|
|*                                                                         *|
|*        To compile for C, use the following basic makefile build rule:   *|
|*                                                                         *|
|*            .SUFFIXES: .mac .c .o                                        *|
|*                                                                         *|
|*            .mac.o:                                                      *|
|*                cp $*.mac $*.c                                           *|
|*                ccmc -DCOMPILE_C -c -o $*.o $*.c           .             *|
|*                rm -f $*.c                                               *|
|*                                                                         *|
|*        The first 8 function arguments are passed in GPR registers       *|
|*        r3 - r10. Arguments beyond 8 are passed on the stack and may     *|
|*        be obtained with the GET_ARG8, GET_ARG9, ... GET ARG15 macros.   *|
|*        Additional GPR registers should be assigned in ascending order   *|
|*        starting from the last function argument. These may be declared  *|
|*        with the DECLARE_rx[ ry] macros. For example, a function with    *|
|*        5 arguments that requires 3 additional GPR registers would       *|
|*        issue: DECLARE r8 r10. r0, if required, should be declared       *|
|*        separately with the DECLARE r0 macro. GPR registers above r12    *|
|*        must be saved and restored using the SAVE_r13[_ry] and           *|
|*        REST_r13[_ry] macros, respectively.                             *|
|*                                                                         *|
|*        FPR registers should be assigned in ascending order starting     *|
|*        with f0[d0]. These may be declared with the DECLARE_f0[_fy]      *|
|*        or DECLARE d0[ dy] macros.                                       *|
|*        For example, DECLARE f0 f11. FPR registers above f13[d13] must   *|
|*        be saved and restored using the SAVE f14[ fy] and REST f14[_fy]  *|
|*        or SAVE_d14[_dy] and REST_d14[_dy] macros, respectively.         *|
|*                                                                         *|
|*        All variables must be assigned a register using the              *|
|*        pre-processor #define directive. GPR registers are named         *|
|*        r0 - r31; Single precision FPR registers are named f0 - f31.     *|
|*        Double precision FPR registers are named d0 - d31. Different     *|
|*        variables may be assigned to the same register as in:            *|
|*                                                                         *|
|*            #define vara   f12                                           *|
|*            #define varb   f12                                           *|
|*                                                                         *|
|*        Functions must begin with the FUNC_PROLOG macro and end          *|
|*        with the FUNC_EPILOG macro.                                      *|
|*                                                                         *|
```

1

```
*         Macros are provided for both Fortran and C entry points.        *
*                                                                         *
*         The GET SALCACHE macro should be used to get the address of     *
*         the "current" salcache buffer into a GPR register.              *
*                                                                         *
*         Avoid terminating macro lines with a semicolon.                 *
*                                                                         *
*         The following example demonstrates typical usage:               *
*                                                                         *
*             #include "salppc.inc"                                       *
*                                                                         *
*             /*                                                          *
*              *   assign variables to registers                         *
*              */                                                         *
*             #define A   r3                                              *
*             #define I   r4                                              *
*             #define B   r5                                              *
*             #define J   r6                                              *
*             #define C   r7                                              *
*             #define K   r8                                              *
*             #define D   r9                                              *
*             #define L   r10                                             *
*             #define N   r12                                             *
*             #define EFLAG  r11                                          *
*             #define count  r11                                          *
*                                                                         *
*             #define t0  r13                                             *
*             #define t1  r13                                             *
*             #define t2  r14                                             *
*             #define t3  r14                                             *
*             #define t4  r15                                             *
*             #define t5  r15                                             *
*             #define t6  r16                                             *
*                                                                         *
*             #define a0  f0                                              *
*             #define a1  f1                                              *
*             #define a2  f2                                              *
*             #define a3  f3                                              *
*             #define b0  f4                                              *
*             #define b1  f5                                              *
*             #define b2  f6                                              *
*             #define b3  f7                                              *
*             #define c0  f8                                              *
*             #define c1  f9                                              *
*             #define c2  f10                                             *
*             #define c3  f11                                             *
*             #define d0  f12                                             *
*             #define d1  f13                                             *
*             #define d2  f14                                             *
*             #define d3  f15                                             *
*                                                                         *
*         FUNC_PROLOG                         /* must precede function */  *
*                                                                         *
*         #if !defined( COMPILE_C )                                       *
*             U ENTRY(foo )                                               *
*             FORTRAN DREF 4(I, J, K, L)                                  *
*             FORTRAN_DREF_ARG8                                           *
*                                                                         *
*             U ENTRY(foo)                                                *
*             LI(EFLAG, 0)                                                *
*             BR(common)                                                  *
*                                                                         *
*             U ENTRY(foo x )                                             *
*             FORTRAN DREF 4(I, J, K, L)                                  *
*             FORTRAN DREF ARG8                                           *
*             FORTRAN_DREF_ARG9                                           *
*         #endif                                                          *
```

2

salppc.inc   3/9/2001

```
|*                                                                      *|
|*          ENTRY 10(foo x, A, I, B, J, C, K, D, L, N, EFLAG)          *|
|*             DECLARE r13 r16                                         *|
|*             DECLARE f0 f15                                          *|
|*             GET_ARG9( EFLAG )   /* get the 9'th arg (EFLAG) off stack */ *|
|*                                                                      *|
|*          LABEL(common)                                              *|
|*                                                                      *|
|*             SAVE CR                 /* needed if using fields 2,3 or 4 */ *|
|*             SAVE r13 r16                                            *|
|*             SAVE f14_f15                                            *|
|*             SAVE LR                 /* needed if making a function call */ *|
|*                                                                      *|
|*             GET_ARG8( N )           /* get the 8'th arg (N) off stack */ *|
|*                                                                      *|
|*                /* ... body of function ... */                       *|
|*                                                                      *|
|*             REST CR                                                 *|
|*             REST r13 r16                                            *|
|*             REST f14_f15                                            *|
|*             REST LR                                                 *|
|*             RETURN                                                  *|
|*                                                                      *|
|*          FUNC_EPILOG                      /* must conclude function */ *|
|*                                                                      *|
|*             .     Mercury Computer Systems, Inc.                    *|
|*             Copyright (c) 1996  All rights reserved                 *|
|*                                                                      *|
|* Revision       Date        Engineer; Reason                        *|
|* --------       ----        ----------------                        *|
|*   0.0        960223      jg; Created                               *|
|*   0.1        970109      jfk; Added POSTING BUFFER COUNT and made  *|
|*                               TEST IF DCBZ macro time "stw" instead *|
|*                               of doing the TEST IF DCBT macro(lwz) *|
|*   0.2        970124      jfk; Added SALCACHE ALLOC SIZE ,          *|
|*                               ALIGN SALCACHE, CREATE_SALCACHE_FRAME *|
|*                               DESTROY SALCACHE FRAME               *|
|*   0.3        970521      jfk; Added SET DCB[TZ] COND macros.       *|
|*                               Made old macros not assemble         *|
|*   0.4        980813      jfk; Changes SALCACHE ALLOC SIZE for 750  *|
+***********************************************************************+
#endif                                     /* header */

#if !defined( BUILD_603 ) && !defined( BUILD_750 ) && !defined( BUILD_MAX )
   #error  You must define BUILD_603 or BUILD_750 or BUILD_MAX
#endif

/*
 *  define single precision floating point field sizes,
 *  limits, and values
 */
#define F_FLOAT_SIZE   32
#define F_FRAC_SIZE    23
#define F_HIDDEN_SIZE   1
#define F_EXP_SIZE      8
#define F_SIGN_SIZE     1
#define F_SIGN_BIT   (F_FLOAT_SIZE - F_SIGN_SIZE)
#define F_EXP_MASK   ((1 << F_EXP_SIZE) - 1)
#define F_EXP_BIAS   ((1 << (F_EXP_SIZE-1)) - 1)
#define F_MAX_EXP   F_EXP_BIAS
#define F_MIN_EXP   (-(F_EXP_BIAS-1))

/*
 *  define double precision floating point field sizes,
 *  limits, and values
 */
#define D_FLOAT_SIZE   64
```

3

salppc.inc   3/9/2001

```
#define D FRAC SIZE  52
#define D HIDDEN SIZE  1
#define D EXP SIZE  11
#define D SIGN SIZE  1
#define D SIGN BIT  (D FLOAT SIZE - D SIGN SIZE)
#define D EXP MASK  ((1 << D EXP SIZE) - 1)
#define D EXP BIAS  ((1 << (D_EXP_SIZE-1)) - 1)
#define D MAX EXP  D EXP BIAS
#define D_MIN_EXP  (-(D_EXP_BIAS-1))


#if defined ( BUILD_603 )

#define  LOG2_CACHE_SIZE   (14)    /* Log (base 2) of 603 data cache */

#elif defined ( BUILD_750 ) || defined ( BUILD_MAX )

#define  LOG2_CACHE_SIZE   (15)    /* Log (base 2) of 750 or MAX data cache
*/

#endif

#define  LOG2 CACHE BSIZE   (LOG2 CACHE SIZE)
#define  LOG2 CACHE HSIZE   (LOG2 CACHE SIZE - 1)
#define  LOG2 CACHE LSIZE   (LOG2 CACHE SIZE - 2)
#define  LOG2 CACHE FSIZE   (LOG2 CACHE SIZE - 2)
#define  LOG2 CACHE DSIZE   (LOG2 CACHE SIZE - 3)
#define  LOG2 CACHE CSIZE   (LOG2 CACHE SIZE - 3)
#define  LOG2_CACHE_ZSIZE   (LOG2_CACHE_SIZE - 4)

#define  CACHE SIZE    (1 << LOG2 CACHE_SIZE)
#define  CACHE BSIZE   (CACHE SIZE)
#define  CACHE HSIZE   (CACHE SIZE >> 1)
#define  CACHE LSIZE   (CACHE SIZE >> 2)
#define  CACHE FSIZE   (CACHE SIZE >> 2)
#define  CACHE DSIZE   (CACHE SIZE >> 3)
#define  CACHE CSIZE   (CACHE SIZE >> 3)
#define  CACHE_ZSIZE   (CACHE_SIZE >> 4)

#define  LOG2 CACHE LINE_SIZE  5
#define  CACHE LINE SIZE  (1 << LOG2 CACHE_LINE SIZE)
#define  CACHE LINE LSIZE (CACHE LINE SIZE >> 2)
#define  CACHE LINE MASK  (CACHE LINE SIZE - 1)
#define  CACHE_LINE_ADDR_MASK  (0xffffffe0)

#define  LOG2 SALCACHE ALIGN  6
#define  SALCACHE ALIGN  (1 << LOG2 SALCACHE ALIGN)
#define  SALCACHE_ALIGN_MASK  (SALCACHE_ALIGN - 1)

#define  SALCACHE SIZE        CACHE SIZE
#define  SALCACHE EXTRA SIZE  (SALCACHE ALIGN + 64)
#define  SALCACHE_ALLOC_SIZE  (SALCACHE_SIZE + SALCACHE_EXTRA_SIZE)

/*
 * Define memory vector non-cache (N) / cache (C) FLAG values for
 * Enhanced SAL calls (final argument). The letters in the symbol
 * correspond to the vectors in the call, moving from left to right
 * so, for example:
 *
 * for VMULX, there are the following 8 possibilities:
 *
 *     VMULX (A, I, B, J, C, K, N, SAL NNN)   A, B, C all not in cache
 *     VMULX (A, I, B, J, C, K, N, SAL NNC)   A, B not in cache, C in cache
 *     VMULX (A, I, B, J, C, K, N, SAL NCN)   A, C not in cache, B in cache
 *     VMULX (A, I, B, J, C, K, N, SAL NCC)   A not in cache, B, C in cache
 *     VMULX (A, I, B, J, C, K, N, SAL CNN)   B, C not in cache, A in cache
 *     VMULX (A, I, B, J, C, K, N, SAL CNC)   B not in cache, A, C in cache
 *     VMULX (A, I, B, J, C, K, N, SAL CCN)   C not in cache, A, B in cache
```

4

```
*       VMULX (A, I, B, J, C, K, N, SAL_CCC)    A, B, C all in cache
*/

/*
*  1 vector algorithms
*/
#define   SAL_N   0
#define   SAL_C   1

/*
*  2 vector algorithms
*/
#define   SAL_NN   0
#define   SAL_NC   1
#define   SAL_CN   2
#define   SAL_CC   3

/*
*  3 vector algorithms
*/
#define   SAL_NNN   0
#define   SAL_NNC   1
#define   SAL_NCN   2
#define   SAL_NCC   3
#define   SAL_CNN   4
#define   SAL_CNC   5
#define   SAL_CCN   6
#define   SAL_CCC   7

/*
*  4 vector algorithms
*/
#define   SAL_NNNN   0
#define   SAL_NNNC   1
#define   SAL_NNCN   2
#define   SAL_NNCC   3
#define   SAL_NCNN   4
#define   SAL_NCNC   5
#define   SAL_NCCN   6
#define   SAL_NCCC   7
#define   SAL_CNNN   8
#define   SAL_CNNC   9
#define   SAL_CNCN   10
#define   SAL_CNCC   11
#define   SAL_CCNN   12
#define   SAL_CCNC   13
#define   SAL_CCCN   14
#define   SAL_CCCC   15

/*
*  5 vector algorithms
*/
#define   SAL_NNNNN   0
#define   SAL_NNNNC   1
#define   SAL_NNNCN   2
#define   SAL_NNNCC   3
#define   SAL_NNCNN   4
#define   SAL_NNCNC   5
#define   SAL_NNCCN   6
#define   SAL_NNCCC   7
#define   SAL_NCNNN   8
#define   SAL_NCNNC   9
#define   SAL_NCNCN   10
#define   SAL_NCNCC   11
#define   SAL_NCCNN   12
#define   SAL_NCCNC   13
#define   SAL_NCCCN   14
```

5

salppc.inc   3/9/2001

```
#define   SAL NCCCC     15
#define   SAL CNNNN     16
#define   SAL CNNNC     17
#define   SAL CNNCN     18
#define   SAL CNNCC     19
#define   SAL CNCNN     20
#define   SAL CNCNC     21
#define   SAL CNCCN     22
#define   SAL CNCCC     23
#define   SAL CCNNN     24
#define   SAL CCNNC     25
#define   SAL CCNCN     26
#define   SAL CCNCC     27
#define   SAL CCCNN     28
#define   SAL CCCNC     29
#define   SAL CCCCN     30
#define   SAL_CCCCC     31


/*
 *   define byte offsets into FFT_setup_ppc603e
 */
#define   FFT SETUP HANDLE            0
#define   FFT SETUP SMALL TWIDP       4
#define   FFT SETUP SMALL BITR TWIDP  8
#define   FFT SETUP SMALL LOG2M       12
#define   FFT SETUP BIG TWIDP         16
#define   FFT SETUP BIG XY TWIDP      20
#define   FFT SETUP BIG LOG2MXY       24
#define   FFT SETUP BIG LOG2X         28
#define   FFT SETUP BIG LOG2Y         32
#define   FFT SETUP BIG STRIPX        36
#define   FFT SETUP RPASS TWIDP       40
#define   FFT SETUP RADIX3 TWIDP      44
#define   FFT SETUP RADIX5_TWIDP      48
#define   FFT SETUP LOG2M             52
#define   FFT SETUP LOG2MR            56
#define   FFT SETUP VMX BITR TWIDP    60
#define   FFT_SETUP_VMX_TABLES        64


/*
 *   ASIC equates
 */
#define   ASIC_H               -1024          /* (0xFBFF + 1) */

#define   PREFETCH CONTROL     (0xFBFFFE00)
#define   PREFETCH CONTROL H   -1024          /* (0xFBFF + 1) */
#define   PREFETCH_CONTROL_L   -512           /* (0xFE00) */

#define   MISCON B             (0xFBFFFC18)
#define   MISCON B H           -1024          /* (0xFBFF + 1) */
#define   MISCON_B_L           -1000          . /* (0xFC18) */

#define   PREFETCH DISABLED    0
#define   PREFETCH AUTO 6      1
#define   PREFETCH AUTO 5      2
#define   PREFETCH AUTO 4      3
#define   PREFETCH AUTO 3      4
#define   PREFETCH AUTO 2      5
#define   PREFETCH AUTO 1      6
#define   PREFETCH_AUTO_0      7

#define   PREFETCH MANUAL 0    8
#define   PREFETCH MANUAL 2    9
#define   PREFETCH MANUAL 4    10
#define   PREFETCH MANUAL 6    11
#define   PREFETCH MANUAL 8    12
#define   PREFETCH_MANUAL_10   13
```

6

salppc.inc   3/9/2001

```
#define    PREFETCH MANUAL 12   14
#define    PREFETCH_MANUAL_14   15

#define    USE PREFETCH_CONTROL  16
#define    USE_MISCON_B          0

#define    PREFETCH_MASK        15

#define    PREFETCH DEFAULT   (USE PREFETCH CONTROL  |  PREFETCH MANUAL 0)
#define    PREFETCH OFF       (USE PREFETCH CONTROL  |  PREFETCH DISABLED)
#define    PREFETCH A6        (USE PREFETCH CONTROL  |  PREFETCH AUTO 6)
#define    PREFETCH A5        (USE PREFETCH CONTROL  |  PREFETCH AUTO 5)
#define    PREFETCH A4        (USE PREFETCH CONTROL  |  PREFETCH AUTO 4)
#define    PREFETCH A3        (USE PREFETCH CONTROL  |  PREFETCH AUTO 3)
#define    PREFETCH A2        (USE PREFETCH CONTROL  |  PREFETCH AUTO 2)
#define    PREFETCH A1        (USE PREFETCH CONTROL  |  PREFETCH AUTO 1)
#define    PREFETCH_A0        (USE_PREFETCH_CONTROL  |  PREFETCH_AUTO_0)

#define    PREFETCH M0        (USE PREFETCH CONTROL  |  PREFETCH MANUAL 0)
#define    PREFETCH M2        (USE PREFETCH CONTROL  |  PREFETCH MANUAL 2)
#define    PREFETCH M4        (USE PREFETCH CONTROL  |  PREFETCH MANUAL 4)
#define    PREFETCH M6        (USE PREFETCH CONTROL  |  PREFETCH MANUAL 6)
#define    PREFETCH M8        (USE PREFETCH CONTROL  |  PREFETCH MANUAL 8)
#define    PREFETCH M10       (USE PREFETCH CONTROL  |  PREFETCH MANUAL 10)
#define    PREFETCH M12       (USE PREFETCH CONTROL  |  PREFETCH MANUAL 12)
#define    PREFETCH_M14       (USE_PREFETCH_CONTROL  |  PREFETCH_MANUAL_14)

/*
 *  macro to compile for PPC assembly (COMPILE_C *not* defined) or
 *  C code (COMPILE_C defined)
 */
#if defined( COMPILE_C )

#include "salppc.h"

#else

/*
 *  GPR register equates
 */
#define r0     0
#define sp     1
#define rtoc   2
#define r3     3
#define r4     4
#define r5     5
#define r6     6
#define r7     7
#define r8     8
#define r9     9
#define r10    10
#define r11    11
#define r12    12
#define r13    13
#define r14    14
#define r15    15
#define r16    16
#define r17    17
#define r18    18
#define r19    19
#define r20    20
#define r21    21
#define r22    22
#define r23    23
#define r24    24
#define r25    25
#define r26    26
```

7

salppc.inc

```
#define r27    27
#define r28    28
#define r29    29
#define r30    30
#define r31    31

/*
 *  FPR single precision register equates
 */
#define f0     0
#define f1     1
#define f2     2
#define f3     3
#define f4     4
#define f5     5
#define f6     6
#define f7     7
#define f8     8
#define f9     9
#define f10    10
#define f11    11
#define f12    12
#define f13    13
#define f14    14
#define f15    15
#define f16    16
#define f17    17
#define f18    18
#define f19    19
#define f20    20
#define f21    21
#define f22    22
#define f23    23
#define f24    24
#define f25    25
#define f26    26
#define f27    27
#define f28    28
#define f29    29
#define f30    30
#define f31    31

/*
 *  FPR double precision register equates
 */
#define d0     0
#define d1     1
#define d2     2
#define d3     3
#define d4     4
#define d5     5
#define d6     6
#define d7     7
#define d8     8
#define d9     9
#define d10    10
#define d11    11
#define d12    12
#define d13    13
#define d14    14
#define d15    15
#define d16    16
#define d17    17
#define d18    18
#define d19    19
#define d20    20
#define d21    21
```

8

salppc.inc   3/9/2001

```
#define d22    22
#define d23    23
#define d24    24
#define d25    25
#define d26    26
#define d27    27
#define d28    28
#define d29    29
#define d30    30
#define d31    31

#if defined( BUILD_MAX )

/*
 *   VMX (g4) register equates
 */
#define v0     0
#define v1     1
#define v2     2
#define v3     3
#define v4     4
#define v5     5
#define v6     6
#define v7     7
#define v8     8
#define v9     9
#define v10    10
#define v11    11
#define v12    12
#define v13    13
#define v14    14
#define v15    15
#define v16    16
#define v17    17
#define v18    18
#define v19    19
#define v20    20
#define v21    21
#define v22    22
#define v23    23
#define v24    24
#define v25    25
#define v26    26
#define v27    27
#define v28    28
#define v29    29
#define v30    30
#define v31    31

#endif

#define FUNC_PROLOG \
.section .text; \
.align 5;

#define FUNC_EPILOG

#define TEXT_SECTION( logb2_align ) \
.section .text; \
.align logb2_align;

#define DATA_SECTION( logb2_align ) \
.section .data; \
.align logb2_align;

#define RODATA_SECTION( logb2_align ) \
.section .rodata; \
```

9

```
.align logb2_align;

#define PC_OFFSET( nbytes )  (. + (nbytes) )

/*
 *  make a "double" concat to fool the preprocessor so that input
 *  arguments get translated before concatenation; otherwise, the
 *  concatenated symbol doesn't get translated properly
 */
#define CONCAT( left, right ) CONCAT_NEST( left, right )
#define CONCAT_NEST( left, right ) left##right

/*
 *  macro for extern declarations and definitions
 */
#define EXTERN_DATA( symbol )

#define EXTERN_FUNC( func )

/*
 *  macro for a global declaration
 */
#define GLOBAL( symbol ) \
.globl symbol

/*
 *  macro for a local declaration
 */
#define LOCAL( symbol )

/*
 *  macros for creating static arrays
 */
#define START_ARRAY( name ) \
name##:

#define START_C_ARRAY( name )  START_ARRAY( name )
#define START_UC_ARRAY( name )  START_ARRAY( name )
#define START_S_ARRAY( name )  START_ARRAY( name )
#define START_US_ARRAY( name )  START_ARRAY( name )
#define START_L_ARRAY( name )  START_ARRAY( name )
#define START_UL_ARRAY( name )  START_ARRAY( name )
#define START_F_ARRAY( name )  START_ARRAY( name )

#define END_ARRAY

#define DATA( type, d1 ) \
.##type d1

#define DATA2( type, d1, d2 ) \
.##type d1, d2

#define DATA4( type, d1, d2, d3, d4 ) \
.##type d1, d2, d3, d4

#define DATA8( type, d1, d2, d3, d4, d5, d6, d7, d8 ) \
.##type d1, d2, d3, d4, d5, d6, d7, d8

#define C_DATA( d1 )    DATA( byte, d1 )
#define UC_DATA( d1 )   DATA( byte, d1 )
#define S_DATA( d1 )    DATA( short, d1 )
#define US_DATA( d1 )   DATA( short, d1 )
#define L_DATA( d1 )    DATA( long, d1 )
#define UL_DATA( d1 )   DATA( long, d1 )
#define F_DATA( d1 )    DATA( float, d1 )

#if defined( LITTLE_ENDIAN )
```

10

```
#define D_DATA( d1, d2 )    DATA2( long, d2, d1 )
#else
#define D_DATA( d1, d2 )    DATA2( long, d1, d2 )
#endif

#define C DATA2( d1, d2 )    DATA2( byte, d1, d2 )
#define UC DATA2( d1, d2 )    DATA2( byte, d1, d2 )
#define S DATA2( d1, d2 )    DATA2( short, d1, d2 )
#define US DATA2( d1, d2 )    DATA2( short, d1, d2 )
#define L DATA2( d1, d2 )    DATA2( long, d1, d2 )
#define UL DATA2( d1, d2 )    DATA2( long, d1, d2 )
#define F_DATA2( d1, d2 )    DATA2( float, d1, d2 )

#define C DATA4( d1, d2, d3, d4 )    DATA4( byte, d1, d2, d3, d4 )
#define UC DATA4( d1, d2, d3, d4 )    DATA4( byte, d1, d2, d3, d4 )
#define S DATA4( d1, d2, d3, d4 )    DATA4( short, d1, d2, d3, d4 )
#define US DATA4( d1, d2, d3, d4 )    DATA4( short, d1, d2, d3, d4 )
#define L DATA4( d1, d2, d3, d4 )    DATA4( long, d1, d2, d3, d4 )
#define UL DATA4( d1, d2, d3, d4 )    DATA4( long, d1, d2, d3, d4 )
#define F_DATA4( d1, d2, d3, d4 )    DATA4( float, d1, d2, d3, d4 )

#define C DATA8( d1, d2, d3, d4, d5, d6, d7, d8 ) \
        DATA8( byte, d1, d2, d3, d4, d5, d6, d7, d8 )
#define UC DATA8( d1, d2, d3, d4, d5, d6, d7, d8 ) \
        DATA8( byte, d1, d2, d3, d4, d5, d6, d7, d8 )
#define S DATA8( d1, d2, d3, d4, d5, d6, d7, d8 ) \
        DATA8( short, d1, d2, d3, d4, d5, d6, d7, d8 )
#define US DATA8( d1, d2, d3, d4, d5, d6, d7, d8 ) \
        DATA8( short, d1, d2, d3, d4, d5, d6, d7, d8 )
#define L DATA8( d1, d2, d3, d4, d5, d6, d7, d8 ) \
        DATA8( long, d1, d2, d3, d4, d5, d6, d7, d8 )
#define UL DATA8( d1, d2, d3, d4, d5, d6, d7, d8 ) \
        DATA8( long, d1, d2, d3, d4, d5, d6, d7, d8 )
#define F DATA8( d1, d2, d3, d4, d5, d6, d7, d8 ) \
        DATA8( float, d1, d2, d3, d4, d5, d6, d7, d8 )

/*
 *   macros for creating vmx permute masks (128-bits)
 */
#if defined( LITTLE_ENDIAN )

#define L PERMUTE MUNGE( l ) ( (l) ^ 0x1c1c1c1c )
#define S PERMUTE MUNGE( s ) ( (s) ^ 0x1e1e )
#define C_PERMUTE_MUNGE( c ) ( (c) ^ 0x1f )

#define L INDEX MUNGE( x ) ( (x) ^ 0x3 )
#define S INDEX MUNGE( x ) ( (x) ^ 0x7 )
#define C_INDEX_MUNGE( x ) ( (x) ^ 0xf )

#else

#define L PERMUTE MUNGE( l ) ( l )
#define S PERMUTE MUNGE( s ) ( s )
#define C_PERMUTE_MUNGE( c ) ( c )

#define L INDEX MUNGE( x ) ( x )
#define S INDEX MUNGE( x ) ( x )
#define C_INDEX_MUNGE( x ) ( x )

#endif

#define L PERMUTE MASK( l1, l2, l3, l4 ) \
.long L PERMUTE MUNGE( l1 ), L PERMUTE MUNGE( l2 ), \
      L_PERMUTE_MUNGE( l3 ), L_PERMUTE_MUNGE( l4 )

#define S PERMUTE MASK( s1, s2, s3, s4, s5, s6, s7, s8 ) \
.short S_PERMUTE_MUNGE( s1 ), S_PERMUTE_MUNGE( s2 ), \
```

11

```
            S PERMUTE MUNGE( s3 ), S PERMUTE MUNGE( s4 ), \
            S PERMUTE MUNGE( s5 ), S PERMUTE MUNGE( s6 ), \
            S_PERMUTE_MUNGE( s7 ), S_PERMUTE_MUNGE( s8 )

#define C_PERMUTE_MASK( c1, c2, c3, c4, c5, c6, c7, c8, \
                        c9, c10, c11, c12, c13, c14, c15, c16 ) \
.byte C PERMUTE MUNGE( c1 ), C PERMUTE MUNGE( c2 ), \
      C PERMUTE MUNGE( c3 ), C PERMUTE MUNGE( c4 ), \
      C PERMUTE MUNGE( c5 ), C PERMUTE MUNGE( c6 ), \
      C PERMUTE MUNGE( c7 ), C PERMUTE MUNGE( c8 ), \
      C PERMUTE MUNGE( c9 ), C PERMUTE MUNGE( c10 ), \
      C PERMUTE MUNGE( c11 ), C PERMUTE MUNGE( c12 ), \
      C PERMUTE MUNGE( c13 ), C PERMUTE MUNGE( c14 ), \
      C_PERMUTE_MUNGE( c15 ), C_PERMUTE_MUNGE( c16 )

/*
 *  macro for a microcode entry point (e.g. vaddx, vaddx_)
 *  U_ENTRY is a "nop" for C code
 */
#define U ENTRY( func_name ) \
.globl func_name; \
func_name:

/*
 *  macros for C function prototypes
 */
#define C PROTOTYPE 0( func name )
#define C PROTOTYPE 1( func name )
#define C PROTOTYPE 2( func name )
#define C PROTOTYPE 3( func name )
#define C PROTOTYPE 4( func name )
#define C PROTOTYPE 5( func name )
#define C PROTOTYPE 6( func name )
#define C PROTOTYPE 7( func name )
#define C PROTOTYPE 8( func name )
#define C PROTOTYPE 9( func name )
#define C PROTOTYPE 10( func name )
#define C PROTOTYPE 11( func name )
#define C PROTOTYPE 12( func name )
#define C PROTOTYPE 13( func name )
#define C PROTOTYPE 14( func name )
#define C PROTOTYPE 15( func name )
#define C_PROTOTYPE_16( func_name )

/*
 *  macros for C and Fortran callable entry points
 */
#define ENTRY 0( func_name ) \
.globl func_name; \
func_name:

#define ENTRY 1( func_name, arg0 ) \
.globl func_name; \
func_name:

#define ENTRY 2( func_name, arg0, arg1 ) \
.globl func_name; \
func_name:

#define ENTRY 3( func_name, arg0, arg1, arg2 ) \
.globl func_name; \
func_name:

#define ENTRY 4( func_name, arg0, arg1, arg2, arg3 ) \
.globl func_name; \
func_name:
```

12

```
#define ENTRY_5( func_name, arg0, arg1, arg2, arg3, arg4 ) \
.globl func_name; \
func_name:

#define ENTRY_6( func_name, arg0, arg1, arg2, arg3, arg4, arg5 ) \
.globl func_name; \
func_name:

#define ENTRY_7( func_name, arg0, arg1, arg2, arg3, arg4, arg5, \
                          arg6 ) \
.globl func_name; \
func_name:

#define ENTRY_8( func_name, arg0, arg1, arg2, arg3, arg4, arg5, \
                          arg6, arg7 ) \
.globl func_name; \
func_name:

#define ENTRY_9( func_name, arg0, arg1, arg2, arg3, arg4, arg5, \
                          arg6, arg7, arg8 ) \
.globl func_name; \
func_name:

#define ENTRY_10( func_name, arg0, arg1, arg2, arg3, arg4, arg5, \
                          arg6, arg7, arg8, arg9 ) \
.globl func_name; \
func_name:

#define ENTRY_11( func_name, arg0, arg1, arg2, arg3, arg4, arg5, \
                          arg6, arg7, arg8, arg9, arg10 ) \
.globl func_name; \
func_name:

#define ENTRY_12( func_name, arg0, arg1, arg2, arg3, arg4, arg5, \
                          arg6, arg7, arg8, arg9, arg10, arg11 ) \
.globl func_name; \
func_name:

#define ENTRY_13( func_name, arg0, arg1, arg2, arg3, arg4, arg5, \
                          arg6, arg7, arg8, arg9, arg10, arg11, \
                          arg12 ) \
.globl func_name; \
func_name:

#define ENTRY_14( func_name, arg0, arg1, arg2, arg3, arg4, arg5, \
                          arg6, arg7, arg8, arg9, arg10, arg11, \
                          arg12, arg13 ) \
.globl func_name; \
func_name:

#define ENTRY_15( func_name, arg0, arg1, arg2, arg3, arg4, arg5, \
                          arg6, arg7, arg8, arg9, arg10, arg11, \
                          arg12, arg13, arg14 ) \
.globl func_name; \
func_name:

#define ENTRY_16( func_name, arg0, arg1, arg2, arg3, arg4, arg5, \
                          arg6, arg7, arg8, arg9, arg10, arg11, \
                          arg12, arg13, arg14, arg15 ) \
.globl func_name; \
func_name:

/*
 *  macros to de-reference any set of the first 8 arguments
 *  passed by reference to the Fortran entry point but by
 *  value to the corresponding C entry point
 */
```

13

salppc.inc   3/9/2001

```
#define FORTRAN DREF 1( arg0 ) \
    lwz arg0, 0(arg0);

#define FORTRAN DREF 2( arg0, arg1 ) \
    lwz arg0, 0(arg0); \
    lwz arg1, 0(arg1);

#define FORTRAN DREF 3( arg0, arg1, arg2 ) \
    lwz arg0, 0(arg0); \
    lwz arg1, 0(arg1); \
    lwz arg2, 0(arg2);

#define FORTRAN DREF 4( arg0, arg1, arg2, arg3 ) \
    lwz arg0, 0(arg0); \
    lwz arg1, 0(arg1); \
    lwz arg2, 0(arg2); \
    lwz arg3, 0(arg3);

#define FORTRAN DREF 5( arg0, arg1, arg2, arg3, arg4 ) \
    lwz arg0, 0(arg0); \
    lwz arg1, 0(arg1); \
    lwz arg2, 0(arg2); \
    lwz arg3, 0(arg3); \
    lwz arg4, 0(arg4);

#define FORTRAN DREF 6( arg0, arg1, arg2, arg3, arg4, arg5 ) \
    lwz arg0, 0(arg0); \
    lwz arg1, 0(arg1); \
    lwz arg2, 0(arg2); \
    lwz arg3, 0(arg3); \
    lwz arg4, 0(arg4); \
    lwz arg5, 0(arg5);

#define FORTRAN DREF 7( arg0, arg1, arg2, arg3, arg4, arg5, arg6 ) \
    lwz arg0, 0(arg0); \
    lwz arg1, 0(arg1); \
    lwz arg2, 0(arg2); \
    lwz arg3, 0(arg3); \
    lwz arg4, 0(arg4); \
    lwz arg5, 0(arg5); \
    lwz arg6, 0(arg6);

#define FORTRAN DREF 8( arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7 ) \
    lwz arg0, 0(arg0); \
    lwz arg1, 0(arg1); \
    lwz arg2, 0(arg2); \
    lwz arg3, 0(arg3); \
    lwz arg4, 0(arg4); \
    lwz arg5, 0(arg5); \
    lwz arg6, 0(arg6); \
    lwz arg7, 0(arg7);

/*
 *  macros to de-reference specific arguments beyond the first 8
 *  passed by value to the C entry point
 */
#define ARG_OFF  (8 - 8*4)

#define FORTRAN DREF_ARG8 \
    lwz r12, (ARG OFF + 8*4)(sp); \
    lwz r12, 0(r12); \
    stw r12, (ARG_OFF + 8*4)(sp);

#define FORTRAN DREF_ARG9 \
    lwz r12, (ARG OFF + 9*4)(sp); \
    lwz r12, 0(r12); \
    stw r12, (ARG_OFF + 9*4)(sp);
```

14

```
#define FORTRAN DREF_ARG10 \
    lwz r12, (ARG OFF + 10*4)(sp); \
    lwz r12, 0(r12); \
    stw r12, (ARG_OFF + 10*4)(sp);

#define FORTRAN DREF_ARG11 \
    lwz r12, (ARG OFF + 11*4)(sp); \
    lwz r12, 0(r12); \
    stw r12, (ARG_OFF + 11*4)(sp);

#define FORTRAN DREF_ARG12 \
    lwz r12, (ARG OFF + 12*4)(sp); \
    lwz r12, 0(r12); \
    stw r12, (ARG_OFF + 12*4)(sp);

#define FORTRAN DREF_ARG13 \
    lwz r12, (ARG OFF + 13*4)(sp); \
    lwz r12, 0(r12); \
    stw r12, (ARG_OFF + 13*4)(sp);

#define FORTRAN DREF_ARG14 \
    lwz r12, (ARG OFF + 14*4)(sp); \
    lwz r12, 0(r12); \
    stw r12, (ARG_OFF + 14*4)(sp);

#define FORTRAN DREF_ARG15 \
    lwz r12, (ARG OFF + 15*4)(sp); \
    lwz r12, 0(r12); \
    stw r12, (ARG_OFF + 15*4)(sp);

#define FORTRAN DREF_ARG16 \
    lwz r12, (ARG OFF + 16*4)(sp); \
    lwz r12, 0(r12); \
    stw r12, (ARG_OFF + 16*4)(sp);

#define FORTRAN DREF_ARG17 \
    lwz r12, (ARG OFF + 17*4)(sp); \
    lwz r12, 0(r12); \
    stw r12, (ARG_OFF + 17*4)(sp);

/*
 *   macros to get GPR arguments beyond 8
 */
#define GET ARG8( rD )                     lwz rD, (ARG OFF + 8*4)(sp);
#define GET ARG9( rD )                     lwz rD, (ARG OFF + 9*4)(sp);
#define GET ARG10( rD )                    lwz rD, (ARG OFF + 10*4)(sp);
#define GET ARG11( rD )                    lwz rD, (ARG OFF + 11*4)(sp);
#define GET ARG12( rD )                    lwz rD, (ARG OFF + 12*4)(sp);
#define GET ARG13( rD )                    lwz rD, (ARG OFF + 13*4)(sp);
#define GET ARG14( rD )                    lwz rD, (ARG OFF + 14*4)(sp);
#define GET ARG15( rD )                    lwz rD, (ARG OFF + 15*4)(sp);
#define GET ARG16( rD )                    lwz rD, (ARG OFF + 16*4)(sp);
#define GET_ARG17( rD )                    lwz rD, (ARG_OFF + 17*4)(sp);

/*
 *   macros to set GPR arguments beyond 8
 */
#define SET ARG8( rD )                     stw rD, (ARG OFF + 8*4)(sp);
#define SET ARG9( rD )                     stw rD, (ARG OFF + 9*4)(sp);
#define SET ARG10( rD )                    stw rD, (ARG OFF + 10*4)(sp);
#define SET ARG11( rD )                    stw rD, (ARG OFF + 11*4)(sp);
#define SET ARG12( rD )                    stw rD, (ARG OFF + 12*4)(sp);
#define SET ARG13( rD )                    stw rD, (ARG OFF + 13*4)(sp);
#define SET ARG14( rD )                    stw rD, (ARG OFF + 14*4)(sp);
#define SET ARG15( rD )                    stw rD, (ARG OFF + 15*4)(sp);
#define SET_ARG16( rD )                    stw rD, (ARG OFF + 16*4)(sp);
```

15

```
       salppc.inc                                           3/9/2001

       #define SET_ARG17( rD )                  stw rD, (ARG_OFF + 17*4)(sp);

       /*
        *   macro to branch from one entry point to another
        */

       #define BR_FUNC( func_name ) \
          b func_name;

       /*
        *   macros to call functions
        */
       #define CALL_FUNC( func_name ) \
          bl func_name;

       #define CALL_0( func_name ) \
          CALL_FUNC( func_name )

       #define CALL_1( func_name, arg0 ) \
          CALL_FUNC( func_name )

       #define CALL_2( func_name, arg0, arg1 ) \
          CALL_FUNC( func_name )

       #define CALL_3( func_name, arg0, arg1, arg2 ) \
          CALL_FUNC( func_name )

       #define CALL_4( func_name, arg0, arg1, arg2, arg3 ) \
          CALL_FUNC( func_name )

       #define CALL_5( func_name, arg0, arg1, arg2, arg3, arg4 ) \
          CALL_FUNC( func_name )

       #define CALL_6( func_name, arg0, arg1, arg2, arg3, arg4, arg5 ) \
          CALL_FUNC( func_name )

       #define CALL_7( func_name, arg0, arg1, arg2, arg3, arg4, arg5, arg6 ) \
          CALL_FUNC( func_name )

       #define CALL_8( func_name, arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7 ) \
          CALL_FUNC( func_name )

       #define CALL_9( func_name, arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
                       arg8 ) \
          CALL_FUNC( func_name )

       #define CALL_10( func_name, arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
                        arg8, arg9 ) \
          CALL_FUNC( func_name )

       #define CALL_11( func_name, arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
                        arg8, arg9, arg10 ) \
          CALL_FUNC( func_name )

       #define CALL_12( func_name, arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
                        arg8, arg9, arg10, arg11 ) \
          CALL_FUNC( func_name )

       #define CALL_13( func_name, arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
                        arg8, arg9, arg10, arg11, arg12 ) \
          CALL_FUNC( func_name )

       #define CALL_14( func_name, arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
                        arg8, arg9, arg10, arg11, arg12, arg13 ) \
          CALL_FUNC( func_name )

       #define CALL_15( func_name, arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
```

16

```
                        arg8, arg9, arg10, arg11, arg12, arg13, arg14 ) \
        CALL_FUNC( func_name )

#define CALL_16( func name, arg0, arg1, arg2, arg3, arg4, arg5, arg6, arg7, \
                        arg8, arg9, arg10, arg11, arg12, arg13, arg14, arg15 ) \
        CALL_FUNC( func_name )

#if defined( BUILD MAX )
#if defined( COMPILE_ESAL_JUMP_TABLE )

/*
 *  G4 macros to create an ESAL jump table for 1, 2, 3 and 4 vector
 *  algorithms. The table name is <root_name>_jump and is made a
 *  local symbol. (not supported in C)
 */
#define DECLARE VMX_V1( root_name ) \
.section .rodata; \
.align 5; \
CONCAT( root name,  jump ): \
.long   CONCAT( root name,  n ); \
.long   CONCAT( root_name, _c );

#define DECLARE VMX_V2( root_name ) \
.section .rodata; \
.align 5; \
CONCAT( root name,  jump ): \
.long   CONCAT( root name,  nn ); \
.long   CONCAT( root name,  nc ); \
.long   CONCAT( root name,  cn ); \
.long   CONCAT( root_name, _cc );

#define DECLARE VMX_V3( root_name ) \
.section .rodata; \
.align 5; \
CONCAT( root name,  jump ): \
.long   CONCAT( root name,  nnn ); \
.long   CONCAT( root name,  nnc ); \
.long   CONCAT( root name,  ncn ); \
.long   CONCAT( root name,  ncc ); \
.long   CONCAT( root name,  cnn ); \
.long   CONCAT( root name,  cnc ); \
.long   CONCAT( root name,  ccn ); \
.long   CONCAT( root_name, _ccc );

#define DECLARE VMX_V4( root_name ) \
.section .rodata; \
.align 5; \
CONCAT( root name,  jump ): \
.long   CONCAT( root name,  nnnn ); \
.long   CONCAT( root name,  nnnc ); \
.long   CONCAT( root name,  nncn ); \
.long   CONCAT( root name,  nncc ); \
.long   CONCAT( root name,  ncnn ); \
.long   CONCAT( root name,  ncnc ); \
.long   CONCAT( root name,  nccn ); \
.long   CONCAT( root name,  nccc ); \
.long   CONCAT( root name,  cnnn ); \
.long   CONCAT( root name,  cnnc ); \
.long   CONCAT( root name,  cncn ); \
.long   CONCAT( root name,  cncc ); \
.long   CONCAT( root name,  ccnn ); \
.long   CONCAT( root name,  ccnc ); \
.long   CONCAT( root name,  cccn ); \
.long   CONCAT( root_name, _cccc );

#define DECLARE VMX_V5( root_name ) \
.section .rodata; \
```

17

```
.align 5; \
CONCAT( root_name,  jump ): \
.long  CONCAT( root_name,  nnnnn ); \
.long  CONCAT( root_name,  nnnnc ); \
.long  CONCAT( root_name,  nnncn ); \
.long  CONCAT( root_name,  nnncc ); \
.long  CONCAT( root_name,  nncnn ); \
.long  CONCAT( root_name,  nncnc ); \
.long  CONCAT( root_name,  nnccn ); \
.long  CONCAT( root_name,  nnccc ); \
.long  CONCAT( root_name,  ncnnn ); \
.long  CONCAT( root_name,  ncnnc ); \
.long  CONCAT( root_name,  ncncn ); \
.long  CONCAT( root_name,  ncncc ); \
.long  CONCAT( root_name,  nccnn ); \
.long  CONCAT( root_name,  nccnc ); \
.long  CONCAT( root_name,  ncccn ); \
.long  CONCAT( root_name,  ncccc ); \
.long  CONCAT( root_name,  cnnnn ); \
.long  CONCAT( root_name,  cnnnc ); \
.long  CONCAT( root_name,  cnncn ); \
.long  CONCAT( root_name,  cnncc ); \
.long  CONCAT( root_name,  cncnn ); \
.long  CONCAT( root_name,  cncnc ); \
.long  CONCAT( root_name,  cnccn ); \
.long  CONCAT( root_name,  cnccc ); \
.long  CONCAT( root_name,  ccnnn ); \
.long  CONCAT( root_name,  ccnnc ); \
.long  CONCAT( root_name,  ccncn ); \
.long  CONCAT( root_name,  ccncc ); \
.long  CONCAT( root_name,  cccnn ); \
.long  CONCAT( root_name,  cccnc ); \
.long  CONCAT( root_name,  ccccn ); \
.long  CONCAT( root_name,  _ccccc );

#define DECLARE_VMX_Z1( root_name )   DECLARE_VMX_V1( root_name )
#define DECLARE_VMX_Z2( root_name )   DECLARE_VMX_V2( root_name )
#define DECLARE_VMX_Z3( root_name )   DECLARE_VMX_V3( root_name )
#define DECLARE_VMX_Z4( root_name )   DECLARE_VMX_V4( root_name )
#define DECLARE_VMX_Z5( root_name )   DECLARE_VMX_V5( root_name )

/*
 *  G4 macros to branch through the <root name> jump table based on
 *  the value of the ESAL flag. (not supported in C)
 *  (uses r0 as scratch and destroys eflag)
 *  (not supported in C)
 */
#define BR_ESAL_JUMP_TABLE_COMMON( root_name, rtemp ) \
    addis rtemp, 0, CONCAT( root_name,  jump@ha ); \
    addi rtemp, rtemp, CONCAT( root_name, _jump@l ); \
    lwzx rtemp, rtemp, r0; \
    mtctr rtemp; \
    bctr;

#define BR_VMX_V1( root_name, eflag, rtemp ) \
    rlwinm r0, eflag, 2, 29, 29; \
    BR_ESAL_JUMP_TABLE_COMMON( root_name, rtemp )

#define BR_VMX_V2( root_name, eflag, rtemp ) \
    rlwinm r0, eflag, 2, 28, 29; \
    BR_ESAL_JUMP_TABLE_COMMON( root_name, rtemp )

#define BR_VMX_V3( root_name, eflag, rtemp ) \
    rlwinm r0, eflag, 2, 27, 29; \
    BR_ESAL_JUMP_TABLE_COMMON( root_name, rtemp )

#define BR_VMX_V4( root_name, eflag, rtemp ) \
```

18

```
    rlwinm r0, eflag, 2, 26, 29; \
    BR_ESAL_JUMP_TABLE_COMMON( root_name, rtemp )

#define BR_VMX_V5( root_name, eflag, rtemp ) \
    rlwinm r0, eflag, 2, 25, 29; \
    BR_ESAL_JUMP_TABLE_COMMON( root_name, rtemp )

#define BR_VMX_Z1( root_name, eflag, rtemp ) \
        BR_VMX_V1( root_name, eflag, rtemp )

#define BR_VMX_Z2( root_name, eflag, rtemp ) \
        BR_VMX_V2( root_name, eflag, rtemp )

#define BR_VMX_Z3( root_name, eflag, rtemp ) \
        BR_VMX_V3( root_name, eflag, rtemp )

#define BR_VMX_Z4( root_name, eflag, rtemp ) \
        BR_VMX_V4( root_name, eflag, rtemp )

#define BR_VMX_Z5( root_name, eflag, rtemp ) \
        BR_VMX_V5( root_name, eflag, rtemp )

#else                                        /* no ESAL jump table */

/*
 *  G4 macros to create a dummy jump table.
 *  (not supported in C)
 */
#define DECLARE_VMX_V1( root_name )
#define DECLARE_VMX_V2( root_name )
#define DECLARE_VMX_V3( root_name )
#define DECLARE_VMX_V4( root_name )
#define DECLARE_VMX_V5( root_name )

#define DECLARE_VMX_Z1( root_name )
#define DECLARE_VMX_Z2( root_name )
#define DECLARE_VMX_Z3( root_name )
#define DECLARE_VMX_Z4( root_name )
#define DECLARE_VMX_Z5( root_name )

/*
 *  G4 macros to simply branch to root_name (no jump table)
 *  (not supported in C)
 */
#define BR_VMX_V1( root_name, eflag, rtemp ) \
    b root_name;

#define BR_VMX_V2( root_name, eflag , rtemp ) \
    b root_name;

#define BR_VMX_V3( root_name, eflag , rtemp ) \
    b root_name;

#define BR_VMX_V4( root_name, eflag , rtemp ) \
    b root_name;

#define BR_VMX_V5( root_name, eflag , rtemp ) \
    b root_name;

#define BR_VMX_Z1( root_name, eflag, rtemp ) \
        BR_VMX_V1( root_name, eflag, rtemp )

#define BR_VMX_Z2( root_name, eflag, rtemp ) \
        BR_VMX_V2( root_name, eflag, rtemp )

#define BR_VMX_Z3( root_name, eflag, rtemp ) \
        BR_VMX_V3( root_name, eflag, rtemp )
```

19

```
        #define BR VMX Z4( root name, eflag, rtemp ) \
                BR_VMX_V4( root_name, eflag, rtemp )

        #define BR VMX Z5( root name, eflag, rtemp ) \
                BR_VMX_V5( root_name, eflag, rtemp )

        #endif                                  /* end COMPILE_ESAL_JUMP_TABLE */

        /*
         *   G4 macros to decide whether to enter a VMX loop
         *   VMX loop is entered if at least minimum count,
         *   all vectors have the same relative alignment
         *   (i.e., same lower 4 bits) and all strides are unit.
         *   Note, a unit s imm argument is provided because some
         *   packed interleaved complex functions (stride 2) such
         *   as cvaddx() can be implemented with a VMX loop.
         *   Only one macro should be invoked per source file.
         *   (uses r0 as scratch)
         *   (not supported in C)
         */
        #define BR IF VMX V1( root_name, min_n_imm, unit_s_imm, p1, s1, n, eflag ) \
            cmplwi n, min n_imm; \
            blt v_skip vmx; \
            cmpwi s1, unit s imm; \
            bne v skip_vmx; \
            BR VMX V1( root_name, eflag, s1 ) \
        v_skip_vmx:

        #define BR_IF_VMX_V1_ALIGNED( root name, min n_imm, unit_s_imm, \
                                      p1, s1, n, eflag ) \
            cmplwi n, min n_imm; \
            blt v_skip vmx; \
            cmpwi s1, unit s imm; \
            bne v_skip vmx; \
            andi. r0, p1, 0xf; \
            bne v skip_vmx; \
            BR VMX V1( root_name, eflag, s1 ) \
        v_skip_vmx:

        #define BR_IF_VMX_V2( root name, min n imm, unit_s_imm, \
                             p1, s1, p2, s2, n, eflag ) \
            cmplwi n, min n_imm; \
            blt v_skip vmx; \
            cmpwi s1, unit s imm; \
            bne v_skip vmx; \
            cmpwi s2, unit s imm; \
            xor r0, p1, p2; \
            bne v_skip vmx; \
            andi. r0, r0, 0xf; \
            bne v skip_vmx; \
            BR VMX V2( root_name, eflag, s1 ) \
        v_skip_vmx:

        #define BR_IF_VMX_V2_LS( root name, min n imm, unit_s_imm, \
                                p1, s1, ps, s2, n, eflag ) \
            cmplwi n, min n_imm; \
            blt v_skip vmx; \
            cmpwi s1, unit s imm; \
            srwi r0, p1, 1; \
            bne v_skip vmx; \
            cmpwi s2, unit s imm; \
            xor r0, r0, ps; \
            bne v_skip vmx; \
            andi. r0, r0, 0x6; \
            bne v skip_vmx; \
            BR_VMX_V2( root_name, eflag, s1 ) \
```

20

```
      v_skip_vmx:

      #define BR_IF_VMX_V2_LC( root name, min_n imm, unit_s_imm, \
                              pl, sl, pc, n, eflag ) \
          cmplwi n, min n_imm; \
          blt v_skip vmx; \
          andi. r0, pc, 1; \
          bne v_skip vmx; \
          cmpwi sl, unit s imm; \
          srwi r0, pl, 2; \
          bne v skip vmx; \
          xor r0, r0, pc; \
          andi. r0, r0, 0x3; \
          bne v skip_vmx; \
          BR VMX V2( root_name, eflag, sl ) \
      v_skip_vmx:

      #define BR_IF_VMX_V2_ALIGNED( root name, min n imm, unit_s_imm, \
                                    pl, sl, p2, s2, n, eflag ) \
          cmplwi n, min n_imm; \
          blt v_skip vmx; \
          cmpwi sl, unit s imm; \
          bne v_skip vmx; \
          cmpwi s2, unit_s_imm; \
          or r0, pl, p2; \
          bne v_skip vmx; \
          andi. r0, r0, 0xf; \
          bne v skip_vmx; \
          BR VMX V2( root_name, eflag, sl ) \
      v_skip_vmx:

      #define BR_IF_VMX_V3( root name, min n imm, unit_s imm, \
                           pl, sl, p2, s2, p3, s3, n, eflag ) \
          cmplwi n, min n_imm; \
          blt v_skip vmx; \
          cmpwi sl, unit s imm; \
          bne v_skip vmx; \
          cmpwi s2, unit s imm; \
          bne v_skip vmx; \
          cmpwi s3, unit s imm; \
          xor r0, pl, p2; \
          bne v_skip vmx; \
          andi. r0, r0, 0xf; \
          xor r0, pl, p3; \
          bne v_skip vmx; \
          andi. r0, r0, 0xf; \
          bne v skip_vmx; \
          BR VMX V3( root_name, eflag, sl ) \
      v_skip_vmx:

      #define BR_IF_VMX_V3_ALIGNED( root name, min n imm, unit_s imm, \
                                    pl, sl, p2, s2, p3, s3, n, eflag ) \
          cmplwi n, min n_imm; \
          blt v_skip vmx; \
          cmpwi sl, unit s imm; \
          bne v_skip vmx; \
          cmpwi s2, unit s imm; \
          bne v_skip vmx; \
          cmpwi s3, unit_s_imm; \
          or r0, pl, p2; \
          bne v_skip vmx; \
          andi. r0, r0, 0xf; \
          or r0, pl, p3; \
          bne v_skip vmx; \
          andi. r0, r0, 0xf; \
          bne v skip_vmx; \
          BR_VMX_V3( root_name, eflag, sl ) \
```

21

salppc.inc

```
v_skip_vmx:

#define BR_IF_VMX_V4( root name, min n imm, unit s imm, \
                      p1, s1, p2, s2, p3, s3, p4, s4, n, eflag ) \
   cmplwi n, min n_imm; \
   blt v_skip vmx; \
   cmpwi s1, unit s imm; \
   bne v_skip vmx; \
   cmpwi s2, unit s imm; \
   bne v_skip vmx; \
   cmpwi s3, unit s imm; \
   bne v_skip vmx; \
   cmpwi s4, unit s imm; \
   xor r0, p1, p2; \
   bne v_skip vmx; \
   andi. r0, r0, 0xf; \
   xor r0, p1, p3; \
   bne v_skip vmx; \
   andi. r0, r0, 0xf; \
   xor r0, p1, p4; \
   bne v_skip vmx; \
   andi. r0, r0, 0xf; \
   bne v skip_vmx; \
   BR VMX V4( root_name, eflag, s1 ) \
v_skip_vmx:

#define BR_IF_VMX_V4_ALIGNED( root name, min n imm, unit s imm, \
                              p1, s1, p2, s2, p3, s3, p4, s4, n, eflag ) \
   cmplwi n, min n_imm; \
   blt v_skip vmx; \
   cmpwi s1, unit s imm; \
   bne v_skip vmx; \
   cmpwi s2, unit s imm; \
   bne v_skip vmx; \
   cmpwi s3, unit s imm; \
   bne v_skip vmx; \
   cmpwi s4, unit_s_imm; \
   or r0, p1, p2; \
   bne v_skip vmx; \
   andi. r0, r0, 0xf; \
   or r0, p1, p3; \
   bne v_skip vmx; \
   andi. r0, r0, 0xf; \
   or r0, p1, p4; \
   bne v_skip vmx; \
   andi. r0, r0, 0xf; \
   bne v skip_vmx; \
   BR VMX V4( root_name, eflag, s1 ) \
v_skip_vmx:

#define BR_IF_VMX_V5( root name, min n imm, unit s imm, \
                      p1, s1, p2, s2, p3, s3, p4, s4, p5, s5, n, eflag ) \
   cmplwi n, min n_imm; \
   blt v_skip vmx; \
   cmpwi s1, unit s imm; \
   bne v_skip vmx; \
   cmpwi s2, unit s imm; \
   bne v_skip vmx; \
   cmpwi s3, unit s imm; \
   bne v_skip vmx; \
   cmpwi s4, unit s imm; \
   bne v_skip vmx; \
   cmpwi s5, unit s imm; \
   xor r0, p1, p2; \
   bne v_skip vmx; \
   andi. r0, r0, 0xf; \
   xor r0, p1, p3; \
```

22

salppc.inc   3/9/2001

```
        bne v_skip vmx; \
        andi. r0, r0, 0xf; \
        xor r0, p1, p4; \
        bne v_skip vmx; \
        andi. r0, r0, 0xf; \
        xor r0, p1, p5; \
        bne v_skip vmx; \
        andi. r0, r0, 0xf; \
        bne v skip_vmx; \
        BR VMX V5( root_name, eflag, s1 ) \
    v_skip_vmx:

    #define BR_IF_VMX_V5_ALIGNED( root_name, min n_imm, unit s_imm, \
                        p1, s1, p2, s2, p3, s3, p4, s4, p5, s5, n, eflag ) \
                        \
        cmplwi n, min n_imm; \
        blt v_skip vmx; \
        cmpwi s1, unit s imm; \
        bne v_skip vmx; \
        cmpwi s2, unit s imm; \
        bne v_skip vmx; \
        cmpwi s3, unit s imm; \
        bne v_skip vmx; \
        cmpwi s4, unit s imm; \
        bne v_skip vmx; \
        cmpwi s5, unit_s_imm; \
        or r0, p1, p2; \
        bne v_skip vmx; \
        andi. r0, r0, 0xf; \
        or r0, p1, p3; \
        bne v_skip vmx; \
        andi. r0, r0, 0xf; \
        or r0, p1, p4; \
        bne v_skip vmx; \
        andi. r0, r0, 0xf; \
        or r0, p1, p5; \
        bne v_skip vmx; \
        andi. r0, r0, 0xf; \
        bne v skip_vmx; \
        BR VMX V5( root_name, eflag, s1 ) \
    v_skip_vmx:

    #define BR_IF_VMX_Z1( root_name, min n_imm, unit_s_imm, \
                        pr1, pi1, s1, n, eflag ) \
        cmplwi n, min n_imm; \
        blt z_skip vmx; \
        cmpwi s1, unit s imm; \
        xor r0, pr1, pi2; \
        bne z_skip vmx; \
        andi. r0, r0, 0xf; \
        bne z skip_vmx; \
        BR VMX Z1( root_name, eflag, s1 ) \
    z_skip_vmx:

    #define BR_IF_VMX_Z2( root_name, min n imm, unit s imm, \
                        pr1, pi1, s1, pr2, pi2, s2, n, eflag ) \
        cmplwi n, min n_imm; \
        blt z_skip vmx; \
        cmpwi s1, unit s imm; \
        bne z_skip vmx; \
        cmpwi s2, unit s imm; \
        xor r0, pr1, pi1; \
        bne z_skip vmx; \
        andi. r0, r0, 0xf; \
        xor r0, pr1, pr2; \
        bne z_skip vmx; \
        andi. r0, r0, 0xf; \
```

23

```
          salppc.inc                                        3/9/2001

          xor r0, pr1, pi2; \
          bne z_skip vmx; \
          andi. r0, r0, 0xf; \
          bne z skip_vmx; \
          BR VMX Z2( root_name, eflag, s1 ) \
    z_skip_vmx:

    #define BR_IF_VMX_Z3( root_name, min n imm, unit s imm, \
                         pr1, pi1, s1, pr2, pi2, s2, pr3, pi3, s3, n, eflag ) \
          cmplwi n, min n_imm; \
          blt z_skip vmx; \
          cmpwi s1, unit s imm; \
          bne z_skip vmx; \
          cmpwi s2, unit s imm; \
          bne z_skip vmx; \
          cmpwi s3, unit s imm; \
          xor r0, pr1, pi1; \
          bne z_skip vmx; \
          andi. r0, r0, 0xf; \
          xor r0, pr1, pr2; \
          bne z_skip vmx; \
          andi. r0, r0, 0xf; \
          xor r0, pr1, pi2; \
          bne z_skip vmx; \
          andi. r0, r0, 0xf; \
          xor r0, pr1, pr3; \
          bne z_skip vmx; \
          andi. r0, r0, 0xf; \
          xor r0, pr1, pi3; \
          bne z_skip vmx; \
          andi. r0, r0, 0xf; \
          bne z skip_vmx; \
          BR VMX Z3( root_name, eflag, s1 ) \
    z_skip_vmx:

    #define BR_IF_VMX_Z4( root_name, min n imm, unit s imm, \
                         pr1, pi1, s1, pr2, pi2, s2, pr3, pi3, s3, \
                         pr4, pi4, s4, n, eflag ) \
          cmplwi n, min n_imm; \
          blt z_skip vmx; \
          cmpwi s1, unit s imm; \
          bne z_skip vmx; \
          cmpwi s2, unit s imm; \
          bne z_skip vmx; \
          cmpwi s3, unit s imm; \
          bne z_skip vmx; \
          cmpwi s4, unit s imm; \
          xor r0, pr1, pi1; \
          bne z_skip vmx; \
          andi. r0, r0, 0xf; \
          xor r0, pr1, pr2; \
          bne z_skip vmx; \
          andi. r0, r0, 0xf; \
          xor r0, pr1, pi2; \
          bne z_skip vmx; \
          andi. r0, r0, 0xf; \
          xor r0, pr1, pr3; \
          bne z_skip vmx; \
          andi. r0, r0, 0xf; \
          xor r0, pr1, pi3; \
          bne z_skip vmx; \
          andi. r0, r0, 0xf; \
          xor r0, pr1, pr4; \
          bne z_skip vmx; \
          andi. r0, r0, 0xf; \
          xor r0, pr1, pi4; \
          bne z_skip_vmx; \
```

24

```
        andi. r0, r0, 0xf; \
        bne z skip_vmx; \
        BR VMX Z4( root_name, eflag, s1 ) \
    z_skip_vmx:

    #define BR_IF_VMX_Z5( root_name, min n imm, unit s imm, \
                          pr1, pi1, s1, pr2, pi2, s2, pr3, pi3, s3, \
                          pr4, pi4, s4, pr5, pi5, s5, n, eflag ) \
        cmplwi n, min n_imm; \
        blt z_skip vmx; \
        cmpwi s1, unit s imm; \
        bne z_skip vmx; \
        cmpwi s2, unit s imm; \
        bne z_skip vmx; \
        cmpwi s3, unit s imm; \
        bne z_skip vmx; \
        cmpwi s4, unit s imm; \
        bne z_skip vmx; \
        cmpwi s5, unit s imm; \
        xor r0, pr1, pi1; \
        bne z_skip vmx; \
        andi. r0, r0, 0xf; \
        xor r0, pr1, pr2; \
        bne z_skip vmx; \
        andi. r0, r0, 0xf; \
        xor r0, pr1, pi2; \
        bne z_skip vmx; \
        andi. r0, r0, 0xf; \
        xor r0, pr1, pr3; \
        bne z_skip vmx; \
        andi. r0, r0, 0xf; \
        xor r0, pr1, pi3; \
        bne z_skip vmx; \
        andi. r0, r0, 0xf; \
        xor r0, pr1, pr4; \
        bne z_skip vmx; \
        andi. r0, r0, 0xf; \
        xor r0, pr1, pi4; \
        bne z_skip vmx; \
        andi. r0, r0, 0xf; \
        xor r0, pr1, pr5; \
        bne z_skip vmx; \
        andi. r0, r0, 0xf; \
        xor r0, pr1, pi5; \
        bne z_skip vmx; \
        andi. r0, r0, 0xf; \
        bne z skip_vmx; \
        BR VMX Z5( root_name, eflag, s1 ) \
    z_skip_vmx:

    #define BR_IF_VMX_CONV( root name, min n imm, \
                          p1, s1, s2, p3, s3, n, eflag ) \
        cmplwi n, min n_imm; \
        blt v_skip vmx; \
        cmpwi s1, 1; \
        bne v_skip vmx; \
        cmpwi s2, 1; \
        beq PC OFFSET( 12 ); \
        cmpwi s2, -1; \
        bne v_skip vmx; \
        cmpwi s3, 1; \
        xor r0, p1, p3; \
        bne v_skip vmx; \
        andi. r0, r0, 0xf; \
        bne v skip_vmx; \
        BR VMX V3( root_name, eflag, s1 ) \
    v_skip_vmx:
```

25

```
#define BR_IF_VMX_ZCONV( root_name, min n imm, \
                         pr1, pi1, s1, s2, pr3, pi3, s3, n, eflag ) \
    cmplwi n, min n_imm; \
    blt z_skip vmx; \
    cmpwi s1, 1; \
    bne z_skip vmx; \
    cmpwi s2, 1; \
    beq PC OFFSET( 12 ); \
    cmpwi s2, -1; \
    bne v_skip vmx; \
    cmpwi s3, 1; \
    xor r0, pr1, pi1; \
    bne z_skip vmx; \
    andi. r0, r0, 0xf; \
    xor r0, pr1, pr3; \
    bne z_skip vmx; \
    andi. r0, r0, 0xf; \
    xor r0, pr1, pi3; \
    bne z_skip vmx; \
    andi. r0, r0, 0xf; \
    bne z skip_vmx; \
    BR VMX Z3( root_name, eflag, s1 ) \
z_skip_vmx:

/*
 * G4 macro to get VMX unaligned word (FP) count
 * assumes that the last 2 bits of ptr are 0
 * sets condition code CR0
 */
#define GET VMX UNALIGNED_COUNT( count, ptr ) \
    neg count, ptr; \
    rlwinm. count, count, 30, 30, 31;

/*
 * G4 macro to get VMX unaligned short count
 * assumes that the last bit of ptr is 0
 * sets condition code CR0
 */
#define GET VMX UNALIGNED_COUNT_S( count, ptr ) \
    neg count, ptr; \
    rlwinm. count, count, 31, 29, 31;

/*
 * G4 macro to get VMX unaligned char count
 * sets condition code CR0
 */
#define GET VMX UNALIGNED_COUNT_C( count, ptr ) \
    neg count, ptr; \
    rlwinm. count, count, 0, 28, 31;

/*
 * G4 macro to load and splat an FP scalar independent of alignment
 */

#if defined( LITTLE ENDIAN )
#define SCALAR_SPLAT( vt, vtmp, scalarp ) \
    lvxl vt, 0, scalarp; \
    lvsr vtmp, 0, scalarp; \
    vperm vt, vt, vt, vtmp; \
    vspltw vt, vt, 3;
#else
#define SCALAR_SPLAT( vt, vtmp, scalarp ) \
    lvxl vt, 0, scalarp; \
    lvsl vtmp, 0, scalarp; \
    vperm vt, vt, vt, vtmp; \
    vspltw vt, vt, 0;
```

26

salppc.inc   3/9/2001

```
#endif

/*
 * G4 macro to construct an FP absolute value mask that can be used with
 * vand to take the absolute value of 4 FP numbers in a vector register
 * vt = 0x7fffffff7fffffff7fffffff7fffffff
 */
#define MAKE_VABS_MASK( vt ) \
  vspltisw vt, -1; \
  vslw vt, vt, vt; \
  vnor vt, vt, vt;

/*
 * G4 macro to construct an FP sign mask that can be used with:
 *      vandc to take the absolute value of
 *      vor to take the negative absolute value of
 *      vxor to negate
 * 4 FP numbers in a vector register
 * vt = 0x80000000800000008000000080000000
 */
#define MAKE_VSIGN_MASK( vt ) \
  vspltisw vt, -1; \
  vslw vt, vt, vt;

/*
 *   G4 macros to construct a coded touch stream control register
 *      "I" indicates argument is passed as an immediate value
 *      "R" indicates argument is passed in an integer register
 *
 *      bytes_per_block = # of bytes in each block
 *          (0 = 512, 16, 32, ..., 480, 512)
 *      block_count = # of blocks (0 = 256, 1, 2, 3, ... 256)
 *      byte_stride = signed byte stride between start of adjacent blocks
 *          (-32768 <= byte_stride < 0; 0 = 32768; 0 < byte_stride < 32768)
 */
#define MAKE_STREAM_CODE_III( rB, bytes_per_block, block_count, byte_stride ) \
  lis rB, ((((bytes_per_block) >> 4) & 31) << 8) | ((block_count) & 255); \
  ori rB, rB, ((byte_stride) & 0x0000ffff);

#define MAKE_STREAM_CODE( rB, bytes_per_block, block_count, byte_stride ) \
        MAKE_STREAM_CODE_III( rB, bytes_per_block, block_count, byte_stride )

#define MAKE_STREAM_CODE_IIR( rB, bytes_per_block, block_count, byte_stride ) \
  lis rB, ((((bytes_per_block) >> 4) & 31) << 8) | ((block_count) & 255); \
  rlwimi rB, byte_stride, 0, 16, 31;

#define MAKE_STREAM_CODE_IRI( rB, bytes_per_block, block_count, byte_stride ) \
  rlwinm rB, block_count, 16, 8, 15; \
  oris rB, rB, ((((bytes_per_block) >> 4) & 31) << 8); \
  ori rB, rB, ((byte_stride) & 0x0000ffff);

#define MAKE_STREAM_CODE_IRR( rB, bytes_per_block, block_count, byte_stride ) \
  rlwinm rB, block_count, 16, 8, 15; \
  oris rB, rB, ((((bytes_per_block) >> 4) & 31) << 8); \
  rlwimi rB, byte_stride, 0, 16, 31;

#define MAKE_STREAM_CODE_RII( rB, bytes_per_block, block_count, byte_stride ) \
  rlwinm rB, bytes_per_block, 20, 3, 7; \
  oris rB, rB, ((block_count) & 255); \
  ori rB, rB, ((byte_stride) & 0x0000ffff);

#define MAKE_STREAM_CODE_RIR( rB, bytes_per_block, block_count, byte_stride )
```

27

```
\
  rlwinm rB, bytes per block, 20, 3, 7; \
  oris rB, rB, ((block count) & 255); \
  rlwimi rB, byte_stride, 0, 16, 31;

#define MAKE_STREAM_CODE_RRI( rB, bytes_per_block, block_count, byte_stride )
\
  rlwinm rB, bytes per block, 20, 3, 7; \
  rlwimi rB, block count, 16, 8, 15; \
  ori rB, rB, ((byte_stride) & 0x0000ffff);

#define MAKE_STREAM_CODE_RRR( rB, bytes_per_block, block_count, byte_stride )
\
  rlwinm rB, bytes per block, 20, 3, 7; \
  rlwimi rB, block count, 16, 8, 15; \
  rlwimi rB, byte_stride, 0, 16, 31;

#endif                                  /* end BUILD_MAX */

#define CACHE TB THRESHOLD  1           /* 2 TB ticks = 12 CPU 100 MHz clks */
#define INSTRUCTION CACHE COUNT  3      /* min. to fully cache instructions */
#define POSTING_BUFFER_COUNT  10        /* min. to fill posting buffer      */

/*
 *  macros to set DCBx conditions explicitly
 */
#define DCBT TRUE( cond_bit, scratch ) \
    li scratch, 0; \
    cmplwi (cond_bit), scratch, 1;

#define DCBZ TRUE( cond_bit, scratch ) \
    DCBT_TRUE( cond_bit, scratch )

#define DCBT FALSE( cond_bit, scratch ) \
    li scratch, 2; \
    cmplwi (cond_bit), scratch, 1;

#define DCBZ FALSE( cond_bit, scratch ) \
    DCBT_FALSE( cond_bit, scratch )

/*
 * This macro will cause a file not to assemble.
 */
#define DO_NOT_ASSEMBLE   add scratch1, scratch2, 256;

/*
 *  Obsolete macro will cause assembler error
 */
#define TEST IF CACHABLE( cond_bit, buffer, scratch1, scratch2 ) \
      DO_NOT_ASSEMBLE
/*
 *  Obsolete macro will cause assembler error
 */

#define TEST IF CACHABLE_ALIGN( cond_bit, buffer, scratch1, scratch2 ) \
      DO_NOT_ASSEMBLE
/*
 *  macros to test if a DCBT or DCBZ instruction should be performed on
 *  a particular buffer based on a bit test (cache bit) on a specified
 *  ESAL flag.
 */

#define TEST_IF_DCBT( cond_bit, cache_bit, eflag, bufer, scratch1, scratch2 )
\
      DO_NOT_ASSEMBLE

#define SET_DCBT_COND( cond_bit, cache_bit, eflag, scratch1 ) \
```

28

salppc.inc   3/9/2001

```
                andi. scratch1, eflag, (cache bit); \
                cmplwi (cond_bit), scratch1, 0;

        /*
         * Set 2 dcbt conditions and ensure only one is true
         *
         *    Ins. 1-3   Set both conditions to "No DCBT"
         *    Ins. 4     See if vec1 has a C
         *    Ins. 5     Set DCBT cond1
         *    Ins. 6     Branch if "DCBT TRUE" (eflag & bit1 = 0)
         *    Ins. 7-8   Set DCBT cond2
         */
        #define SET_2_DCBT_COND( cond1 bit, cache_bit1, cond2_bit, cache_bit2, \
                                 eflag, scratch ) \
                li scratch, 2; \
                cmplwi (cond1 bit), scratch, 1; \
                cmplwi (cond2 bit), scratch, 1; \
                andi. scratch, eflag, (cache_bit1); \
                cmplwi (cond1 bit), scratch, 0; \
                bc 12, ((cond1_bit)<<2)+2, PC OFFSET( 12 ); \
                andi. scratch, eflag, (cache_bit2); \
                cmplwi (cond2_bit), scratch, 0;

        /*
         * Set 3 dcbt conditions and ensure only one is true
         *
         * Logic is the similar to SET_2_DCBT_COND() macro
         */
        #define SET_3_DCBT_COND( cond1 bit, cache bit1, cond2 bit, cache_bit2, \
                                 cond3_bit, cache_bit3, eflag, scratch ) \
                li scratch, 2; \
                cmplwi (cond1 bit), scratch, 1; \
                cmplwi (cond2 bit), scratch, 1; \
                cmplwi (cond3 bit), scratch, 1; \
                andi. scratch, eflag, (cache_bit3); \
                cmplwi (cond3 bit), scratch, 0; \
                bc 12, ((cond3_bit)<<2)+2, PC OFFSET( 24 ); \
                andi. scratch, eflag, (cache_bit2); \
                cmplwi (cond2 bit), scratch, 0; \
                bc 12, ((cond2_bit)<<2)+2, PC OFFSET( 12 ); \
                andi. scratch, eflag, (cache_bit1); \
                cmplwi (cond1_bit), scratch, 0;

        /*
         * Set 4 dcbt conditions and ensure only one is true
         *
         * Logic is the similar to SET_2_DCBT_COND() macro
         */
        #define SET_4_DCBT_COND( cond1 bit, cache bit1, cond2 bit, cache bit2, \
                                 cond3 bit, cache_bit3, cond4_bit, cache_bit4, \
                                 eflag, scratch ) \
                li scratch, 2; \
                cmplwi (cond1 bit), scratch, 1; \
                cmplwi (cond2 bit), scratch, 1; \
                cmplwi (cond3 bit), scratch, 1; \
                cmplwi (cond4 bit), scratch, 1; \
                andi. scratch, eflag, (cache_bit4); \
                cmplwi (cond4 bit), scratch, 0; \
                bc 12, ((cond4_bit)<<2)+2, PC OFFSET( 36 ); \
                andi. scratch, eflag, (cache_bit3); \
                cmplwi (cond3 bit), scratch, 0; \
                bc 12, ((cond3_bit)<<2)+2, PC OFFSET( 24 ); \
                andi. scratch, eflag, (cache_bit2); \
                cmplwi (cond2 bit), scratch, 0; \
                bc 12, ((cond2_bit)<<2)+2, PC OFFSET( 12 ); \
                andi. scratch, eflag, (cache_bit1); \
                cmplwi (cond1_bit), scratch, 0;
```

29

```
#if !defined COMPILE_NO_DCBZ

#define SET_DCBZ_COND( cond bit, cache bit, eflag, buffer, stride, \
                       unit stride, count, tmp1, tmp2, tmp3) \
    andi. tmp3, eflag, (cache bit); \
    cmplwi (cond bit), tmp3, 0; \
    bne PC_OFFSET( 104 ); \
    cmplwi 1, stride, unit stride; \
    bne 1, PC_OFFSET( 92 ); \
    cmplwi 1, count, (CACHE_LINE_LSIZE<<unit_stride); \
    blt 1, PC OFFSET( 84 ); \
    addi tmp2, buffer, CACHE LINE SIZE; \
    li tmp3, CACHE LINE ADDR_MASK; \
    and tmp2, tmp2, tmp3; \
    mfcr tmp3; \
    stw tmp3, CR_SAVE_OFF(sp); \
    mflr tmp3; \
    stw tmp3, LR SAVE OFF(sp); \
    CREATE STACK_FRAME( 0 ) \
    mr tmp1, r3; \
    mr r3, tmp2; \
    bl ppc buf is dcbz safe; \
    DESTROY STACK FRAME \
    lwz tmp3, LR_SAVE_OFF(sp); \
    mtlr tmp3; \
    lwz tmp3, CR_SAVE_OFF(sp); \
    mtcr tmp3; \
    li tmp2, 0; \
    cmplw 1, tmp2, r3; \
    mr r3, tmp1; \
    bne 1, PC OFFSET( 8 ); \
    cmpwi (cond_bit), count, -1;

#define SET_DCBZ_ALIGN_COND( cond bit, cache bit, eflag, buffer, stride, \
                             unit stride, count, tmp1, tmp2, tmp3) \
    andi. tmp3, eflag, (cache bit); \
    cmplwi (cond bit), tmp3, 0; \
    bne PC_OFFSET( 100 ); \
    cmplwi 1, stride, unit stride; \
    bne 1, PC_OFFSET( 88 ); \
    cmplwi 1, count, (CACHE_LINE_LSIZE<<unit_stride); \
    blt 1, PC OFFSET( 80 ); \
    andi. tmp3, buffer, CACHE_LINE_MASK; \
    bne PC OFFSET( 72 ); \
    mfcr tmp3; \
    stw tmp3, CR_SAVE_OFF(sp); \
    mflr tmp3; \
    stw tmp3, LR SAVE OFF(sp); \
    CREATE STACK_FRAME( 0 ) \
    mr tmp1, r3; \
    mr r3, buffer; \
    bl ppc buf is dcbz safe; \
    DESTROY STACK FRAME \
    lwz tmp3, LR_SAVE_OFF(sp); \
    mtlr tmp3; \
    lwz tmp3, CR_SAVE_OFF(sp); \
    mtcr tmp3; \
    li tmp2, 0; \
    cmplw 1, tmp2, r3; \
    mr r3, tmp1; \
    bne 1, PC OFFSET( 8 ); \
    cmpwi (cond_bit), count, -1;

#else /* COMPILE_NO_DCBZ is defined */

#define SET_DCBZ_COND( cond_bit, cache_bit, eflag, buffer, stride, \
```

30

```
                              unit stride, count, tmp1, tmp2, tmp3) \
        DCBZ_FALSE( cond_bit, tmp1 )

#define SET_DCBZ_ALIGN_COND( cond bit, cache bit, eflag, buffer, stride, \
                             unit_stride, count, tmp1, tmp2, tmp3) \
        DCBZ_FALSE( cond_bit, tmp1 )

#endif /* COMPILE_NO_DCBZ */

/*
 * macro to perform [or skip] a dcbt instruction based on the result
 * of a prior call to TEST IF DCBT (specifying the same condition bit).
 * dcbt is performed if the cond "<=" is true; otherwise dcbt is skipped.
 */
#define DCBT IF( cond bit, rA, rB ) \
        bc 12, ((cond_bit)<<2)+1, PC_OFFSET( 8 ); \
        dcbt rA, rB;

/*
 * macro to perform [or skip] a dcbz instruction based on the result
 * of a prior call to TEST IF DCBZ (specifying the same condition bit).
 * dcbz is performed if the cond "<=" is true; otherwise dcbz is skipped.
 */
#if !defined COMPILE_NO_DCBZ

#define DCBZ IF( cond bit, rA, rB ) \
        bc 12, ((cond_bit)<<2)+1, PC_OFFSET( 8 ); \
        dcbz rA, rB;

#else

#define DCBZ IF( cond bit, rA, rB ) \
        bc 12, ((cond_bit)<<2)+1, PC_OFFSET( 8 ); \
        nop;

#endif

/*
 * macro to branch to a label if the buffer specified in a prior
 * call to TEST_IF CACHABLE (also specifying the same condition bit)
 * was cachable (i.e. TB read time was <= CACHE_TB_THRESHOLD).
 */
#define BR IF COND TRUE( cond bit, label ) \
        bc 4, ((cond_bit)<<2)+1, label;                 /* <= */

/*
 * macro to branch to a label if the buffer specified in a prior
 * call to TEST IF CACHABLE (also specifying the same condition bit)
 * was NOT cachable (i.e. TB read time was > CACHE_TB_THRESHOLD).
 */
#define BR IF COND FALSE( cond bit, label ) \
        bc 12, ((cond_bit)<<2)+1, label;               /* > */

/*
 * ASIC macros
 */
#if defined( COMPILE_PREFETCH )

#define LOAD PREFETCH_CONTROL( mode, scratch1, scratch2 ) \
        li scratch1, mode; \
        addis scratch2, 0, PREFETCH CONTROL H; \
        stw scratch1, PREFETCH_CONTROL_L( scratch2 );

#define LOAD MISCON B( mode, scratch1, scratch2 ) \
        li scratch1, mode; \
        addis scratch2, 0, MISCON_B H; \
        stw scratch1, MISCON_B_L( scratch2 );
```

31

```
#define RESET PREFETCH CONTROL( scratch1, scratch2 ) \
    addis scratch2, 0, ASIC H; \
    lwz scratch1, MISCON B L( scratch2 ); \
    andi. scratch1, scratch1, PREFETCH MASK; \
    ori scratch1, scratch1, USE PREFETCH CONTROL; \
    stw scratch1, PREFETCH_CONTROL_L( scratch2 );

#else

#define LOAD PREFETCH CONTROL( mode, scratch1, scratch2 )
#define LOAD MISCON B( mode, scratch1, scratch2 )
#define RESET_PREFETCH_CONTROL( scratch1, scratch2 )

#endif

/*
 *   instruction macros
 */
#define ADD( rD, rA, rB )                add rD, rA, rB;
#define ADD C( rD, rA, rB )              add. rD, rA, rB;
#define ADDI( rD, rA, SIMM )             addi rD, rA, (SIMM);
#define ADDIC C( rD, rA, SIMM )          addic. rD, rA, (SIMM);
#define ADDIS( rD, rA, SIMM )            addis rD, rA, (SIMM);
#define AND( rA, rS, rB )                and rA, rS, rB;
#define AND C( rA, rS, rB )              and. rA, rS, rB;
#define ANDC( rA, rS, rB )               andc rA, rS, rB;
#define ANDC C( rA, rS, rB )             andc. rA, rS, rB;
#define ANDI C( rA, rS, UIMM )           andi. rA, rS, (UIMM);
#define ANDIS C( rA, rS, UIMM )          andis. rA, rS, (UIMM);
#define BA( label )                      ba label;
#define BCTR                             bctr;
#define BCTRL                            bctrl;
#define BEQ( label )                     beq label;
#define BEQ PLUS( label )                beq+ label;
#define BEQ MINUS( label )               beq- label;
#define BEQ CR( bit, label )             beq (bit), label;
#define BEQ CR PLUS( bit, label )        beq+ (bit), label;
#define BEQ CR_MINUS( bit, label )       beq- (bit), label;
#define BEQLR                            beqlr;
#define BEQLR PLUS                       beqlr+;
#define BEQLR MINUS                      beqlr-;
#define BEQLR CR( bit )                  beqlr (bit);
#define BEQLR CR PLUS( bit )             beqlr+ (bit);
#define BEQLR CR MINUS( bit )            beqlr- (bit);
#define BGE( label )                     bge label;
#define BGE PLUS( label )                bge+ label;
#define BGE MINUS( label )               bge- label;
#define BGE CR( bit, label )             bge (bit), label;
#define BGE CR PLUS( bit, label )        bge+ (bit), label;
#define BGE CR_MINUS( bit, label )       bge- (bit), label;
#define BGELR                            bgelr;
#define BGELR PLUS                       bgelr+;
#define BGELR MINUS                      bgelr-;
#define BGELR CR( bit )                  bgelr (bit);
#define BGELR CR PLUS( bit )             bgelr+ (bit);
#define BGELR CR MINUS( bit )            bgelr- (bit);
#define BGT( label )                     bgt label;
#define BGT PLUS( label )                bgt+ label;
#define BGT MINUS( label )               bgt- label;
#define BGT CR( bit, label )             bgt (bit), label;
#define BGT CR PLUS( bit, label )        bgt+ (bit), label;
#define BGT CR_MINUS( bit, label )       bgt- (bit), label;
#define BGTLR                            bgtlr;
#define BGTLR PLUS                       bgtlr+;
#define BGTLR MINUS                      bgtlr-;
#define BGTLR_CR( bit )                  bgtlr (bit);
```

32

```
#define BGTLR CR PLUS( bit )              bgtlr+ (bit);
#define BGTLR CR MINUS( bit )             bgtlr- (bit);
#define BL( label )                       bl label;
#define BLE( label )                      ble label;
#define BLE PLUS( label )                 ble+ label;
#define BLE MINUS( label )                ble- label;
#define BLE CR( bit, label )              ble (bit), label;
#define BLE CR PLUS( bit, label )         ble+ (bit), label;
#define BLE CR_MINUS( bit, label )        ble- (bit), label;
#define BLELR                             blelr;
#define BLELR PLUS                        blelr+;
#define BLELR MINUS                       blelr-;
#define BLELR CR( bit )                   blelr (bit);
#define BLELR CR PLUS( bit )              blelr+ (bit);
#define BLELR_CR_MINUS( bit )             blelr- (bit);
#define BLR                               blr;
#define BLRL                              blrl;
#define BLT( label )                      blt label;
#define BLT PLUS( label )                 blt+ label;
#define BLT MINUS( label )                blt- label;
#define BLT CR( bit, label )              blt (bit), label;
#define BLT CR PLUS( bit, label )         blt+ (bit), label;
#define BLT CR_MINUS( bit, label )        blt- (bit), label;
#define BLTLR                             bltlr;
#define BLTLR PLUS                        bltlr+;
#define BLTLR MINUS                       bltlr-;
#define BLTLR CR( bit )                   bltlr (bit);
#define BLTLR CR PLUS( bit )              bltlr+ (bit);
#define BLTLR CR MINUS( bit )             bltlr- (bit);
#define BNE( label )                      bne label;
#define BNE PLUS( label )                 bne+ label;
#define BNE MINUS( label )                bne- label;
#define BNE CR( bit, label )              bne (bit), label;
#define BNE CR PLUS( bit, label )         bne+ (bit), label;
#define BNE CR_MINUS( bit, label )        bne- (bit), label;
#define BNELR                             bnelr;
#define BNELR PLUS                        bnelr+;
#define BNELR MINUS                       bnelr-;
#define BNELR CR( bit )                   bnelr (bit);
#define BNELR CR PLUS( bit )              bnelr+ (bit);
#define BNELR CR MINUS( bit )             bnelr- (bit);
#define BR( label )                       b label;
#define CLRLWI( rA, rS, nbits )           clrlwi rA, rS, (nbits);
#define CLRLWI C( rA, rS, nbits )         clrlwi. rA, rS, (nbits);
#define CLRRWI( rA, rS, nbits )           clrrwi rA, rS, (nbits);
#define CLRRWI_C( rA, rS, nbits )         clrrwi. rA, rS, (nbits);
#define CMPLW( rA, rB )                   cmplw rA, rB;
#define CMPLW CR( bit, rA, rB )           cmplw bit, rA, rB;
#define CMPLWI( rA, UIMM )                cmplwi rA, (UIMM);
#define CMPLWI CR( bit, rA, UIMM )        cmplwi bit, rA, (UIMM);
#define CMPW( rA, rB )                    cmpw rA, rB;
#define CMPW CR( bit, rA, rB )            cmpw bit, rA, rB;
#define CMPWI( rA, SIMM )                 cmpwi rA, (SIMM);
#define CMPWI_CR( bit, rA, SIMM )         cmpwi bit, rA, (SIMM);
#define DCBF( rA, rB )                    dcbf rA, rB;
#define DCBI( rA, rB )                    dcbi rA, rB;
#define DCBST( rA, rB )                   dcbst rA, rB;
#define DCBT( rA, rB )                    dcbt rA, rB;
#define DCBTST( rA, rB )                  dcbtst rA, rB;
#if !defined COMPILE_NO_DCBZ
#define DCBZ( rA, rB )                    dcbz rA, rB;
#else
#define DCBZ( rA, rB )
#endif                                    nop;
#define DECR( rD )                        addi rD, rD, -1;
#define DECR C( rD )                      addic. rD, rD, -1;
#define DIVW( rD, rA, rB )                divw rD, rA, rB;
```

33

```
#define DIVW C( rD, rA, rB )              divw. rD, rA, rB;
#define DIVWU( rD, rA, rB )               divwu rD, rA, rB;
#define DIVWU C( rD, rA, rB )             divwu. rD, rA, rB;
#define EQV( rA, rS, rB )                 eqv rA, rS, rB;
#define EQV C( rA, rS, rB )               eqv. rA, rS, rB;
#define EXTLWI( rA, rS, n, b )            rlwinm rA, rS, (b), 0, (n)-1;
#define EXTLWI C( rA, rS, n, b )          rlwinm. rA, rS, (b), 0, (n)-1;
#define EXTRWI( rA, rS, n, b )            rlwinm rA, rS, (b)+(n), 32-(n), 31;
#define EXTRWI C( rA, rS, n, b )          rlwinm. rA, rS, (b)+(n), 32-(n), 31;
#define FABS( frD, frB )                  fabs frD, frB;
#define FADD( frD, frA, frB )             fadd frD, frA, frB;
#define FADDS( frD, frA, frB )            fadds frD, frA, frB;
#define FCMPO( bit, frA, frB )            fcmpo bit, frA, frB;
#define FCMPU( bit, frA, frB )            fcmpu bit, frA, frB;
#define FCTIW( frD, frB )                 fctiw frD, frB;
#define FCTIWZ( frD, frB )                fctiwz frD, frB;
#define FDIV( frD, frA, frB )             fdiv frD, frA, frB;
#define FDIVS( frD, frA, frB )            fdivs frD, frA, frB;
#define FMADD( frD, frA, frC, frB )       fmadd frD, frA, frC, frB;
#define FMADDS( frD, frA, frC, frB )      fmadds frD, frA, frC, frB;
#define FMOV( frD, frB )                  FMR( frD, frB )
#define FMR( frD, frB )                   fmr frD, frB;
#define FMUL( frD, frA, frB )             fmul frD, frA, frB;
#define FMULS( frD, frA, frB )            fmuls frD, frA, frB;
#define FMSUB( frD, frA, frC, frB )       fmsub frD, frA, frC, frB;
#define FMSUBS( frD, frA, frC, frB )      fmsubs frD, frA, frC, frB;
#define FNABS( frD, frB )                 fnabs frD, frB;
#define FNEG( frD, frB )                  fneg frD, frB;
#define FNMADD( frD, frA, frC, frB )      fnmadd frD, frA, frC, frB;
#define FNMADDS( frD, frA, frC, frB )     fnmadds frD, frA, frC, frB;
#define FNMSUB( frD, frA, frC, frB )      fnmsub frD, frA, frC, frB;
#define FNMSUBS( frD, frA, frC, frB )     fnmsubs frD, frA, frC, frB;
#define FRES( frD, frB )                  fres frD, frB;
#define FRSP( frD, frB )                  frsp frD, frB;
#define FRSQRTE( frD, frB )               frsqrte frD, frB;
#define FSEL( frD, frA, frC, frB )        fsel frD, frA, frC, frB;
#define FSUB( frD, frA, frB )             fsub frD, frA, frB;
#define FSUBS( frD, frA, frB )            fsubs frD, frA, frB;
#define GOTO( label )                     BR( label )
#define INCR( rD )                        addi rD, rD, 1;
#define INCR C( rD )                      addic. rD, rD, 1;
#define INSLWI( rA, rS, n, b )            rlwimi rA, rS, 32-(b), (b), (b)+(n)-1;
#define INSLWI_C( rA, rS, n, b )          rlwimi. rA, rS, 32-(b), (b), (b)
+(n)-1;
#define INSRWI( rA, rS, n, b )            rlwimi rA, rS, 32-((b)+(n)), (b), (b)
+(n)-1;
#define INSRWI_C( rA, rS, n, b )          rlwimi. rA, rS, 32-((b)+(n)), (b), (b)
+(n)-1;
#define LA( rD, symbol, SIMM )            addis rD, 0, (symbol+(SIMM))@ha; \
                                          addi rD, rD, (symbol+(SIMM))@l;
#define LABEL( label )                    label:
#define LBZ( rD, rA, d )                  lbz rD, (d)(rA);
#define LBZA( rD, symbol )                addis rD, 0, (symbol)@ha; \
                                          lbz rD, (symbol)@l(rD);
#define LBZU( rD, rA, d )                 lbzu rD, (d)(rA);
#define LBZUX( rD, rA, rB )               lbzux rD, rA, rB;
#define LBZX( rD, rA, rB )                lbzx rD, rA, rB;
#define LFD( frD, rA, d )                 lfd frD, (d)(rA);
#define LFDU( frD, rA, d )                lfdu frD, (d)(rA);
#define LFDUX( frD, rA, rB )              lfdux frD, rA, rB;
#define LFDX( frD, rA, rB )               lfdx frD, rA, rB;
#define LFS( frD, rA, d )                 lfs frD, (d)(rA);
#define LFSA( frD, symbol, rT )           addis rT, 0, (symbol)@ha; \
                                          lfs frD, (symbol)@l(rT);
#define LFSU( frD, rA, d )                lfsu frD, (d)(rA);
#define LFSUX( frD, rA, rB )              lfsux frD, rA, rB;
#define LFSX( frD, rA, rB )               lfsx frD, rA, rB;
```

34

```
        salppc.inc                                           3/9/2001

        #define LHA( rD, rA, d )                lha rD, (d)(rA);
        #define LHAA( rD, symbol )              addis rD, 0, (symbol)@ha; \
                                                lha rD, (symbol)@l(rD);

        #define LHAU( rD, rA, d )               lhau rD, (d)(rA);
        #define LHAUX( rD, rA, rB )             lhaux rD, rA, rB;
        #define LHAX( rD, rA, rB )              lhax rD, rA, rB;
        #define LHZ( rD, rA, d )                lhz rD, (d)(rA);
        #define LHZA( rD, symbol )              addis rD, 0, (symbol)@ha; \
                                                lhz rD, (symbol)@l(rD);

        #define LHZU( rD, rA, d )               lhzu rD, (d)(rA);
        #define LHZUX( rD, rA, rB )             lhzux rD, rA, rB;
        #define LHZX( rD, rA, rB )              lhzx rD, rA, rB;
        #define LI( rD, SIMM )                  li rD, (SIMM);
        #define LIS( rD, SIMM )                 lis rD, (SIMM);
        #define LOAD_COUNT( rD )                mtctr rD;
        #define LWZ( rD, rA, d )                lwz rD, (d)(rA);
        #define LWZA( rD, symbol )              addis rD, 0, (symbol)@ha; \
                                                lwz rD, (symbol)@l(rD);

        #define LWZU( rD, rA, d )               lwzu rD, (d)(rA);
        #define LWZUX( rD, rA, rB )             lwzux rD, rA, rB;
        #define LWZX( rD, rA, rB )              lwzx rD, rA, rB;
        #define MCRF( crfD, crfS )              mcrf crfD, crfS;
        #define MCRFS( crfD, crfS )             mcrfs crfD, crfS;
        #define MFCR( rD )                      mfcr rD;
        #define MFCTR( rD )                     mfctr rD;
        #define MFLR( rD )                      mflr rD;
        #define MFSPR( rD, SPR )                mfspr rD, SPR;
        #define MR( rA, rS )                    mr rA, rS;
        #define MR_C( rA, rS )                  or. rA, rS, rS;
        #define MOV( rA, rS )                   MR( rA, rS )
        #define MOV_C( rA, rS )                 MR_C( rA, rS )
        #define MTCR( rD )                      mtcr rD;
        #define MTCTR( rD )                     mtctr rD;
        #define MTFSFI( crfD, IMM )             mtfsfi (crfD), (IMM);
        #define MTLR( rD )                      mtlr rD;
        #define MTSPR( SPR, rS )                mtspr SPR, rS;
        #define MULLI( rD, rA, SIMM )           mulli rD, rA, (SIMM);
        #define MULLW( rD, rA, rB )             mullw rD, rA, rB;
        #define MULLW_C( rD, rA, rB )           mullw. rD, rA, rB;
        #define NAND( rA, rS, rB )              nand rA, rS, rB;
        #define NAND_C( rA, rS, rB )            nand. rA, rS, rB;
        #define NEG( rD, rA )                   neg rD, rA;
        #define NEG_C( rD, rA )                 neg. rD, rA;
        #define NOP                             nop;
        #define NOR( rA, rS, rB )               nor rA, rS, rB;
        #define NOR_C( rA, rS, rB )             nor. rA, rS, rB;
        #define OR( rA, rS, rB )                or rA, rS, rB;
        #define OR_C( rA, rS, rB )              or. rA, rS, rB;
        #define ORC( rA, rS, rB )               orc rA, rS, rB;
        #define ORC_C( rA, rS, rB )             orc. rA, rS, rB;
        #define ORI( rA, rS, UIMM )             ori rA, rS, (UIMM);
        #define ORIS( rA, rS, UIMM )            oris rA, rS, (UIMM);
        #define RETURN                          BLR
        #define RLWIMI( rA, rS, SH, MB, ME )    rlwimi rA, rS, SH, MB, ME;
        #define RLWIMI_C( rA, rS, SH, MB, ME )  rlwimi. rA, rS, SH, MB, ME;
        #define RLWINM( rA, rS, SH, MB, ME )    rlwinm rA, rS, SH, MB, ME;
        #define RLWINM_C( rA, rS, SH, MB, ME )  rlwinm. rA, rS, SH, MB, ME;
        #define RLWNM( rA, rS, rB, MB, ME )     rlwnm rA, rS, rB, MB, ME;
        #define RLWNM_C( rA, rS, rB, MB, ME )   rlwnm. rA, rS, rB, MB, ME;
        #define ROTLW( rA, rS, rB )             rlwnm rA, rS, rB, 0, 31;
        #define ROTLW_C( rA, rS, rB )           rlwnm. rA, rS, rB, 0, 31;
        #define ROTLWI( rA, rS, n )             rlwinm rA, rS, (n), 0, 31;
        #define ROTLWI_C( rA, rS, n )           rlwinm. rA, rS, (n), 0, 31;
        #define ROTRWI( rA, rS, n )             rlwinm rA, rS, 32-(n), 0, 31;
        #define ROTRWI_C( rA, rS, n )           rlwinm. rA, rS, 32-(n), 0, 31;
        #define SLW( rA, rS, rB )               slw rA, rS, rB;
        #define SLW_C( rA, rS, rB )             slw. rA, rS, rB;
```

35

```
        #define SLWI( rA, rS, SH )            slwi rA, rS, (SH);
        #define SLWI C( rA, rS, SH )          slwi. rA, rS, (SH);
        #define SRAW( rA, rS, rB )            sraw rA, rS, rB;
        #define SRAW C( rA, rS, rB )          sraw. rA, rS, rB;
        #define SRAWI( rA, rS, SH )           srawi rA, rS, (SH);
        #define SRAWI C( rA, rS, SH )         srawi. rA, rS, (SH);
        #define SRW( rA, rS, rB )             srw rA, rS, rB;
        #define SRW C( rA, rS, rB )           srw. rA, rS, rB;
        #define SRWI( rA, rS, SH )            srwi rA, rS, (SH);
        #define SRWI_C( rA, rS, SH )          srwi. rA, rS, (SH);
        #define STB( rS, rA, d )              stb rS, (d)(rA);
        #define STBU( rS, rA, d )             stbu rS, (d)(rA);
        #define STBUX( rS, rA, rB )           stbux rS, rA, rB;
        #define STBX( rS, rA, rB )            stbx rS, rA, rB;
        #define STFD( frD, rA, d )            stfd frD, (d)(rA);
        #define STFDU( frD, rA, d )           stfdu frD, (d)(rA);
        #define STFDUX( frD, rA, rB )         stfdux frD, rA, rB;
        #define STFDX( frD, rA, rB )          stfdx frD, rA, rB;
        #define STFS( frD, rA, d )            stfs frD, (d)(rA);
        #define STFSU( frD, rA, d )           stfsu frD, (d)(rA);
        #define STFSUX( frD, rA, rB )         stfsux frD, rA, rB;
        #define STFSX( frD, rA, rB )          stfsx frD, rA, rB;
        #define STH( rS, rA, d )              sth rS, (d)(rA);
        #define STHU( rS, rA, d )             sthu rS, (d)(rA);
        #define STHUX( rS, rA, rB )           sthux rS, rA, rB;
        #define STHX( rS, rA, rB )            sthx rS, rA, rB;
        #define STW( rS, rA, d )              stw rS, (d)(rA);
        #define STWU( rS, rA, d )             stwu rS, (d)(rA);
        #define STWUX( rS, rA, rB )           stwux rS, rA, rB;
        #define STWX( rS, rA, rB )            stwx rS, rA, rB;
        #define SUB( rD, rA, rB )             sub rD, rA, rB;
        #define SUB C( rD, rA, rB )           sub. rD, rA, rB;
        #define SUBFIC( rD, rA, SIMM )        subfic rD, rA, (SIMM);
        #define SUBI( rD, rA, SIMM )          subi rD, rA, (SIMM);
        #define SUBIC C( rD, rA, SIMM )       subic. rD, rA, (SIMM);
        #define SUBIS( rD, rA, SIMM )         subis rD, rA, (SIMM);
        #define TEST_COUNT( label )           bdnz label;
        #define XOR( rA, rS, rB )             xor rA, rS, rB;
        #define XOR C( rA, rS, rB )           xor. rA, rS, rB;
        #define XORI( rA, rS, UIMM )          xori rA, rS, (UIMM);
        #define XORIS( rA, rS, UIMM )         xoris rA, rS, (UIMM);


        /*
         *   VMX instructions
         */
        #define BR VMX ALL TRUE( label )      bt 24, label;
        #define BR VMX ALL FALSE( label )     bt 26, label;
        #define BR VMX NONE TRUE( label )     bt 26, label;
        #define BR VMX SOME FALSE( label )    bf 24, label;
        #define BR VMX SOME_TRUE( label )     bf 26, label;
        #define DSS( STRM )                   dss STRM, 0;
        #define DSSALL                        dss 0, 1;
        #define DST( rA, rB, STRM )           dst rA, rB, STRM;
        #define DSTST( rA, rB, STRM )         dstst rA, rB, STRM;
        #define DSTT( rA, rB, STRM )          dstt rA, rB, STRM;
        #define DSTSTT( rA, rB, STRM )        dststt rA, rB, STRM;
        #define LVEBX( vT, rA, rB )           lvebx vT, rA, rB;
        #define LVEHX( vT, rA, rB )           lvehx vT, rA, rB;
        #define LVEWX( vT, rA, rB )           lvewx vT, rA, rB;

        #if defined( LITTLE ENDIAN )
        #define LVSL( vT, rA, rB )            lvsr vT, rA, rB;
        #define LVSR( vT, rA, rB )            lvsl vT, rA, rB;
        #else
        #define LVSL( vT, rA, rB )            lvsl vT, rA, rB;
        #define LVSR( vT, rA, rB )            lvsr vT, rA, rB;
        #endif
```

36

```
#define LVX( vT, rA, rB )                lvx vT, rA, rB;
#define LVXL( vT, rA, rB )               lvxl vT, rA, rB;
#define STVEBX( vS, rA, rB )             stvebx vS, rA, rB;
#define STVEHX( vS, rA, rB )             stvehx vS, rA, rB;
#define STVEWX( vS, rA, rB )             stvewx vS, rA, rB;
#define STVX( vS, rA, rB )               stvx vS, rA, rB;
#define STVXL( vS, rA, rB )              stvxl vS, rA, rB;
#define VADDFP( vT, vA, vB )             vaddfp vT, vA, vB;
#define VADDSBS( vT, vA, vB )            vaddsbs vT, vA, vB;
#define VADDSHS( vT, vA, vB )            vaddshs vT, vA, vB;
#define VADDSWS( vT, vA, vB )            vaddsws vT, vA, vB;
#define VADDUBM( vT, vA, vB )            vaddubm vT, vA, vB;
#define VADDUBS( vT, vA, vB )            vaddubs vT, vA, vB;
#define VADDUHM( vT, vA, vB )            vadduhm vT, vA, vB;
#define VADDUHS( vT, vA, vB )            vadduhs vT, vA, vB;
#define VADDUWM( vT, vA, vB )            vadduwm vT, vA, vB;
#define VADDUWS( vT, vA, vB )            vadduws vT, vA, vB;
#define VAND( vT, vA, vB )               vand vT, vA, vB;
#define VANDC( vT, vA, vB )              vandc vT, vA, vB;
#define VCMPEQFP( vT, vA, vB )           vcmpeqfp vT, vA, vB;
#define VCMPEQFP C( vT, vA, vB )         vcmpeqfp. vT, vA, vB;
#define VCMPEQUB( vT, vA, vB )           vcmpequb vT, vA, vB;
#define VCMPEQUB C( vT, vA, vB )         vcmpequb. vT, vA, vB;
#define VCMPEQUH( vT, vA, vB )           vcmpequh vT, vA, vB;
#define VCMPEQUH C( vT, vA, vB )         vcmpequh. vT, vA, vB;
#define VCMPEQUW( vT, vA, vB )           vcmpequw vT, vA, vB;
#define VCMPEQUW C( vT, vA, vB )         vcmpequw. vT, vA, vB;
#define VCMPGEFP( vT, vA, vB )           vcmpgefp vT, vA, vB;
#define VCMPGEFP C( vT, vA, vB )         vcmpgefp. vT, vA, vB;
#define VCMPGTFP( vT, vA, vB )           vcmpgtfp vT, vA, vB;
#define VCMPGTFP C( vT, vA, vB )         vcmpgtfp. vT, vA, vB;
#define VCMPGTSB( vT, vA, vB )           vcmpgtsb vT, vA, vB;
#define VCMPGTSB C( vT, vA, vB )         vcmpgtsb. vT, vA, vB;
#define VCMPGTSH( vT, vA, vB )           vcmpgtsh vT, vA, vB;
#define VCMPGTSH C( vT, vA, vB )         vcmpgtsh. vT, vA, vB;
#define VCMPGTSW( vT, vA, vB )           vcmpgtsw vT, vA, vB;
#define VCMPGTSW C( vT, vA, vB )         vcmpgtsw. vT, vA, vB;
#define VCMPGTUB( vT, vA, vB )           vcmpgtub vT, vA, vB;
#define VCMPGTUB C( vT, vA, vB )         vcmpgtub. vT, vA, vB;
#define VCMPGTUH( vT, vA, vB )           vcmpgtuh vT, vA, vB;
#define VCMPGTUH C( vT, vA, vB )         vcmpgtuh. vT, vA, vB;
#define VCMPGTUW( vT, vA, vB )           vcmpgtuw vT, vA, vB;
#define VCMPGTUW C( vT, vA, vB )         vcmpgtuw. vT, vA, vB;
#define VCFSX( vT, vB, UIMM )            vcfsx vT, vB, (UIMM);
#define VCFUX( vT, vB, UIMM )            vcfux vT, vB, (UIMM);
#define VCTSXS( vT, vB, UIMM )           vctsxs vT, vB, (UIMM);
#define VCTUXS( vT, vB, UIMM )           vctuxs vT, vB, (UIMM);
#define VEXPTEFP( vT, vB )               vexptefp vT, vB;
#define VLOGEFP( vT, vB )                vlogefp vT, vB;
#define VMADDFP( vT, vA, vC, vB )        vmaddfp vT, vA, vC, vB;
#define VMAXFP( vT, vA, vB )             vmaxfp vT, vA, vB;
#define VMAXSB( vT, vA, vB )             vmaxsb vT, vA, vB;
#define VMAXSH( vT, vA, vB )             vmaxsh vT, vA, vB;
#define VMAXSW( vT, vA, vB )             vmaxsw vT, vA, vB;
#define VMAXUB( vT, vA, vB )             vmaxub vT, vA, vB;
#define VMAXUH( vT, vA, vB )             vmaxuh vT, vA, vB;
#define VMAXUW( vT, vA, vB )             vmaxuw vT, vA, vB;
#define VMHADDSHS( vD, vA, vB, vC )      vmhaddshs vD, vA, vB, vC;
#define VMHRADDSHS( vD, vA, vB, vC )     vmhraddshs vD, vA, vB, vC;
#define VMINFP( vT, vA, vB )             vminfp vT, vA, vB;
#define VMINSB( vT, vA, vB )             vminsb vT, vA, vB;
#define VMINSH( vT, vA, vB )             vminsh vT, vA, vB;
#define VMINSW( vT, vA, vB )             vminsw vT, vA, vB;
#define VMINUB( vT, vA, vB )             vminub vT, vA, vB;
#define VMINUH( vT, vA, vB )             vminuh vT, vA, vB;
#define VMINUW( vT, vA, vB )             vminuw vT, vA, vB;
```

37

salppc.inc   3/9/2001

```
#define VMLADDUHM( vD, vA, vB, vC )        vmladduhm vD, vA, vB, vC;
#define VMR( vD, vS )                      vor vD, vS, vS;

#if defined( LITTLE_ENDIAN )
#define VMRGHB( vT, vA, vB )               vmrglb vT, vB, vA;
#define VMRGHH( vT, vA, vB )               vmrglh vT, vB, vA;
#define VMRGHW( vT, vA, vB )               vmrglw vT, vB, vA;
#define VMRGLB( vT, vA, vB )               vmrghb vT, vB, vA;
#define VMRGLH( vT, vA, vB )               vmrghh vT, vB, vA;
#define VMRGLW( vT, vA, vB )               vmrghw vT, vB, vA;
#else
#define VMRGHB( vT, vA, vB )               vmrghb vT, vA, vB;
#define VMRGHH( vT, vA, vB )               vmrghh vT, vA, vB;
#define VMRGHW( vT, vA, vB )               vmrghw vT, vA, vB;
#define VMRGLB( vT, vA, vB )               vmrglb vT, vA, vB;
#define VMRGLH( vT, vA, vB )               vmrglh vT, vA, vB;
#define VMRGLW( vT, vA, vB )               vmrglw vT, vA, vB;
#endif

#define VMSUMMBM( vT, vA, vB, vC )         vmsummbm vT, vA, vB, vC;
#define VMSUMSHM( vT, vA, vB, vC )         vmsumshm vT, vA, vB, vC;
#define VMSUMSHS( vT, vA, vB, vC )         vmsumshs vT, vA, vB, vC;
#define VMSUMUBM( vT, vA, vB, vC )         vmsumubm vT, vA, vB, vC;
#define VMSUMUHM( vT, vA, vB, vC )         vmsumuhm vT, vA, vB, vC;
#define VMSUMUHS( vT, vA, vB, vC )         vmsumuhs vT, vA, vB, vC;
#define VMULESB( vT, vA, vB )              vmulesb vT, vA, vB;
#define VMULESH( vT, vA, vB )              vmulesh vT, vA, vB;
#define VMULEUB( vT, vA, vB )              vmuleub vT, vA, vB;
#define VMULEUH( vT, vA, vB )              vmuleuh vT, vA, vB;
#define VMULOSB( vT, vA, vB )              vmulosb vT, vA, vB;
#define VMULOSH( vT, vA, vB )              vmulosh vT, vA, vB;
#define VMULOUB( vT, vA, vB )              vmuloub vT, vA, vB;
#define VMULOUH( vT, vA, vB )              vmulouh vT, vA, vB;
#define VNMSUBFP( vT, vA, vC, vB )         vnmsubfp vT, vA, vC, vB;
#define VNOR( vT, vA, vB )                 vnor vT, vA, vB;
#define VNOT( vT, vA )                     vnor vT, vA, vA;
#define VOR( vT, vA, vB )                  vor vT, vA, vB;

#if defined( LITTLE ENDIAN )
#define VPERM( vT, vA, vB, vC )            vperm vT, vB, vA, vC;
#define VPKUHUM( vT, vA, vB )              vpkuhum vT, vB, vA;
#define VPKUHUS( vT, vA, vB )              vpkuhus vT, vB, vA;
#define VPKSHUS( vT, vA, vB )              vpkshus vT, vB, vA;
#define VPKSHSS( vT, vA, vB )              vpkshss vT, vB, vA;
#define VPKUWUM( vT, vA, vB )              vpkuwum vT, vB, vA;
#define VPKUWUS( vT, vA, vB )              vpkuwus vT, vB, vA;
#define VPKSWUS( vT, vA, vB )              vpkswus vT, vB, vA;
#define VPKSWSS( vT, vA, vB )              vpkswss vT, vB, vA;
#else
#define VPERM( vT, vA, vB, vC )            vperm vT, vA, vB, vC;
#define VPKUHUM( vT, vA, vB )              vpkuhum vT, vA, vB;
#define VPKUHUS( vT, vA, vB )              vpkuhus vT, vA, vB;
#define VPKSHUS( vT, vA, vB )              vpkshus vT, vA, vB;
#define VPKSHSS( vT, vA, vB )              vpkshss vT, vA, vB;
#define VPKUWUM( vT, vA, vB )              vpkuwum vT, vA, vB;
#define VPKUWUS( vT, vA, vB )              vpkuwus vT, vA, vB;
#define VPKSWUS( vT, vA, vB )              vpkswus vT, vA, vB;
#define VPKSWSS( vT, vA, vB )              vpkswss vT, vA, vB;
#endif

#define VREFP( vT, vB )                    vrefp vT, vB;
#define VRFIM( vT, vB )                    vrfim vT, vB;
#define VRFIN( vT, vB )                    vrfin vT, vB;
#define VRFIP( vT, vB )                    vrfip vT, vB;
#define VRFIZ( vT, vB )                    vrfiz vT, vB;
#define VRLB( vT, vA, vB )                 vrlb vT, vA, vB;
#define VRLH( vT, vA, vB )                 vrlh vT, vA, vB;
```

38

salppc.inc   3/9/2001

```
#define VRLW( vT, vA, vB )                vrlw vT, vA, vB;
#define VRSQRTEFP( vT, vB )               vrsqrtefp vT, vB;
#define VSEL( vT, vA, vB, vC )            vsel vT, vA, vB, vC;
#define VSL( vT, vA, vB )                 vsl vT, vA, vB;

#if defined( LITTLE_ENDIAN )
#define VSLDOI( vT, vA, vB, UIMM )        vsldoi vT, vB, vA, (16 - (UIMM));
#else
#define VSLDOI( vT, vA, vB, UIMM )        vsldoi vT, vA, vB, (UIMM);
#endif

#define VSLB( vT, vA, vB )                vslb vT, vA, vB;
#define VSLH( vT, vA, vB )                vslh vT, vA, vB;
#define VSLO( vT, vA, vB )                vslo vT, vA, vB;
#define VSLW( vT, vA, vB )                vslw vT, vA, vB;
#define VSR( vT, vA, vB )                 vsr vT, vA, vB;
#define VSRAB( vT, vA, vB )               vsrab vT, vA, vB;
#define VSRAH( vT, vA, vB )               vsrah vT, vA, vB;
#define VSRAW( vT, vA, vB )               vsraw vT, vA, vB;
#define VSRB( vT, vA, vB )                vsrb vT, vA, vB;
#define VSRH( vT, vA, vB )                vsrh vT, vA, vB;
#define VSRO( vT, vA, vB )                vsro vT, vA, vB;
#define VSRW( vT, vA, vB )                vsrw vT, vA, vB;
#define VSPLTB( vT, vB, UIMM )            vspltb vT, vB, C INDEX MUNGE( UIMM );
#define VSPLTH( vT, vB, UIMM )            vsplth vT, vB, S INDEX MUNGE( UIMM );
#define VSPLTW( vT, vB, UIMM )            vspltw vT, vB, L INDEX_MUNGE( UIMM );
#define VSPLTISB( vT, SIMM )              vspltisb vT, (SIMM);
#define VSPLTISH( vT, SIMM )              vspltish vT, (SIMM);
#define VSPLTISW( vT, SIMM )              vspltisw vT, (SIMM);
#define VSUBFP( vT, vA, vB )              vsubfp vT, vA, vB;
#define VSUBSBS( vT, vA, vB )             vsubsbs vT, vA, vB;
#define VSUBSHS( vT, vA, vB )             vsubshs vT, vA, vB;
#define VSUBSWS( vT, vA, vB )             vsubsws vT, vA, vB;
#define VSUBUBM( vT, vA, vB )             vsububm vT, vA, vB;
#define VSUBUBS( vT, vA, vB )             vsububs vT, vA, vB;
#define VSUBUHM( vT, vA, vB )             vsubuhm vT, vA, vB;
#define VSUBUHS( vT, vA, vB )             vsubuhs vT, vA, vB;
#define VSUBUWM( vT, vA, vB )             vsubuwm vT, vA, vB;
#define VSUBUWS( vT, vA, vB )             vsubuws vT, vA, vB;
#define VSUMSWS( vT, vA, vB )             vsumsws vT, vA, vB;
#define VSUM2SWS( vT, vA, vB )            vsum2sws vT, vA, vB;
#define VSUM4SBS( vT, vA, vB )            vsum4sbs vT, vA, vB;
#define VSUM4SHS( vT, vA, vB )            vsum4shs vT, vA, vB;
#define VSUM4UBS( vT, vA, vB )            vsum4ubs vT, vA, vB;

#if defined( LITTLE ENDIAN )
#define VUPKHSB( vT, vB )                 vupklsb vT, vB;
#define VUPKHSH( vT, vB )                 vupklsh vT, vB;
#define VUPKLSB( vT, vB )                 vupkhsb vT, vB;
#define VUPKLSH( vT, vB )                 vupkhsh vT, vB;
#else
#define VUPKHSB( vT, vB )                 vupkhsb vT, vB;
#define VUPKHSH( vT, vB )                 vupkhsh vT, vB;
#define VUPKLSB( vT, vB )                 vupklsb vT, vB;
#define VUPKLSH( vT, vB )                 vupklsh vT, vB;
#endif

#define VXOR( vT, vA, vB )                vxor vT, vA, vB;

/*
 *  stack and register macros
 */
#define VRSAVE_COND 7                     /* recommended VR condition bit */

#undef VOLATILE_r13                       /* r13 volatile or non-volatile */

#define MIN_STACK_ALIGN  16
```

39

salppc.inc   3/9/2001

```
#define MIN_STACK_ALIGN_MASK   (MIN_STACK_ALIGN - 1)

#define ALIGN STACK( nbytes ) \
   (((nbytes) + MIN_STACK_ALIGN_MASK) & ~MIN_STACK_ALIGN_MASK)

#define LR SAVE OFF   4
#define FPR_SAVE_OFF   (-(32-14)*8)

#if defined( VOLATILE_r13 )
#define GPR_SAVE_OFF   (FPR_SAVE_OFF - (32-14)*4)
#else
#define GPR_SAVE_OFF   (FPR_SAVE_OFF - (32-13)*4)
#endif

#define CR_SAVE_OFF   (GPR_SAVE_OFF - 4)

#if defined( BUILD_MAX )

#define VRSAVE_SAVE_OFF   (CR_SAVE_OFF - 4)

#if defined( VOLATILE r13 )
#define ALIGNMENT_PADDING_OFF   (VRSAVE_SAVE_OFF - 0)
#else
#define ALIGNMENT_PADDING_OFF   (VRSAVE_SAVE_OFF - 12)
#endif

#define VR SAVE OFF   (ALIGNMENT_PADDING_OFF - (32-20)*16)
#define LAST_OFF   VR_SAVE_OFF

#else

#define LAST_OFF   CR_SAVE_OFF

#endif

#define REG SAVE SIZE   (-LAST_OFF)
#define MAX NARGS   18
#define ARGS SIZE   (MAX_NARGS * 4)
#define LINK SIZE   8
#define STACK_FRAME_SIZE   (REG_SAVE_SIZE + ARGS_SIZE + LINK_SIZE)

/*
 * macros to obtain the byte offset into the stack for the last FPR
 * and GPR registers for small temporary storage.
 * FPR_SAVE AREA OFFSET points to an area of 8 * (# of unsaved non-volatile
 * FPR registers).
 * GPR_SAVE AREA OFFSET points to an area of 4 * (# of unsaved non-volatile
 * GPR registers).
 * GET FPR SAVE AREA places the start of the FPR save area into a register
 * GET_GPR_SAVE_AREA places the start of the GPR save area into a register
 *
 * For MAX only:
 *
 * VR_SAVE AREA OFFSET points to an area of 16 * (# of unsaved non-volatile
 * VR registers).
 * GET_VR_SAVE_AREA places the start of the VR save area into a register
 */
#define FPR SAVE AREA OFFSET FPR SAVE OFF
#define GPR_SAVE_AREA_OFFSET GPR_SAVE_OFF

#define GET FPR SAVE AREA( ptr ) \
   addi ptr, sp, FPR_SAVE_AREA_OFFSET;

#define GET GPR SAVE AREA( ptr ) \
   addi ptr, sp, GPR_SAVE_AREA_OFFSET;

#if defined( BUILD_MAX )
```

40

salppc.inc   3/9/2001

```
#define VR_SAVE_AREA_OFFSET VR_SAVE_OFF

#define GET_VR_SAVE_AREA( ptr ) \
    addi ptr, sp, VR_SAVE_AREA_OFFSET;
#endif

/*
 *  if the function creates a stack frame with local storage,
 *  LOCAL_STORAGE_OFFSET is the stack offset to the start of this
 *  storage and is guaranteed to have the minimum stack alignment.
 */
#define LOCAL_STORAGE_OFFSET  (LINK_SIZE + ARGS_SIZE)

/*
 * macros to create and destroy a stack frame.
 *
 * CREATE_STACK_FRAME[ X] creates a stack frame that can handle up to
 * 18 GPR register arguments and a local storage size <=
 * 32768 - 512 = 32,256 bytes.
 *
 * CREATE_STACK_FRAME_X destroys r0.
 *
 * For CREATE_STACK_FRAME_X, local_nbytes_reg must not be r0.
 *
 * Both CREATE_STACK_FRAME[ X] and DESTROY_STACK_FRAME should not be
 * called before registers are saved or after they are restored.
 *
 * The stack pointer "output from" CREATE_STACK_FRAME[_X] must be
 * the same "input to" DESTROY_STACK_FRAME.
 */
#define CREATE_STACK_FRAME( local_nbytes ) \
    stwu sp, -ALIGN_STACK( STACK_FRAME_SIZE + (local_nbytes) )(sp);

#define CREATE_STACK_FRAME_X( local_nbytes_reg ) \
    addi r0, local_nytes_reg, (STACK_FRAME_SIZE + MIN_STACK_ALIGN_SIZE); \
    andi. r0, r0, ~MIN_STACK_ALIGN_MASK; \
    stwux sp, sp, r0;

#define DESTROY_STACK_FRAME \
    lwz sp, 0(sp);

/*
 *  macros to allocate and free space on the user stack.
 *  with a fixed alignment of MIN_STACK_ALIGN.
 *  nbytes must be <= (32768 - 432 = 32,336).
 *  On return, sp points to a buffer of nbytes bytes.
 */
#define PUSH_STACK( nbytes ) \
    addi sp, sp, -ALIGN_STACK( REG_SAVE_SIZE + (nbytes) );

#define POP_STACK( nbytes ) \
    addi sp, sp, ALIGN_STACK( REG_SAVE_SIZE + (nbytes) );

#define ALLOCATE_STACK_SPACE( ptr, nbytes ) \
    PUSH_STACK( nbytes ) \
    mr ptr, sp;

#define FREE_STACK_SPACE( nbytes ) POP_STACK( nbytes )

/*
 * macros to create and destroy a stack buffer with a variable
 * alignment and size.
 *
 * CREATE_STACK_BUFFER[ X] creates a buffer of size nbytes and alignment
 * byte align on the stack, returning a pointer to the buffer in the
 * GPR bufferp.
 *
```

41

```
 * bufferp must be a GPR other than r0 and r1 (sp).
 * byte align must be a power of 2 such that 2 <= byte_align <= 4096.
 * CREATE_STACK_BUFFER destroys r0.
 *
 * CREATE STACK BUFFER[ X] stores the original value of the stack pointer
 * below the buffer at offset 0 from the new stack pointer.
 *
 * DESTROY STACK BUFFER sets the stack pointer to the value stored
 * at the address pointed to by the input stack pointer.
 *
 * Both CREATE STACK BUFFER[ X] and DESTROY STACK BUFFER should not be
 * called before registers are saved or after they are restored.
 *
 * The stack pointer "output from" CREATE STACK_BUFFER[_X] must be
 * the same "input to" DESTROY_STACK_BUFFER.
 */
#define CREATE STACK BUFFER( bufferp, byte align, nbytes ) \
    addis bufferp, sp, (-(REG SAVE SIZE + (nbytes)) + 32768)@h; \
    li r0, (((byte align) - 1) | MIN STACK ALIGN MASK); \
    addi bufferp, bufferp, (-(REG_SAVE_SIZE + (nbytes)))@l; \
    andc bufferp, bufferp, r0; \
    sub r0, bufferp, sp; \
    addic r0, r0, -MIN_STACK_ALIGN; \
    stwux sp, sp, r0;

#define CREATE STACK BUFFER X( bufferp, byte_align, nbytes_reg ) \
    sub bufferp, sp, nbytes_reg; \
    li r0, (((byte align) - 1) | MIN STACK_ALIGN_MASK); \
    addi bufferp, bufferp, -REG SAVE_SIZE; \
    andc bufferp, bufferp, r0; \
    sub r0, bufferp, sp; \
    addic r0, r0, -MIN_STACK_ALIGN; \
    stwux sp, sp, r0;

#define DESTROY STACK_BUFFER \
    lwz sp, 0(sp);

/*
 * macros to create and destroy the salcache buffer on the user stack.
 *
 * CREATE_STACK_SALCACHE destroys r0.
 *
 * Both CREATE STACK SALCACHE and DESTROY STACK SALCACHE should not be
 * called before registers are saved or after they are restored.
 */
#define CREATE STACK SALCACHE( cachep ) \
        CREATE_STACK_BUFFER( cachep, SALCACHE_ALIGN, SALCACHE_ALLOC_SIZE )

#define DESTROY_STACK_SALCACHE DESTROY_STACK_BUFFER

/*
 *   macros for saving and restoring non-volatile
 *   floating point registers (FPRs)
 */
#define SAVE f14    SR_f14( stfd )
#define SAVE f14 f15   SR f14 f15( stfd )
#define SAVE f14 f16   SR f14 f16( stfd )
#define SAVE f14 f17   SR f14 f17( stfd )
#define SAVE f14 f18   SR f14 f18( stfd )
#define SAVE f14 f19   SR f14 f19( stfd )
#define SAVE f14 f20   SR f14 f20( stfd )
#define SAVE f14 f21   SR f14 f21( stfd )
#define SAVE f14 f22   SR f14 f22( stfd )
#define SAVE f14 f23   SR f14 f23( stfd )
#define SAVE f14 f24   SR f14 f24( stfd )
#define SAVE f14 f25   SR f14 f25( stfd )
#define SAVE_f14_f26   SR_f14_f26( stfd )
```

42

```
#define SAVE f14 f27    SR f14 f27( stfd )
#define SAVE f14 f28    SR f14 f28( stfd )
#define SAVE f14 f29    SR f14 f29( stfd )
#define SAVE f14 f30    SR f14 f30( stfd )
#define SAVE_f14_f31    SR_f14_f31( stfd )

#define SAVE d14    SR_f14( stfd )
#define SAVE d14 d15    SR f14 f15( stfd )
#define SAVE d14 d16    SR f14 f16( stfd )
#define SAVE d14 d17    SR f14 f17( stfd )
#define SAVE d14 d18    SR f14 f18( stfd )
#define SAVE d14 d19    SR f14 f19( stfd )
#define SAVE d14 d20    SR f14 f20( stfd )
#define SAVE d14 d21    SR f14 f21( stfd )
#define SAVE d14 d22    SR f14 f22( stfd )
#define SAVE d14 d23    SR f14 f23( stfd )
#define SAVE d14 d24    SR f14 f24( stfd )
#define SAVE d14 d25    SR f14 f25( stfd )
#define SAVE d14 d26    SR f14 f26( stfd )
#define SAVE d14 d27    SR f14 f27( stfd )
#define SAVE d14 d28    SR f14 f28( stfd )
#define SAVE d14 d29    SR f14 f29( stfd )
#define SAVE d14 d30    SR f14 f30( stfd )
#define SAVE_d14_d31    SR_f14_f31( stfd )

#define REST f14    SR_f14( lfd )
#define REST f14 f15    SR f14 f15( lfd )
#define REST f14 f16    SR f14 f16( lfd )
#define REST f14 f17    SR f14 f17( lfd )
#define REST f14 f18    SR f14 f18( lfd )
#define REST f14 f19    SR f14 f19( lfd )
#define REST f14 f20    SR f14 f20( lfd )
#define REST f14 f21    SR f14 f21( lfd )
#define REST f14 f22    SR f14 f22( lfd )
#define REST f14 f23    SR f14 f23( lfd )
#define REST f14 f24    SR f14 f24( lfd )
#define REST f14 f25    SR f14 f25( lfd )
#define REST f14 f26    SR f14 f26( lfd )
#define REST f14 f27    SR f14 f27( lfd )
#define REST f14 f28    SR f14 f28( lfd )
#define REST f14 f29    SR f14 f29( lfd )
#define REST f14 f30    SR f14 f30( lfd )
#define REST_f14_f31    SR_f14_f31( lfd )

#define REST d14    SR_f14( lfd )
#define REST d14 d15    SR f14 f15( lfd )
#define REST d14 d16    SR f14 f16( lfd )
#define REST d14 d17    SR f14 f17( lfd )
#define REST d14 d18    SR f14 f18( lfd )
#define REST d14 d19    SR f14 f19( lfd )
#define REST d14 d20    SR f14 f20( lfd )
#define REST d14 d21    SR f14 f21( lfd )
#define REST d14 d22    SR f14 f22( lfd )
#define REST d14 d23    SR f14 f23( lfd )
#define REST d14 d24    SR f14 f24( lfd )
#define REST d14 d25    SR f14 f25( lfd )
#define REST d14 d26    SR f14 f26( lfd )
#define REST d14 d27    SR f14 f27( lfd )
#define REST d14 d28    SR f14 f28( lfd )
#define REST d14 d29    SR f14 f29( lfd )
#define REST d14 d30    SR f14 f30( lfd )
#define REST_d14_d31    SR_f14_f31( lfd )

/*
 *    macros common to both FPR save and restore
 */
#define SR_f14( opcode ) \
```

43

```
        opcode f14, (FPR_SAVE_OFF + 17*8)(sp);
#define SR_f14_f15( opcode ) \
        opcode f15, (FPR_SAVE_OFF + 16*8)(sp); \
        SR_f14( opcode )
#define SR_f14_f16( opcode ) \
        opcode f16, (FPR_SAVE_OFF + 15*8)(sp); \
        SR_f14_f15( opcode )
#define SR_f14_f17( opcode ) \
        opcode f17, (FPR_SAVE_OFF + 14*8)(sp); \
        SR_f14_f16( opcode )
#define SR_f14_f18( opcode ) \
        opcode f18, (FPR_SAVE_OFF + 13*8)(sp); \
        SR_f14_f17( opcode )
#define SR_f14_f19( opcode ) \
        opcode f19, (FPR_SAVE_OFF + 12*8)(sp); \
        SR_f14_f18( opcode )
#define SR_f14_f20( opcode ) \
        opcode f20, (FPR_SAVE_OFF + 11*8)(sp); \
        SR_f14_f19( opcode )
#define SR_f14_f21( opcode ) \
        opcode f21, (FPR_SAVE_OFF + 10*8)(sp); \
        SR_f14_f20( opcode )
#define SR_f14_f22( opcode ) \
        opcode f22, (FPR_SAVE_OFF + 9*8)(sp); \
        SR_f14_f21( opcode )
#define SR_f14_f23( opcode ) \
        opcode f23, (FPR_SAVE_OFF + 8*8)(sp); \
        SR_f14_f22( opcode )
#define SR_f14_f24( opcode ) \
        opcode f24, (FPR_SAVE_OFF + 7*8)(sp); \
        SR_f14_f23( opcode )
#define SR_f14_f25( opcode ) \
        opcode f25, (FPR_SAVE_OFF + 6*8)(sp); \
        SR_f14_f24( opcode )
#define SR_f14_f26( opcode ) \
        opcode f26, (FPR_SAVE_OFF + 5*8)(sp); \
        SR_f14_f25( opcode )
#define SR_f14_f27( opcode ) \
        opcode f27, (FPR_SAVE_OFF + 4*8)(sp); \
        SR_f14_f26( opcode )
#define SR_f14_f28( opcode ) \
        opcode f28, (FPR_SAVE_OFF + 3*8)(sp); \
        SR_f14_f27( opcode )
#define SR_f14_f29( opcode ) \
        opcode f29, (FPR_SAVE_OFF + 2*8)(sp); \
        SR_f14_f28( opcode )
#define SR_f14_f30( opcode ) \
        opcode f30, (FPR_SAVE_OFF + 1*8)(sp); \
        SR_f14_f29( opcode )
#define SR_f14_f31( opcode ) \
        opcode f31, (FPR_SAVE_OFF)(sp); \
        SR_f14_f30( opcode )

/*
 *   macros for saving and restoring non-volatile
 *   general purpose registers (GPRs)
 */
#if defined( VOLATILE_r13 )

#define SAVE_r13
#define SAVE_r13_r14    SR_r14( stw )
#define SAVE_r13_r15    SR_r14_r15( stw )
#define SAVE_r13_r16    SR_r14_r16( stw )
#define SAVE_r13_r17    SR_r14_r17( stw )
#define SAVE_r13_r18    SR_r14_r18( stw )
#define SAVE_r13_r19    SR_r14_r19( stw )
#define SAVE_r13_r20    SR_r14_r20( stw )
```

44

```
     salppc.inc                                              3/9/2001
     #define SAVE r13 r21   SR r14 r21( stw )
     #define SAVE r13 r22   SR r14 r22( stw )
     #define SAVE r13 r23   SR r14 r23( stw )
     #define SAVE r13 r24   SR r14 r24( stw )
     #define SAVE r13 r25   SR r14 r25( stw )
     #define SAVE r13 r26   SR r14 r26( stw )
     #define SAVE r13 r27   SR r14 r27( stw )
     #define SAVE r13 r28   SR r14 r28( stw )
     #define SAVE r13 r29   SR r14 r29( stw )
     #define SAVE r13 r30   SR r14 r30( stw )
     #define SAVE_r13_r31   SR_r14_r31( stw )

     #define REST r13
     #define REST r13 r14   SR r14( lwz )
     #define REST r13 r15   SR r14 r15( lwz )
     #define REST r13 r16   SR r14 r16( lwz )
     #define REST r13 r17   SR r14 r17( lwz )
     #define REST r13 r18   SR r14 r18( lwz )
     #define REST r13 r19   SR r14 r19( lwz )
     #define REST r13 r20   SR r14 r20( lwz )
     #define REST r13 r21   SR r14 r21( lwz )
     #define REST r13 r22   SR r14 r22( lwz )
     #define REST r13 r23   SR r14 r23( lwz )
     #define REST r13 r24   SR r14 r24( lwz )
     #define REST r13 r25   SR r14 r25( lwz )
     #define REST r13 r26   SR r14 r26( lwz )
     #define REST r13 r27   SR r14 r27( lwz )
     #define REST r13 r28   SR r14 r28( lwz )
     #define REST r13 r29   SR r14 r29( lwz )
     #define REST r13 r30   SR r14 r30( lwz )
     #define REST_r13_r31   SR_r14_r31( lwz )

     #else                              /* r13 is non-volatile */

     #define SAVE r13   SR_r13( stw )
     #define SAVE r13 r14   SR r13 r14( stw )
     #define SAVE r13 r15   SR r13 r15( stw )
     #define SAVE r13 r16   SR r13 r16( stw )
     #define SAVE r13 r17   SR r13 r17( stw )
     #define SAVE r13 r18   SR r13 r18( stw )
     #define SAVE r13 r19   SR r13 r19( stw )
     #define SAVE r13 r20   SR r13 r20( stw )
     #define SAVE r13 r21   SR r13 r21( stw )
     #define SAVE r13 r22   SR r13 r22( stw )
     #define SAVE r13 r23   SR r13 r23( stw )
     #define SAVE r13 r24   SR r13 r24( stw )
     #define SAVE r13 r25   SR r13 r25( stw )
     #define SAVE r13 r26   SR r13 r26( stw )
     #define SAVE r13 r27   SR r13 r27( stw )
     #define SAVE r13 r28   SR r13 r28( stw )
     #define SAVE r13 r29   SR r13 r29( stw )
     #define SAVE r13 r30   SR r13 r30( stw )
     #define SAVE_r13_r31   SR_r13_r31( stw )

     #define REST r13   SR_r13( lwz )
     #define REST r13 r14   SR r13 r14( lwz )
     #define REST r13 r15   SR r13 r15( lwz )
     #define REST r13 r16   SR r13 r16( lwz )
     #define REST r13 r17   SR r13 r17( lwz )
     #define REST r13 r18   SR r13 r18( lwz )
     #define REST r13 r19   SR r13 r19( lwz )
     #define REST r13 r20   SR r13 r20( lwz )
     #define REST r13 r21   SR r13 r21( lwz )
     #define REST r13 r22   SR r13 r22( lwz )
     #define REST r13 r23   SR r13 r23( lwz )
     #define REST r13 r24   SR r13 r24( lwz )
     #define REST_r13_r25   SR_r13_r25( lwz )
```
45

```
#define REST r13 r26    SR r13 r26( lwz )
#define REST r13 r27    SR r13 r27( lwz )
#define REST r13 r28    SR r13 r28( lwz )
#define REST r13 r29    SR r13 r29( lwz )
#define REST r13 r30    SR r13 r30( lwz )
#define REST_r13_r31    SR_r13_r31( lwz )


/*
 *   macros common to both GPR save and restore
 */
#define SR r13( opcode ) \
    opcode r13, (GPR_SAVE OFF + 18*4)(sp);
#define SR r13_r14( opcode ) \
    opcode r14, (GPR_SAVE_OFF + 17*4)(sp); \
    SR r13( opcode )
#define SR r13_r15( opcode ) \
    opcode r15, (GPR SAVE_OFF + 16*4)(sp); \
    SR r13 r14( opcode )
#define SR r13_r16( opcode ) \
    opcode r16, (GPR SAVE_OFF + 15*4)(sp); \
    SR r13 r15( opcode )
#define SR r13_r17( opcode ) \
    opcode r17, (GPR SAVE_OFF + 14*4)(sp); \
    SR r13 r16( opcode )
#define SR r13_r18( opcode ) \
    opcode r18, (GPR SAVE_OFF + 13*4)(sp); \
    SR r13 r17( opcode )
#define SR r13_r19( opcode ) \
    opcode r19, (GPR SAVE_OFF + 12*4)(sp); \
    SR r13 r18( opcode )
#define SR r13_r20( opcode ) \
    opcode r20, (GPR SAVE_OFF + 11*4)(sp); \
    SR r13 r19( opcode )
#define SR r13_r21( opcode ) \
    opcode r21, (GPR SAVE_OFF + 10*4)(sp); \
    SR r13 r20( opcode )
#define SR r13_r22( opcode ) \
    opcode r22, (GPR SAVE_OFF + 9*4)(sp); \
    SR r13 r21( opcode )
#define SR r13_r23( opcode ) \
    opcode r23, (GPR SAVE_OFF + 8*4)(sp); \
    SR r13 r22( opcode )
#define SR r13_r24( opcode ) \
    opcode r24, (GPR SAVE_OFF + 7*4)(sp); \
    SR r13 r23( opcode )
#define SR r13_r25( opcode ) \
    opcode r25, (GPR SAVE_OFF + 6*4)(sp); \
    SR r13 r24( opcode )
#define SR r13_r26( opcode ) \
    opcode r26, (GPR SAVE_OFF + 5*4)(sp); \
    SR r13 r25( opcode )
#define SR r13_r27( opcode ) \
    opcode r27, (GPR SAVE_OFF + 4*4)(sp); \
    SR r13 r26( opcode )
#define SR r13_r28( opcode ) \
    opcode r28, (GPR SAVE_OFF + 3*4)(sp); \
    SR r13 r27( opcode )
#define SR r13_r29( opcode ) \
    opcode r29, (GPR SAVE_OFF + 2*4)(sp); \
    SR r13 r28( opcode )
#define SR r13_r30( opcode ) \
    opcode r30, (GPR SAVE_OFF + 1*4)(sp); \
    SR r13 r29( opcode )
#define SR r13_r31( opcode ) \
    opcode r31, (GPR SAVE_OFF)(sp); \
    SR_r13_r30( opcode )
```

46

salppc.inc   3/9/2001

```
#endif                                    /* end VOLATILE_r13 */

#define SAVE r14      SR_r14( stw )
#define SAVE r14 r15  SR r14 r15( stw )
#define SAVE r14 r16  SR r14 r16( stw )
#define SAVE r14 r17  SR r14 r17( stw )
#define SAVE r14 r18  SR r14 r18( stw )
#define SAVE r14 r19  SR r14 r19( stw )
#define SAVE r14 r20  SR r14 r20( stw )
#define SAVE r14 r21  SR r14 r21( stw )
#define SAVE r14 r22  SR r14 r22( stw )
#define SAVE r14 r23  SR r14 r23( stw )
#define SAVE r14 r24  SR r14 r24( stw )
#define SAVE r14 r25  SR r14 r25( stw )
#define SAVE r14 r26  SR r14 r26( stw )
#define SAVE r14 r27  SR r14 r27( stw )
#define SAVE r14 r28  SR r14 r28( stw )
#define SAVE r14 r29  SR r14 r29( stw )
#define SAVE r14 r30  SR r14 r30( stw )
#define SAVE_r14_r31  SR_r14_r31( stw )

#define REST r14      SR_r14( lwz )
#define REST r14 r15  SR r14 r15( lwz )
#define REST r14 r16  SR r14 r16( lwz )
#define REST r14 r17  SR r14 r17( lwz )
#define REST r14 r18  SR r14 r18( lwz )
#define REST r14 r19  SR r14 r19( lwz )
#define REST r14 r20  SR r14 r20( lwz )
#define REST r14 r21  SR r14 r21( lwz )
#define REST r14 r22  SR r14 r22( lwz )
#define REST r14 r23  SR r14 r23( lwz )
#define REST r14 r24  SR r14 r24( lwz )
#define REST r14 r25  SR r14 r25( lwz )
#define REST r14 r26  SR r14 r26( lwz )
#define REST r14 r27  SR r14 r27( lwz )
#define REST r14 r28  SR r14 r28( lwz )
#define REST r14 r29  SR r14 r29( lwz )
#define REST r14 r30  SR r14 r30( lwz )
#define REST_r14_r31  SR_r14_r31( lwz )

/*
 *   macros common to both GPR save and restore
 */
#define SR r14( opcode ) \
    opcode r14, (GPR_SAVE OFF + 17*4)(sp);
#define SR r14_r15( opcode ) \
    opcode r15, (GPR_SAVE_OFF + 16*4)(sp); \
    SR r14( opcode )
#define SR r14_r16( opcode ) \
    opcode r16, (GPR SAVE_OFF + 15*4)(sp); \
    SR r14 r15( opcode )
#define SR r14_r17( opcode ) \
    opcode r17, (GPR SAVE_OFF + 14*4)(sp); \
    SR r14 r16( opcode )
#define SR r14_r18( opcode ) \
    opcode r18, (GPR SAVE_OFF + 13*4)(sp); \
    SR r14 r17( opcode )
#define SR r14_r19( opcode ) \
    opcode r19, (GPR SAVE_OFF + 12*4)(sp); \
    SR r14 r18( opcode )
#define SR r14_r20( opcode ) \
    opcode r20, (GPR SAVE_OFF + 11*4)(sp); \
    SR r14 r19( opcode )
#define SR r14_r21( opcode ) \
    opcode r21, (GPR SAVE_OFF + 10*4)(sp); \
    SR r14 r20( opcode )
#define SR_r14_r22( opcode ) \
```

47

```
      opcode r22, (GPR SAVE_OFF + 9*4)(sp); \
      SR_r14_r21( opcode )
#define SR_r14_r23( opcode ) \
      opcode r23, (GPR SAVE_OFF + 8*4)(sp); \
      SR_r14_r22( opcode )
#define SR_r14_r24( opcode ) \
      opcode r24, (GPR SAVE_OFF + 7*4)(sp); \
      SR_r14_r23( opcode )
#define SR_r14_r25( opcode ) \
      opcode r25, (GPR SAVE_OFF + 6*4)(sp); \
      SR_r14_r24( opcode )
#define SR_r14_r26( opcode ) \
      opcode r26, (GPR SAVE_OFF + 5*4)(sp); \
      SR_r14_r25( opcode )
#define SR_r14_r27( opcode ) \
      opcode r27, (GPR SAVE_OFF + 4*4)(sp); \
      SR_r14_r26( opcode )
#define SR_r14_r28( opcode ) \
      opcode r28, (GPR SAVE_OFF + 3*4)(sp); \
      SR_r14_r27( opcode )
#define SR_r14_r29( opcode ) \
      opcode r29, (GPR SAVE_OFF + 2*4)(sp); \
      SR_r14_r28( opcode )
#define SR_r14_r30( opcode ) \
      opcode r30, (GPR SAVE_OFF + 1*4)(sp); \
      SR_r14_r29( opcode )
#define SR_r14_r31( opcode ) \
      opcode r31, (GPR SAVE_OFF)(sp); \
      SR_r14_r30( opcode )

#define SAVE_r15     SR_r15( stw )
#define SAVE_r15_r16  SR_r15_r16( stw )
#define SAVE_r15_r17  SR_r15_r17( stw )
#define SAVE_r15_r18  SR_r15_r18( stw )
#define SAVE_r15_r19  SR_r15_r19( stw )
#define SAVE_r15_r20  SR_r15_r20( stw )
#define SAVE_r15_r21  SR_r15_r21( stw )
#define SAVE_r15_r22  SR_r15_r22( stw )
#define SAVE_r15_r23  SR_r15_r23( stw )
#define SAVE_r15_r24  SR_r15_r24( stw )
#define SAVE_r15_r25  SR_r15_r25( stw )
#define SAVE_r15_r26  SR_r15_r26( stw )
#define SAVE_r15_r27  SR_r15_r27( stw )
#define SAVE_r15_r28  SR_r15_r28( stw )
#define SAVE_r15_r29  SR_r15_r29( stw )
#define SAVE_r15_r30  SR_r15_r30( stw )
#define SAVE_r15_r31  SR_r15_r31( stw )

#define REST_r15     SR_r15( lwz )
#define REST_r15_r16  SR_r15_r16( lwz )
#define REST_r15_r17  SR_r15_r17( lwz )
#define REST_r15_r18  SR_r15_r18( lwz )
#define REST_r15_r19  SR_r15_r19( lwz )
#define REST_r15_r20  SR_r15_r20( lwz )
#define REST_r15_r21  SR_r15_r21( lwz )
#define REST_r15_r22  SR_r15_r22( lwz )
#define REST_r15_r23  SR_r15_r23( lwz )
#define REST_r15_r24  SR_r15_r24( lwz )
#define REST_r15_r25  SR_r15_r25( lwz )
#define REST_r15_r26  SR_r15_r26( lwz )
#define REST_r15_r27  SR_r15_r27( lwz )
#define REST_r15_r28  SR_r15_r28( lwz )
#define REST_r15_r29  SR_r15_r29( lwz )
#define REST_r15_r30  SR_r15_r30( lwz )
#define REST_r15_r31  SR_r15_r31( lwz )

      /*
```

48

salppc.inc

```
*  macros common to both GPR save and restore
*/
#define SR_r15( opcode ) \
    opcode r15, (GPR_SAVE_OFF + 16*4)(sp);
#define SR_r15_r16( opcode ) \
    opcode r16, (GPR_SAVE_OFF + 15*4)(sp); \
    SR_r15( opcode )
#define SR_r15_r17( opcode ) \
    opcode r17, (GPR_SAVE_OFF + 14*4)(sp); \
    SR_r15_r16( opcode )
#define SR_r15_r18( opcode ) \
    opcode r18, (GPR_SAVE_OFF + 13*4)(sp); \
    SR_r15_r17( opcode )
#define SR_r15_r19( opcode ) \
    opcode r19, (GPR_SAVE_OFF + 12*4)(sp); \
    SR_r15_r18( opcode )
#define SR_r15_r20( opcode ) \
    opcode r20, (GPR_SAVE_OFF + 11*4)(sp); \
    SR_r15_r19( opcode )
#define SR_r15_r21( opcode ) \
    opcode r21, (GPR_SAVE_OFF + 10*4)(sp); \
    SR_r15_r20( opcode )
#define SR_r15_r22( opcode ) \
    opcode r22, (GPR_SAVE_OFF + 9*4)(sp); \
    SR_r15_r21( opcode )
#define SR_r15_r23( opcode ) \
    opcode r23, (GPR_SAVE_OFF + 8*4)(sp); \
    SR_r15_r22( opcode )
#define SR_r15_r24( opcode ) \
    opcode r24, (GPR_SAVE_OFF + 7*4)(sp); \
    SR_r15_r23( opcode )
#define SR_r15_r25( opcode ) \
    opcode r25, (GPR_SAVE_OFF + 6*4)(sp); \
    SR_r15_r24( opcode )
#define SR_r15_r26( opcode ) \
    opcode r26, (GPR_SAVE_OFF + 5*4)(sp); \
    SR_r15_r25( opcode )
#define SR_r15_r27( opcode ) \
    opcode r27, (GPR_SAVE_OFF + 4*4)(sp); \
    SR_r15_r26( opcode )
#define SR_r15_r28( opcode ) \
    opcode r28, (GPR_SAVE_OFF + 3*4)(sp); \
    SR_r15_r27( opcode )
#define SR_r15_r29( opcode ) \
    opcode r29, (GPR_SAVE_OFF + 2*4)(sp); \
    SR_r15_r28( opcode )
#define SR_r15_r30( opcode ) \
    opcode r30, (GPR_SAVE_OFF + 1*4)(sp); \
    SR_r15_r29( opcode )
#define SR_r15_r31( opcode ) \
    opcode r31, (GPR_SAVE_OFF)(sp); \
    SR_r15_r30( opcode )

#define SAVE_r16      SR_r16( stw )
#define SAVE_r16_r17  SR_r16_r17( stw )
#define SAVE_r16_r18  SR_r16_r18( stw )
#define SAVE_r16_r19  SR_r16_r19( stw )
#define SAVE_r16_r20  SR_r16_r20( stw )
#define SAVE_r16_r21  SR_r16_r21( stw )
#define SAVE_r16_r22  SR_r16_r22( stw )
#define SAVE_r16_r23  SR_r16_r23( stw )
#define SAVE_r16_r24  SR_r16_r24( stw )
#define SAVE_r16_r25  SR_r16_r25( stw )
#define SAVE_r16_r26  SR_r16_r26( stw )
#define SAVE_r16_r27  SR_r16_r27( stw )
#define SAVE_r16_r28  SR_r16_r28( stw )
#define SAVE_r16_r29  SR_r16_r29( stw )
```

49

```
             salppc.inc                                              3/9/2001

    #define SAVE r16 r30   SR r16 r30( stw )
    #define SAVE_r16_r31   SR_r16_r31( stw )

    #define REST r16   SR_r16( lwz )
    #define REST r16 r17   SR r16 r17( lwz )
    #define REST r16 r18   SR r16 r18( lwz )
    #define REST r16 r19   SR r16 r19( lwz )
    #define REST r16 r20   SR r16 r20( lwz )
    #define REST r16 r21   SR r16 r21( lwz )
    #define REST r16 r22   SR r16 r22( lwz )
    #define REST r16 r23   SR r16 r23( lwz )
    #define REST r16 r24   SR r16 r24( lwz )
    #define REST r16 r25   SR r16 r25( lwz )
    #define REST r16 r26   SR r16 r26( lwz )
    #define REST r16 r27   SR r16 r27( lwz )
    #define REST r16 r28   SR r16 r28( lwz )
    #define REST r16 r29   SR r16 r29( lwz )
    #define REST r16 r30   SR r16 r30( lwz )
    #define REST_r16_r31   SR_r16_r31( lwz )

    /*
     *   macros common to both GPR save and restore
     */
    #define SR r16( opcode ) \
       opcode r16, (GPR_SAVE_OFF + 15*4)(sp);
    #define SR r16_r17( opcode ) \
       opcode r17, (GPR_SAVE_OFF + 14*4)(sp); \
       SR r16( opcode )
    #define SR r16_r18( opcode ) \
       opcode r18, (GPR_SAVE_OFF + 13*4)(sp); \
       SR r16 r17( opcode )
    #define SR r16_r19( opcode ) \
       opcode r19, (GPR_SAVE_OFF + 12*4)(sp); \
       SR r16 r18( opcode )
    #define SR r16_r20( opcode ) \
       opcode r20, (GPR_SAVE_OFF + 11*4)(sp); \
       SR r16 r19( opcode )
    #define SR r16_r21( opcode ) \
       opcode r21, (GPR_SAVE_OFF + 10*4)(sp); \
       SR r16 r20( opcode )
    #define SR r16_r22( opcode ) \
       opcode r22, (GPR_SAVE_OFF + 9*4)(sp); \
       SR r16 r21( opcode )
    #define SR r16_r23( opcode ) \
       opcode r23, (GPR_SAVE_OFF + 8*4)(sp); \
       SR r16 r22( opcode )
    #define SR r16_r24( opcode ) \
       opcode r24, (GPR_SAVE_OFF + 7*4)(sp); \
       SR r16 r23( opcode )
    #define SR r16_r25( opcode ) \
       opcode r25, (GPR_SAVE_OFF + 6*4)(sp); \
       SR r16 r24( opcode )
    #define SR r16_r26( opcode ) \
       opcode r26, (GPR_SAVE_OFF + 5*4)(sp); \
       SR r16 r25( opcode )
    #define SR r16_r27( opcode ) \
       opcode r27, (GPR_SAVE_OFF + 4*4)(sp); \
       SR r16 r26( opcode )
    #define SR r16_r28( opcode ) \
       opcode r28, (GPR_SAVE_OFF + 3*4)(sp); \
       SR r16 r27( opcode )
    #define SR r16_r29( opcode ) \
       opcode r29, (GPR_SAVE_OFF + 2*4)(sp); \
       SR r16 r28( opcode )
    #define SR r16_r30( opcode ) \
       opcode r30, (GPR_SAVE_OFF + 1*4)(sp); \
       SR_r16_r29( opcode )
```

50

salppc.inc   3/9/2001

```
#define SR_r16_r31( opcode ) \
    opcode r31, (GPR_SAVE_OFF)(sp); \
    SR_r16_r30( opcode )

#if defined( BUILD_MAX )

/*
 *   macros for saving and restoring non-volatile
 *   vector registers (VRs)
 *   (uses r0 as scratch register)
 */
#define SAVE_v20     SR_v20( stvx )
#define SAVE_v20_v21  SR_v20_v21( stvx )
#define SAVE_v20_v22  SR_v20_v22( stvx )
#define SAVE_v20_v23  SR_v20_v23( stvx )
#define SAVE_v20_v24  SR_v20_v24( stvx )
#define SAVE_v20_v25  SR_v20_v25( stvx )
#define SAVE_v20_v26  SR_v20_v26( stvx )
#define SAVE_v20_v27  SR_v20_v27( stvx )
#define SAVE_v20_v28  SR_v20_v28( stvx )
#define SAVE_v20_v29  SR_v20_v29( stvx )
#define SAVE_v20_v30  SR_v20_v30( stvx )
#define SAVE_v20_v31  SR_v20_v31( stvx )

#define REST_v20     SR_v20( lvx )
#define REST_v20_v21  SR_v20_v21( lvx )
#define REST_v20_v22  SR_v20_v22( lvx )
#define REST_v20_v23  SR_v20_v23( lvx )
#define REST_v20_v24  SR_v20_v24( lvx )
#define REST_v20_v25  SR_v20_v25( lvx )
#define REST_v20_v26  SR_v20_v26( lvx )
#define REST_v20_v27  SR_v20_v27( lvx )
#define REST_v20_v28  SR_v20_v28( lvx )
#define REST_v20_v29  SR_v20_v29( lvx )
#define REST_v20_v30  SR_v20_v30( lvx )
#define REST_v20_v31  SR_v20_v31( lvx )

/*
 *   macros common to both VR save and restore
 *   (uses r0 as scratch register)
 */
#define SR_v20( opcode ) \
    li r0, (VR_SAVE_OFF + 11*16); \
    opcode v20, sp, r0;
#define SR_v20_v21( opcode ) \
    li r0, (VR_SAVE_OFF + 10*16); \
    opcode v21, sp, r0; \
    SR_v20( opcode )
#define SR_v20_v22( opcode ) \
    li r0, (VR_SAVE_OFF + 9*16); \
    opcode v22, sp, r0; \
    SR_v20_v21( opcode )
#define SR_v20_v23( opcode ) \
    li r0, (VR_SAVE_OFF + 8*16); \
    opcode v23, sp, r0; \
    SR_v20_v22( opcode )
#define SR_v20_v24( opcode ) \
    li r0, (VR_SAVE_OFF + 7*16); \
    opcode v24, sp, r0; \
    SR_v20_v23( opcode )
#define SR_v20_v25( opcode ) \
    li r0, (VR_SAVE_OFF + 6*16); \
    opcode v25, sp, r0; \
    SR_v20_v24( opcode )
#define SR_v20_v26( opcode ) \
    li r0, (VR_SAVE_OFF + 5*16); \
    opcode v26, sp, r0; \
```

51

```
        SR v20 v25( opcode )
#define SR v20 v27( opcode ) \
    li r0, (VR SAVE_OFF + 4*16); \
    opcode v27, sp, r0; \
    SR v20 v26( opcode )
#define SR v20 v28( opcode ) \
    li r0, (VR SAVE_OFF + 3*16); \
    opcode v28, sp, r0; \
    SR v20 v27( opcode )
#define SR v20 v29( opcode ) \
    li r0, (VR SAVE_OFF + 2*16); \
    opcode v29, sp, r0; \
    SR v20 v28( opcode )
#define SR v20 v30( opcode ) \
    li r0, (VR SAVE_OFF + 1*16); \
    opcode v30, sp, r0; \
    SR v20 v29( opcode )
#define SR v20 v31( opcode ) \
    li r0, (VR SAVE_OFF); \
    opcode v31, sp, r0; \
    SR_v20_v30( opcode )


/*
 *  macros for saving, updating and restoring VRSAVE and saving and
 *  restoring non-volatile vector registers (v0 - v31)
 *  (destroys r0 and CR0 field of CR)
 */
#define NON VOLATILE VR TEST( last vreg ) \
    andi. r0, r0, ((-1 << (31 - (last_vreg))) & 0x0fff);

#define RECORD v0 v15( last_vreg ) \
    oris r0, r0, ((-1 << (15 - (last_vreg))) & 0xffff); \
    mtspr %VRSAVE, r0;

#define RECORD v16 v31( last_vreg ) \
    oris r0, r0, 0xffff; \
    ori r0, r0, ((-1 << (31 - (last_vreg))) & 0xffff); \
    mtspr %VRSAVE, r0;

#define USE v0 v15( cond, last_vreg ) \
    mfspr r0, %VRSAVE; \
    cmplwi (cond), r0, 0; \
    beq (cond), PC OFFSET( 8 ); \
    stw r0, VRSAVE_SAVE OFF(sp); \
    RECORD_v0_v15( last_vreg )

#define USE v16 v19( cond, last_vreg ) \
    mfspr r0, %VRSAVE; \
    cmplwi (cond), r0, 0; \
    beq (cond), PC OFFSET( 8 ); \
    stw r0, VRSAVE SAVE OFF(sp); \
    RECORD_v16_v31( last_vreg )

#define FREE_v0_v19( cond ) \
    li r0, 0; \
    beq (cond), PC OFFSET( 8 ); \
    lwz r0, VRSAVE_SAVE_OFF(sp); \
    mtspr %VRSAVE, r0;

/*
 *  user-callable macros
 */
#define USE THRU v0( cond )     USE v0 v15( cond, 0 )
#define USE THRU v1( cond )     USE v0 v15( cond, 1 )
#define USE THRU v2( cond )     USE v0 v15( cond, 2 )
#define USE THRU v3( cond )     USE v0 v15( cond, 3 )
#define USE_THRU_v4( cond )     USE_v0_v15( cond, 4 )
```

52

salppc.inc   3/9/2001

```
#define USE THRU v5( cond )      USE v0 v15( cond, 5 )
#define USE THRU v6( cond )      USE v0 v15( cond, 6 )
#define USE THRU v7( cond )      USE v0 v15( cond, 7 )
#define USE THRU v8( cond )      USE v0 v15( cond, 8 )
#define USE THRU v9( cond )      USE v0 v15( cond, 9 )
#define USE THRU v10( cond )     USE v0 v15( cond, 10 )
#define USE THRU v11( cond )     USE v0 v15( cond, 11 )
#define USE THRU v12( cond )     USE v0 v15( cond, 12 )
#define USE THRU v13( cond )     USE v0 v15( cond, 13 )
#define USE THRU v14( cond )     USE v0 v15( cond, 14 )
#define USE THRU v15( cond )     USE v0 v15( cond, 15 )
#define USE THRU v16( cond )     USE v16 v19( cond, 16 )
#define USE THRU v17( cond )     USE v16 v19( cond, 17 )
#define USE THRU v18( cond )     USE v16 v19( cond, 18 )
#define USE_THRU_v19( cond )     USE_v16_v19( cond, 19 )

#define USE THRU v20( cond ) \
    mfspr r0, %VRSAVE; \
    cmplwi (cond), r0, 0; \
    beq (cond), PC_OFFSET( 32 );         /* cond set to equal if VRSAVE = 0 */
    \
    stw r0, VRSAVE SAVE OFF(sp); \
    NON_VOLATILE VR TEST( 20 )           /* v20 in use? */ \
    beq PC_OFFSET(16);                   /* no, cond is set to greater than */
    \
    SAVE v20                             /* leaves a negative value in r0 */ \
    cmpwi (cond), r0, 0x7fff;            /* cond is set to less than */ \
    mfspr r0, %VRSAVE;                   /* reload VRSAVE into r0 */ \
    RECORD_v16_v31( 20 )                 /* indicate v0 - v20 in use */

#define USE THRU v21( cond ) \
    mfspr r0, %VRSAVE; \
    cmplwi (cond), r0, 0; \
    beq (cond), PC_OFFSET(40);           /* cond set to equal if VRSAVE = 0 */
    \
    stw r0, VRSAVE SAVE OFF(sp); \
    NON_VOLATILE VR TEST( 21 )           /* v20 - v21 in use? */ \
    beq PC_OFFSET(24);                   /* no, cond is set to greater than */
    \
    SAVE v20 v21                         /* leaves a negative value in r0 */ \
    cmpwi (cond), r0, 0x7fff;            /* cond is set to less than */ \
    mfspr r0, %VRSAVE;                   /* reload VRSAVE into r0 */ \
    RECORD_v16_v31( 21 )                 /* indicate v0 - v21 in use */

#define USE THRU v22( cond ) \
    mfspr r0, %VRSAVE; \
    cmplwi (cond), r0, 0; \
    beq (cond), PC_OFFSET(48);           /* cond set to equal if VRSAVE = 0 */
    \
    stw r0, VRSAVE SAVE OFF(sp); \
    NON_VOLATILE VR TEST( 22 )           /* v20 - v22 in use? */ \
    beq PC_OFFSET(32);                   /* no, cond is set to greater than */
    \
    SAVE v20 v22                         /* leaves a negative value in r0 */ \
    cmpwi (cond), r0, 0x7fff;            /* cond is set to less than */ \
    mfspr r0, %VRSAVE;                   /* reload VRSAVE into r0 */ \
    RECORD_v16_v31( 22 )                 /* indicate v0 - v22 in use */

#define USE THRU v23( cond ) \
    mfspr r0, %VRSAVE; \
    cmplwi (cond), r0, 0; \
    beq (cond), PC_OFFSET(56);           /* cond set to equal if VRSAVE = 0 */
    \
    stw r0, VRSAVE SAVE OFF(sp); \
    NON_VOLATILE VR TEST( 23 )           /* v20 - v23 in use? */ \
    beq PC_OFFSET(40);                   /* no, cond is set to greater than */
    \
```

53

salppc.inc   3/9/2001

```
        SAVE v20 v23                        /* leaves a negative value in r0 */ \
        cmpwi (cond), r0, 0x7fff;           /* cond is set to less than */ \
        mfspr r0, %VRSAVE;                   /* reload VRSAVE into r0 */ \
        RECORD_v16_v31( 23 )                 /* indicate v0 - v23 in use */

#define USE THRU v24( cond ) \
        mfspr r0, %VRSAVE; \
        cmplwi (cond), r0, 0; \
        beq (cond), PC_OFFSET(64);          /* cond set to equal if VRSAVE = 0 */
        \
        stw r0, VRSAVE SAVE OFF(sp); \
        NON_VOLATILE VR TEST( 24 )           /* v20 - v24 in use? */ \
        beq PC_OFFSET(48);                   /* no, cond is set to greater than */
        \
        SAVE v20 v24                        /* leaves a negative value in r0 */ \
        cmpwi (cond), r0, 0x7fff;           /* cond is set to less than */ \
        mfspr r0, %VRSAVE;                   /* reload VRSAVE into r0 */ \
        RECORD_v16_v31( 24 )                 /* indicate v0 - v24 in use */

#define USE THRU v25( cond ) \
        mfspr r0, %VRSAVE; \
        cmplwi (cond), r0, 0; \
        beq (cond), PC_OFFSET(72);          /* cond set to equal if VRSAVE = 0 */
        \
        stw r0, VRSAVE SAVE OFF(sp); \
        NON_VOLATILE VR TEST( 25 )           /* v20 - v25 in use? */ \
        beq PC_OFFSET(56);                   /* no, cond is set to greater than */
        \
        SAVE v20 v25                        /* leaves a negative value in r0 */ \
        cmpwi (cond), r0, 0x7fff;           /* cond is set to less than */ \
        mfspr r0, %VRSAVE;                   /* reload VRSAVE into r0 */ \
        RECORD_v16_v31( 25 )                 /* indicate v0 - v25 in use */

#define USE THRU v26( cond ) \
        mfspr r0, %VRSAVE; \
        cmplwi (cond), r0, 0; \
        beq (cond), PC_OFFSET(80);          /* cond set to equal if VRSAVE = 0 */
        \
        stw r0, VRSAVE SAVE OFF(sp); \
        NON_VOLATILE VR TEST( 26 )           /* v20 - v26 in use? */ \
        beq PC_OFFSET(64);                   /* no, cond is set to greater than */
        \
        SAVE v20 v26                        /* leaves a negative value in r0 */ \
        cmpwi (cond), r0, 0x7fff;           /* cond is set to less than */ \
        mfspr r0, %VRSAVE;                   /* reload VRSAVE into r0 */ \
        RECORD_v16_v31( 26 )                 /* indicate v0 - v26 in use */

#define USE THRU v27( cond ) \
        mfspr r0, %VRSAVE; \
        cmplwi (cond), r0, 0; \
        beq (cond), PC_OFFSET(88);          /* cond set to equal if VRSAVE = 0 */
        \
        stw r0, VRSAVE SAVE OFF(sp); \
        NON_VOLATILE VR TEST( 27 )           /* v20 - v27 in use? */ \
        beq PC_OFFSET(72);                   /* no, cond is set to greater than */
        \
        SAVE v20 v27                        /* leaves a negative value in r0 */ \
        cmpwi (cond), r0, 0x7fff;           /* cond is set to less than */ \
        mfspr r0, %VRSAVE;                   /* reload VRSAVE into r0 */ \
        RECORD_v16_v31( 27 )                 /* indicate v0 - v27 in use */

#define USE THRU v28( cond ) \
        mfspr r0, %VRSAVE; \
        cmplwi (cond), r0, 0; \
        beq (cond), PC_OFFSET(96);          /* cond set to equal if VRSAVE = 0 */
        \
        stw r0, VRSAVE_SAVE_OFF(sp); \
```

54

salppc.inc   3/9/2001

```
        NON_VOLATILE VR TEST( 28 )              /* v20 - v28 in use? */ \
        beq PC_OFFSET(80);                      /* no, cond is set to greater than */
        \
        SAVE v20 v28                            /* leaves a negative value in r0 */ \
        cmpwi (cond), r0, 0x7fff;               /* cond is set to less than */ \
        mfspr r0, %VRSAVE;                       /* reload VRSAVE into r0 */ \
        RECORD_v16_v31( 28 )                     /* indicate v0 - v28 in use */

#define USE_THRU_v29( cond ) \
        mfspr r0, %VRSAVE; \
        cmplwi (cond), r0, 0; \
        beq (cond), PC_OFFSET(104);             /* cond set to equal if VRSAVE = 0 */
        \
        stw r0, VRSAVE_SAVE_OFF(sp); \
        NON_VOLATILE VR TEST( 29 )              /* v20 - v29 in use? */ \
        beq PC_OFFSET(88);                      /* no, cond is set to greater than */
        \
        SAVE v20 v29                            /* leaves a negative value in r0 */ \
        cmpwi (cond), r0, 0x7fff;               /* cond is set to less than */ \
        mfspr r0, %VRSAVE;                       /* reload VRSAVE into r0 */ \
        RECORD_v16_v31( 29 )                     /* indicate v0 - v29 in use */

#define USE_THRU_v30( cond ) \
        mfspr r0, %VRSAVE; \
        cmplwi (cond), r0, 0; \
        beq (cond), PC_OFFSET(112);             /* cond set to equal if VRSAVE = 0 */
        \
        stw r0, VRSAVE_SAVE_OFF(sp); \
        NON_VOLATILE VR TEST( 30 )              /* v20 - v30 in use? */ \
        beq PC_OFFSET(96);                      /* no, cond is set to greater than */
        \
        SAVE v20 v30                            /* leaves a negative value in r0 */ \
        cmpwi (cond), r0, 0x7fff;               /* cond is set to less than */ \
        mfspr r0, %VRSAVE;                       /* reload VRSAVE into r0 */ \
        RECORD_v16_v31( 30 )                     /* indicate v0 - v30 in use */

#define USE_THRU_v31( cond ) \
        mfspr r0, %VRSAVE; \
        cmplwi (cond), r0, 0; \
        beq (cond), PC_OFFSET(120);             /* cond set to equal if VRSAVE = 0 */
        \
        stw r0, VRSAVE_SAVE_OFF(sp); \
        NON_VOLATILE VR TEST( 31 )              /* v20 - v31 in use? */ \
        beq PC_OFFSET(104);                     /* no, cond is set to greater than */
        \
        SAVE v20 v31                            /* leaves a negative value in r0 */ \
        cmpwi (cond), r0, 0x7fff;               /* cond is set to less than */ \
        mfspr r0, %VRSAVE;                       /* reload VRSAVE into r0 */ \
        RECORD_v16_v31( 31 )                     /* indicate v0 - v31 in use */

#define FREE_THRU_v0( cond )     FREE_v0_v19( cond )
#define FREE_THRU_v1( cond )     FREE_v0_v19( cond )
#define FREE_THRU_v2( cond )     FREE_v0_v19( cond )
#define FREE_THRU_v3( cond )     FREE_v0_v19( cond )
#define FREE_THRU_v4( cond )     FREE_v0_v19( cond )
#define FREE_THRU_v5( cond )     FREE_v0_v19( cond )
#define FREE_THRU_v6( cond )     FREE_v0_v19( cond )
#define FREE_THRU_v7( cond )     FREE_v0_v19( cond )
#define FREE_THRU_v8( cond )     FREE_v0_v19( cond )
#define FREE_THRU_v9( cond )     FREE_v0_v19( cond )
#define FREE_THRU_v10( cond )    FREE_v0_v19( cond )
#define FREE_THRU_v11( cond )    FREE_v0_v19( cond )
#define FREE_THRU_v12( cond )    FREE_v0_v19( cond )
#define FREE_THRU_v13( cond )    FREE_v0_v19( cond )
#define FREE_THRU_v14( cond )    FREE_v0_v19( cond )
#define FREE_THRU_v15( cond )    FREE_v0_v19( cond )
#define FREE_THRU_v16( cond )    FREE_v0_v19( cond )
```

55

salppc.inc   3/9/2001

```
#define FREE_THRU_v17( cond )   FREE_v0_v19( cond )
#define FREE_THRU_v18( cond )   FREE_v0_v19( cond )
#define FREE_THRU_v19( cond )   FREE_v0_v19( cond )

#define FREE_THRU_v20( cond ) \
    li r0, 0; \
    beq (cond), PC_OFFSET(20); \
    bgt (cond), PC_OFFSET(12); \
    REST v20; \
    lwz r0, VRSAVE_SAVE_OFF(sp); \
    mtspr %VRSAVE, r0;

#define FREE_THRU_v21( cond ) \
    li r0, 0; \
    beq (cond), PC_OFFSET(28); \
    bgt (cond), PC_OFFSET(20); \
    REST v20 v21; \
    lwz r0, VRSAVE_SAVE_OFF(sp); \
    mtspr %VRSAVE, r0;

#define FREE_THRU_v22( cond ) \
    li r0, 0; \
    beq (cond), PC_OFFSET(36); \
    bgt (cond), PC_OFFSET(28); \
    REST v20 v22; \
    lwz r0, VRSAVE_SAVE_OFF(sp); \
    mtspr %VRSAVE, r0;

#define FREE_THRU_v23( cond ) \
    li r0, 0; \
    beq (cond), PC_OFFSET(44); \
    bgt (cond), PC_OFFSET(36); \
    REST v20 v23; \
    lwz r0, VRSAVE_SAVE_OFF(sp); \
    mtspr %VRSAVE, r0;

#define FREE_THRU_v24( cond ) \
    li r0, 0; \
    beq (cond), PC_OFFSET(52); \
    bgt (cond), PC_OFFSET(44); \
    REST v20 v24; \
    lwz r0, VRSAVE_SAVE_OFF(sp); \
    mtspr %VRSAVE, r0;

#define FREE_THRU_v25( cond ) \
    li r0, 0; \
    beq (cond), PC_OFFSET(60); \
    bgt (cond), PC_OFFSET(52); \
    REST v20 v25; \
    lwz r0, VRSAVE_SAVE_OFF(sp); \
    mtspr %VRSAVE, r0;

#define FREE_THRU_v26( cond ) \
    li r0, 0; \
    beq (cond), PC_OFFSET(68); \
    bgt (cond), PC_OFFSET(60); \
    REST v20 v26; \
    lwz r0, VRSAVE_SAVE_OFF(sp); \
    mtspr %VRSAVE, r0;

#define FREE_THRU_v27( cond ) \
    li r0, 0; \
    beq (cond), PC_OFFSET(76); \
    bgt (cond), PC_OFFSET(68); \
    REST v20 v27; \
    lwz r0, VRSAVE_SAVE_OFF(sp); \
    mtspr %VRSAVE, r0;
```

56

```
#define FREE_THRU_v28( cond ) \
    li r0, 0; \
    beq (cond), PC OFFSET(84); \
    bgt (cond), PC OFFSET(76); \
    REST v20 v28; \
    lwz r0, VRSAVE_SAVE_OFF(sp); \
    mtspr %VRSAVE, r0;

#define FREE_THRU_v29( cond ) \
    li r0, 0; \
    beq (cond), PC OFFSET(92); \
    bgt (cond), PC OFFSET(84); \
    REST v20 v29; \
    lwz r0, VRSAVE_SAVE_OFF(sp); \
    mtspr %VRSAVE, r0;

#define FREE_THRU_v30( cond ) \
    li r0, 0; \
    beq (cond), PC OFFSET(100); \
    bgt (cond), PC OFFSET(92); \
    REST v20 v30; \
    lwz r0, VRSAVE_SAVE_OFF(sp); \
    mtspr %VRSAVE, r0;

#define FREE_THRU_v31( cond ) \
    li r0, 0; \
    beq (cond), PC OFFSET(108); \
    bgt (cond), PC OFFSET(100); \
    REST v20 v31; \
    lwz r0, VRSAVE_SAVE_OFF(sp); \
    mtspr %VRSAVE, r0;

#endif                                   /* end BUILD_MAX */

/*
 *   macros to save and restore the CR register
 *   (uses r0 as scratch register)
 */
#define SAVE CR \
    mfcr r0; \
    stw r0, CR_SAVE_OFF(sp);

#define REST CR \
    lwz r0, CR_SAVE_OFF(sp); \
    mtcr r0;

/*
 *   macros to save and restore the LR register
 *   (uses r0 as scratch register)
 */
#define SAVE LR \
    mflr r0; \
    stw r0, LR_SAVE_OFF(sp);

#define REST LR \
    lwz r0, LR_SAVE_OFF(sp); \
    mtlr r0;

#endif                                   /* end COMPILE_C */

/*
 *   macros for declaring GPR, FPR and VMX registers
 */

/*
 *   declare r0
```

57

```
   */
   #define DECLARE_r0

   /*
    *  r3 declare set
    */
   #define DECLARE r3
   #define DECLARE r3 r4
   #define DECLARE r3 r5
   #define DECLARE r3 r6
   #define DECLARE r3 r7
   #define DECLARE r3 r8
   #define DECLARE r3 r9
   #define DECLARE r3 r10
   #define DECLARE r3 r11
   #define DECLARE r3 r12
   #define DECLARE r3 r13
   #define DECLARE r3 r14
   #define DECLARE r3 r15
   #define DECLARE r3 r16
   #define DECLARE r3 r17
   #define DECLARE r3 r18
   #define DECLARE r3 r19
   #define DECLARE r3 r20
   #define DECLARE r3 r21
   #define DECLARE r3 r22
   #define DECLARE r3 r23
   #define DECLARE r3 r24
   #define DECLARE r3 r25
   #define DECLARE r3 r26
   #define DECLARE r3 r27
   #define DECLARE r3 r28
   #define DECLARE r3 r29
   #define DECLARE r3 r30
   #define DECLARE_r3_r31

   /*
    *  r4 declare set
    */
   #define DECLARE r4
   #define DECLARE r4 r5
   #define DECLARE r4 r6
   #define DECLARE r4 r7
   #define DECLARE r4 r8
   #define DECLARE r4 r9
   #define DECLARE r4 r10
   #define DECLARE r4 r11
   #define DECLARE r4 r12
   #define DECLARE r4 r13
   #define DECLARE r4 r14
   #define DECLARE r4 r15
   #define DECLARE r4 r16
   #define DECLARE r4 r17
   #define DECLARE r4 r18
   #define DECLARE r4 r19
   #define DECLARE r4 r20
   #define DECLARE r4 r21
   #define DECLARE r4 r22
   #define DECLARE r4 r23
   #define DECLARE r4 r24
   #define DECLARE r4 r25
   #define DECLARE r4 r26
   #define DECLARE r4 r27
   #define DECLARE r4 r28
   #define DECLARE r4 r29
   #define DECLARE r4 r30
   #define DECLARE_r4_r31
```

58

```
                salppc.inc                                  3/9/2001


        /*
         *   r5 declare set
         */
        #define DECLARE  r5
        #define DECLARE  r5  r6
        #define DECLARE  r5  r7
        #define DECLARE  r5  r8
        #define DECLARE  r5  r9
        #define DECLARE  r5  r10
        #define DECLARE  r5  r11
        #define DECLARE  r5  r12
        #define DECLARE  r5  r13
        #define DECLARE  r5  r14
        #define DECLARE  r5  r15
        #define DECLARE  r5  r16
        #define DECLARE  r5  r17
        #define DECLARE  r5  r18
        #define DECLARE  r5  r19
        #define DECLARE  r5  r20
        #define DECLARE  r5  r21
        #define DECLARE  r5  r22
        #define DECLARE  r5  r23
        #define DECLARE  r5  r24
        #define DECLARE  r5  r25
        #define DECLARE  r5  r26
        #define DECLARE  r5  r27
        #define DECLARE  r5  r28
        #define DECLARE  r5  r29
        #define DECLARE  r5  r30
        #define DECLARE_r5_r31

        /*
         *   r6 declare set
         */
        #define DECLARE  r6
        #define DECLARE  r6  r7
        #define DECLARE  r6  r8
        #define DECLARE  r6  r9
        #define DECLARE  r6  r10
        #define DECLARE  r6  r11
        #define DECLARE  r6  r12
        #define DECLARE  r6  r13
        #define DECLARE  r6  r14
        #define DECLARE  r6  r15
        #define DECLARE  r6  r16
        #define DECLARE  r6  r17
        #define DECLARE  r6  r18
        #define DECLARE  r6  r19
        #define DECLARE  r6  r20
        #define DECLARE  r6  r21
        #define DECLARE  r6  r22
        #define DECLARE  r6  r23
        #define DECLARE  r6  r24
        #define DECLARE  r6  r25
        #define DECLARE  r6  r26
        #define DECLARE  r6  r27
        #define DECLARE  r6  r28
        #define DECLARE  r6  r29
        #define DECLARE  r6  r30
        #define DECLARE_r6_r31

        /*
         *   r7 declare set
         */
        #define DECLARE  r7
        #define DECLARE_r7_r8
```

59

salppc.inc   3/9/2001

```
#define DECLARE r7 r9
#define DECLARE r7 r10
#define DECLARE r7 r11
#define DECLARE r7 r12
#define DECLARE r7 r13
#define DECLARE r7 r14
#define DECLARE r7 r15
#define DECLARE r7 r16
#define DECLARE r7 r17
#define DECLARE r7 r18
#define DECLARE r7 r19
#define DECLARE r7 r20
#define DECLARE r7 r21
#define DECLARE r7 r22
#define DECLARE r7 r23
#define DECLARE r7 r24
#define DECLARE r7 r25
#define DECLARE r7 r26
#define DECLARE r7 r27
#define DECLARE r7 r28
#define DECLARE r7 r29
#define DECLARE r7 r30
#define DECLARE_r7_r31

/*
 *   r8 declare set
 */
#define DECLARE r8
#define DECLARE r8 r9
#define DECLARE r8 r10
#define DECLARE r8 r11
#define DECLARE r8 r12
#define DECLARE r8 r13
#define DECLARE r8 r14
#define DECLARE r8 r15
#define DECLARE r8 r16
#define DECLARE r8 r17
#define DECLARE r8 r18
#define DECLARE r8 r19
#define DECLARE r8 r20
#define DECLARE r8 r21
#define DECLARE r8 r22
#define DECLARE r8 r23
#define DECLARE r8 r24
#define DECLARE r8 r25
#define DECLARE r8 r26
#define DECLARE r8 r27
#define DECLARE r8 r28
#define DECLARE r8 r29
#define DECLARE r8 r30
#define DECLARE_r8_r31

/*
 *   r9 declare set
 */
#define DECLARE r9
#define DECLARE r9 r10
#define DECLARE r9 r11
#define DECLARE r9 r12
#define DECLARE r9 r13
#define DECLARE r9 r14
#define DECLARE r9 r15
#define DECLARE r9 r16
#define DECLARE r9 r17
#define DECLARE r9 r18
#define DECLARE r9 r19
#define DECLARE_r9_r20
```

60

salppc.inc   3/9/2001

```
#define DECLARE r9 r21
#define DECLARE r9 r22
#define DECLARE r9 r23
#define DECLARE r9 r24
#define DECLARE r9 r25
#define DECLARE r9 r26
#define DECLARE r9 r27
#define DECLARE r9 r28
#define DECLARE r9 r29
#define DECLARE r9 r30
#define DECLARE_r9_r31

/*
 *   r10 declare set
 */
#define DECLARE r10
#define DECLARE r10 r11
#define DECLARE r10 r12
#define DECLARE r10 r13
#define DECLARE r10 r14
#define DECLARE r10 r15
#define DECLARE r10 r16
#define DECLARE r10 r17
#define DECLARE r10 r18
#define DECLARE r10 r19
#define DECLARE r10 r20
#define DECLARE r10 r21
#define DECLARE r10 r22
#define DECLARE r10 r23
#define DECLARE r10 r24
#define DECLARE r10 r25
#define DECLARE r10 r26
#define DECLARE r10 r27
#define DECLARE r10 r28
#define DECLARE r10 r29
#define DECLARE r10 r30
#define DECLARE_r10_r31

/*
 *   r11 declare set
 */
#define DECLARE r11
#define DECLARE r11 r12
#define DECLARE r11 r13
#define DECLARE r11 r14
#define DECLARE r11 r15
#define DECLARE r11 r16
#define DECLARE r11 r17
#define DECLARE r11 r18
#define DECLARE r11 r19
#define DECLARE r11 r20
#define DECLARE r11 r21
#define DECLARE r11 r22
#define DECLARE r11 r23
#define DECLARE r11 r24
#define DECLARE r11 r25
#define DECLARE r11 r26
#define DECLARE r11 r27
#define DECLARE r11 r28
#define DECLARE r11 r29
#define DECLARE r11 r30
#define DECLARE_r11_r31

/*
 *   r12 declare set
 */
#define DECLARE_r12
```

61

salppc.inc   3/9/2001

```
#define DECLARE r12 r13
#define DECLARE r12 r14
#define DECLARE r12 r15
#define DECLARE r12 r16
#define DECLARE r12 r17
#define DECLARE r12 r18
#define DECLARE r12 r19
#define DECLARE r12 r20
#define DECLARE r12 r21
#define DECLARE r12 r22
#define DECLARE r12 r23
#define DECLARE r12 r24
#define DECLARE r12 r25
#define DECLARE r12 r26
#define DECLARE r12 r27
#define DECLARE r12 r28
#define DECLARE r12 r29
#define DECLARE r12 r30
#define DECLARE_r12_r31

/*
 *  r13 declare set
 */
#define DECLARE r13
#define DECLARE r13 r14
#define DECLARE r13 r15
#define DECLARE r13 r16
#define DECLARE r13 r17
#define DECLARE r13 r18
#define DECLARE r13 r19
#define DECLARE r13 r20
#define DECLARE r13 r21
#define DECLARE r13 r22
#define DECLARE r13 r23
#define DECLARE r13 r24
#define DECLARE r13 r25
#define DECLARE r13 r26
#define DECLARE r13 r27
#define DECLARE r13 r28
#define DECLARE r13 r29
#define DECLARE r13 r30
#define DECLARE_r13_r31

/*
 *  r14 declare set
 */
#define DECLARE r14
#define DECLARE r14 r15
#define DECLARE r14 r16
#define DECLARE r14 r17
#define DECLARE r14 r18
#define DECLARE r14 r19
#define DECLARE r14 r20
#define DECLARE r14 r21
#define DECLARE r14 r22
#define DECLARE r14 r23
#define DECLARE r14 r24
#define DECLARE r14 r25
#define DECLARE r14 r26
#define DECLARE r14 r27
#define DECLARE r14 r28
#define DECLARE r14 r29
#define DECLARE r14 r30
#define DECLARE_r14_r31

/*
 *  r15 declare set
```

62

salppc.inc   3/9/2001

```
 */
#define DECLARE r15
#define DECLARE r15 r16
#define DECLARE r15 r17
#define DECLARE r15 r18
#define DECLARE r15 r19
#define DECLARE r15 r20
#define DECLARE r15 r21
#define DECLARE r15 r22
#define DECLARE r15 r23
#define DECLARE r15 r24
#define DECLARE r15 r25
#define DECLARE r15 r26
#define DECLARE r15 r27
#define DECLARE r15 r28
#define DECLARE r15 r29
#define DECLARE r15 r30
#define DECLARE_r15_r31


/*
 *   r16 declare set
 */
#define DECLARE r16
#define DECLARE r16 r17
#define DECLARE r16 r18
#define DECLARE r16 r19
#define DECLARE r16 r20
#define DECLARE r16 r21
#define DECLARE r16 r22
#define DECLARE r16 r23
#define DECLARE r16 r24
#define DECLARE r16 r25
#define DECLARE r16 r26
#define DECLARE r16 r27
#define DECLARE r16 r28
#define DECLARE r16 r29
#define DECLARE r16 r30
#define DECLARE_r16_r31


/*
 *   r17 declare set
 */
#define DECLARE r17
#define DECLARE r17 r18
#define DECLARE r17 r19
#define DECLARE r17 r20
#define DECLARE r17 r21
#define DECLARE r17 r22
#define DECLARE r17 r23
#define DECLARE r17 r24
#define DECLARE r17 r25
#define DECLARE r17 r26
#define DECLARE r17 r27
#define DECLARE r17 r28
#define DECLARE r17 r29
#define DECLARE r17 r30
#define DECLARE_r17_r31


/*
 *   r18 declare set
 */
#define DECLARE r18
#define DECLARE r18 r19
#define DECLARE r18 r20
#define DECLARE r18 r21
#define DECLARE r18 r22
#define DECLARE_r18_r23
```

63

```
salppc.inc
         #define DECLARE r18 r24
         #define DECLARE r18 r25
         #define DECLARE r18 r26
         #define DECLARE r18 r27
         #define DECLARE r18 r28
         #define DECLARE r18 r29
         #define DECLARE r18 r30
         #define DECLARE_r18_r31

         /*
          *  r19 declare set
          */
         #define DECLARE r19
         #define DECLARE r19 r20
         #define DECLARE r19 r21
         #define DECLARE r19 r22
         #define DECLARE r19 r23
         #define DECLARE r19 r24
         #define DECLARE r19 r25
         #define DECLARE r19 r26
         #define DECLARE r19 r27
         #define DECLARE r19 r28
         #define DECLARE r19 r29
         #define DECLARE r19 r30
         #define DECLARE_r19_r31

         /*
          *  FPR single precision declare set
          */
         #define DECLARE f0
         #define DECLARE f0 f1
         #define DECLARE f0 f2
         #define DECLARE f0 f3
         #define DECLARE f0 f4
         #define DECLARE f0 f5
         #define DECLARE f0 f6
         #define DECLARE f0 f7
         #define DECLARE f0 f8
         #define DECLARE f0 f9
         #define DECLARE f0 f10
         #define DECLARE f0 f11
         #define DECLARE f0 f12
         #define DECLARE f0 f13
         #define DECLARE f0 f14
         #define DECLARE f0 f15
         #define DECLARE f0 f16
         #define DECLARE f0 f17
         #define DECLARE f0 f18
         #define DECLARE f0 f19
         #define DECLARE f0 f20
         #define DECLARE f0 f21
         #define DECLARE f0 f22
         #define DECLARE f0 f23
         #define DECLARE f0 f24
         #define DECLARE f0 f25
         #define DECLARE f0 f26
         #define DECLARE f0 f27
         #define DECLARE f0 f28
         #define DECLARE f0 f29
         #define DECLARE f0 f30
         #define DECLARE_f0_f31

         /*
          *  FPR double precision declare set
          */
         #define DECLARE d0
         #define DECLARE_d0_d1
```

64

```
            salppc.inc                                              3/9/2001
            #define DECLARE_d0_d2
            #define DECLARE_d0_d3
            #define DECLARE_d0_d4
            #define DECLARE_d0_d5
            #define DECLARE_d0_d6
            #define DECLARE_d0_d7
            #define DECLARE_d0_d8
            #define DECLARE_d0_d9
            #define DECLARE_d0_d10
            #define DECLARE_d0_d11
            #define DECLARE_d0_d12
            #define DECLARE_d0_d13
            #define DECLARE_d0_d14
            #define DECLARE_d0_d15
            #define DECLARE_d0_d16
            #define DECLARE_d0_d17
            #define DECLARE_d0_d18
            #define DECLARE_d0_d19
            #define DECLARE_d0_d20
            #define DECLARE_d0_d21
            #define DECLARE_d0_d22
            #define DECLARE_d0_d23
            #define DECLARE_d0_d24
            #define DECLARE_d0_d25
            #define DECLARE_d0_d26
            #define DECLARE_d0_d27
            #define DECLARE_d0_d28
            #define DECLARE_d0_d29
            #define DECLARE_d0_d30
            #define DECLARE_d0_d31

            /*
             *    VMX declare set
             */
            #define DECLARE_v0
            #define DECLARE_v0_v1
            #define DECLARE_v0_v2
            #define DECLARE_v0_v3
            #define DECLARE_v0_v4
            #define DECLARE_v0_v5
            #define DECLARE_v0_v6
            #define DECLARE_v0_v7
            #define DECLARE_v0_v8
            #define DECLARE_v0_v9
            #define DECLARE_v0_v10
            #define DECLARE_v0_v11
            #define DECLARE_v0_v12
            #define DECLARE_v0_v13
            #define DECLARE_v0_v14
            #define DECLARE_v0_v15
            #define DECLARE_v0_v16
            #define DECLARE_v0_v17
            #define DECLARE_v0_v18
            #define DECLARE_v0_v19
            #define DECLARE_v0_v20
            #define DECLARE_v0_v21
            #define DECLARE_v0_v22
            #define DECLARE_v0_v23
            #define DECLARE_v0_v24
            #define DECLARE_v0_v25
            #define DECLARE_v0_v26
            #define DECLARE_v0_v27
            #define DECLARE_v0_v28
            #define DECLARE_v0_v29
            #define DECLARE_v0_v30
            #define DECLARE_v0_v31
```

65

salppc.inc   3/9/2001

```
      #endif                                /* end SALPPC_INC */

      /*
       *-------------------------------------------------------------
       *
       *                    END OF FILE salppc.inc
       *
       *-------------------------------------------------------------
       */
```

```
/*-------------------------------------------------------------------+
|--- MC Standard Algorithms -- PPC Macro language Version   ---|
|-------------------------------------------------------------------|
|                                                                   |
|   File Name:    SVE3 8BIT.MAC                                     |
|   Description:  Sum the elements of 3 signed byte vectors         |
|                 each of length N.                                |
|                                                                   |
|   sve3_8bit ( char *A, char *B, char *C, long *SUM, int N )      |
|                                                                   |
|   Restrictions:  A, B and C must all be 16-byte aligned.         |
|                  N must be a multiple of 16 and >= 16.           |
|                                                                   |
|              Mercury Computer Systems, Inc.                      |
|              Copyright (c) 2000  All rights reserved             |
|                                                                   |
|   Revision      Date      Engineer  Reason                       |
|   --------      ----      --------  --------                     |
|      0.0       000605       fpl     Created                      |
+-------------------------------------------------------------------*/

#include "salppc.inc"

/**
 Input parameters
**/
#define A       r3
#define B       r4
#define C       r5
#define SUM     r6
#define N       r7

#define A0p     A
#define B0p     B
#define C0p     C
#define A1p     r8
#define B1p     r9
#define C1p     r10
#define index   r11

#define zero    v0
#define one     v1
#define a0      v2
#define a1      v3
#define b0      v4
#define b1      v5
#define c0      v6
#define c1      v7
#define sum0    v8
#define sum1    v9
#define sum2    v10

FUNC_PROLOG

ENTRY_5( sve3_8bit, A, B, C, SUM, N )

  USE_THRU_v10( VRSAVE_COND )

  LI( index, 0 )
        VXOR( zero, zero, zero )
  ADDIC( N, N, -32 )
    LVX( a0, A0p, index )
      VSPLTISB( one, 1 )
    LVX( b0, B0p, index )
  ADDI( A1p, A0p, 16 )
        VXOR( sum0, sum0, sum0 )
```

1

sve3_8bit.mac   2/23/2001

```
    ADDI( B1p, B0p, 16 )
          VXOR( sum1, sum1, sum1 )
    ADDI( C1p, C0p, 16 )
          VXOR( sum2, sum2, sum2 )
    BLT( do16 )

LABEL( loop )
  ADDIC C( N, N, -32 )
    LVX( c0, C0p, index )
          VMSUMMBM( sum0, a0, one, sum0 )
    LVX( a1, A1p, index )
          VMSUMMBM( sum1, b0, one, sum1 )
    LVX( b1, B1p, index )
          VMSUMMBM( sum2, c0, one, sum2 )
    LVX( c1, C1p, index )
  ADDI( index, index, 32 )
          VMSUMMBM( sum0, a1, one, sum0 )
    LVX( a0, A0p, index )
          VMSUMMBM( sum1, b1, one, sum1 )
    LVX( b0, B0p, index )
          VMSUMMBM( sum2, c1, one, sum2 )
    BGE( loop )

  CMPWI( N, -32 )
    BEQ( combine )

LABEL( do16 )
    LVX( c0, C0p, index )
          VMSUMMBM( sum0, a0, one, sum0 )
          VMSUMMBM( sum1, b0, one, sum1 )
          VMSUMMBM( sum2, c0, one, sum2 )

LABEL( combine )
          VADDUWM( sum0, sum0, sum1 )
          VADDUWM( sum0, sum0, sum2 )
          VSUMSWS( sum0, sum0, zero )
      VSPLTW( sum0, sum0, 3 )
    STVEWX( sum0, 0, SUM )

  FREE THRU_v10( VRSAVE_COND )
  RETURN

FUNC_EPILOG
```

2

voter_sync.vhd   3/9/2001

```
-- ***************************************************************
--****************************************************************
--**
--**   Majority Voter/Sync Control logic TOP LEVEL Module: voter_sync.vhd
--**
--**   Description: This Module is the top level of the
--**   Majority Voter and Raceway Sync Logic
--**
--**   Author      : Steven Imperiali
--**   Date        : 7-05-2000
--**   Date        : 10-25-2000 Modified cable clock and sync
--**
--****************************************************************
--
-- This PLD handles the following functions:
--        1) Raceway clock source and skew control
--        2) Raceway sync generation
--        3) Majority voter logic
--        4) I2C reset logic
--        5) Inverter for the HS LED signal


LIBRARY IEEE;
USE IEEE.STD LOGIC 1164.ALL;
USE STD.TEXTIO.ALL;
use ieee.std logic arith.all;
use ieee.std_logic_unsigned.all;

ENTITY voter_sync IS
  PORT(
        clk 66 pal6      :IN       std logic;
        clk 33 pal1      :IN       std logic;
        reset 0          :IN       std logic;
        x rst brd 0      :OUT      std logic;
        x rst brd 1      :OUT      std logic;
        pll rng sel      :OUT      std logic;
        pll freq sel     :OUT      std logic;
        fb sk sel        :OUT      std logic;
        fb dev by 2 0    :OUT      std logic;
        main sk sel0     :OUT      std logic;
        main sk sel1     :OUT      std logic;
        jk sk sel0       :OUT      std logic;
        jk sk sel1       :OUT      std logic;
        jx1 clk oe       :OUT      std logic;
        jx2 clk oe       :OUT      std logic;
        sw clk mode2_1   :IN       std logic vector(2 downto 1);
        mux clk sel0     :OUT      std logic;
        mux_clk_sel1     :OUT      std_logic;


        testn            :IN       std logic;
        tms0             :IN       std logic;
        rsync x nd0      :OUT      std logic;
        rsync x nd1      :OUT      std logic;
        rsync x nd2      :OUT      std logic;
        rsync x nd3      :OUT      std logic;
        rsync x pxb0     :OUT      std logic;
        rsync_x_xbar     :OUT      std_logic;

        nd0 resetreq 0   :IN       std logic;
        nd1 resetreq 0   :IN       std logic;
        nd2 resetreq 0   :IN       std logic;
        nd3 resetreq 0   :IN       std logic;
        pq resetreq_0    :IN       std logic;
        resetvote_0      :OUT      std_logic;

        nd0_ckstpreqnd0_0 :IN      std_logic;
```

1

voter_sync.vhd   3/9/2001

```
          nd0 ckstpreqnd1 0 :IN    std logic;
          nd0 ckstpreqnd2 0 :IN    std logic;
          nd0 ckstpreqnd3 0 :IN    std logic;
          nd0 ckstpreqpq 0  :IN    std logic;
          nd1 ckstpreqnd0 0 :IN    std logic;
          nd1 ckstpreqnd1 0 :IN    std logic;
          nd1 ckstpreqnd2 0 :IN    std logic;
          nd1 ckstpreqnd3 0 :IN    std logic;
          nd1 ckstpreqpq 0  :IN    std logic;
          nd2 ckstpreqnd0 0 :IN    std logic;
          nd2 ckstpreqnd1 0 :IN    std logic;
          nd2 ckstpreqnd2 0 :IN    std logic;
          nd2 ckstpreqnd3 0 :IN    std logic;
          nd2 ckstpreqpq 0  :IN    std logic;
          nd3 ckstpreqnd0 0 :IN    std logic;
          nd3 ckstpreqnd1 0 :IN    std logic;
          nd3 ckstpreqnd2 0 :IN    std logic;
          nd3 ckstpreqnd3 0 :IN    std logic;
          nd3 ckstpreqpq 0  :IN    std logic;
          pq ckstpreqnd0 0  :IN    std logic;
          pq ckstpreqnd1 0  :IN    std logic;
          pq ckstpreqnd2 0  :IN    std logic;
          pq ckstpreqnd3 0  :IN    std logic;
          pq ckstpreqpq_0   :IN    std logic;
          pq ckstopin 0     :OUT   std logic;
          nd0 ckstopin 0    :OUT   std logic;
          nd1 ckstopin 0    :OUT   std logic;
          nd2 ckstopin 0    :OUT   std logic;
          nd3_ckstopin_0    :OUT   std_logic;

          i2c_rst_0         :IN    std logic;
          sda               :INOUT std logic;
          scl               :INOUT std logic;
          pxb0 hs_led       :IN    std logic;
          hs_led            :OUT   std_logic
          );

END voter_sync;

ARCHITECTURE TOP_LEVEL_voter_sync OF voter_sync IS

--*************************************************************
--*************************************************************
--**   Component Declearation
--*************************************************************
--*************************************************************


COMPONENT m voter PORT(
          clk 66 pal6    :IN    std logic;
          reset 0        :IN    std logic;
          request0 0     :IN    std logic;
          request1 0     :IN    std logic;
          request2 0     :IN    std logic;
          request3 0     :IN    std logic;
          request4 0     :IN    std logic;
          healthy0 1     :IN    std logic;
          healthy1 1     :IN    std logic;
          healthy2 1     :IN    std logic;
          healthy3 1     :IN    std logic;
          healthy4 1     :IN    std logic;
          voteout_0      :OUT   std_logic);
END COMPONENT;


--*************************************************************
```

2

voter_sync.vhd   3/9/2001

```
--** Signals to Connect All of the Components Together
--****************************************************************

Signal healthy0 1         :std logic;
Signal healthy1 1         :std logic;
Signal healthy2 1         :std logic;
Signal healthy3 1         :std logic;
Signal healthy4_1         :std logic;
Signal sync d1            :std logic;
Signal sync d2            :std logic;
Signal sync d3            :std logic;
Signal nd0 ckstop_0, nd1_ckstop_0, nd2_ckstop_0, nd3_ckstop_0, pq_ckstop_0
:std logic;
Signal  g nd0 resetreq 0 :std logic;
Signal  g nd1 resetreq 0 :std logic;
Signal  g nd2 resetreq 0 :std logic;
Signal  g_nd3_resetreq_0 :std_logic;




BEGIN


--****************************************************************
--**   Begin Architecture Here (Instantiations)
--****************************************************************



nd0_ckstop voter : m_voter PORT Map(
        clk 66 pal6,
        reset 0,
        nd0 ckstpreqnd0 0,
        nd1 ckstpreqnd0 0,
        nd2 ckstpreqnd0 0,
        nd3 ckstpreqnd0 0,
        pq ckstpreqnd0_0,
        healthy0 1,
        healthy1 1,
        healthy2 1,
        healthy3 1,
        healthy4 1,
        nd0_ckstop_0);


nd1_ckstop voter : m_voter PORT Map(
        clk 66 pal6,
        reset 0,   .
        nd0 ckstpreqnd1 0,
        nd1 ckstpreqnd1 0,
        nd2 ckstpreqnd1 0,
        nd3 ckstpreqnd1 0,
        pq ckstpreqnd1_0,
        healthy0 1,
        healthy1 1,
        healthy2 1,
        healthy3 1,
        healthy4 1,
        nd1_ckstop_0);


nd2_ckstop voter : m_voter PORT Map(
        clk 66 pal6,
        reset 0,
        nd0 ckstpreqnd2 0,
        nd1 ckstpreqnd2 0,
        nd2_ckstpreqnd2_0,
```

3

voter_sync.vhd   3/9/2001

```
                nd3 ckstpreqnd2 0,
                pq ckstpreqnd2_0,
                healthy0 1,
                healthy1 1,
                healthy2 1,
                healthy3 1,
                healthy4 1,
                nd2_ckstop_0);


        nd3_ckstop voter : m_voter PORT Map(
                clk 66 pal6,
                reset 0,
                nd0 ckstpreqnd3 0,
                nd1 ckstpreqnd3 0,
                nd2 ckstpreqnd3 0,
                nd3 ckstpreqnd3 0,
                pq ckstpreqnd3_0,
                healthy0 1,
                healthy1 1,
                healthy2 1,
                healthy3 1,
                healthy4 1,
                nd3_ckstop_0);


        pq_ckstop voter : m voter PORT Map(
                clk 66 pal6,
                reset 0,
                nd0 ckstpreqpq 0,
                nd1 ckstpreqpq 0,
                nd2 ckstpreqpq 0,
                nd3 ckstpreqpq 0,
                pq ckstpreqpq_0,
                healthy0 1,
                healthy1 1,
                healthy2 1,
                healthy3 1,
                healthy4 1,
                pq_ckstop_0);



        -- ###################################################
        -- this section was added to force a board level reset when
        -- the 8240 has a watchdog failure.

        -- this should have been done by feeding the 8240's WDFAIL
        -- to the reset PLD instead of forcing the 8240's resetreq
        -- to drive all other resetrequests.

        g nd0 resetreq 0 <= nd0 resetreq 0 AND pq resetreq 0;
        g nd1 resetreq 0 <= nd1 resetreq 0 AND pq resetreq 0 ;
        g nd2 resetreq 0 <= nd2 resetreq 0 AND pq resetreq 0 ;
        g_nd3_resetreq_0 <= nd3_resetreq_0 AND pq_resetreq_0 ;

        -- ###################################################


        reset_req voter : m voter PORT Map(
                clk 66 pal6,
                reset 0,
                g nd0 resetreq 0,
                g nd1 resetreq 0,
                g nd2 resetreq 0,
                g_nd3_resetreq_0,
```

4

voter_sync.vhd   3/9/2001

```
        pq resetreq_0,
        healthy0 1,
        healthy1 1,
        healthy2 1,
        healthy3 1,
        healthy4 1,
        resetvote_0);


        healthy0 1 <= nd0 ckstop 0;
        healthy1 1 <= nd1 ckstop 0;
        healthy2 1 <= nd2 ckstop 0;
        healthy3 1 <= nd3 ckstop 0;
        healthy4_1 <= pq_ckstop_0;

        nd0 ckstopin 0    <= nd0 ckstop 0;
        nd1 ckstopin 0    <= nd1 ckstop 0;
        nd2 ckstopin 0    <= nd2 ckstop 0;
        nd3 ckstopin 0    <= nd3 ckstop 0;
        pq_ckstopin_0     <= pq_ckstop_0;



    WITH i2c_rst_0 SELECT

        sda <= clk_33_pall WHEN '0',
               'Z'         WHEN '1',
        'Z'     WHEN OTHERS;

    WITH i2c_rst_0 SELECT

        scl <= clk_33_pall WHEN '0',
               'Z'         WHEN '1',
        'Z'     WHEN OTHERS;



        hs_led  <= NOT(pxb0_hs_led);



-- Sync Control
process(clk_66_pal6,reset_0)
BEGIN
        IF (reset 0 = '0') THEN
                sync d1          <= '1';
                sync d2          <= '1';
                sync d3          <= '1';
                rsync x nd0      <= '0';
                rsync x nd1      <= '0';
                rsync x nd2      <= '0';
                rsync x nd3      <= '0';
                rsync x pxb0     <= '0';
                rsync_x_xbar     <= '0';

        ELSIF (testn = '0' AND reset 0 = '1') THEN
                rsync x nd0      <= tms0;
                rsync x nd1      <= tms0;
                rsync x nd2      <= tms0;
                rsync x nd3      <= tms0;
                rsync x pxb0     <= '0';
                rsync_x_xbar     <= '0';

        ELSIF rising edge(clk 66 pal6) THEN
                sync d1 <= NOT(sync d1);
                sync_d2 <= (NOT(sync_d2) AND sync_d1 OR sync_d2 AND
```

5

voter_sync.vhd   3/9/2001

```
                    NOT(sync d1))
                    sync d3 <= (NOT(NOT(sync d1) AND sync_d2));
                    rsync x nd0      <= sync d3;
                    rsync x nd1      <= sync d3;
                    rsync x nd2      <= sync d3;
                    rsync x nd3      <= sync d3;
                    rsync x pxb0     <= sync d3;
                    rsync_x_xbar     <= sync_d3;
            END IF;
            END process;


    x rst brd 0 <= reset 0;
    x_rst_brd_1 <= NOT(reset_0);



    WITH sw clk mode2 1 SELECT
    mux_clk_sel0     <=        '0'     WHEN    "00",    -- 66MHz local
                                       '0'     WHEN    "01",    -- 33MHz cable 1
                               '1' WHEN    "10",    -- 33MHz cable 2
                                       '0'     WHEN    "11",    -- 66 MHz local
                                       '1'     WHEN OTHERS;


    WITH sw clk mode2 1 SELECT
    mux_clk_sel1     <=        '0'     WHEN    "00",
                                       '1'     WHEN    "01",
                               '1' WHEN    "10",
                                       '0'     WHEN    "11",
                               '1'       WHEN OTHERS;


    WITH sw clk mode2 1 SELECT
    fb_dev_by_2_0    <=        '0'     WHEN    "00",
                                       'Z'     WHEN    "01",
                               'Z' WHEN    "10",
                                       '0'     WHEN    "11",
                               '1'       WHEN OTHERS;


    WITH sw clk_mode2 1 SELECT
    jx1_clk_oe       <=        '1'     WHEN    "00",
                               '1' WHEN    "01",
                               '1'     WHEN    "10",
                               '1' WHEN    "11",
                               '1'       WHEN OTHERS;


    WITH sw clk_mode2 1 SELECT
    jx2_clk_oe       <=        '1'     WHEN    "00",
                               '1' WHEN    "01",
                               '1'     WHEN    "10",
                               '1' WHEN    "11",
                               '1'       WHEN OTHERS;



    WITH sw clk_mode2 1 SELECT
    pll_rng_sel      <=        '1'     WHEN    "00",
                                       '1'     WHEN    "01",
                               '1' WHEN    "10",
                                       '1'     WHEN    "11",
                               '1'       WHEN OTHERS;

    WITH sw clk mode2 1 SELECT
    pll_freq_sel     <=        'Z'     WHEN    "00",
                                       '0'     WHEN    "01",
                               '0' WHEN    "10",
                                       'Z'     WHEN    "11",
```

6

```
                              '1'      WHEN OTHERS;


        -- select 0 skew for all modes

        WITH sw_clk mode2_1 SELECT
                fb_sk_sel <=    'Z'     WHEN     "00",
                                'Z'     WHEN     "01",
                        'Z'     WHEN     "10",
                                'Z'     WHEN     "11",
                        '1'     WHEN OTHERS;

        WITH sw_clk mode2 1 SELECT
                main_sk_sel0 <= 'Z'     WHEN     "00",
                                'Z'     WHEN     "01",
                        'Z'     WHEN     "10",
                                'Z'     WHEN     "11",
                        '1'     WHEN OTHERS;

        WITH sw_clk mode2 1 SELECT
                main_sk_sel1 <= 'Z'     WHEN     "00",
                                'Z'     WHEN     "01",
                        'Z'     WHEN     "10",
                                'Z'     WHEN     "11",
                        '1'     WHEN OTHERS;

        WITH sw_clk mode2 1 SELECT
                jk_sk_sel0 <=   'Z'     WHEN     "00",
                                'Z'     WHEN     "01",
                        'Z'     WHEN     "10",
                                'Z'     WHEN     "11",
                        '1'     WHEN OTHERS;

        WITH sw_clk mode2 1 SELECT
                jk_sk_sel1 <=   'Z'     WHEN     "00",
                                'Z'     WHEN     "01",
                        'Z'     WHEN     "10",
                                'Z'     WHEN     "11",
                        '1'     WHEN OTHERS;


        END TOP_LEVEL_voter_sync;
```

7

zdotpr4_vmx.k   2/23/2001

```
/*-------------------------------------------------------------+
|--- MC Standard Algorithms -- PPC Macro language Version   ---|
|-------------------------------------------------------------|
|                                                             |
|  File Name:    ZDOTPR4 VMX.K                                 |
|  Description:  CPP Source code for Vector Single Precision   |
|               Split Complex Dot Product given that input    |
|               vectors are relivatively unaligned.           |
|                                                             |
|  Entry/params: ZDOTPR4 VMX (A, I, B, J, C, N)               |
|               _ZIDOTPR4_VMX (A, I, B, J, C, N)              |
|                                                             |
|  Formula: C[0] = sum (A->realp[mI]*B->realp[mJ]             |
|                       -/+ A->imagp[mI]*B->imagp[mJ])        |
|          C[1] = sum (A->realp[mI]*B->imagp[mJ]              |
|                       +/- A->imagp[mI]*B->realp[mJ])        |
|                   for m=0 to N-1                            |
|                                                             |
|            Mercury Computer Systems, Inc.                   |
|            Copyright (c) 2000  All rights reserved          |
|                                                             |
|  Revision   Date     Engineer Reason                        |
|  --------   ----     -------- -------                        |
|    0.0     000608      fpl     Created (from zdotpr vmx.k)   |
+-------------------------------------------------------------*/
#include "salppc.inc"
/**
 ESAL CPP definitions
**/
#undef   FUNC ENTRY
#undef   LOAD A
#undef   LOAD B
#undef   SUFFIX

#if defined( VMX_SAL )

#define  FUNC ENTRY          zdotpr4 vmx
#define  FUNC CONJ ENTRY    _zidotpr4 vmx
#define  LOAD A( vT, rA, rB )  LVX( vT, rA, rB )
#define  LOAD B( vT, rA, rB )  LVX( vT, rA, rB )
#define  SUFFIX( label )  label

#elif defined( VMX_NN )

#define  FUNC ENTRY          zdotpr4 vmx nn
#define  FUNC CONJ ENTRY    _zidotpr4_vmx_nn
#define  LOAD A( vT, rA, rB )  LVXL( vT, rA, rB )
#define  LOAD B( vT, rA, rB )  LVXL( vT, rA, rB )
#define  SUFFIX( label )  label##_nn

#elif defined( VMX_NC )

#define  FUNC ENTRY          zdotpr4 vmx nc
#define  FUNC CONJ ENTRY    _zidotpr4_vmx_nc
#define  LOAD A( vT, rA, rB )  LVXL( vT, rA, rB )
#define  LOAD B( vT, rA, rB )  LVX( vT, rA, rB )
#define  SUFFIX( label )  label##_nc

#elif defined( VMX_CN )

#define  FUNC ENTRY          zdotpr4 vmx cn
#define  FUNC CONJ ENTRY    _zidotpr4 vmx cn
#define  LOAD A( vT, rA, rB )  LVX( vT, rA, rB )
#define  LOAD B( vT, rA, rB )  LVXL( vT, rA, rB )
#define  SUFFIX( label )  label##_cn

#elif defined( VMX_CC )
```

1

```
#define  FUNC ENTRY              zdotpr4 vmx cc
#define  FUNC CONJ ENTRY        _zidotpr4 vmx cc
#define  LOAD A( vT, rA, rB )    LVX( vT, rA, rB )
#define  LOAD B( vT, rA, rB )    LVX( vT, rA, rB )
#define  SUFFIX( label )    label##_cc

#else
#error   YOU MUST DEFINE VMX_xxx, where x = C or N

#endif

#define VREGSAVE_COND  VRSAVE_COND  /* defined as 7 in salppc.inc */

/**
 Local CPP definitions
**/
#define NMASK2 0x8
#define NMASK1 0x4
#define NSHIFT 4
#define ADDRESS_INCREMENT 16

/**
 Input args
**/
#define A     r3
#define I     r4
#define B     r5
#define J     r6
#define C     r7
#define N     r8
#define EFLAG r9

/**
 Split complex parameters
**/
#define Ar0 A
#define Ai0 r10
#define Br0 B
#define Bi0 r11
#define Cr  C
#define Ci  r12

/**
 Local registers
**/
#define count r4
#define rtmp0 r4
#define rtmp1 r13

#define Ar1 r13
#define Ai1 r14
#define Ar2 r15
#define Ai2 r16
#define Ar3 r17
#define Ai3 r18

#define Br1 r19
#define Bi1 r20
#define Br2 r21
#define Bi2 r22
#define Br3 r23
#define Bi3 r24
#define aoffset r25
#define coffset r25
#define boffset r26
#define addr_incr r27
```

2

zdotpr4_vmx.k

```
/**
 VMX registers
**/
#define rsumr v0
#define rsumi v1
#define isumr v2
#define isumi v3
#define rsum0 v4
#define rsum1 v5
#define isum0 v6
#define isum1 v7

#define ar0 v4
#define ai0 v5
#define ar1 v6
#define ai1 v7
#define ar2 v8
#define ai2 v9
#define ar3 v10
#define ai3 v11

#define br0 v12
#define bi0 v13
#define br1 v14
#define bi1 v15
#define br2 v16
#define bi2 v17
#define br3 v18
#define bi3 v19
#define apC v20

#define atr0 v21
#define ati0 v22
#define atr1 v23
#define ati1 v24
#define atr2 v25
#define ati2 v26
#define atr3 v27
#define ati3 v28

/**
 FPU registers
**/
#define far      f0
#define fbr      f1
#define fai      f2
#define fbi      f3
#define frsumr   f4
#define frsumi   f5
#define fisumi   f6
#define fisumr   f7
#define frsum    f8
#define fisum    f9
#define rsum_vmx f10
#define isum_vmx f11

/**
 Begin code text, Save some registers
 Here for conjugate inner product
**/
U_ENTRY( FUNC CONJ_ENTRY )
    MR(rtmp0, Cr)
    MR(Cr, Ci)
    MR(Ci, rtmp0)
    MR(rtmp0, Br0)
    MR(Br0, Bi0)
    MR(Bi0, rtmp0)
```

3

```
zdotpr4_vmx.k                                          2/23/2001

/**
 Here for normal inner product
**/
FUNC PROLOG
U_ENTRY( FUNC ENTRY )
    DECLARE f0 f11
    DECLARE r3 r27
    DECLARE_v0_v28
/**
 Initial setup code
**/
    SAVE r13 r27
    USE THRU v28( VREGSAVE_COND )
    LFS( frsumr, Ar0, 0 )
    FSUBS(frsumr, frsumr, frsumr)
    FMR(frsumi, frsumr)
    FMR(fisumr, frsumr)
    FMR(fisumi, frsumr)
    FMR(rsum vmx, frsumr)
    FMR(isum_vmx, frsumr)
/**
 Process unaligned vector section first
**/
LABEL( SUFFIX( cont ) )
    GET_VMX UNALIGNED_COUNT( count, Br0 )
    LI( aoffset, 0 )
    LI( boffset, 0 )
    BEQ( SUFFIX( aligned ) )
    SUB( N, N, count )          /* adjust N for after loop */
/**
 Here to do first 1 to 3 points using standard FP
 Store result for later post_loop processing
**/
  LFSX( far, Ar0, aoffset )
  LFSX( fai, Ai0, aoffset )
  DECR C( count )
  LFSX( fbr, Br0, boffset )
  LFSX( fbi, Bi0, boffset )
  FMULS( frsumr, far, fbr )
  FMULS( frsumi, fai, fbi )
  FMULS( fisumi, far, fbi )
  FMULS( fisumr, fai, fbr )
  ADDI( Ar0, Ar0, 4 )
  ADDI( Ai0, Ai0, 4 )
  ADDI( Br0, Br0, 4 )
  ADDI( Bi0, Bi0, 4 )
  BEQ( SUFFIX( aligned ) )
/**
 Loop does 1 or 2 more sum updates
**/
LABEL( SUFFIX( pre_loop ) )
    LFSX( far, Ar0, aoffset )
    LFSX( fai, Ai0, aoffset )
    DECR C( count )
    LFSX( fbr, Br0, boffset )
    LFSX( fbi, Bi0, boffset )
    FMADDS( frsumr, far, fbr, frsumr )
    ADDI( Ar0, Ar0, 4 )
    FMADDS( frsumi, fai, fbi, frsumi )
    ADDI( Ai0, Ai0, 4 )
    FMADDS( fisumi, far, fbi, fisumi )
    ADDI( Br0, Br0, 4 )
    FMADDS( fisumr, fai, fbr, fisumr )
    ADDI( Bi0, Bi0, 4 )
    BNE( SUFFIX( pre_loop) )
/**
  Here for VMX aligned loop code
```

4

```
      Prepare for loop entry: assign loop pointers, counters
**/
LABEL( SUFFIX( aligned ) )
      SRWI C( count, N, 4 )    /* 16 per trip */
      LVSL( apC, Ar0, aoffset )
      LI( aoffset, 0 )
      LI( boffset, 0 )

      ADDI( Ar1, Ar0, 16 )
      VXOR( rsumr, rsumr, rsumr )
      ADDI( Ar2, Ar0, 32 )
      ADDI( Ar3, Ar0, 48 )

      ADDI( Ai1, Ai0, 16 )
      VXOR( isumi, isumi, isumi )
      ADDI( Ai2, Ai0, 32 )
      ADDI( Ai3, Ai0, 48 )

      ADDI( Br1, Br0, 16 )
      VXOR( rsumi, rsumi, rsumi )
      ADDI( Br2, Br0, 32 )
      ADDI( Br3, Br0, 48 )

      ADDI( Bi1, Bi0, 16 )
      ADDI( Bi2, Bi0, 32 )
      VXOR( isumr, isumr, isumr )
      ADDI( Bi3, Bi0, 48 )
      BEQ( SUFFIX(two_left) )
/**
 Loop windin section
**/
      LOAD A( atr0, Ar0, aoffset )
      LOAD A( ati0, Ai0, aoffset )
      LOAD A( atr1, Ar1, aoffset )
      LOAD_A( ati1, Ai1, aoffset )

      LOAD A( atr2, Ar2, aoffset )
      LOAD A( ati2, Ai2, aoffset )
      VPERM( ar0, atr0, atr1, apC )
      LOAD B( br0, Br0, boffset )
      LOAD B( bi0, Bi0, boffset )
      DECR C( count )
      VPERM( ai0, ati0, ati1, apC )
      LOAD B( br1, Br1, boffset )
      VPERM( ar1, atr1, atr2, apC )
      LOAD A( atr3, Ar3, aoffset )
      BR( SUFFIX( mid_loop ) )
/**
 Top of vector loop
**/
LABEL( SUFFIX( loop ) )
/* { */
      LOAD A( atr2, Ar2, aoffset )
      VMADDFP( rsumr, ar3, br3, rsumr )
      LOAD A( ati2, Ai2, aoffset )
      VPERM( ar0, atr0, atr1, apC ) /* uses last pass value */
      VMADDFP( rsumi, ai3, bi3, rsumi )
      LOAD B( br0, Br0, boffset )
      LOAD B( bi0, Bi0, boffset )
      DECR C( count )
      VPERM( ai0, ati0, ati1, apC )
      LOAD B( br1, Br1, boffset )
      VPERM( ar1, atr1, atr2, apC )
      VMADDFP( isumi, ar3, bi3, isumi )
      LOAD A( atr3, Ar3, aoffset )
      VMADDFP( isumr, ai3, br3, isumr )
/**
```

5

zdotpr4_vmx.k

```
 Loop entry
**/
LABEL( SUFFIX( mid loop ) )
    VMADDFP( rsumr, ar0, br0, rsumr )
    VPERM( ai1, ati1, ati2, apC )
    VMADDFP( rsumi, ai0, bi0, rsumi )
    LOAD A( ati3, Ai3, aoffset )
    VMADDFP( isumr, ai0, br0, isumr )
    LOAD B( bi1, Bi1, boffset )
    ADDI( aoffset, aoffset, 64 )
    VPERM( ar2, atr2, atr3, apC )
    VMADDFP( isumi, ar0, bi0, isumi )
    LOAD B( br2, Br2, boffset )
    VMADDFP( rsumr, ar1, br1, rsumr )
    LOAD B( bi2, Bi2, boffset )
    VMADDFP( isumr, ai1, br1, isumr )
/**
 Loop exit
**/
    VPERM( ai2, ati2, ati3, apC )
    BEQ( SUFFIX(loop exit ) )
    LOAD A( atr0, Ar0, aoffset )
    VMADDFP( rsumi, ai1, bi1, rsumi )
    LOAD A( ati0, Ai0, aoffset )
    VMADDFP( isumi, ar1, bi1, isumi )
    LOAD B( br3, Br3, boffset )
    VPERM( ar3, atr3, atr0, apC )
    VMADDFP( rsumr, ar2, br2, rsumr )
    LOAD A( atr1, Ar1, aoffset )
    VMADDFP( rsumi, ai2, bi2, rsumi )
    VPERM( ai3, ati3, ati0, apC )
    VMADDFP( isumi, ar2, bi2, isumi )
    LOAD B( bi3, Bi3, boffset )
    ADDI( boffset, boffset, 64 )
    LOAD A( ati1, Ai1, aoffset )
    VMADDFP( isumr, ai2, br2, isumr )
/* } */
    BR( SUFFIX( loop ) )
/**
 windout section
**/
LABEL( SUFFIX(loop exit ) )
    LOAD A( atr0, Ar0, aoffset )
    VMADDFP( rsumi, ai1, bi1, rsumi )
    LOAD A( ati0, Ai0, aoffset )
    VMADDFP( isumi, ar1, bi1, isumi )
    LOAD B( br3, Br3, boffset )
    VPERM( ar3, atr3, atr0, apC )
    VMADDFP( rsumr, ar2, br2, rsumr )
    VMADDFP( rsumi, ai2, bi2, rsumi )
    VPERM( ai3, ati3, ati0, apC )
    VMADDFP( isumi, ar2, bi2, isumi )
    LOAD B( bi3, Bi3, boffset )
    ADDI( boffset, boffset, 64 )
    VMADDFP( isumr, ai2, br2, isumr )
    VMADDFP( rsumr, ar3, br3, rsumr )
    VMADDFP( rsumi, ai3, bi3, rsumi )
    VMADDFP( isumi, ar3, bi3, isumi )
    VMADDFP( isumr, ai3, br3, isumr )
/**
 Remaining sum updates
**/
LABEL( SUFFIX(two_left) )
    ANDI_C( count, N, 0x8 )   /* bit 3 */
    BEQ( SUFFIX(one_left ) )

    LOAD_B( br0, Br0, boffset )
```

6

```
        LOAD B( bi0, Bi0, boffset )
        LOAD B( br1, Br1, boffset )
        LOAD B( bi1, Bi1, boffset )
        ADDI( boffset, boffset, 32 )

        LOAD A( atr0, Ar0, aoffset )
        LOAD A( ati0, Ai0, aoffset )
        LOAD A( atr1, Ar1, aoffset )
        LOAD A( ati1, Ai1, aoffset )
        LOAD A( atr2, Ar2, aoffset )
        LOAD A( ati2, Ai2, aoffset )
        ADDI( aoffset, aoffset, 32 )

        VPERM( ar0, atr0, atr1, apC ) /* uses last pass value */
        VPERM( ai0, ati0, ati1, apC )
        VPERM( ar1, atr1, atr2, apC )
        VPERM( ai1, ati1, ati2, apC )

        VMADDFP( rsumr, ar0, br0, rsumr )
        VMADDFP( rsumi, ai0, bi0, rsumi )
        VMADDFP( isumr, ai0, br0, isumr )
        VMADDFP( isumi, ar0, bi0, isumi )

        VMADDFP( rsumr, ar1, br1, rsumr )
        VMADDFP( isumr, ai1, br1, isumr )
        VMADDFP( rsumi, ai1, bi1, rsumi )
        VMADDFP( isumi, ar1, bi1, isumi )
        VMR(atr3, atr1)
        VMR(ati3, ati1)

    LABEL( SUFFIX(one_left) )
        ANDI_C( count, N, 0x4 )  /* bit 2 */
        BEQ( SUFFIX(combine ) )

        LOAD B( br0, Br0, boffset )
        LOAD B( bi0, Bi0, boffset )
        ADDI( boffset, boffset, 16 )

        LOAD A( atr0, Ar0, aoffset )
        LOAD A( ati0, Ai0, aoffset )
        LOAD A( atr1, Ar1, aoffset )
        LOAD A( ati1, Ai1, aoffset )
        ADDI( aoffset, aoffset, 16 )

        VPERM( ar0, atr0, atr1, apC ) /* uses last pass value */
        VPERM( ai0, ati0, ati1, apC )

        VMADDFP( rsumr, ar0, br0, rsumr )
        VMADDFP( rsumi, ai0, bi0, rsumi )
        VMADDFP( isumr, ai0, br0, isumr )
        VMADDFP( isumi, ar0, bi0, isumi )
/**
 combine partial sums, permute, write out results
**/
    LABEL( SUFFIX(combine) )
        VSUBFP( rsumr, rsumr, rsumi ) /* rsumr = rsumr - rsumi */
        VADDFP( isumi, isumi, isumr )
/**
 8 bytes/cycle shuffle:
 real/imag logic should be intermixed for efficiency
**/
        VMRGHW(rsum0, rsumr, rsumr)
        ANDI C( addr incr, N, 0x3 )
        VMRGHW(isum0, isumi, isumi)
        VMRGLW(rsum1, rsumr, rsumr)
        SUB( addr incr, N, addr incr ) /* offset index for remainders */
        VMRGLW(isum1, isumi, isumi)
```

7

```
    VADDFP( rsum0, rsum1, rsum0 )
    SLWI(addr incr, addr incr, 2) /* byte offset */
    VADDFP( isum0, isum1, isum0 )

    VMRGHW(rsum1, rsum0, rsum0)
    ADD(Ar0, Ar0, addr incr)
    VMRGHW(isum1, isum0, isum0)
    ADD(Ai0, Ai0, addr incr)
    VMRGLW(rsum0, rsum0, rsum0)
    ADD(Br0, Br0, addr incr)
    VMRGLW(isum0, isum0, isum0)
    ADD(Bi0, Bi0, addr incr)
    VADDFP( rsumr, rsum1, rsum0 )
    LI(coffset, 0) /* needed for output */
    VADDFP( isumi, isum1, isum0 )
/**
 4 byte stores
**/
    STVEWX( rsumr, Cr, coffset )
    STVEWX( isumi, Ci, coffset )
/**
 Remainders of 1-3 more to do
**/
    ANDI_C( N, N, 3 )
    LFS( rsum vmx, Cr, 0 )
    LFS( isum vmx, Ci, 0 )
    BEQ( SUFFIX( scaler_vmx_combine ) )
/**
 Here to do last 1-3 points using standard FP
**/
LABEL( SUFFIX( post_loop ) )
    LFS( far, Ar0, 0 )
    LFS( fai, Ai0, 0 )
    DECR_C( N )
    LFS( fbr, Br0, 0 )
    LFS( fbi, Bi0, 0 )
    FMADDS( frsumr, far, fbr, frsumr )
    FMADDS( frsumi, fai, fbi, frsumi )
    FMADDS( fisumi, far, fbi, fisumi )
    FMADDS( fisumr, fai, fbr, fisumr )
    ADDI(Ar0, Ar0, 4)
    ADDI(Br0, Br0, 4)
    ADDI(Ai0, Ai0, 4)
    ADDI(Bi0, Bi0, 4)
    BNE( SUFFIX( post_loop) )
/**
 Write out result
**/
LABEL( SUFFIX( scaler vmx combine ) )
    FSUBS( frsum, frsumr, frsumi ) /* rsumr = rsumr - rsumi */
    FADDS( fisum, fisumi, fisumr )
    FADDS( frsum, frsum, rsum vmx )
    FADDS( fisum, fisum, isum_vmx )
    STFS( frsum, Cr, 0 )
    STFS( fisum, Ci, 0 )
/**
 return
**/
LABEL( SUFFIX(ret) )
    FREE THRU v28( VREGSAVE_COND )
    REST r13_r27
    RETURN
FUNC_EPILOG
```

8

```
/*---------------------------------------------------------------+
|--- MC Standard Algorithms -- PPC Macro language Version    ---|
|---------------------------------------------------------------|
|                                                               |
|   File Name:    ZDOTPR4 VMX.MAC                                |
|   Description:  Vector Single Precision Complex Dot Product    |
|                 CPP dummy file for unaligned vector processing |
|                                                               |
|   Entry/params: ZDOTPR4 VMX (A, I, B, J, C, N)                 |
|   Formula: C[0] = sum (A->realp[mI]*B->realp[mJ]               |
|                        - A->imagp[mI]*B->imagp[mJ])            |
|            C[1] = sum (A->realp[mI]*B->imagp[mJ]               |
|                        + A->imagp[mI]*B->realp[mJ])            |
|                  for m=0 to N-1                                |
|                                                               |
|             Mercury Computer Systems, Inc.                    |
|             Copyright (c) 1998  All rights reserved           |
|                                                               |
|   Revision  Date    Engineer  Reason                          |
|   --------  ----    --------  --------                         |
|    0.0     000607    fpl     Created (from zdotpr vmx.mac)     |
+---------------------------------------------------------------*/
#if defined( BUILD_MAX )

#undef VMX SAL
#undef VMX NN
#undef VMX NC
#undef VMX CN
#undef VMX_CC

#if !defined( COMPILE_ESAL_JUMP TABLE )
                              /* 1 variant: _zdotpr4_vmx() */
#define VMX SAL
#include "zdotpr4_vmx.k"

#else                     /* 5 variants based on ESAL flag */
#define VMX NN
#include "zdotpr4_vmx.k"

#undef VMX NN
#define VMX NC
#include "zdotpr4_vmx.k"

#undef VMX NC
#define VMX CN
#include "zdotpr4_vmx.k"

#undef VMX CN
#define VMX CC
#include "zdotpr4_vmx.k"
#undef VMX_CC
#endif                    /* end COMPILE_ESAL_JUMP_TABLE */

#endif                    /* end BUILD_MAX */
```

1

zdotpr_vmx.k   2/23/2001

```
/*-------------------------------------------------------------------+
|--- MC Standard Algorithms -- PPC Macro language Version    ---|
|-------------------------------------------------------------------|
|                                                                   |
|  File Name:    ZDOTPR.K                                            |
|  Description:  CPP Source code for Vector Single Precision         |
|               Split Complex Dot Product                           |
|  Entry/params: ZDOTPR (A, I, B, J, C, N)                          |
|               ZIDOTPR (A, I, B, J, C, N)                          |
|                                                                   |
|  Formula: C[0] = sum (A->realp[mI]*B->realp[mJ]                    |
|                       -/+ A->imagp[mI]*B->imagp[mJ])              |
|           C[1] = sum (A->realp[mI]*B->imagp[mJ]                    |
|                       +/- A->imagp[mI]*B->realp[mJ])              |
|                     for m=0 to N-1                                 |
|                                                                   |
|            Mercury Computer Systems, Inc.                         |
|            Copyright (c) 1998  All rights reserved                |
|                                                                   |
|  Revision   Date      Engineer Reason                             |
|  --------   ----      -------- --------                           |
|    0.0      981215      fpl    Created                            |
|    0.1      990310      fpl    Integrated with 750 library        |
|    0.2      000131      jfk    salppc.inc changes                 |
|    0.3      000223      fpl    Fixed pre-loop bug                 |
|    0.4      000717      fpl    Added dsts, removed LVXLs          |
+-------------------------------------------------------------------*/
#include "salppc.inc"

/**
 ESAL CPP definitions
**/
#undef  FUNC CONJ ENTRY
#undef  FUNC ENTRY
#undef  LOAD A
#undef  LOAD B
#undef  SUFFIX

#if defined( VMX_SAL )

#define  FUNC ENTRY          zdotpr vmx
#define  FUNC CONJ ENTRY    _zidotpr_vmx
#define  LOAD A( vT, rA, rB )  LVX( vT, rA, rB )
#define  LOAD B( vT, rA, rB )  LVX( vT, rA, rB )
#define  SUFFIX( label )   label
#undef   DSTA( ptr, control )
#undef   DSTB( ptr, control )
#define  DSTA( ptr, control )
#define  DSTB( ptr, control )
#undef   DST_ENABLE

#elif defined( VMX_NN )

#define  FUNC ENTRY          zdotpr vmx nn
#define  FUNC CONJ ENTRY    _zidotpr_vmx_nn
#define  LOAD A( vT, rA, rB )  LVX( vT, rA, rB )
#define  LOAD B( vT, rA, rB )  LVX( vT, rA, rB )
#define  SUFFIX( label )   label##_nn
#undef   DSTA( ptr, control )
#undef   DSTB( ptr, control )
#define  DSTA( ptr, control )
#define  DSTB( ptr, control )
#undef   DST_ENABLE

#elif defined( VMX_NC )

#define  FUNC_ENTRY          _zdotpr_vmx_nc
```

1

```
zdotpr_vmx.k                                            2/23/2001

#define  FUNC CONJ ENTRY    _zidotpr_vmx_nc
#define  LOAD A( vT, rA, rB )  LVX( vT, rA, rB )
#define  LOAD B( vT, rA, rB )  LVX( vT, rA, rB )
#define  SUFFIX( label )  label##_nc
#undef   DSTA( ptr, control )
#undef   DSTB( ptr, control )
#define  DSTA( ptr, control ) DST( ptr, control, 0 ) \
                                    ADDI( ptr, ptr, 64 )
#define  DSTB( ptr, control )
#define DST_ENABLE

#elif defined( VMX_CN )

#define  FUNC ENTRY          zdotpr vmx cn
#define  FUNC CONJ ENTRY    _zidotpr_vmx_cn
#define  LOAD A( vT, rA, rB )  LVX( vT, rA, rB )
#define  LOAD B( vT, rA, rB )  LVX( vT, rA, rB )
#define  SUFFIX( label )  label##_cn
#undef   DSTA( ptr, control )
#undef   DSTB( ptr, control )
#define  DSTA( ptr, control )
#define  DSTB( ptr, control ) DST( ptr, control, 0 ) \
                                    ADDI( ptr, ptr, 64 )
#define DST_ENABLE

#elif defined( VMX_CC )

//#define  FUNC ENTRY          zdotpr vmx_cc
#define  FUNC ENTRY          zdotpr vmx
#define  FUNC CONJ ENTRY    _zidotpr_vmx_cc
#define  LOAD A( vT, rA, rB )  LVX( vT, rA, rB )
#define  LOAD B( vT, rA, rB )  LVX( vT, rA, rB )
#define  SUFFIX( label )  label##_cc
#undef   DSTA( ptr, control )
#undef   DSTB( ptr, control )
#define  DSTA( ptr, control )
#define  DSTB( ptr, control )
#undef   DST_ENABLE

#else
#error   YOU MUST DEFINE VMX_xxx, where x = C or N

#endif

#define VREGSAVE_COND  VRSAVE_COND  /* defined as 7 in salppc.inc */

/**
 Local CPP definitions
**/
#define NMASK2 0x8
#define NMASK1 0x4
#define NSHIFT 4
#define ADDRESS_INCREMENT 16

/**
 Input args
**/
#define A    r3
#define I    r4
#define B    r5
#define J    r6
#define C    r7
#define N    r8
#define EFLAG r9

/**
 Split complex parameters
```

2

zdotpr_vmx.k   2/23/2001

```
**/
#define Ar0 A
#define Ai0 r10
#define Br0 B
#define Bi0 r11
#define Cr  C
#define Ci  r12

/**
 Local registers
**/
#define count r4
#define rtmp0 r4
#define rtmp1 r13

#define dst_stride r13
#define num_blocks r14
#define Ar1 r13
#define Ai1 r14
#define Ar2 r15
#define Ai2 r16
#define Ar3 r17
#define Ai3 r18

#define Br1 r19
#define Bi1 r20
#define Br2 r21
#define Bi2 r22
#define Br3 r23
#define Bi3 r24
#define ptr_offset0 r25
#define ptr_offset1 r26
#define addr_incr r27
#define dst_rptr r28
#define dst_iptr r29
#define dst_control r30

/**
 VMX registers
**/
#define rsumr v0
#define rsumi v1
#define isumr v2
#define isumi v3
#define rsum0 v4
#define rsum1 v5
#define isum0 v6
#define isum1 v7

#define ar0 v4
#define ai0 v5
#define ar1 v6
#define ai1 v7
#define ar2 v8
#define ai2 v9
#define ar3 v10
#define ai3 v11

#define br0 v12
#define bi0 v13
#define br1 v14
#define bi1 v15
#define br2 v16
#define bi2 v17
#define br3 v18
#define bi3 v19
/**
```

3

```
 FPU registers
**/
#define far       f0
#define fbr       f1
#define fai       f2
#define fbi       f3
#define frsumr    f4
#define frsumi    f5
#define fisumi    f6
#define fisumr    f7
#define frsum     f8
#define fisum     f9
#define rsum_vmx  f10
#define isum_vmx  f11


/**
 Begin code text, Save some registers
 Here for conjugate inner product
**/
U_ENTRY( FUNC CONJ_ENTRY )
    MR(rtmp0, Cr)
    MR(Cr, Ci)
    MR(Ci, rtmp0)
    MR(rtmp0, Br0)
    MR(Br0, Bi0)
    MR(Bi0, rtmp0)
/**
 Here for normal inner product
**/
U_ENTRY( FUNC ENTRY )
    DECLARE f0 f11
    DECLARE r3 r30
    DECLARE_v0_v19
/**
 Initial setup code
**/
    SAVE r13 r30
    USE THRU v19( VREGSAVE_COND )
    LFS( frsumr, Ar0, 0 )
    FSUBS(frsumr, frsumr, frsumr)
    FMR(frsumi, frsumr)
    FMR(fisumr, frsumr)
    FMR(fisumi, frsumr)
    FMR(rsum_vmx, frsumr)
    FMR(isum_vmx, frsumr)
/**
 Process unaligned vector section first
**/
LABEL( SUFFIX( cont ) )
    GET_VMX UNALIGNED COUNT( count, Ar0 )
    LI( ptr offset0, 0 )
    BEQ( SUFFIX( aligned ) )
    SUB( N, N, count )          /* adjust N for after loop */
/**
 Here to do first 1 to 3 points using standard FP
 Store result for later post_loop processing
**/
    LFSX( far, Ar0, ptr offset0 )
    LFSX( fai, Ai0, ptr_offset0 )
    DECR C( count )
    LFSX( fbr, Br0, ptr offset0 )
    LFSX( fbi, Bi0, ptr_offset0 )
    FMULS( frsumr, far, fbr )
    FMULS( frsumi, fai, fbi )
    FMULS( fisumi, far, fbi )
    FMULS( fisumr, fai, fbr )
    ADDI( Ar0, Ar0, 4 )
```

4

```
          zdotpr_vmx.k                                    2/23/2001

     ADDI( Ai0, Ai0, 4 )
     ADDI( Br0, Br0, 4 )
     ADDI( Bi0, Bi0, 4 )
     BEQ( SUFFIX( aligned ) ) )
/**
 Loop does 1 or 2 more sum updates
**/
LABEL( SUFFIX( pre_loop ) )
   LFSX( far, Ar0, ptr offset0 )
   LFSX( fai, Ai0, ptr_offset0 )
   DECR C( count )
   LFSX( fbr, Br0, ptr offset0 )
   LFSX( fbi, Bi0, ptr offset0 )
   FMADDS( frsumr, far, fbr, frsumr )
   ADDI( Ar0, Ar0, 4 )
   FMADDS( frsumi, fai, fbi, frsumi )
   ADDI( Ai0, Ai0, 4 )
   FMADDS( fisumi, far, fbi, fisumi )
   ADDI( Br0, Br0, 4 )
   FMADDS( fisumr, fai, fbr, fisumr )
   ADDI( Bi0, Bi0, 4 )
   BNE( SUFFIX( pre_loop) )
/**
 Here for VMX aligned loop code
 Prepare for loop entry: assign loop pointers, counters
**/
LABEL( SUFFIX( aligned ) )
/**
 DST setup: bring in 2 cachelines
 MAKE STREAM_CODE( control_register, bytes_per_block, block_count,
 byte_stride )
**/
#if defined( DST_ENABLE )

#if defined( EXPAND_NCC )
   MR( dst rptr, Ar )
   MR( dst iptr, Ai )
#elif defined( EXPAND_CNC )
   MR( dst rptr, Br )
   MR( dst_iptr, Bi )
#endif

   MAKE STREAM CODE( dst control, 64, 1, 0 )
   DSTA( dst rptr, dst control )
   DSTA( dst iptr, dst control )
   DSTB( dst rptr, dst control )
   DSTB( dst_iptr, dst_control )
#endif

   SRWI C( count, N, NSHIFT )          /* 16 per trip */
   LI(addr incr, ADDRESS INCREMENT)  /* constants defined above */
   SLWI(ptr offset1, addr incr, 2)
   NEG(ptr_offset1, ptr_offset1)      /* will be adding addr_incr << 3 */

   ADD(Ar1, Ar0, addr incr)
   VXOR( rsumr, rsumr, rsumr )
   ADD(Br1, Br0, addr incr)
   ADD(Ai1, Ai0, addr incr)
   VXOR( rsumi, rsumi, rsumi )
   ADD(Bi1, Bi0, addr_incr)

   ADD(Ar2, Ar1, addr incr)
   VXOR( isumr, isumr, isumr )
   ADD(Br2, Br1, addr incr)
   ADD(Ai2, Ai1, addr incr)
   VXOR( isumi, isumi, isumi )
   ADD(Bi2, Bi1, addr_incr)
```

5

```
        ADD(Ar3, Ar2, addr incr)
        ADD(Br3, Br2, addr incr)
        ADD(Ai3, Ai2, addr incr)
        ADD(Bi3, Bi2, addr incr)
        SLWI(addr_incr, addr_incr, 3) /* bump by 8 elements */
/**
 Loop entry code
**/
        DSTA( dst rptr, dst control )
        LOAD A( ar0, Ar0, ptr offset0 )
        DSTB( dst rptr, dst control )
        LOAD B( br0, Br0, ptr offset0 )
        LOAD A( ai0, Ai0, ptr offset0 )
        LOAD_B( bi0, Bi0, ptr_offset0 )
/**
 Top of double loop structure
**/
LABEL( SUFFIX(loop0 ) )
        LOAD A( ar1, Ar1, ptr offset0 )
        VMADDFP( rsumr, ar0, br0, rsumr )
        DSTA( dst iptr, dst control )
        LOAD B( br1, Br1, ptr offset0 )
        VMADDFP( rsumi, ai0, bi0, rsumi )
        LOAD A( ai1, Ai1, ptr offset0 )
        LOAD B( bi1, Bi1, ptr offset0 )
        DSTB( dst iptr, dst_control )
        DECR C( count )
        LOAD A( ar2, Ar2, ptr offset0 )
        VMADDFP( isumi, ar0, bi0, isumi )
        VMADDFP( isumr, ai0, br0, isumr )
        LOAD B( br2, Br2, ptr offset0 )
        VMADDFP( rsumr, ar1, br1, rsumr )
        ADD(ptr offset1, ptr_offset1, addr_incr)
        VMADDFP( rsumi, ai1, bi1, rsumi )
        LOAD A( ai2, Ai2, ptr offset0 )
        VMADDFP( isumi, ar1, bi1, isumi )
        LOAD B( bi2, Bi2, ptr offset0 )
        VMADDFP( isumr, ai1, br1, isumr )
        VMADDFP( rsumr, ar2, br2, rsumr )
        LOAD A( ar3, Ar3, ptr offset0 )
        VMADDFP( rsumi, ai2, bi2, rsumi )
        LOAD B( br3, Br3, ptr offset0 )
        LOAD A( ai3, Ai3, ptr offset0 )
        VMADDFP( isumi, ar2, bi2, isumi )
        LOAD B( bi3, Bi3, ptr offset0 )
        VMADDFP( isumr, ai2, br2, isumr )
        BEQ( SUFFIX(loop0 exit ) )
        DSTA( dst rptr, dst control )
        LOAD A( ar0, Ar0, ptr offset1 )
        VMADDFP( rsumr, ar3, br3, rsumr )
        VMADDFP( rsumi, ai3, bi3, rsumi )
        DSTB( dst rptr, dst control )
        LOAD B( br0, Br0, ptr offset1 )
        VMADDFP( isumi, ar3, bi3, isumi )
        LOAD A( ai0, Ai0, ptr offset1 )
        LOAD B( bi0, Bi0, ptr offset1 )
        VMADDFP( isumr, ai3, br3, isumr )
        BR( SUFFIX(loop1 ) )
/**
 loop exit
**/
LABEL( SUFFIX(loop0 exit ) )
        MR(ptr offset0, ptr offset1)
        BR( SUFFIX(loop1_exit ) )
/**
 Top of second loop
```

6

zdotpr_vmx.k   2/23/2001

```
**/
LABEL( SUFFIX(loop1 ) )
    LOAD A( ar1, Ar1, ptr offset1 )
    VMADDFP( rsumr, ar0, br0, rsumr )
    DSTA( dst iptr, dst control )
    LOAD B( br1, Br1, ptr offset1 )
    VMADDFP( rsumi, ai0, bi0, rsumi )
    LOAD A( ai1, Ai1, ptr offset1 )
    LOAD B( bi1, Bi1, ptr offset1 )
    DSTB( dst iptr, dst_control )
    DECR C( count )
    LOAD A( ar2, Ar2, ptr offset1 )
    VMADDFP( isumi, ar0, bi0, isumi )
    VMADDFP( isumr, ai0, br0, isumr )
    LOAD B( br2, Br2, ptr offset1 )
    VMADDFP( rsumr, ar1, br1, rsumr )
    ADD(ptr offset0, ptr_offset0, addr_incr)
    VMADDFP( rsumi, ai1, bi1, rsumi )
    LOAD A( ai2, Ai2, ptr offset1 )
    VMADDFP( isumi, ar1, bi1, isumi )
    LOAD B( bi2, Bi2, ptr offset1 )
    VMADDFP( isumr, ai1, br1, isumr )
    VMADDFP( rsumr, ar2, br2, rsumr )
    LOAD A( ar3, Ar3, ptr offset1 )
    VMADDFP( rsumi, ai2, bi2, rsumi )
    LOAD B( br3, Br3, ptr offset1 )
    LOAD A( ai3, Ai3, ptr offset1 )
    VMADDFP( isumi, ar2, bi2, isumi )
    LOAD B( bi3, Bi3, ptr offset1 )
    VMADDFP( isumr, ai2, br2, isumr )
    BEQ( SUFFIX(loop1 exit ) )
    DSTA( dst rptr, dst control )
    LOAD A( ar0, Ar0, ptr offset0 )
    VMADDFP( rsumr, ar3, br3, rsumr )
    VMADDFP( rsumi, ai3, bi3, rsumi )
    DSTB( dst rptr, dst control )
    LOAD B( br0, Br0, ptr offset0 )
    VMADDFP( isumi, ar3, bi3, isumi )
    LOAD A( ai0, Ai0, ptr offset0 )
    LOAD B( bi0, Bi0, ptr offset0 )
    VMADDFP( isumr, ai3, br3, isumr )
    BR( SUFFIX(loop0 ) )
/**
 Drop out of loop, flush pipe
**/
LABEL( SUFFIX(loop1 exit ) )
    VMADDFP( rsumr, ar3, br3, rsumr )
    VMADDFP( rsumi, ai3, bi3, rsumi )
    VMADDFP( isumi, ar3, bi3, isumi )
    VMADDFP( isumr, ai3, br3, isumr )
/**
 Remaining sum updates
**/
LABEL( SUFFIX(two_left) )
    ANDI_C( count, N, 0x8 )   /* bit 3 */
    BEQ( SUFFIX(one_left ) )

    LOAD A( ar0, Ar0, ptr offset0 )
    LOAD B( br0, Br0, ptr offset0 )
    LOAD A( ai0, Ai0, ptr offset0 )
    LOAD_B( bi0, Bi0, ptr_offset0 )

    LOAD A( ar1, Ar1, ptr offset0 )
    LOAD B( br1, Br1, ptr offset0 )
    LOAD A( ai1, Ai1, ptr offset0 )
    LOAD_B( bi1, Bi1, ptr_offset0 )
```

7

zdotpr_vmx.k   2/23/2001

```
        VMADDFP( rsumr, ar0, br0, rsumr )
        VMADDFP( rsumi, ai0, bi0, rsumi )
        VMADDFP( isumi, ar0; bi0, isumi )
        VMADDFP( isumr, ai0, br0, isumr )

        VMADDFP( rsumr, ar1, br1, rsumr )
        VMADDFP( rsumi, ai1, bi1, rsumi )
        VMADDFP( isumi, ar1, bi1, isumi )
        VMADDFP( isumr, ai1, br1, isumr )
        ADDI( ptr_offset0, ptr_offset0, 32 )

LABEL( SUFFIX(one_left) )
        ANDI_C( count, N, 0x4 )   /* bit 2 */
        BEQ( SUFFIX(combine ) )
        LOAD A( ar0, Ar0, ptr offset0 )
        LOAD B( br0, Br0, ptr offset0 )
        LOAD A( ai0, Ai0, ptr offset0 )
        LOAD B( bi0, Bi0, ptr offset0 )
        VMADDFP( rsumr, ar0, br0, rsumr )
        VMADDFP( rsumi, ai0, bi0, rsumi )
        VMADDFP( isumi, ar0, bi0, isumi )
        VMADDFP( isumr, ai0, br0, isumr )
        ADDI( ptr_offset0, ptr_offset0, 16 )
/**
 combine partial sums, permute, write out results
**/
LABEL( SUFFIX(combine) )
      VSUBFP( rsumr, rsumr, rsumi ) /* rsumr = rsumr - rsumi */
      VADDFP( isumi, isumi, isumr )
/**
 8 bytes/cycle shuffle:
 real/imag logic should be intermixed for efficiency
**/
      VMRGHW(rsum0, rsumr, rsumr)
      ANDI C( addr incr, N, 0x3 )
      VMRGHW(isum0, isumi, isumi)
      VMRGLW(rsum1, rsumr, rsumr)
      SUB( addr incr, N, addr incr ) /* offset index for remainders */
      VMRGLW(isum1, isumi, isumi)
      VADDFP( rsum0, rsum1, rsum0 )
      SLWI(addr incr, addr incr, 2) /* byte offset */
      VADDFP( isum0, isum1, isum0 )

      VMRGHW(rsum1, rsum0, rsum0)
      ADD(Ar0, Ar0, addr incr)
      VMRGHW(isum1, isum0, isum0)
      ADD(Ai0, Ai0, addr incr)
      VMRGLW(rsum0, rsum0, rsum0)
      ADD(Br0, Br0, addr incr)
      VMRGLW(isum0, isum0, isum0)
      ADD(Bi0, Bi0, addr incr)
      VADDFP( rsumr, rsum1, rsum0 )
      LI(ptr offset0, 0) /* needed for output */
      VADDFP( isumi, isum1, isum0 )
/**
 4 byte stores
**/
      STVEWX( rsumr, Cr, ptr offset0 )
      STVEWX( isumi, Ci, ptr_offset0 )
/**
 Remainders of 1-3 more to do
**/
      ANDI_C( N, N, 3 )
      LFS( rsum vmx, Cr, 0 )
      LFS( isum vmx, Ci, 0 )
      BEQ( SUFFIX( scaler_vmx_combine ) )
```

8

```
/**
 Here to do last 1-3 points using standard FP
**/
LABEL( SUFFIX( post_loop ) )
   LFS( far, Ar0, 0 )
   LFS( fai, Ai0, 0 )
   DECR_C( N )
   LFS( fbr, Br0, 0 )
   LFS( fbi, Bi0, 0 )
   FMADDS( frsumr, far, fbr, frsumr )
   FMADDS( frsumi, fai, fbi, frsumi )
   FMADDS( fisumi, far, fbi, fisumi )
   FMADDS( fisumr, fai, fbr, fisumr )
   ADDI(Ar0, Ar0, 4)
   ADDI(Br0, Br0, 4)
   ADDI(Ai0, Ai0, 4)
   ADDI(Bi0, Bi0, 4)
   BNE( SUFFIX( post_loop) )
/**
 Write out result
**/
LABEL( SUFFIX( scaler vmx combine ) )
   FSUBS( frsum, frsumr, frsumi ) /* rsumr = rsumr - rsumi */
   FADDS( fisum, fisumi, fisumr )
   FADDS( frsum, frsum, rsum_vmx )
   FADDS( fisum, fisum, isum_vmx )
   STFS( frsum, Cr, 0 )
   STFS( fisum, Ci, 0 )
/**
 return
**/
LABEL( SUFFIX(ret) )
   FREE THRU v19( VREGSAVE_COND )
   REST r13_r30
   RETURN
FUNC_EPILOG
```

9

```
#define ZDOTPR 0
#define ZIDOTPR 1

/*------------------------------------------------------------------+
|--- MC Standard Algorithms -- PPC Macro language Version    ---|
|------------------------------------------------------------------|
|                                                                  |
|   File Name:     ZDOTPR.MAC                                       |
|   Description:   Vector Single Precision Complex Dot Product      |
|   Entry/params: ZDOTPR (A, I, B, J, C, N)                         |
|   Formula: C[0] = sum (A->realp[mI]*B->realp[mJ]                  |
|                         - A->imagp[mI]*B->imagp[mJ])              |
|           C[1] = sum (A->realp[mI]*B->imagp[mJ]                   |
|                         + A->imagp[mI]*B->realp[mJ])              |
|                    for m=0 to N-1                                 |
|                                                                  |
|           Mercury Computer Systems, Inc.                         |
|           Copyright (c) 1998  All rights reserved                |
|                                                                  |
|   Revision       Date      Engineer Reason                       |
|   --------       ----      -------- --------                     |
|     0.0        981209         fpl   Created (from cdotpr.mac)     |
|     0.1        990310         fpl   750/G4 integration            |
|     0.1        990322         fpl   Stylistic changes             |
+------------------------------------------------------------------*/

#define COMPILE_ESAL_JUMP_TABLE

#define FUNC_TYPE ZDOTPR

#if defined( BUILD_MAX )

#undef VMX_SAL
#undef VMX_NN
#undef VMX_NC
#undef VMX_CN
#undef VMX_CC

#if !defined( COMPILE_ESAL_JUMP_TABLE ) || defined(
COMPILE_NO_ESAL_JUMP_TABLE )
                              /* 1 variant: _zdotpr_vmx() */
#define VMX_SAL
#include "zdotpr_vmx.k"

#else                    /* 5 variants based on ESAL flag */

#define VMX_NN
#include "zdotpr_vmx.k"

#undef VMX_NN
#define VMX_NC
#include "zdotpr_vmx.k"

#undef VMX_NC
#define VMX_CN
#include "zdotpr_vmx.k"

#undef VMX_CN
#define VMX_CC
#include "zdotpr_vmx.k"
#undef VMX_CC
#endif                   /* end COMPILE_ESAL_JUMP_TABLE */

#endif                   /* end BUILD_MAX */
```

1